

# **Linux Standard Base Core Specification for S390X**

## **Linux Standard Base Core Specification for S390X**

LSB Core - S390X 5.0

Copyright © 2015 Linux Foundation

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.1; with no Invariant Sections, with no Front-Cover Texts, and with no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".

Portions of the text may be copyrighted by the following parties:

- The Regents of the University of California
- Free Software Foundation
- Ian F. Darwin
- Paul Vixie
- BSDI (now Wind River)
- Jean-loup Gailly and Mark Adler
- Massachusetts Institute of Technology
- Apple Inc.
- Easy Software Products
- artofcode LLC
- Till Kamppeter
- Manfred Wassman
- Python Software Foundation

These excerpts are being used in accordance with their respective licenses.

Linux is the registered trademark of Linus Torvalds in the U.S. and other countries.

UNIX is a registered trademark of The Open Group.

LSB is a trademark of the Linux Foundation in the United States and other countries.

AMD is a trademark of Advanced Micro Devices, Inc.

Intel and Itanium are registered trademarks and Intel386 is a trademark of Intel Corporation.

PowerPC is a registered trademark and PowerPC Architecture is a trademark of the IBM Corporation.

S/390 is a registered trademark of the IBM Corporation.

OpenGL is a registered trademark of Silicon Graphics, Inc.

PAM documentation is Copyright (C) Andrew G. Morgan 1996-9. All rights reserved. Used under the following conditions:

1. Redistributions of source code must retain the above copyright notice, and the entire permission notice in its entirety, including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

## Contents

<b>I Introductory Elements.....</b>
1 Scope.....
1.1 General.....
1.2 Module Specific Scope.....
2 References.....
2.1 Normative References.....
2.2 Informative References/Bibliography.....
3 Requirements.....
3.1 Relevant Libraries.....
3.2 LSB Implementation Conformance.....
3.3 LSB Application Conformance.....
4 Terms and Definitions.....
5 Documentation Conventions.....
<b>II Executable and Linking Format (ELF).....</b>
6 Introduction.....
7 Low Level System Information.....
7.1 Machine Interface.....
7.2 Function Calling Sequence.....
7.3 Operating System Interface.....
7.4 Process Initialization.....
7.5 Coding Examples.....
7.6 Debug Information.....
8 Object Format.....
8.1 Introduction.....
8.2 ELF Header.....
8.3 Sections.....
8.4 Symbol Table.....
8.5 Relocation.....
9 Program Loading and Dynamic Linking.....
9.1 Introduction.....
9.2 Program Loading.....
9.3 Dynamic Linking.....
<b>III Base Libraries.....</b>
10 Libraries.....
10.1 Program Interpreter/Dynamic Linker.....
10.2 Interfaces for libc.....
10.3 Data Definitions for libc.....
10.4 Interfaces for libm.....
10.5 Data Definitions for libm.....
10.6 Interface Definitions for libm.....
10.7 Interfaces for libpthread.....
10.8 Data Definitions for libpthread.....
10.9 Interfaces for libgcc_s.....
10.10 Data Definitions for libgcc_s.....
10.11 Interface Definitions for libgcc_s.....
10.12 Interfaces for libdl.....
10.13 Data Definitions for libdl.....
10.14 Interfaces for libcrypt.....
10.15 Data Definitions for libcrypt.....
<b>IV Utility Libraries.....</b>
11 Libraries.....
11.1 Interfaces for libz.....
11.2 Data Definitions for libz.....
11.3 Interfaces for libncurses.....

## LSB Core - S390X 5.0

<a href="#">11.4 Data Definitions for libcurses.....</a>
<a href="#">11.5 Interfaces for libcursesw.....</a>
<a href="#">11.6 Data Definitions for libcursesw.....</a>
<a href="#">11.7 Interfaces for libutil.....</a>
<a href="#"><b>V Base Libraries.....</b></a>
<a href="#">12 Libraries.....</a>
<a href="#">12.1 Interfaces for libstdcxx.....</a>
<a href="#">12.2 Interface Definitions for libstdcxx.....</a>
<a href="#"><b>VI Package Format and Installation.....</b></a>
<a href="#">13 Software Installation.....</a>
<a href="#">13.1 Package Dependencies.....</a>
<a href="#">13.2 Package Architecture Considerations.....</a>
<a href="#"><b>A Alphabetical Listing of Interfaces by Library.....</b></a>
<a href="#">A.1 libc.....</a>
<a href="#">A.2 libcrypt.....</a>
<a href="#">A.3 libdl.....</a>
<a href="#">A.4 libgcc_s.....</a>
<a href="#">A.5 libm.....</a>
<a href="#">A.6 libpthread.....</a>
<a href="#">A.7 librt.....</a>
<a href="#">A.8 libutil.....</a>
<a href="#"><b>B GNU Free Documentation License (Informative).....</b></a>
<a href="#">B.1 PREAMBLE.....</a>
<a href="#">B.2 APPLICABILITY AND DEFINITIONS.....</a>
<a href="#">B.3 VERBATIM COPYING.....</a>
<a href="#">B.4 COPYING IN QUANTITY.....</a>
<a href="#">B.5 MODIFICATIONS.....</a>
<a href="#">B.6 COMBINING DOCUMENTS.....</a>
<a href="#">B.7 COLLECTIONS OF DOCUMENTS.....</a>
<a href="#">B.8 AGGREGATION WITH INDEPENDENT WORKS.....</a>
<a href="#">B.9 TRANSLATION.....</a>
<a href="#">B.10 TERMINATION.....</a>
<a href="#">B.11 FUTURE REVISIONS OF THIS LICENSE.....</a>
<a href="#">B.12 How to use this License for your documents.....</a>

## List of Tables

<a href="#">2-1 Normative References</a>	.....
<a href="#">2-2 Other References</a>	.....
<a href="#">3-1 Standard Library Names</a>	.....
<a href="#">8-1 ELF Special Sections</a>	.....
<a href="#">8-2 Additional Special Sections</a>	.....
<a href="#">10-1 libc Definition</a>	.....
<a href="#">10-2 libc - RPC Function Interfaces</a>	.....
<a href="#">10-3 libc - RPC Deprecated Function Interfaces</a>	.....
<a href="#">10-4 libc - System Calls Function Interfaces</a>	.....
<a href="#">10-5 libc - System Calls Deprecated Function Interfaces</a>	.....
<a href="#">10-6 libc - Standard I/O Function Interfaces</a>	.....
<a href="#">10-7 libc - Standard I/O Deprecated Function Interfaces</a>	.....
<a href="#">10-8 libc - Standard I/O Data Interfaces</a>	.....
<a href="#">10-9 libc - Signal Handling Function Interfaces</a>	.....
<a href="#">10-10 libc - Signal Handling Deprecated Function Interfaces</a>	.....
<a href="#">10-11 libc - Signal Handling Data Interfaces</a>	.....
<a href="#">10-12 libc - Localization Functions Function Interfaces</a>	.....
<a href="#">10-13 libc - Localization Functions Data Interfaces</a>	.....
<a href="#">10-14 libc - Posix Spawn Option Function Interfaces</a>	.....
<a href="#">10-15 libc - Posix Advisory Option Function Interfaces</a>	.....
<a href="#">10-16 libc - Socket Interface Function Interfaces</a>	.....
<a href="#">10-17 libc - Socket Interface Data Interfaces</a>	.....
<a href="#">10-18 libc - Wide Characters Function Interfaces</a>	.....
<a href="#">10-19 libc - Wide Characters Deprecated Function Interfaces</a>	.....
<a href="#">10-20 libc - String Functions Function Interfaces</a>	.....
<a href="#">10-21 libc - String Functions Deprecated Function Interfaces</a>	.....
<a href="#">10-22 libc - IPC Functions Function Interfaces</a>	.....
<a href="#">10-23 libc - Regular Expressions Function Interfaces</a>	.....
<a href="#">10-24 libc - Character Type Functions Function Interfaces</a>	.....
<a href="#">10-25 libc - Time Manipulation Function Interfaces</a>	.....
<a href="#">10-26 libc - Time Manipulation Data Interfaces</a>	.....
<a href="#">10-27 libc - Terminal Interface Functions Function Interfaces</a>	.....
<a href="#">10-28 libc - System Database Interface Function Interfaces</a>	.....
<a href="#">10-29 libc - System Database Interface Deprecated Function Interfaces</a>	.....
<a href="#">10-30 libc - Language Support Function Interfaces</a>	.....
<a href="#">10-31 libc - Large File Support Function Interfaces</a>	.....
<a href="#">10-32 libc - Large File Support Deprecated Function Interfaces</a>	.....
<a href="#">10-33 libc - Standard Library Function Interfaces</a>	.....
<a href="#">10-34 libc - Standard Library Deprecated Function Interfaces</a>	.....
<a href="#">10-35 libc - Standard Library Data Interfaces</a>	.....
<a href="#">10-36 libc - GNU Extensions for libc Function Interfaces</a>	.....
<a href="#">10-37 libm Definition</a>	.....
<a href="#">10-38 libm - Math Function Interfaces</a>	.....
<a href="#">10-39 libm - Math Deprecated Function Interfaces</a>	.....
<a href="#">10-40 libm - Math Data Interfaces</a>	.....
<a href="#">10-41 libpthread Definition</a>	.....
<a href="#">10-42 libpthread - Realtime Threads Function Interfaces</a>	.....
<a href="#">10-43 libpthread - Advanced Realtime Threads Function Interfaces</a>	.....
<a href="#">10-44 libpthread - Posix Threads Function Interfaces</a>	.....
<a href="#">10-45 libpthread - Posix Threads Deprecated Function Interfaces</a>	.....
<a href="#">10-46 libpthread - Thread aware versions of libc interfaces Function Interfaces</a>	.....
<a href="#">10-47 libpthread - GNU Extensions for libpthread Function Interfaces</a>	.....
<a href="#">10-48 libpthread - System Calls Function Interfaces</a>	.....
<a href="#">10-49 libpthread - Standard I/O Function Interfaces</a>	.....
<a href="#">10-50 libpthread - Signal Handling Function Interfaces</a>	.....

<a href="#">10-51 libpthread - Standard Library Function Interfaces</a>	.....
<a href="#">10-52 libpthread - Socket Interface Function Interfaces</a>	.....
<a href="#">10-53 libpthread - Terminal Interface Functions Function Interfaces</a>	.....
<a href="#">10-54 libgcc_s Definition</a>	.....
<a href="#">10-55 libgcc_s - Unwind Library Function Interfaces</a>	.....
<a href="#">10-56 libdl Definition</a>	.....
<a href="#">10-57 libdl - Dynamic Loader Function Interfaces</a>	.....
<a href="#">10-58 libcrypt Definition</a>	.....
<a href="#">10-59 libcrypt - Encryption Function Interfaces</a>	.....
<a href="#">11-1 libz Definition</a>	.....
<a href="#">11-2 libncurses Definition</a>	.....
<a href="#">11-3 libncursesw Definition</a>	.....
<a href="#">11-4 libutil Definition</a>	.....
<a href="#">11-5 libutil - Utility Functions Function Interfaces</a>	.....
<a href="#">12-1 libstdcxx Definition</a>	.....
<a href="#">12-2 libstdcxx - C++ Runtime Support Function Interfaces</a>	.....
<a href="#">12-3 typeinfo for type_info</a>	.....
<a href="#">12-4 typeinfo for cxxabiv1:: enum_type_info</a>	.....
<a href="#">12-5 typeinfo for cxxabiv1:: array_type_info</a>	.....
<a href="#">12-6 Primary vtable for cxxabiv1:: class_type_info</a>	.....
<a href="#">12-7 typeinfo for cxxabiv1:: class_type_info</a>	.....
<a href="#">12-8 libstdcxx - Class cxxabiv1:: class_type_info Function Interfaces</a>	.....
<a href="#">12-9 typeinfo for cxxabiv1:: pbase_type_info</a>	.....
<a href="#">12-10 typeinfo for cxxabiv1:: pointer_type_info</a>	.....
<a href="#">12-11 typeinfo for cxxabiv1:: function_type_info</a>	.....
<a href="#">12-12 Primary vtable for cxxabiv1:: si_class_type_info</a>	.....
<a href="#">12-13 typeinfo for cxxabiv1:: si_class_type_info</a>	.....
<a href="#">12-14 libstdcxx - Class cxxabiv1:: si_class_type_info Function Interfaces</a>	.....
<a href="#">12-15 Primary vtable for cxxabiv1:: vmi_class_type_info</a>	.....
<a href="#">12-16 typeinfo for cxxabiv1:: vmi_class_type_info</a>	.....
<a href="#">12-17 libstdcxx - Class cxxabiv1:: vmi_class_type_info Function Interfaces</a>	.....
<a href="#">12-18 typeinfo for cxxabiv1:: fundamental_type_info</a>	.....
<a href="#">12-19 typeinfo for cxxabiv1:: pointer_to_member_type_info</a>	.....
<a href="#">12-20 libstdcxx - Class gnu_cxx:: pool_alloc_base Function Interfaces</a>	.....
<a href="#">12-21 Primary vtable for gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt;&gt;</a>	.....
<a href="#">12-22 Primary vtable for gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</a>	.....
<a href="#">12-23 typeinfo for exception</a>	.....
<a href="#">12-24 typeinfo for bad_typeid</a>	.....
<a href="#">12-25 typeinfo for logic_error</a>	.....
<a href="#">12-26 typeinfo for range_error</a>	.....
<a href="#">12-27 typeinfo for domain_error</a>	.....
<a href="#">12-28 typeinfo for length_error</a>	.....
<a href="#">12-29 typeinfo for out_of_range</a>	.....
<a href="#">12-30 typeinfo for bad_exception</a>	.....
<a href="#">12-31 typeinfo for runtime_error</a>	.....
<a href="#">12-32 typeinfo for overflow_error</a>	.....
<a href="#">12-33 typeinfo for underflow_error</a>	.....
<a href="#">12-34 typeinfo for invalid_argument</a>	.....
<a href="#">12-35 typeinfo for bad_cast</a>	.....
<a href="#">12-36 typeinfo for bad_alloc</a>	.....
<a href="#">12-37 libstdcxx - struct numeric_limits&lt; float128&gt; Data Interfaces</a>	.....
<a href="#">12-38 typeinfo for ctype_base</a>	.....
<a href="#">12-39 libstdcxx - Class ctype&lt;char&gt; Function Interfaces</a>	.....
<a href="#">12-40 typeinfo for ctype&lt;wchar_t&gt;</a>	.....
<a href="#">12-41 libstdcxx - Class ctype&lt;wchar_t&gt; Function Interfaces</a>	.....
<a href="#">12-42 typeinfo for ctype_byname&lt;char&gt;</a>	.....
<a href="#">12-43 libstdcxx - Class ctype_byname&lt;char&gt; Function Interfaces</a>	.....

[12-44 typeinfo for ctype\\_byname<wchar\\_t>.....](#)  
[12-45 libstdcxx - Class ctype\\_byname<wchar\\_t> Function Interfaces.....](#)  
[12-46 libstdcxx - Class basic\\_string<char, char\\_traits<char>, allocator<char>> Function Interfaces.....](#)  
[12-47 libstdcxx - Class basic\\_string<wchar\\_t, char\\_traits<wchar\\_t>, allocator<wchar\\_t>> Function Interfaces.....](#)  
[12-48 Primary vtable for basic\\_stringstream<char, char\\_traits<char>, allocator<char>>.....](#)  
[12-49 Secondary vtable for basic\\_stringstream<char, char\\_traits<char>, allocator<char>>.....](#)  
[12-50 Secondary vtable for basic\\_stringstream<char, char\\_traits<char>, allocator<char>>.....](#)  
[12-51 VTT for basic\\_stringstream<char, char\\_traits<char>, allocator<char>>.....](#)  
[12-52 libstdcxx - Class basic\\_stringstream<char, char\\_traits<char>, allocator<char>> Function Interfaces.....](#)  
[12-53 Primary vtable for basic\\_stringstream<wchar\\_t, char\\_traits<wchar\\_t>, allocator<wchar\\_t>>.....](#)  
[12-54 Secondary vtable for basic\\_stringstream<wchar\\_t, char\\_traits<wchar\\_t>, allocator<wchar\\_t>>.....](#)  
[12-55 Secondary vtable for basic\\_stringstream<wchar\\_t, char\\_traits<wchar\\_t>, allocator<wchar\\_t>>.....](#)  
[12-56 VTT for basic\\_stringstream<wchar\\_t, char\\_traits<wchar\\_t>, allocator<wchar\\_t>>.....](#)  
[12-57 libstdcxx - Class basic\\_stringstream<wchar\\_t, char\\_traits<wchar\\_t>, allocator<wchar\\_t>> Function Interfaces.....](#)  
[12-58 Primary vtable for basic\\_istringstream<char, char\\_traits<char>, allocator<char>>.....](#)  
[12-59 Secondary vtable for basic\\_istringstream<char, char\\_traits<char>, allocator<char>>.....](#)  
[12-60 VTT for basic\\_istringstream<char, char\\_traits<char>, allocator<char>>.....](#)  
[12-61 libstdcxx - Class basic\\_istringstream<char, char\\_traits<char>, allocator<char>> Function Interfaces.....](#)  
[12-62 Primary vtable for basic\\_istringstream<wchar\\_t, char\\_traits<wchar\\_t>, allocator<wchar\\_t>>.....](#)  
[12-63 Secondary vtable for basic\\_istringstream<wchar\\_t, char\\_traits<wchar\\_t>, allocator<wchar\\_t>>.....](#)  
[12-64 VTT for basic\\_istringstream<wchar\\_t, char\\_traits<wchar\\_t>, allocator<wchar\\_t>>.....](#)  
[12-65 libstdcxx - Class basic\\_istringstream<wchar\\_t, char\\_traits<wchar\\_t>, allocator<wchar\\_t>> Function Interfaces.....](#)  
[12-66 Primary vtable for basic\\_ostringstream<char, char\\_traits<char>, allocator<char>>.....](#)  
[12-67 Secondary vtable for basic\\_ostringstream<char, char\\_traits<char>, allocator<char>>.....](#)  
[12-68 VTT for basic\\_ostringstream<char, char\\_traits<char>, allocator<char>>.....](#)  
[12-69 libstdcxx - Class basic\\_ostringstream<char, char\\_traits<char>, allocator<char>> Function Interfaces.....](#)  
[12-70 Primary vtable for basic\\_ostringstream<wchar\\_t, char\\_traits<wchar\\_t>, allocator<wchar\\_t>>.....](#)  
[12-71 Secondary vtable for basic\\_ostringstream<wchar\\_t, char\\_traits<wchar\\_t>, allocator<wchar\\_t>>.....](#)  
[12-72 VTT for basic\\_ostringstream<wchar\\_t, char\\_traits<wchar\\_t>, allocator<wchar\\_t>>.....](#)  
[12-73 libstdcxx - Class basic\\_ostringstream<wchar\\_t, char\\_traits<wchar\\_t>, allocator<wchar\\_t>> Function Interfaces.....](#)  
[12-74 Primary vtable for basic\\_stringbuf<char, char\\_traits<char>, allocator<char>>.....](#)  
[12-75 typeinfo for basic\\_stringbuf<char, char\\_traits<char>, allocator<char>>.....](#)  
[12-76 libstdcxx - Class basic\\_stringbuf<char, char\\_traits<char>, allocator<char>> Function Interfaces.....](#)  
[12-77 Primary vtable for basic\\_stringbuf<wchar\\_t, char\\_traits<wchar\\_t>, allocator<wchar\\_t>>.....](#)

<a href="#">allocator&lt;wchar_t&gt;</a>	.....
<a href="#">12-78 typeinfo for basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</a>	.....
<code>&gt;</code>	.....
<a href="#">12-79 libstdcxx - Class basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; Function Interfaces</a>	.....
<a href="#">12-80 Primary vtable for basic_iostream&lt;char, char_traits&lt;char&gt;&gt;</a>	.....
<a href="#">12-81 Secondary vtable for basic_iostream&lt;char, char_traits&lt;char&gt;&gt;</a>	.....
<a href="#">12-82 Secondary vtable for basic_iostream&lt;char, char_traits&lt;char&gt;&gt;</a>	.....
<a href="#">12-83 VTT for basic_iostream&lt;char, char_traits&lt;char&gt;&gt;</a>	.....
<a href="#">12-84 libstdcxx - Class basic_iostream&lt;char, char_traits&lt;char&gt;&gt; Function Interfaces</a>	.....
<a href="#">12-85 Primary vtable for basic_iostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</a>	.....
<a href="#">12-86 Secondary vtable for basic_iostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</a>	.....
<a href="#">12-87 Secondary vtable for basic_iostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</a>	.....
<a href="#">12-88 VTT for basic_iostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</a>	.....
<a href="#">12-89 libstdcxx - Class basic_iostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; Function Interfaces</a>	.....
<a href="#">12-90 Primary vtable for basic_istream&lt;char, char_traits&lt;char&gt;&gt;</a>	.....
<a href="#">12-91 Secondary vtable for basic_istream&lt;char, char_traits&lt;char&gt;&gt;</a>	.....
<a href="#">12-92 VTT for basic_istream&lt;char, char_traits&lt;char&gt;&gt;</a>	.....
<a href="#">12-93 libstdcxx - Class basic_istream&lt;char, char_traits&lt;char&gt;&gt; Function Interfaces</a>	.....
<a href="#">12-94 Primary vtable for basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</a>	.....
<a href="#">12-95 Secondary vtable for basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</a>	.....
<a href="#">12-96 VTT for basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</a>	.....
<a href="#">12-97 libstdcxx - Class basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; Function Interfaces</a>	.....
<a href="#">12-98 Primary vtable for basic_ostream&lt;char, char_traits&lt;char&gt;&gt;</a>	.....
<a href="#">12-99 Secondary vtable for basic_ostream&lt;char, char_traits&lt;char&gt;&gt;</a>	.....
<a href="#">12-100 VTT for basic_ostream&lt;char, char_traits&lt;char&gt;&gt;</a>	.....
<a href="#">12-101 libstdcxx - Class basic_ostream&lt;char, char_traits&lt;char&gt;&gt; Function Interfaces</a>	.....
<a href="#">12-102 Primary vtable for basic_ostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</a>	.....
<a href="#">12-103 Secondary vtable for basic_ostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</a>	.....
<a href="#">12-104 VTT for basic_ostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</a>	.....
<a href="#">12-105 libstdcxx - Class basic_ostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; Function Interfaces</a>	.....
<a href="#">12-106 Primary vtable for basic_fstream&lt;char, char_traits&lt;char&gt;&gt;</a>	.....
<a href="#">12-107 Secondary vtable for basic_fstream&lt;char, char_traits&lt;char&gt;&gt;</a>	.....
<a href="#">12-108 Secondary vtable for basic_fstream&lt;char, char_traits&lt;char&gt;&gt;</a>	.....
<a href="#">12-109 VTT for basic_fstream&lt;char, char_traits&lt;char&gt;&gt;</a>	.....
<a href="#">12-110 libstdcxx - Class basic_fstream&lt;char, char_traits&lt;char&gt;&gt; Function Interfaces</a>	.....
<a href="#">12-111 Primary vtable for basic_fstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</a>	.....
<a href="#">12-112 Secondary vtable for basic_fstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</a>	.....
<a href="#">12-113 Secondary vtable for basic_fstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</a>	.....
<a href="#">12-114 VTT for basic_fstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</a>	.....
<a href="#">12-115 libstdcxx - Class basic_fstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; Function Interfaces</a>	.....
<a href="#">12-116 Primary vtable for basic_ifstream&lt;char, char_traits&lt;char&gt;&gt;</a>	.....
<a href="#">12-117 Secondary vtable for basic_ifstream&lt;char, char_traits&lt;char&gt;&gt;</a>	.....
<a href="#">12-118 VTT for basic_ifstream&lt;char, char_traits&lt;char&gt;&gt;</a>	.....
<a href="#">12-119 libstdcxx - Class basic_ifstream&lt;char, char_traits&lt;char&gt;&gt; Function Interfaces</a>	.....
<a href="#">12-120 Primary vtable for basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</a>	.....
<a href="#">12-121 Secondary vtable for basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</a>	.....
<a href="#">12-122 VTT for basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</a>	.....
<a href="#">12-123 libstdcxx - Class basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; Function Interfaces</a>	.....
<a href="#">12-124 Primary vtable for basic_ofstream&lt;char, char_traits&lt;char&gt;&gt;</a>	.....
<a href="#">12-125 Secondary vtable for basic_ofstream&lt;char, char_traits&lt;char&gt;&gt;</a>	.....
<a href="#">12-126 VTT for basic_ofstream&lt;char, char_traits&lt;char&gt;&gt;</a>	.....
<a href="#">12-127 libstdcxx - Class basic_ofstream&lt;char, char_traits&lt;char&gt;&gt; Function Interfaces</a>	.....

<a href="#">12-128 Primary vtable for basic_ofstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;.....</a>
<a href="#">12-129 Secondary vtable for basic_ofstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;.....</a>
<a href="#">12-130 VTT for basic_ofstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;.....</a>
<a href="#">12-131 libstdcxx - Class basic_ofstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; Function Interfaces.....</a>
<a href="#">12-132 Primary vtable for basic_streampbuf&lt;char, char_traits&lt;char&gt;&gt;.....</a>
<a href="#">12-133 typeinfo for basic_streampbuf&lt;char, char_traits&lt;char&gt;&gt;.....</a>
<a href="#">12-134 libstdcxx - Class basic_streampbuf&lt;char, char_traits&lt;char&gt;&gt; Function Interfaces.....</a>
<a href="#">12-135 Primary vtable for basic_streampbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;.....</a>
<a href="#">12-136 typeinfo for basic_streampbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;.....</a>
<a href="#">12-137 libstdcxx - Class basic_streampbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; Function Interfaces.....</a>
<a href="#">12-138 Primary vtable for basic_filebuf&lt;char, char_traits&lt;char&gt;&gt;.....</a>
<a href="#">12-139 typeinfo for basic_filebuf&lt;char, char_traits&lt;char&gt;&gt;.....</a>
<a href="#">12-140 libstdcxx - Class basic_filebuf&lt;char, char_traits&lt;char&gt;&gt; Function Interfaces.....</a>
<a href="#">12-141 Primary vtable for basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;.....</a>
<a href="#">12-142 typeinfo for basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;.....</a>
<a href="#">12-143 libstdcxx - Class basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; Function Interfaces.....</a>
<a href="#">12-144 typeinfo for ios_base.....</a>
<a href="#">12-145 typeinfo for basic_ios&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;.....</a>
<a href="#">12-146 typeinfo for ios_base::failure.....</a>
<a href="#">12-147 typeinfo for_timepunct&lt;char&gt;.....</a>
<a href="#">12-148 libstdcxx - Class_timepunct&lt;char&gt; Function Interfaces.....</a>
<a href="#">12-149 typeinfo for_timepunct&lt;wchar_t&gt;.....</a>
<a href="#">12-150 libstdcxx - Class_timepunct&lt;wchar_t&gt; Function Interfaces.....</a>
<a href="#">12-151 typeinfo for messages_base.....</a>
<a href="#">12-152 libstdcxx - Class_messages&lt;char&gt; Function Interfaces.....</a>
<a href="#">12-153 libstdcxx - Class_messages&lt;wchar_t&gt; Function Interfaces.....</a>
<a href="#">12-154 typeinfo for messages_byname&lt;char&gt;.....</a>
<a href="#">12-155 libstdcxx - Class_messages_byname&lt;char&gt; Function Interfaces.....</a>
<a href="#">12-156 typeinfo for messages_byname&lt;wchar_t&gt;.....</a>
<a href="#">12-157 libstdcxx - Class_messages_byname&lt;wchar_t&gt; Function Interfaces.....</a>
<a href="#">12-158 typeinfo for_numpunct&lt;char&gt;.....</a>
<a href="#">12-159 libstdcxx - Class_numpunct&lt;char&gt; Function Interfaces.....</a>
<a href="#">12-160 typeinfo for_numpunct&lt;wchar_t&gt;.....</a>
<a href="#">12-161 libstdcxx - Class_numpunct&lt;wchar_t&gt; Function Interfaces.....</a>
<a href="#">12-162 typeinfo for_numpunct_byname&lt;char&gt;.....</a>
<a href="#">12-163 libstdcxx - Class_numpunct_byname&lt;char&gt; Function Interfaces.....</a>
<a href="#">12-164 typeinfo for_numpunct_byname&lt;wchar_t&gt;.....</a>
<a href="#">12-165 libstdcxx - Class_numpunct_byname&lt;wchar_t&gt; Function Interfaces.....</a>
<a href="#">12-166 typeinfo for_codecvt_base.....</a>
<a href="#">12-167 Primary vtable for_codecvt&lt;char, char, mbstate_t&gt;.....</a>
<a href="#">12-168 typeinfo for_codecvt&lt;char, char, mbstate_t&gt;.....</a>
<a href="#">12-169 libstdcxx - Class_codecvt&lt;char, char, mbstate_t&gt; Function Interfaces.....</a>
<a href="#">12-170 Primary vtable for_codecvt&lt;wchar_t, char, mbstate_t&gt;.....</a>
<a href="#">12-171 typeinfo for_codecvt&lt;wchar_t, char, mbstate_t&gt;.....</a>
<a href="#">12-172 libstdcxx - Class_codecvt&lt;wchar_t, char, mbstate_t&gt; Function Interfaces.....</a>
<a href="#">12-173 Primary vtable for_codecvt_byname&lt;char, char, mbstate_t&gt;.....</a>
<a href="#">12-174 typeinfo for_codecvt_byname&lt;char, char, mbstate_t&gt;.....</a>
<a href="#">12-175 libstdcxx - Class_codecvt_byname&lt;char, char, mbstate_t&gt; Function Interfaces.....</a>
<a href="#">12-176 Primary vtable for_codecvt_byname&lt;wchar_t, char, mbstate_t&gt;.....</a>
<a href="#">12-177 typeinfo for_codecvt_byname&lt;wchar_t, char, mbstate_t&gt;.....</a>
<a href="#">12-178 libstdcxx - Class_codecvt_byname&lt;wchar_t, char, mbstate_t&gt; Function Interfaces.....</a>
<a href="#">12-179 typeinfo for_collate&lt;char&gt;.....</a>
<a href="#">12-180 libstdcxx - Class_collate&lt;char&gt; Function Interfaces.....</a>
<a href="#">12-181 typeinfo for_collate&lt;wchar_t&gt;.....</a>

[12-182 libstdcxx - Class collate<wchar\\_t> Function Interfaces](#).....  
[12-183 typeinfo for collate\\_byname<char>](#).....  
[12-184 libstdcxx - Class collate\\_byname<char> Function Interfaces](#).....  
[12-185 typeinfo for collate\\_byname<wchar\\_t>](#).....  
[12-186 libstdcxx - Class collate\\_byname<wchar\\_t> Function Interfaces](#).....  
[12-187 typeinfo for time\\_base](#).....  
[12-188 typeinfo for time\\_get\\_byname<char, istreambuf\\_iterator<char, char\\_traits<char>>](#).....  
[12-189 libstdcxx - Class time\\_get\\_byname<char, istreambuf\\_iterator<char, char\\_traits<char>>>](#).....  
[12-190 typeinfo for time\\_get\\_byname<wchar\\_t, istreambuf\\_iterator<wchar\\_t, char\\_traits<wchar\\_t>>>](#).....  
[12-191 libstdcxx - Class time\\_get\\_byname<wchar\\_t, istreambuf\\_iterator<wchar\\_t, char\\_traits<wchar\\_t>>>](#).....  
[12-192 typeinfo for time\\_put\\_byname<char, ostreambuf\\_iterator<char, char\\_traits<char>>>](#).....  
[12-193 libstdcxx - Class time\\_put\\_byname<char, ostreambuf\\_iterator<char, char\\_traits<char>>>](#).....  
[12-194 typeinfo for time\\_put\\_byname<wchar\\_t, ostreambuf\\_iterator<wchar\\_t, char\\_traits<wchar\\_t>>>](#).....  
[12-195 libstdcxx - Class time\\_put\\_byname<wchar\\_t, ostreambuf\\_iterator<wchar\\_t, char\\_traits<wchar\\_t>>>](#).....  
[12-196 libstdcxx - Class time\\_get<char, istreambuf\\_iterator<char, char\\_traits<char>>>](#).....  
[Function Interfaces](#).....  
[12-197 libstdcxx - Class time\\_get<wchar\\_t, istreambuf\\_iterator<wchar\\_t, char\\_traits<wchar\\_t>>>](#).....  
[Function Interfaces](#).....  
[12-198 typeinfo for time\\_put<char, ostreambuf\\_iterator<char, char\\_traits<char>>>](#).....  
[12-199 libstdcxx - Class time\\_put<char, ostreambuf\\_iterator<char, char\\_traits<char>>>](#).....  
[Function Interfaces](#).....  
[12-200 typeinfo for time\\_put<wchar\\_t, ostreambuf\\_iterator<wchar\\_t, char\\_traits<wchar\\_t>>>](#).....  
[Function Interfaces](#).....  
[12-201 libstdcxx - Class time\\_put<wchar\\_t, ostreambuf\\_iterator<wchar\\_t, char\\_traits<wchar\\_t>>>](#).....  
[Function Interfaces](#).....  
[12-202 libstdcxx - Class moneypunct<char, false> Function Interfaces](#).....  
[12-203 libstdcxx - Class moneypunct<char, true> Function Interfaces](#).....  
[12-204 libstdcxx - Class moneypunct<wchar\\_t, false> Function Interfaces](#).....  
[12-205 libstdcxx - Class moneypunct<wchar\\_t, true> Function Interfaces](#).....  
[12-206 typeinfo for moneypunct\\_byname<char, false>](#).....  
[12-207 libstdcxx - Class moneypunct\\_byname<char, false> Function Interfaces](#).....  
[12-208 typeinfo for moneypunct\\_byname<char, true>](#).....  
[12-209 libstdcxx - Class moneypunct\\_byname<char, true> Function Interfaces](#).....  
[12-210 typeinfo for moneypunct\\_byname<wchar\\_t, false>](#).....  
[12-211 libstdcxx - Class moneypunct\\_byname<wchar\\_t, false> Function Interfaces](#).....  
[12-212 typeinfo for moneypunct\\_byname<wchar\\_t, true>](#).....  
[12-213 libstdcxx - Class moneypunct\\_byname<wchar\\_t, true> Function Interfaces](#).....  
[12-214 typeinfo for money\\_base](#).....  
[12-215 typeinfo for money\\_get<char, istreambuf\\_iterator<char, char\\_traits<char>>>](#).....  
[12-216 libstdcxx - Class money\\_get<char, istreambuf\\_iterator<char, char\\_traits<char>>>](#).....  
[Function Interfaces](#).....  
[12-217 libstdcxx - Class money\\_get<char, istreambuf\\_iterator<char, char\\_traits<char>>>](#).....  
[Data Interfaces](#).....  
[12-218 typeinfo for money\\_get<wchar\\_t, istreambuf\\_iterator<wchar\\_t, char\\_traits<wchar\\_t>>>](#).....  
[12-219 libstdcxx - Class money\\_get<wchar\\_t, istreambuf\\_iterator<wchar\\_t, char\\_traits<wchar\\_t>>>](#).....  
[Function Interfaces](#).....  
[12-220 libstdcxx - Class money\\_get<wchar\\_t, istreambuf\\_iterator<wchar\\_t, char\\_traits<wchar\\_t>>>](#).....  
[Data Interfaces](#).....  
[12-221 typeinfo for money\\_put<char, ostreambuf\\_iterator<char, char\\_traits<char>>>](#)...

<a href="#">12-222 libstdcxx - Class money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;</a>	<a href="#">&gt; Function Interfaces</a>
<a href="#">12-223 libstdcxx - Class money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;</a>	<a href="#">&gt; Data Interfaces</a>
<a href="#">12-224 typeinfo for money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</a>	
<a href="#">12-225 libstdcxx - Class money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</a>	<a href;"="">&gt;&gt; Function Interfaces</a>
<a href="#">12-226 libstdcxx - Class money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</a>	<a href;"="">&gt;&gt; Data Interfaces</a>
<a href="#">12-227 libstdcxx - Class locale Function Interfaces</a>	
<a href="#">12-228 typeinfo for locale::facet</a>	
<a href="#">12-229 libstdcxx - facet functions Function Interfaces</a>	
<a href="#">12-230 typeinfo for num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;</a>	
<a href="#">12-231 libstdcxx - Class num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;</a>	<a href="#">Function Interfaces</a>
<a href="#">12-232 libstdcxx - Class num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;</a>	<a href="#">Data Interfaces</a>
<a href="#">12-233 typeinfo for num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;</a>	
<a href="#">12-234 libstdcxx - Class num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;</a>	<a href="#">Function Interfaces</a>
<a href="#">12-235 libstdcxx - Class num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;</a>	<a href="#">Data Interfaces</a>
<a href="#">12-236 typeinfo for num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;</a>	
<a href="#">12-237 libstdcxx - Class num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;</a>	<a href="#">&gt; Function Interfaces</a>
<a href="#">12-238 libstdcxx - Class num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;</a>	<a href;"="">&gt; Data Interfaces</a>
<a href="#">12-239 typeinfo for num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;</a>	
<a href="#">12-240 libstdcxx - Class num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;</a>	<a href="#">Function Interfaces</a>
<a href="#">12-241 libstdcxx - Class num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;</a>	<a href="#">Data Interfaces</a>
<a href="#">12-242 libstdcxx - Class gslice Function Interfaces</a>	
<a href="#">12-243 libstdcxx - Class basic_file&lt;char&gt; Function Interfaces</a>	
<a href="#">12-244 libstdcxx - Class valarray&lt;unsigned int&gt; Function Interfaces</a>	
<a href="#">12-245 libstdcxx - Class gnu_cxx:: pool&lt;true&gt; Function Interfaces</a>	
<a href="#">12-246 libstdcxx - Class gnu_cxx:: pool&lt;false&gt; Function Interfaces</a>	
<a href="#">12-247 libstdcxx - Class gnu_cxx::free_list Function Interfaces</a>	
<a href="#">12-248 libstdcxx - Class locale:: Impl Function Interfaces</a>	
<a href="#">12-249 libstdcxx - Namespace std Functions Function Interfaces</a>	
<a href="#">A-1 libc Function Interfaces</a>	
<a href="#">A-2 libc Data Interfaces</a>	
<a href="#">A-3 libcrypt Function Interfaces</a>	
<a href="#">A-4 libdl Function Interfaces</a>	
<a href="#">A-5 libgcc_s Function Interfaces</a>	
<a href="#">A-6 libm Function Interfaces</a>	
<a href="#">A-7 libm Data Interfaces</a>	
<a href="#">A-8 libpthread Function Interfaces</a>	
<a href="#">A-9 librht Function Interfaces</a>	
<a href="#">A-10 libutil Function Interfaces</a>	

## **Foreword**

This is version 5.0 of the Linux Standard Base Core Specification for S390X. This specification is one of a series of volumes under the collective title *Linux Standard Base*:

- Common
- Core
- Desktop
- Languages
- Imaging

Note that the Core and Desktop volumes consist of a generic volume augmented by an architecture-specific volume.

## **Status of this Document**

This is a released specification, version 5.0. Other documents may supersede or augment this specification.

A list of current released Linux Standard Base (LSB) specifications is available at <http://refspecs.linuxbase.org> (<http://refspecs.linuxbase.org/>).

If you wish to make comments regarding this document in a manner that is tracked by the LSB project, please submit them using our public bug database at <http://bugs.linux-base.org>. Please enter your feedback, carefully indicating the title of the section for which you are submitting feedback, and the volume and version of the specification where you found the problem, quoting the incorrect text if appropriate. If you are suggesting a new feature, please indicate what the problem you are trying to solve is. That is more important than the solution, in fact.

If you do not have or wish to create a bug database account then you can also e-mail feedback to <[lsb-discuss@lists.linuxfoundation.org](mailto:lsb-discuss@lists.linuxfoundation.org)> (subscribe (<http://lists.linuxfoundation.org/mailman/listinfo/lsb-discuss>), archives (<http://lists.linuxfoundation.org/pipermail/lsb-discuss/>)), and arrangements will be made to transpose the comments to our public bug database.

## Introduction

The LSB defines a binary interface for application programs that are compiled and packaged for LSB-conforming implementations on many different hardware architectures. A binary specification must include information specific to the computer processor architecture for which it is intended. To avoid the complexity of conditional descriptions, the specification has instead been divided into generic parts which are augmented by one of several architecture-specific parts, depending on the target processor architecture; the generic part will indicate when reference must be made to the architecture part, and vice versa.

This document should be used in conjunction with the documents it references. This document enumerates the system components it includes, but descriptions of those components may be included entirely or partly in this document, partly in other documents, or entirely in other reference documents. For example, the section that describes system service routines includes a list of the system routines supported in this interface, formal declarations of the data structures they use that are visible to applications, and a pointer to the underlying referenced specification for information about the syntax and semantics of each call. Only those routines not described in standards referenced by this document, or extensions to those standards, are described in the detail. Information referenced in this way is as much a part of this document as is the information explicitly included here.

The specification carries a version number of either the form  $x.y$  or  $x.y.z$ . This version number carries the following meaning:

1. The first number ( $x$ ) is the major version number. Versions sharing the same major version number shall be compatible in a backwards direction; that is, a newer version shall be compatible with an older version. Any deletion of a library results in a new major version number. Interfaces marked as deprecated may be removed from the specification at a major version change.
2. The second number ( $y$ ) is the minor version number. Libraries and individual interfaces may be added, but not removed. Interfaces may be marked as deprecated at a minor version change. Other minor changes may be permitted at the discretion of the LSB workgroup.
3. The third number ( $z$ ), if present, is the editorial level. Only editorial changes should be included in such versions.

Since this specification is a descriptive Application Binary Interface, and not a source level API specification, it is not possible to make a guarantee of 100% backward compatibility between major releases. However, it is the intent that those parts of the binary interface that are visible in the source level API will remain backward compatible from version to version, except where a feature marked as "Deprecated" in one release may be removed from a future release. Implementors are strongly encouraged to make use of symbol versioning to permit simultaneous support of applications conforming to different releases of this specification.

LSB is a trademark of the Linux Foundation. Developers of applications or implementations interested in using the trademark should see the Linux Foundation Certification Policy for details.

# I Introductory Elements

## **1 Scope**

### **1.1 General**

The Linux Standard Base (LSB) defines a system interface for compiled applications and a minimal environment for support of installation scripts. Its purpose is to enable a uniform industry standard environment for high-volume applications conforming to the LSB.

These specifications are composed of two basic parts: a common part describing those parts of the interface that remain constant across all implementations of the LSB, and an architecture-specific part describing the parts of the interface that vary by processor architecture. Together, the common part and the relevant architecture-specific part for a single hardware architecture provide a complete interface specification for compiled application programs on systems that share a common hardware architecture.

The LSB contains both a set of Application Program Interfaces (APIs) and Application Binary Interfaces (ABIs). APIs may appear in the source code of portable applications, while the compiled binary of that application may use the larger set of ABIs. A conforming implementation provides all of the ABIs listed here. The compilation system may replace (e.g. by macro definition) certain APIs with calls to one or more of the underlying binary interfaces, and may insert calls to binary interfaces as needed.

The LSB is primarily a binary interface definition. Not all of the source level APIs available to applications may be contained in this specification.

### **1.2 Module Specific Scope**

This is the S390X architecture specific part of the Core module of the Linux Standard Base (LSB). This part supplements the common part of the LSB Core module with those interfaces that differ between architectures.

This part should be used in conjunction with LSB Core - Generic, the common part. Whenever a section of the common part is supplemented by architecture-specific information, the common part includes a reference to the architecture-specific part. This part may also contain additional information that is not referenced in the common part.

Interfaces described in this part of the LSB Core Specification are mandatory except where explicitly listed otherwise. Interfaces described in the LSB Core module are supplemented by other LSB modules. All other modules depend on the presence of LSB Core.

## 2 References

### 2.1 Normative References

The following specifications are incorporated by reference into this specification. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced specification (including any amendments) applies.

**Note:** Where copies of a referenced specification are available on the World Wide Web, a Uniform Resource Locator (URL) is given, for informative purposes only. Such URL might at any given time resolve to a more recent copy of the specification, or be out of date (not resolve). Reference copies of specifications at the revision level indicated may be found at the Linux Foundation's Reference Specifications (<http://refspecs.linuxbase.org>) site.

**Table 2-1 Normative References**

Name	Title	URL
LSB Core - Generic	Linux Standard Base - Core Specification - Generic	<a href="http://www.linuxbase.org/spec/">http://www.linuxbase.org/spec/</a>
Filesystem Hierarchy Standard	Filesystem Hierarchy Standard (FHS) 3.0	<a href="http://refspecs.linuxbase.org/fhs">http://refspecs.linuxbase.org/fhs</a>
ISO C (1999)	ISO/IEC 9899:1999 - Programming Languages -- C	
ISO/IEC 14882: 2003 C+ + Language	ISO/IEC 14882: 2003 Programming languages --C++	
Itanium™ C++ ABI	Itanium™ C++ ABI (Revision 1.86)	<a href="http://refspecs.linuxfoundation.org/cxxabi-1.86.html">http://refspecs.linuxfoundation.org/cxxabi-1.86.html</a>
Large File Support	Large File Support	<a href="http://www.UNIX-systems.org/version2/whatsnew/lfs20mar.html">http://www.UNIX-systems.org/version2/whatsnew/lfs20mar.html</a>
Libncursesw API	Libncursesw API	<a href="http://invisible-island.net/ncurses/man/ncurses.3x.html">http://invisible-island.net/ncurses/man/ncurses.3x.html</a>
Libncursesw Placeholder	Libncursesw Specification Placeholder	<a href="http://refspecs.linux-foundation.org/libncursesw/libncursesw.html">http://refspecs.linux-foundation.org/libncursesw/libncursesw.html</a>
LINUX for zSeries Application Binary Interface Supplement	LINUX for zSeries Application Binary Interface Supplement	<a href="http://www.linux-foundation.org/spec/ELF/zSeries/lzsabi0_zSeries.html">http://www.linux-foundation.org/spec/ELF/zSeries/lzsabi0_zSeries.html</a>
POSIX 1003.1-2001 (ISO/IEC 9945-2003)	ISO/IEC 9945-1:2003 Information technology -- Portable Operating System Interface (POSIX) -- Part 1: Base Definitions ISO/IEC 9945-2:2003 Information technology -- Portable Operating System Interface (POSIX) -- Part 2: System Interfaces	<a href="http://www.unix.org/version3/">http://www.unix.org/version3/</a>

	ISO/IEC 9945-3:2003 Information technology -- Portable Operating System Interface (POSIX) -- Part 3: Shell and Utilities ISO/IEC 9945-4:2003 Information technology -- Portable Operating System Interface (POSIX) -- Part 4: Rationale Including Technical Cor. 1: 2004	
POSIX 1003.1-2008 (ISO/IEC 9945-2009)	Portable Operating System Interface (POSIX®) 2008 Edition / The Open Group Technical Standard Base Specifications, Issue 7	<a href="http://www.unix.org/version4/">http://www.unix.org/version4/</a>
SUSv2	CAE Specification, January 1997, System Interfaces and Headers (XSH), Issue 5 (ISBN: 1-85912-181-0, C606)	<a href="http://www.opengroup.org/publications/catalog/un.htm">http://www.opengroup.org/publications/catalog/un.htm</a>
SVID Issue 3	American Telephone and Telegraph Company, System V Interface Definition, Issue 3; Morristown, NJ, UNIX Press, 1989. (ISBN 0201566524)	
SVID Issue 4	System V Interface Definition, Fourth Edition	<a href="http://refspecs.linuxfoundation.org/svid4/">http://refspecs.linuxfoundation.org/svid4/</a>
System V ABI	System V Application Binary Interface, Edition 4.1	<a href="http://www.sco.com/developers/devspecs/gabi41.pdf">http://www.sco.com/developers/devspecs/gabi41.pdf</a>
System V ABI Update	System V Application Binary Interface - DRAFT - 17 December 2003	<a href="http://www.sco.com/developers/gabi/2003-12-17/contents.html">http://www.sco.com/developers/gabi/2003-12-17/contents.html</a>
X/Open Curses, Issue 7	X/Open Curses, Issue 7 (ISBN: 1-931624-83-6, The Open Group, November 2009)	<a href="https://www2.opengroup.org/ogsys/catalog/C094">https://www2.opengroup.org/ogsys/catalog/C094</a>
z/Architecture Principles of Operation	z/Architecture Principles of Operation	<a href="http://publibz.boulder.ibm.com/epubs/pdf/dz9zs001.pdf">http://publibz.boulder.ibm.com/epubs/pdf/dz9zs001.pdf</a>

## 2.2 Informative References/Bibliography

The documents listed below provide essential background information to implementors of this specification. These references are included for information only, and do not represent normative parts of this specification.

**Table 2-2 Other References**

Name	Title	URL
DWARF Debugging Information Format, Version 4	DWARF Debugging Information Format, Version 4 (June 10, 2010)	<a href="http://www.dwarfstd.org/doc/DWARF4.pdf">http://www.dwarfstd.org/doc/DWARF4.pdf</a>
IEC 60559/IEEE 754 Floating Point	IEC 60559:1989 Binary floating-point arithmetic for microprocessor systems	<a href="http://www.ieee.org/">http://www.ieee.org/</a>
ISO/IEC TR14652	ISO/IEC Technical Report 14652:2002 Specification method for cultural conventions	
ITU-T V.42	International Telecommunication Union Recommendation V.42 (2002): Error-correcting procedures for DCEs using asynchronous-to-synchronous conversion ITUV	<a href="http://www.itu.int/rec/recommendation.asp?type=folders&amp;lang=e&amp;parent=T-REC-V.42">http://www.itu.int/rec/recommendation.asp?type=folders&amp;lang=e&amp;parent=T-REC-V.42</a>
Li18nux Globalization Specification	LI18NUX 2000 Globalization Specification, Version 1.0 with Amendment 4	<a href="http://www.openi18n.org/docs/html/LI18NUX-2000-amd4.htm">http://www.openi18n.org/docs/html/LI18NUX-2000-amd4.htm</a>
Linux Allocated Device Registry	LINUX ALLOCATED DEVICES	<a href="http://www.lanana.org/docs/device-list/devices-2.6+.txt">http://www.lanana.org/docs/device-list/devices-2.6+.txt</a>
Linux Assigned Names And Numbers Authority	Linux Assigned Names And Numbers Authority	<a href="http://www.lanana.org/">http://www.lanana.org/</a>
Mozilla's NSS SSL Reference	Mozilla's NSS SSL Reference	<a href="http://www.mozilla.org/projects/security/pki/nss/ref/ssl/">http://www.mozilla.org/projects/security/pki/nss/ref/ssl/</a>
NSPR Reference	Mozilla's NSPR Reference	<a href="http://refspecs.linuxfoundation.org/NSPR_API_Reference/NSPR_API.html">http://refspecs.linuxfoundation.org/NSPR_API_Reference/NSPR_API.html</a>
PAM	Open Software Foundation, Request For Comments: 86.0 , October 1995, V. Samar & R.Schemers (SunSoft)	<a href="http://www.opengroup.org/tech/rfc/mirror-rfc/rfc86.0.txt">http://www.opengroup.org/tech/rfc/mirror-rfc/rfc86.0.txt</a>
RFC 1321: The MD5 Message-Digest Algorithm	IETF RFC 1321: The MD5 Message-Digest Algorithm	<a href="http://www.ietf.org/rfc/rfc1321.txt">http://www.ietf.org/rfc/rfc1321.txt</a>
RFC 1833: Binding Protocols for ONC RPC Version 2	IETF RFC 1833: Binding Protocols for ONC RPC Version 2	<a href="http://www.ietf.org/rfc/rfc1833.txt">http://www.ietf.org/rfc/rfc1833.txt</a>
RFC 1950: ZLIB Compressed Data Format Specification	IETF RFC 1950: ZLIB Compressed Data Format Specification	<a href="http://www.ietf.org/rfc/rfc1950.txt">http://www.ietf.org/rfc/rfc1950.txt</a>
RFC 1951: DEFLATE Compressed Data Format	IETF RFC 1951: DEFLATE Compressed	<a href="http://www.ietf.org/rfc/rfc1951.txt">http://www.ietf.org/rfc/rfc1951.txt</a>

Specification	Data Format Specification version 1.3	
RFC 1952: GZIP File Format Specification	IETF RFC 1952: GZIP file format specification version 4.3	<a href="http://www.ietf.org/rfc/rfc1952.txt">http://www.ietf.org/rfc/rfc1952.txt</a>
RFC 2440: OpenPGP Message Format	IETF RFC 2440: OpenPGP Message Format	<a href="http://www.ietf.org/rfc/rfc2440.txt">http://www.ietf.org/rfc/rfc2440.txt</a>
RFC 2821:Simple Mail Transfer Protocol	IETF RFC 2821: Simple Mail Transfer Protocol	<a href="http://www.ietf.org/rfc/rfc2821.txt">http://www.ietf.org/rfc/rfc2821.txt</a>
RFC 2822:Internet Message Format	IETF RFC 2822: Internet Message Format	<a href="http://www.ietf.org/rfc/rfc2822.txt">http://www.ietf.org/rfc/rfc2822.txt</a>
RFC 5531/4506 RPC & XDR	IETF RFC 5531 & 4506	<a href="http://www.ietf.org/">http://www.ietf.org/</a>
RFC 791:Internet Protocol	IETF RFC 791: Internet Protocol Specification	<a href="http://www.ietf.org/rfc/rfc791.txt">http://www.ietf.org/rfc/rfc791.txt</a>
RPM Package Format	RPM Package Format V3.0	<a href="http://www.rpm.org/max-rpm/s1-rpm-file-format-rpm-file-format.html">http://www.rpm.org/max-rpm/s1-rpm-file-format-rpm-file-format.html</a>
zlib Manual	zlib 1.2 Manual	<a href="http://www.gzip.org/zlib/">http://www.gzip.org/zlib/</a>

## 3 Requirements

### 3.1 Relevant Libraries

The libraries listed in [Table 3-1](#) shall be available on S390X Linux Standard Base systems, with the specified runtime names. These names override or supplement the names specified in the generic LSB (LSB Core - Generic) specification. The specified program interpreter, referred to as proginterp in this table, shall be used to load the shared libraries specified by DT\_NEEDED entries at run time.

**Table 3-1 Standard Library Names**

Library	Runtime Name
libc	libc.so.6
libcrypt	libcrypt.so.1
libdl	libdl.so.2
libgcc_s	libgcc_s.so.1
libm	libm.so.6
libncurses	libncurses.so.5
libncursesw	libncursesw.so.5
libpthread	libpthread.so.0
libstdcxx	libstdc++.so.6
libutil	libutil.so.1
libz	libz.so.1
proginterp	/lib64/ld-lsb-s390x.so.3

These libraries will be in an implementation-defined directory which the dynamic linker shall search by default.

### 3.2 LSB Implementation Conformance

A conforming implementation is necessarily architecture specific, and must provide the interfaces specified by both the generic LSB Core specification (LSB Core - Generic) and the relevant architecture specific part of the LSB Core Specification.

**Rationale:** An implementation must provide *at least* the interfaces specified in these specifications. It may also provide additional interfaces.

A conforming implementation shall satisfy the following requirements:

- A processor architecture represents a family of related processors which may not have identical feature sets. The architecture specific parts of the LSB Core Specification that supplement this specification for a given target processor architecture describe a minimum acceptable processor. The implementation shall provide all features of this processor, whether in hardware or through emulation transparent to the application.
- The implementation shall be capable of executing compiled applications having the format and using the system interfaces described in this specification.
- The implementation shall provide libraries containing the interfaces specified by this specification, and shall provide a dynamic linking mechanism that allows these interfaces to be attached to applications at runtime. All the interfaces shall behave as specified in this specification.
- The map of virtual memory provided by the implementation shall conform to the requirements of this specification.

- The implementation's low-level behavior with respect to function call linkage, system traps, signals, and other such activities shall conform to the formats described in this specification.
- The implementation shall provide all of the mandatory interfaces in their entirety.
- The implementation may provide one or more of the optional interfaces. Each optional interface that is provided shall be provided in its entirety. The product documentation shall state which optional interfaces are provided.
- The implementation shall provide all files and utilities specified as part of this specification in the format defined here and in other documents normatively included by reference. All commands and utilities shall behave as required by this specification. The implementation shall also provide all mandatory components of an application's runtime environment that are included or referenced in this specification.
- The implementation, when provided with standard data formats and values at a named interface, shall provide the behavior defined for those values and data formats at that interface. However, a conforming implementation may consist of components which are separately packaged and/or sold. For example, a vendor of a conforming implementation might sell the hardware, operating system, and windowing system as separately packaged items.
- The implementation may provide additional interfaces with different names. It may also provide additional behavior corresponding to data values outside the standard ranges, for standard named interfaces.

### 3.3 LSB Application Conformance

A conforming application containing object files is necessarily architecture specific, and must conform to both the generic LSB Core specification (LSB Core - Generic) and the relevant architecture specific part of the LSB Core Specification. A conforming application which contains no object files may be architecture neutral. Architecture neutral applications shall conform only to the requirements of the generic LSB Core specification (LSB Core - Generic).

A conforming application shall satisfy the following requirements:

- Executable files shall be either object files in the format defined in the Object Format section of this specification, or script files in a scripting language where the interpreter is required by this specification.
- Object files shall participate in dynamic linking as defined in the Program Loading and Linking section of this specification.
- Object files shall employ only the instructions, traps, and other low-level facilities defined as being for use by applications in the Low-Level System Information section of this specification
- If the application requires any optional interface defined in this specification in order to be installed or to execute successfully, the requirement for that optional interface shall be stated in the application's documentation.
- The application shall not use any interface or data format that is not required to be provided by a conforming implementation, unless such an interface or data format is supplied by another application through direct invocation of that application during execution. The other application must also be a conforming application, and the use of such interface or data format, as well as its source (in other words, the other conforming application), shall be identified in the documentation of the application.
- The application shall not use any values for a named interface that are reserved for vendor extensions.

A strictly conforming application shall not require or use any interface, facility, or implementation-defined extension not defined in this specification in order to be installed or to execute successfully.

## 4 Terms and Definitions

For the purposes of this document, the terms given in *ISO/IEC Directives, Part 2, Annex H* and the following apply.

### archLSB

Some LSB specification documents have both a generic, architecture-neutral part and an architecture-specific part. The latter describes elements whose definitions may be unique to a particular processor architecture. The term archLSB may be used in the generic part to refer to the corresponding section of the architecture-specific part.

### Binary Standard, ABI

The total set of interfaces that are available to be used in the compiled binary code of a conforming application, including the run-time details such as calling conventions, binary format, C++ name mangling, etc.

### Implementation-defined

Describes a value or behavior that is not defined by this document but is selected by an implementor. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence of the value or behavior. An application that relies on such a value or behavior cannot be assured to be portable across conforming implementations. The implementor shall document such a value or behavior so that it can be used correctly by an application.

### Shell Script

A file that is read by an interpreter (e.g., awk). The first line of the shell script includes a reference to its interpreter binary.

### Source Standard, API

The total set of interfaces that are available to be used in the source code of a conforming application. Due to translations, the Binary Standard and the Source Standard may contain some different interfaces.

### Undefined

Describes the nature of a value or behavior not defined by this document which results from use of an invalid program construct or invalid data input. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence or validity of the value or behavior. An application that relies on any particular value or behavior cannot be assured to be portable across conforming implementations.

### Unspecified

Describes the nature of a value or behavior not specified by this document which results from use of a valid program construct or valid data input. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence or validity of the value or behavior. An application that relies on any particular value or behavior cannot be assured to be portable across conforming implementations.

In addition, for the portions of this specification which build on IEEE Std 1003.1-2001, the definitions given in *IEEE Std 1003.1-2001, Base Definitions, Chapter 3* apply.

## 5 Documentation Conventions

Throughout this document, the following typographic conventions are used:

**function()**

the name of a function

**command**

the name of a command or utility

**CONSTANT**

a constant value

*parameter*

a parameter

**variable**

a variable

Throughout this specification, several tables of interfaces are presented. Each entry in these tables has the following format:

**name**

the name of the interface

**(symver)**

An optional symbol version identifier, if required.

**[refno]**

A reference number indexing the table of referenced specifications that follows this table.

For example,

**forkpty(GLIBC\_2.0) [SUSv4]**

refers to the interface named `forkpty()` with symbol version `GLIBC_2.0` that is defined in the reference indicated by the tag `SUSv4`.

**Note:** For symbols with versions which differ between architectures, the symbol versions are defined in the architecture specific parts of this module specification only. In the generic part, they will appear without symbol versions.

## **II Executable and Linking Format (ELF)**

## **6 Introduction**

Executable and Linking Format (ELF) defines the object format for compiled applications. This specification supplements the information found in [System V ABI Update](#) and [LINUX for zSeries Application Binary Interface Supplement](#), and is intended to document additions made since the publication of that document.

## 7 Low Level System Information

### 7.1 Machine Interface

#### 7.1.1 Processor Architecture

The z/Architecture is specified by the following documents

- [LINUX for zSeries Application Binary Interface Supplement](#)
- [z/Architecture Principles of Operation](#)

Only the non optional features of z/Architecture processor instruction set may be assumed to be present. An application should determine if any additional instruction set features are available before using those additional features. If a feature is not present, then a conforming application shall not use it.

Conforming applications shall not invoke the implementations underlying system call interface directly. The interfaces in the implementation base libraries shall be used instead.

**Rationale:** Implementation-supplied base libraries may use the system call interface but applications must not assume any particular operating system or kernel version is present.

Applications conforming to this specification must provide feedback to the user if a feature that is required for correct execution of the application is not present. Applications conforming to this specification should attempt to execute in a diminished capacity if a required instruction set feature is not present.

This specification does not provide any performance guarantees of a conforming system. A system conforming to this specification may be implemented in either hardware or software.

#### 7.1.2 Data Representation

LSB-conforming applications shall use the data representation as defined in Chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

##### 7.1.2.1 Byte Ordering

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

##### 7.1.2.2 Fundamental Types

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

##### 7.1.2.3 Aggregates and Unions

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

##### 7.1.2.4 Bit Fields

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### 7.2 Function Calling Sequence

LSB-conforming applications shall use the function calling sequence as defined in Chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

#### 7.2.1 Registers

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

## 7.2.2 Stack Frame

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

## 7.2.3 Parameter Passing

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

## 7.2.4 Variable Argument Lists

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

## 7.2.5 Return Values

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

# 7.3 Operating System Interface

LSB-conforming applications shall use the Operating System Interfaces as defined in Chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

## 7.3.1 Virtual Address Space

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

## 7.3.2 Page Size

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

## 7.3.3 Virtual Address Assignments

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

## 7.3.4 Managing the Process Stack

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

## 7.3.5 Coding Guidelines

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

## 7.3.6 Processor Execution Mode

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

## 7.3.7 Exception Interface

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

## 7.3.8 Signal Delivery

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### 7.3.8.1 Signal Handler Interface

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

# 7.4 Process Initialization

LSB-conforming applications shall use the Process Initialization as defined in Chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

## 7.4.1 Registers

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

## 7.4.2 Process Stack

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

## 7.5 Coding Examples

LSB-conforming applications may implement fundamental operations using the Coding Examples as defined in Chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### 7.5.1 Code Model Overview

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### 7.5.2 Function Prolog and Epilog

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### 7.5.3 Profiling

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### 7.5.4 Data Objects

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### 7.5.5 Function Calls

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### 7.5.6 Dynamic Stack Space Allocation

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

## 7.6 Debug Information

The LSB does not currently specify the format of Debug information.

## 8 Object Format

### 8.1 Introduction

LSB-conforming implementations shall support the Executable and Linking Format (ELF) object file format, as defined by the following documents:

- [System V ABI](#)
- [System V ABI Update](#)
- [LINUX for zSeries Application Binary Interface Supplement](#)
- [LSB Core - Generic](#)
- this document

### 8.2 ELF Header

#### 8.2.1 Machine Information

LSB-conforming applications shall use the Machine Information as defined in Chapter 2 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### 8.3 Sections

See chapter 2 of the [LINUX for zSeries Application Binary Interface Supplement](#).

#### 8.3.1 Special Sections

The following sections are defined in the [LINUX for zSeries Application Binary Interface Supplement](#).

**Table 8-1 ELF Special Sections**

Name	Type	Attributes
.got	SHT_PROGBITS	SHF_ALLOC+SHF_WRITE
.plt	SHT_PROGBITS	SHF_ALLOC+SHF_EXECINSTR

.got

This section holds the global offset table.

.plt

This section holds the procedure linkage table.

#### 8.3.2 Linux Special Sections

The following Linux S/390 specific sections are defined here.

**Table 8-2 Additional Special Sections**

Name	Type	Attributes
.rela.dyn	SHT_RELAT	SHF_ALLOC
.rela.plt	SHT_RELAT	SHF_ALLOC
.sbss	SHT_PROGBITS	SHF_WRITE

.rela.dyn

This section holds RELA type relocation information for all sections of a shared

library except the PLT.

#### .rela.plt

This section holds RELA type relocation information for the PLT section of a shared library or dynamically linked application

#### .sbss

This section holds uninitialized data that contribute to the program's memory image. The system initializes the data with zeroes when the program begins to run.

## 8.4 Symbol Table

LSB-conforming applications shall use the Symbol Table as defined in Chapter 2 of the [LINUX for zSeries Application Binary Interface Supplement](#).

## 8.5 Relocation

LSB-conforming applications shall use Relocations as defined in Chapter 2 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### 8.5.1 Relocation Types

See chapter 2 of the [LINUX for zSeries Application Binary Interface Supplement](#).

## 9 Program Loading and Dynamic Linking

### 9.1 Introduction

LSB-conforming implementations shall support the object file information and system actions that create running programs as specified in the [System V ABI](#), [System V ABI Update](#), [LINUX for zSeries Application Binary Interface Supplement](#) and as supplemented by the [LSB Core - Generic](#) and this document.

### 9.2 Program Loading

See Chapter 3 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### 9.3 Dynamic Linking

See Chapter 3 of the [LINUX for zSeries Application Binary Interface Supplement](#).

#### 9.3.1 Dynamic Section

The following dynamic entries are defined in the [LINUX for zSeries Application Binary Interface Supplement](#).

##### DT\_JMPREL

This entry is associated with a table of relocation entries for the procedure linkage table. This entry is mandatory both for executable and shared object files

##### DT\_PLTGOT

This entry's d\_ptr member gives the address of the first byte in the procedure linkage table

#### 9.3.2 Global Offset Table

See Chapter 3 of the [LINUX for zSeries Application Binary Interface Supplement](#).

#### 9.3.3 Function Addresses

See chapter 3 of the [LINUX for zSeries Application Binary Interface Supplement](#).

#### 9.3.4 Procedure Linkage Table

See chapter 3 of the [LINUX for zSeries Application Binary Interface Supplement](#).

## **III Base Libraries**

## 10 Libraries

An LSB-conforming implementation shall support base libraries which provide interfaces for accessing the operating system, processor and other hardware in the system.

Only interfaces and interface details which are unique to the S390X platform are defined here. This section should be used in conjunction with the corresponding section of LSB Core - Generic.

### 10.1 Program Interpreter/Dynamic Linker

The Program Interpreter shall be [/lib64/ld-lsb-s390x.so.3](#).

### 10.2 Interfaces for libc

[Table 10-1](#) defines the library name and shared object name for the libc library

**Table 10-1 libc Definition**

Library:	libc
SONAME:	libc.so.6

The behavior of the interfaces in this library is specified by the following specifications:

[LFS] [Large File Support](#)

[LSB] [LSB Core - Generic](#)

[RPC + XDR] [RFC 5531/4506 RPC & XDR](#)

[SUSv2] [SUSv2](#)

[SUSv3] [POSIX 1003.1-2001 \(ISO/IEC 9945-2003\)](#)

[SUSv4] [POSIX 1003.1-2008 \(ISO/IEC 9945-2009\)](#)

[SVID.4] [SVID Issue 4](#)

### 10.2.1 RPC

#### 10.2.1.1 Interfaces for RPC

An LSB conforming implementation shall provide the architecture specific functions for RPC specified in [Table 10-2](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-2 libc - RPC Function Interfaces**

authnone_create(GLIBC_2.2) <a href="#">[SVID.4]</a>	callrpc(GLIBC_2.2) <a href="#">[RPC + XDR]</a>	clnt_create(GLIBC_2.2) <a href="#">[SVID.4]</a>	clnt_pcreateerror(GLIBC_2.2) <a href="#">[SVID.4]</a>
clnt_perrno(GLIBC_2.2) <a href="#">[SVID.4]</a>	clnt_perror(GLIBC_2.2) <a href="#">[SVID.4]</a>	clnt_spcreateerror(GLIBC_2.2) <a href="#">[SVID.4]</a>	clnt_serrno(GLIBC_2.2) <a href="#">[SVID.4]</a>
clnt_sperror(GLIBC_2.2) <a href="#">[SVID.4]</a>	clntraw_create(GLIBC_2.2) <a href="#">[RPC + XDR]</a>	clnttcp_create(GLIBC_2.2) <a href="#">[RPC + XDR]</a>	clntudp_bufcreate(GLIBC_2.2) <a href="#">[RPC + XDR]</a>
clntudp_create(GLIBC_2.2) <a href="#">[RPC + XDR]</a>	key_decryptsession(GLIBC_2.2) <a href="#">[SVID.4]</a>	pmap_getport(GLIBC_2.2) <a href="#">[LSB]</a>	pmap_set(GLIBC_2.2) <a href="#">[LSB]</a>
pmap_unset(GLIBC_2.2) <a href="#">[LSB]</a>	svc_getreqset(GLIBC_2.2) <a href="#">[SVID.4]</a>	svc_register(GLIBC_2.2) <a href="#">[LSB]</a>	svc_run(GLIBC_2.2) <a href="#">[LSB]</a>
svc_sendreply(GLIBC_2.2) <a href="#">[LSB]</a>	svcerr_auth(GLIBC_2.2) <a href="#">[SVID.4]</a>	svcerr_decode(GLIBC_2.2) <a href="#">[SVID.4]</a>	svcerr_noproc(GLIBC_2.2) <a href="#">[SVID.4]</a>

svcerr_noprog(GLIBC_2.2) [SVID.4]	svcerr_progvers(GLIBC_2.2) [SVID.4]	svcerr_systemerr(GLIBC_2.2) [SVID.4]	svcerr_weakauth(GLIBC_2.2) [SVID.4]
svcfд_create(GLIBC_2.2) [RPC + XDR]	svcraw_create(GLIBC_2.2) [RPC + XDR]	svctcp_create(GLIBC_2.2) [LSB]	svcupd_create(GLIBC_2.2) [LSB]
xdr_accepted_replay(GLIBC_2.2) [SVID.4]	xdr_array(GLIBC_2.2) [SVID.4]	xdr_bool(GLIBC_2.2) [SVID.4]	xdr_bytes(GLIBC_2.2) [SVID.4]
xdr_callhdr(GLIBC_2.2) [SVID.4]	xdr_callmsg(GLIBC_2.2) [SVID.4]	xdr_char(GLIBC_2.2) [SVID.4]	xdr_double(GLIBC_2.2) [SVID.4]
xdr_enum(GLIBC_2.2) [SVID.4]	xdr_float(GLIBC_2.2) [SVID.4]	xdr_free(GLIBC_2.2) [SVID.4]	xdr_int(GLIBC_2.2) [SVID.4]
xdr_long(GLIBC_2.2) [SVID.4]	xdr_opaque(GLIBC_2.2) [SVID.4]	xdr_opaque_auth(GLIBC_2.2) [SVID.4]	xdr_pointer(GLIBC_2.2) [SVID.4]
xdr_reference(GLIBC_2.2) [SVID.4]	xdr_rejected_reply(GLIBC_2.2) [SVID.4]	xdr_replymsg(GLIBC_2.2) [SVID.4]	xdr_short(GLIBC_2.2) [SVID.4]
xdr_string(GLIBC_2.2) [SVID.4]	xdr_u_char(GLIBC_2.2) [SVID.4]	xdr_u_int(GLIBC_2.2) [LSB]	xdr_u_long(GLIBC_2.2) [SVID.4]
xdr_u_short(GLIBC_2.2) [SVID.4]	xdr_union(GLIBC_2.2) [SVID.4]	xdr_vector(GLIBC_2.2) [SVID.4]	xdr_void(GLIBC_2.2) [SVID.4]
xdr_wrapstring(GLIBC_2.2) [SVID.4]	xdrmem_create(GLIBC_2.2) [SVID.4]	xdrrec_create(GLIBC_2.2) [SVID.4]	xdrrec_endofrecord(GLIBC_2.2) [RPC + XDR]
xdrrec_eof(GLIBC_2.2) [SVID.4]	xdrrec_skiprecord(GLIBC_2.2) [RPC + XDR]	xdrstdio_create(GLIBC_2.2) [LSB]	

An LSB conforming implementation shall provide the architecture specific deprecated functions for RPC specified in [Table 10-3](#), with the full mandatory functionality as described in the referenced underlying specification.

**Note:** These interfaces are deprecated, and applications should avoid using them. These interfaces may be withdrawn in future releases of this specification.

**Table 10-3 libc - RPC Deprecated Function Interfaces**

key_decryptsession(GLIBC_2.2) [SVID.4]			
-------------------------------------------	--	--	--

## 10.2.2 Epoll

### 10.2.2.1 Interfaces for Epoll

No external functions are defined for libc - Epoll in this part of the specification. See also the generic specification.

## 10.2.3 System Calls

### 10.2.3.1 Interfaces for System Calls

An LSB conforming implementation shall provide the architecture specific functions for System Calls specified in [Table 10-4](#), with the full mandatory functionality as described

in the referenced underlying specification.

**Table 10-4 libc - System Calls Function Interfaces**

<code>_fxstat(GLIBC_2.2) [LSB]</code>	<code>_getpgid(GLIBC_2.2) [LSB]</code>	<code>_lxstat(GLIBC_2.2) [LSB]</code>	<code>_xmknod(GLIBC_2.2) [LSB]</code>
<code>_xstat(GLIBC_2.2) [LSB]</code>	<code>access(GLIBC_2.2) [SUSv4]</code>	<code>acct(GLIBC_2.2) [LSB]</code>	<code>alarm(GLIBC_2.2) [SUSv4]</code>
<code>backtrace(GLIBC_2.2) [LSB]</code>	<code>backtrace_symbol_s(GLIBC_2.2) [LSB]</code>	<code>backtrace_symbol_s_fd(GLIBC_2.2) [LSB]</code>	<code>brk(GLIBC_2.2) [SUSv2]</code>
<code>chdir(GLIBC_2.2) [SUSv4]</code>	<code>chmod(GLIBC_2.2) [SUSv4]</code>	<code>chown(GLIBC_2.2) [SUSv4]</code>	<code>chroot(GLIBC_2.2) [SUSv2]</code>
<code>clock(GLIBC_2.2) [SUSv4]</code>	<code>close(GLIBC_2.2) [SUSv4]</code>	<code>closedir(GLIBC_2.2) [SUSv4]</code>	<code>creat(GLIBC_2.2) [SUSv4]</code>
<code>dup(GLIBC_2.2) [SUSv4]</code>	<code>dup2(GLIBC_2.2) [SUSv4]</code>	<code>execl(GLIBC_2.2) [SUSv4]</code>	<code>execle(GLIBC_2.2) [SUSv4]</code>
<code>execlp(GLIBC_2.2) [SUSv4]</code>	<code>execv(GLIBC_2.2) [SUSv4]</code>	<code>execve(GLIBC_2.2) [SUSv4]</code>	<code>execvp(GLIBC_2.2) [SUSv4]</code>
<code>exit(GLIBC_2.2) [SUSv4]</code>	<code>fchdir(GLIBC_2.2) [SUSv4]</code>	<code>fchmod(GLIBC_2.2) [SUSv4]</code>	<code>fchown(GLIBC_2.2) [SUSv4]</code>
<code>fcntl(GLIBC_2.2) [LSB]</code>	<code>fdatasync(GLIBC_2.2) [SUSv4]</code>	<code>fexecve(GLIBC_2.2) [SUSv4]</code>	<code>flock(GLIBC_2.2) [LSB]</code>
<code>fork(GLIBC_2.2) [SUSv4]</code>	<code>fstatfs(GLIBC_2.2) [LSB]</code>	<code>fstatvfs(GLIBC_2.2) [SUSv4]</code>	<code>fsync(GLIBC_2.2) [SUSv4]</code>
<code>ftime(GLIBC_2.2) [SUSv3]</code>	<code>ftruncate(GLIBC_2.2) [SUSv4]</code>	<code>getcontext(GLIBC_2.2) [SUSv3]</code>	<code>getdtablesize(GLIBC_2.2) [LSB]</code>
<code>getegid(GLIBC_2.2) [SUSv4]</code>	<code>geteuid(GLIBC_2.2) [SUSv4]</code>	<code>getgid(GLIBC_2.2) [SUSv4]</code>	<code>getgroups(GLIBC_2.2) [SUSv4]</code>
<code>getitimer(GLIBC_2.2) [SUSv4]</code>	<code>getloadavg(GLIBC_2.2) [LSB]</code>	<code>getpagesize(GLIBC_2.2) [LSB]</code>	<code>getpgid(GLIBC_2.2) [SUSv4]</code>
<code>getpgrp(GLIBC_2.2) [SUSv4]</code>	<code>getpid(GLIBC_2.2) [SUSv4]</code>	<code>getppid(GLIBC_2.2) [SUSv4]</code>	<code>getpriority(GLIBC_2.2) [SUSv4]</code>
<code>getrlimit(GLIBC_2.2) [LSB]</code>	<code>getrusage(GLIBC_2.2) [SUSv4]</code>	<code>getsid(GLIBC_2.2) [SUSv4]</code>	<code>getuid(GLIBC_2.2) [SUSv4]</code>
<code>getwd(GLIBC_2.2) [SUSv3]</code>	<code>initgroups(GLIBC_2.2) [LSB]</code>	<code>ioctl(GLIBC_2.2) [LSB]</code>	<code>kill(GLIBC_2.2) [LSB]</code>
<code>killpg(GLIBC_2.2) [SUSv4]</code>	<code>lchown(GLIBC_2.2) [SUSv4]</code>	<code>link(GLIBC_2.2) [LSB]</code>	<code>lockf(GLIBC_2.2) [SUSv4]</code>
<code>lseek(GLIBC_2.2) [SUSv4]</code>	<code>mkdir(GLIBC_2.2) [SUSv4]</code>	<code>mkdirat(GLIBC_2.2) [SUSv4]</code>	<code>mlock(GLIBC_2.2) [SUSv4]</code>
<code>mlockall(GLIBC_2.2) [SUSv4]</code>	<code>mmap(GLIBC_2.2) [SUSv4]</code>	<code>mprotect(GLIBC_2.2) [SUSv4]</code>	<code>mremap(GLIBC_2.2) [LSB]</code>
<code>msync(GLIBC_2.2) [SUSv4]</code>	<code>munlock(GLIBC_2.2) [SUSv4]</code>	<code>munlockall(GLIBC_2.2) [SUSv4]</code>	<code>munmap(GLIBC_2.2) [SUSv4]</code>
<code>nanosleep(GLIBC_2.2) [SUSv4]</code>	<code>nice(GLIBC_2.2) [SUSv4]</code>	<code>open(GLIBC_2.2) [SUSv4]</code>	<code>opendir(GLIBC_2.2) [SUSv4]</code>
<code>pathconf(GLIBC_2.2) [SUSv4]</code>	<code>pause(GLIBC_2.2) [SUSv4]</code>	<code>pipe(GLIBC_2.2) [SUSv4]</code>	<code>poll(GLIBC_2.2) [SUSv4]</code>
<code>pread(GLIBC_2.2) [SUSv4]</code>	<code>pselect(GLIBC_2.2) [SUSv4]</code>	<code>ptrace(GLIBC_2.2) [LSB]</code>	<code>pwrite(GLIBC_2.2) [SUSv4]</code>

read(GLIBC_2.2) [SUSv4]	readdir(GLIBC_2.2) [SUSv4]	readdir_r(GLIBC_2.2) [SUSv4]	readlink(GLIBC_2.2) [SUSv4]
readv(GLIBC_2.2) [SUSv4]	rename(GLIBC_2.2) [SUSv4]	rmdir(GLIBC_2.2) [SUSv4]	sbrk(GLIBC_2.2) [SUSv2]
sched_get_priority_max(GLIBC_2.2) [SUSv4]	sched_get_priority_min(GLIBC_2.2) [SUSv4]	sched_getparam(GLIBC_2.2) [SUSv4]	sched_getschedule(GLIBC_2.2) [SUSv4]
sched_rr_get_interval(GLIBC_2.2) [SUSv4]	sched_setparam(GLIBC_2.2) [SUSv4]	sched_setschedule(GLIBC_2.2) [LSB]	sched_yield(GLIBC_2.2) [SUSv4]
select(GLIBC_2.2) [SUSv4]	setcontext(GLIBC_2.2) [SUSv3]	setegid(GLIBC_2.2) [SUSv4]	seteuid(GLIBC_2.2) [SUSv4]
setgid(GLIBC_2.2) [SUSv4]	setitimer(GLIBC_2.2) [SUSv4]	setpgid(GLIBC_2.2) [SUSv4]	setpgrp(GLIBC_2.2) [SUSv4]
setpriority(GLIBC_2.2) [SUSv4]	setregid(GLIBC_2.2) [SUSv4]	setreuid(GLIBC_2.2) [SUSv4]	setrlimit(GLIBC_2.2) [LSB]
setrlimit64(GLIBC_2.2) [LFS]	setsid(GLIBC_2.2) [SUSv4]	setuid(GLIBC_2.2) [SUSv4]	sleep(GLIBC_2.2) [SUSv4]
statfs(GLIBC_2.2) [LSB]	statvfs(GLIBC_2.2) [SUSv4]	stime(GLIBC_2.2) [LSB]	symlink(GLIBC_2.2) [SUSv4]
sync(GLIBC_2.2) [SUSv4]	sysconf(GLIBC_2.2) [LSB]	sysinfo(GLIBC_2.2) [LSB]	time(GLIBC_2.2) [SUSv4]
times(GLIBC_2.2) [SUSv4]	truncate(GLIBC_2.2) [SUSv4]	ulimit(GLIBC_2.2) [SUSv4]	umask(GLIBC_2.2) [SUSv4]
uname(GLIBC_2.2) [SUSv4]	unlink(GLIBC_2.2) [LSB]	utime(GLIBC_2.2) [SUSv4]	utimes(GLIBC_2.2) [SUSv4]
vfork(GLIBC_2.2) [SUSv3]	wait(GLIBC_2.2) [SUSv4]	wait4(GLIBC_2.2) [LSB]	waitid(GLIBC_2.2) [SUSv4]
waitpid(GLIBC_2.2) [SUSv4]	write(GLIBC_2.2) [SUSv4]	writev(GLIBC_2.2) [SUSv4]	

An LSB conforming implementation shall provide the architecture specific deprecated functions for System Calls specified in [Table 10-5](#), with the full mandatory functionality as described in the referenced underlying specification.

**Note:** These interfaces are deprecated, and applications should avoid using them. These interfaces may be withdrawn in future releases of this specification.

**Table 10-5 libc - System Calls Deprecated Function Interfaces**

fstatfs(GLIBC_2.2) [LSB]	getdtablesize(GLIBC_2.2) [LSB]	getpagesize(GLIBC_2.2) [LSB]	getwd(GLIBC_2.2) [SUSv3]
statfs(GLIBC_2.2) [LSB]			

## 10.2.4 Standard I/O

### 10.2.4.1 Interfaces for Standard I/O

An LSB conforming implementation shall provide the architecture specific functions for Standard I/O specified in [Table 10-6](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-6 libc - Standard I/O Function Interfaces**

<code>_IO_feof(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>_IO_getc(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>_IO_putc(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>_IO_puts(GLIBC_2.2)</code> <a href="#">[LSB]</a>
<code>__fprintf_chk(GLIBC_2.4)</code> <a href="#">[LSB]</a>	<code>__printf_chk(GLIBC_2.4)</code> <a href="#">[LSB]</a>	<code>__snprintf_chk(GLIBC_2.4)</code> <a href="#">[LSB]</a>	<code>__sprintf_chk(GLIBC_2.4)</code> <a href="#">[LSB]</a>
<code>__vfprintf_chk(GLIBC_2.4)</code> <a href="#">[LSB]</a>	<code>__vprintf_chk(GLIBC_2.4)</code> <a href="#">[LSB]</a>	<code>__vsnprintf_chk(GLIBC_2.4)</code> <a href="#">[LSB]</a>	<code>__vsprintf_chk(GLIBC_2.4)</code> <a href="#">[LSB]</a>
<code>asprintf(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>asprintf(GLIBC_2.4)</code> <a href="#">[LSB]</a>	<code>clearerr(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>clearerr_unlocked(GLIBC_2.2)</code> <a href="#">[LSB]</a>
<code>ctermid(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>dprintf(GLIBC_2.4)</code> <a href="#">[SUSv4]</a>	<code>fclose(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>fdopen(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>feof(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>feof_unlocked(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>ferror(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>ferror_unlocked(GLIBC_2.2)</code> <a href="#">[LSB]</a>
<code>fflush(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>fflush_unlocked(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>fgetc(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>fgetc_unlocked(GLIBC_2.2)</code> <a href="#">[LSB]</a>
<code>fgetpos(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>fgets(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>fgets_unlocked(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>fgetwc_unlocked(GLIBC_2.2)</code> <a href="#">[LSB]</a>
<code>fgetws_unlocked(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>fileno(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>fileno_unlocked(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>flockfile(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>fopen(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>fprintf(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>fprintf(GLIBC_2.4)</code> <a href="#">[SUSv4]</a>	<code>fputc(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>fputc_unlocked(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>fputs(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>fputs_unlocked(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>fputwc_unlocked(GLIBC_2.2)</code> <a href="#">[LSB]</a>
<code>fputws_unlocked(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>fread(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>fread_unlocked(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>freopen(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>fscanf(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>fscanf(GLIBC_2.4)</code> <a href="#">[LSB]</a>	<code>fseek(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>fseeko(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>fsetpos(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>ftell(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>ftello(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>fwrite(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>fwrite_unlocked(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>getc(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>getc_unlocked(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>getchar(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>getchar_unlocked(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>getdelim(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>getline(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>getw(GLIBC_2.2)</code> <a href="#">[SUSv2]</a>
<code>getwc_unlocked(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>getwchar_unlocked(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>pclose(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>popen(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>printf(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>printf(GLIBC_2.4)</code> <a href="#">[SUSv4]</a>	<code>putc(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>putc_unlocked(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>putchar(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>putchar_unlocked(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>puts(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>putw(GLIBC_2.2)</code> <a href="#">[SUSv2]</a>
<code>putwc_unlocked(GLIBC_2.2)</code>	<code>putwchar_unlocked(GLIBC_2.2)</code>	<code>remove(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>rewind(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>

[LSB]	[LSB]		
rewinddir(GLIBC_2.2) [SUSv4]	scanf(GLIBC_2.2) [LSB]	scanf(GLIBC_2.4) [LSB]	seekdir(GLIBC_2.2) [SUSv4]
setbuf(GLIBC_2.2) [SUSv4]	setbuffer(GLIBC_2.2) [LSB]	setvbuf(GLIBC_2.2) [SUSv4]	snprintf(GLIBC_2.2) [SUSv4]
snprintf(GLIBC_2.4) [SUSv4]	sprintf(GLIBC_2.2) [SUSv4]	sprintf(GLIBC_2.4) [SUSv4]	sscanf(GLIBC_2.2) [LSB]
sscanf(GLIBC_2.4) [LSB]	telldir(GLIBC_2.2) [SUSv4]	tempnam(GLIBC_2.2) [SUSv4]	ungetc(GLIBC_2.2) [SUSv4]
vasprintf(GLIBC_2.2) [LSB]	vasprintf(GLIBC_2.4) [LSB]	vdprintf(GLIBC_2.2) [SUSv4]	vdprintf(GLIBC_2.4) [SUSv4]
vfprintf(GLIBC_2.2) [SUSv4]	vfprintf(GLIBC_2.4) [SUSv4]	vprintf(GLIBC_2.2) [SUSv4]	vprintf(GLIBC_2.4) [SUSv4]
vsnprintf(GLIBC_2.2) [SUSv4]	vsnprintf(GLIBC_2.4) [SUSv4]	vsprintf(GLIBC_2.2) [SUSv4]	vsprintf(GLIBC_2.4) [SUSv4]

An LSB conforming implementation shall provide the architecture specific deprecated functions for Standard I/O specified in [Table 10-7](#), with the full mandatory functionality as described in the referenced underlying specification.

**Note:** These interfaces are deprecated, and applications should avoid using them. These interfaces may be withdrawn in future releases of this specification.

**Table 10-7 libc - Standard I/O Deprecated Function Interfaces**

asprintf(GLIBC_2.2) [LSB]	fprintf(GLIBC_2.2) [SUSv4]	fscanf(GLIBC_2.2) [LSB]	printf(GLIBC_2.2) [SUSv4]
scanf(GLIBC_2.2) [LSB]	snprintf(GLIBC_2.2) [SUSv4]	sprintf(GLIBC_2.2) [SUSv4]	sscanf(GLIBC_2.2) [LSB]
tempnam(GLIBC_2.2) [SUSv4]	vasprintf(GLIBC_2.2) [LSB]	vdprintf(GLIBC_2.2) [SUSv4]	vfprintf(GLIBC_2.2) [SUSv4]
vprintf(GLIBC_2.2) [SUSv4]	vsnprintf(GLIBC_2.2) [SUSv4]	vsprintf(GLIBC_2.2) [SUSv4]	

An LSB conforming implementation shall provide the architecture specific data interfaces for Standard I/O specified in [Table 10-8](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-8 libc - Standard I/O Data Interfaces**

stderr(GLIBC_2.2) [SUSv4]	stdin(GLIBC_2.2) [SUSv4]	stdout(GLIBC_2.2) [SUSv4]	
---------------------------	--------------------------	---------------------------	--

## 10.2.5 Signal Handling

### 10.2.5.1 Interfaces for Signal Handling

An LSB conforming implementation shall provide the architecture specific functions for Signal Handling specified in [Table 10-9](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-9 libc - Signal Handling Function Interfaces**

__libc_current_sigrtmax(GLIBC_2.2) [LSB]	__libc_current_sigrtmin(GLIBC_2.2) [LSB]	__sigsetjmp(GLIBC_2.2) [LSB]	__sysv_signal(GLIBC_2.2) [LSB]
__xpg_sigpause(G)	bsd_signal(GLIBC_2.2)	psignal(GLIBC_2.2)	raise(GLIBC_2.2)

LIBC_2.2) <a href="#">[LSB]</a>	C_2.2) <a href="#">[SUSv3]</a>	2) <a href="#">[SUSv4]</a>	<a href="#">[SUSv4]</a>
sigaction(GLIBC_2.2) <a href="#">[SUSv4]</a>	sigaddset(GLIBC_2.2) <a href="#">[SUSv4]</a>	sigaltstack(GLIBC_2.2) <a href="#">[SUSv4]</a>	sigandset(GLIBC_2.2) <a href="#">[LSB]</a>
sigdelset(GLIBC_2.2) <a href="#">[SUSv4]</a>	sigemptyset(GLIBC_2.2) <a href="#">[SUSv4]</a>	sigfillset(GLIBC_2.2) <a href="#">[SUSv4]</a>	sighold(GLIBC_2.2) <a href="#">[SUSv4]</a>
sigignore(GLIBC_2.2) <a href="#">[SUSv4]</a>	siginterrupt(GLIBC_2.2) <a href="#">[SUSv4]</a>	sigisemptyset(GLIBC_2.2) <a href="#">[LSB]</a>	sigismember(GLIBC_2.2) <a href="#">[SUSv4]</a>
siglongjmp(GLIBC_2.2) <a href="#">[SUSv4]</a>	signal(GLIBC_2.2) <a href="#">[SUSv4]</a>	sigorset(GLIBC_2.2) <a href="#">[LSB]</a>	sigpause(GLIBC_2.2) <a href="#">[LSB]</a>
sigpending(GLIBC_2.2) <a href="#">[SUSv4]</a>	sigprocmask(GLIBC_2.2) <a href="#">[SUSv4]</a>	sigqueue(GLIBC_2.2) <a href="#">[SUSv4]</a>	sigrelse(GLIBC_2.2) <a href="#">[SUSv4]</a>
sigreturn(GLIBC_2.2) <a href="#">[LSB]</a>	sigset(GLIBC_2.2) <a href="#">[SUSv4]</a>	sigsuspend(GLIBC_2.2) <a href="#">[SUSv4]</a>	sigtimedwait(GLIBC_2.2) <a href="#">[SUSv4]</a>
sigwait(GLIBC_2.2) <a href="#">[SUSv4]</a>	sigwaitinfo(GLIBC_2.2) <a href="#">[SUSv4]</a>		

An LSB conforming implementation shall provide the architecture specific deprecated functions for Signal Handling specified in [Table 10-10](#), with the full mandatory functionality as described in the referenced underlying specification.

**Note:** These interfaces are deprecated, and applications should avoid using them. These interfaces may be withdrawn in future releases of this specification.

**Table 10-10 libc - Signal Handling Deprecated Function Interfaces**

sigpause(GLIBC_2.2) <a href="#">[LSB]</a>			
-------------------------------------------	--	--	--

An LSB conforming implementation shall provide the architecture specific data interfaces for Signal Handling specified in [Table 10-11](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-11 libc - Signal Handling Data Interfaces**

_sys_siglist(GLIBC_2.3.3) <a href="#">[LSB]</a>			
-------------------------------------------------	--	--	--

## 10.2.6 Localization Functions

### 10.2.6.1 Interfaces for Localization Functions

An LSB conforming implementation shall provide the architecture specific functions for Localization Functions specified in [Table 10-12](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-12 libc - Localization Functions Function Interfaces**

bind_textdomain_codeset(GLIBC_2.2) <a href="#">[LSB]</a>	bindtextdomain(GLIBC_2.2) <a href="#">[LSB]</a>	catclose(GLIBC_2.2) <a href="#">[SUSv4]</a>	catgets(GLIBC_2.2) <a href="#">[SUSv4]</a>
catopen(GLIBC_2.2) <a href="#">[SUSv4]</a>	dcgettext(GLIBC_2.2) <a href="#">[LSB]</a>	dcngettext(GLIBC_2.2) <a href="#">[LSB]</a>	dgettext(GLIBC_2.2) <a href="#">[LSB]</a>
dnggettext(GLIBC_2.2) <a href="#">[LSB]</a>	gettext(GLIBC_2.2) <a href="#">[LSB]</a>	iconv(GLIBC_2.2) <a href="#">[SUSv4]</a>	iconv_close(GLIBC_2.2) <a href="#">[SUSv4]</a>
iconv_open(GLIBC_2.2) <a href="#">[SUSv4]</a>	localeconv(GLIBC_2.2) <a href="#">[SUSv4]</a>	ngettext(GLIBC_2.2) <a href="#">[LSB]</a>	nl_langinfo(GLIBC_2.2) <a href="#">[SUSv4]</a>
setlocale(GLIBC_	textdomain(GLIB		

2.2) [SUSv4]	C_2.2) [LSB]		
--------------	--------------	--	--

An LSB conforming implementation shall provide the architecture specific data interfaces for Localization Functions specified in [Table 10-13](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-13 libc - Localization Functions Data Interfaces**

_nl_msg_cat_cntr( GLIBC_2.2) <a href="#">[LSB]</a>			
----------------------------------------------------------	--	--	--

## 10.2.7 Posix Spawn Option

### 10.2.7.1 Interfaces for Posix Spawn Option

An LSB conforming implementation shall provide the architecture specific functions for Posix Spawn Option specified in [Table 10-14](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-14 libc - Posix Spawn Option Function Interfaces**

posix_spawn(GLIBC_2.15) <a href="#">[SUSv4]</a>	posix_spawn_file_actions_addclose(GLIBC_2.2) <a href="#">[SUSv4]</a>	posix_spawn_file_actions_adddup2(GLIBC_2.2) <a href="#">[SUSv4]</a>	posix_spawn_file_actions_addopen(GLIBC_2.2) <a href="#">[SUSv4]</a>
posix_spawn_file_actions_destroy(GLIBC_2.2) <a href="#">[SUSv4]</a>	posix_spawn_file_actions_init(GLIBC_2.2) <a href="#">[SUSv4]</a>	posix_spawnattr_destroy(GLIBC_2.2) <a href="#">[SUSv4]</a>	posix_spawnattr_getflags(GLIBC_2.2) <a href="#">[SUSv4]</a>
posix_spawnattr_gtpgroup(GLIBC_2.2) <a href="#">[SUSv4]</a>	posix_spawnattr_gtcschedparam(GLIBC_2.2) <a href="#">[SUSv4]</a>	posix_spawnattr_gtcschedpolicy(GLIBC_2.2) <a href="#">[SUSv4]</a>	posix_spawnattr_gtsigdefault(GLIBC_2.2) <a href="#">[SUSv4]</a>
posix_spawnattr_gtsigmask(GLIBC_2.2) <a href="#">[SUSv4]</a>	posix_spawnattr_init(GLIBC_2.2) <a href="#">[SUSv4]</a>	posix_spawnattr_setflags(GLIBC_2.2) <a href="#">[SUSv4]</a>	posix_spawnattr_setpgroup(GLIBC_2.2) <a href="#">[SUSv4]</a>
posix_spawnattr_setschedparam(GLIBC_2.2) <a href="#">[SUSv4]</a>	posix_spawnattr_setschedpolicy(GLIBC_2.2) <a href="#">[SUSv4]</a>	posix_spawnattr_setsigdefault(GLIBC_2.2) <a href="#">[SUSv4]</a>	posix_spawnattr_setsigmask(GLIBC_2.2) <a href="#">[SUSv4]</a>
posix_spawnp(GLIBC_2.15) <a href="#">[SUSv4]</a>			

## 10.2.8 Posix Advisory Option

### 10.2.8.1 Interfaces for Posix Advisory Option

An LSB conforming implementation shall provide the architecture specific functions for Posix Advisory Option specified in [Table 10-15](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-15 libc - Posix Advisory Option Function Interfaces**

posix_fadvise(GLIBC_2.2) <a href="#">[SUSv4]</a>	posix_fallocate(GLIBC_2.2) <a href="#">[SUSv4]</a>	posix_madvise(GLIBC_2.2) <a href="#">[SUSv4]</a>	posix_memalign(GLIBC_2.2) <a href="#">[SUSv4]</a>
-----------------------------------------------------	-------------------------------------------------------	-----------------------------------------------------	------------------------------------------------------

## 10.2.9 Socket Interface

### 10.2.9.1 Interfaces for Socket Interface

An LSB conforming implementation shall provide the architecture specific functions for Socket Interface specified in [Table 10-16](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-16 libc - Socket Interface Function Interfaces**

__h_errno_locatio n(GLIBC_2.2) [LSB]	accept(GLIBC_2. 2) [SUSv4]	bind(GLIBC_2.2) [SUSv4]	bindresvport(GLI BC_2.2) [LSB]
connect(GLIBC_2 .2) [SUSv4]	gethostid(GLIBC_ 2.2) [SUSv4]	gethostname(GLI BC_2.2) [SUSv4]	getpeername(GLI BC_2.2) [SUSv4]
getsockname(GLI BC_2.2) [SUSv4]	getsockopt(GLIB C_2.2) [LSB]	if_freenameindex(	if_indextoname(G LIBC_2.2) [SUSv4]
if_nameindex(GLI BC_2.2) [SUSv4]	if_nametoindex(G LIBC_2.2) [SUSv4]	listen(GLIBC_2.2) [SUSv4]	recv(GLIBC_2.2) [SUSv4]
recvfrom(GLIBC_ 2.2) [SUSv4]	recvmsg(GLIBC_ 2.2) [SUSv4]	send(GLIBC_2.2) [SUSv4]	sendmsg(GLIBC_ 2.2) [SUSv4]
sendto(GLIBC_2. 2) [SUSv4]	setsockopt(GLIBC _2.2) [LSB]	shutdown(GLIBC _2.2) [SUSv4]	socketmark(GLIB C_2.2.4) [SUSv4]
socket(GLIBC_2. 2) [SUSv4]	socketpair(GLIBC _2.2) [SUSv4]		

An LSB conforming implementation shall provide the architecture specific data interfaces for Socket Interface specified in [Table 10-17](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-17 libc - Socket Interface Data Interfaces**

in6addr_any(GLI BC_2.2) [SUSv3]	in6addr_loopback(	GLIBC_2.2) [SUSv3]	
------------------------------------	-------------------	-----------------------	--

## 10.2.10 Wide Characters

### 10.2.10.1 Interfaces for Wide Characters

An LSB conforming implementation shall provide the architecture specific functions for Wide Characters specified in [Table 10-18](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-18 libc - Wide Characters Function Interfaces**

__wcstod_internal (GLIBC_2.2) [LSB]	__wcstof_internal(	__wcstol_internal(	__wcstold_interna l(GLIBC_2.2) [LSB]
__wcstold_interna l(GLIBC_2.4) [LSB]	__wcstoul_interna l(GLIBC_2.2) [LSB]	btowc(GLIBC_2.2 ) [SUSv4]	fgetwc(GLIBC_2. 2) [SUSv4]
fgetws(GLIBC_2. 2) [SUSv4]	fputwc(GLIBC_2. 2) [SUSv4]	fputws(GLIBC_2. 2) [SUSv4]	fwide(GLIBC_2.2 ) [SUSv4]
fwprintf(GLIBC_ 2.2) [SUSv4]	fwprintf(GLIBC_ 2.4) [SUSv4]	fwscanf(GLIBC_2. 2) [LSB]	fwscanf(GLIBC_2. 4) [LSB]

getwc(GLIBC_2.2 ) [SUSv4]	getwchar(GLIBC_2.2) [SUSv4]	mblen(GLIBC_2.2 ) [SUSv4]	mbrlen(GLIBC_2.2) [SUSv4]
mbrtowc(GLIBC_2.2) [SUSv4]	mbsinit(GLIBC_2.2) [SUSv4]	mbsnrtowcs(GLIBC_2.2) [SUSv4]	mbsrtowcs(GLIBC_2.2) [SUSv4]
mbstowcs(GLIBC_2.2) [SUSv4]	mbtowc(GLIBC_2.2) [SUSv4]	putwc(GLIBC_2.2) [SUSv4]	putwchar(GLIBC_2.2) [SUSv4]
swprintf(GLIBC_2.2) [SUSv4]	swprintf(GLIBC_2.4) [SUSv4]	swscanf(GLIBC_2.2) [LSB]	swscanf(GLIBC_2.4) [LSB]
towctrans(GLIBC_2.2) [SUSv4]	towlower(GLIBC_2.2) [SUSv4]	toupper(GLIBC_2.2) [SUSv4]	ungetwc(GLIBC_2.2) [SUSv4]
vfwprintf(GLIBC_2.2) [SUSv4]	vfwprintf(GLIBC_2.4) [SUSv4]	vfwscanf(GLIBC_2.2) [LSB]	vfwscanf(GLIBC_2.4) [LSB]
vswprintf(GLIBC_2.2) [SUSv4]	vswprintf(GLIBC_2.4) [SUSv4]	vswscanf(GLIBC_2.2) [LSB]	vswscanf(GLIBC_2.4) [LSB]
vwprintf(GLIBC_2.2) [SUSv4]	vwprintf(GLIBC_2.4) [SUSv4]	vwscanf(GLIBC_2.2) [LSB]	vwscanf(GLIBC_2.4) [LSB]
wcpncpy(GLIBC_2.2) [SUSv4]	wcpncpy(GLIBC_2.2) [SUSv4]	wcrtomb(GLIBC_2.2) [SUSv4]	wcscasecmp(GLIBC_2.2) [SUSv4]
wcscat(GLIBC_2.2) [SUSv4]	wcscchr(GLIBC_2.2) [SUSv4]	wescmp(GLIBC_2.2) [SUSv4]	wescoll(GLIBC_2.2) [SUSv4]
wcscpy(GLIBC_2.2) [SUSv4]	wcscspn(GLIBC_2.2) [SUSv4]	wcsdup(GLIBC_2.2) [SUSv4]	wcsftime(GLIBC_2.2) [SUSv4]
wcslen(GLIBC_2.2) [SUSv4]	wcsncasecmp(GLIBC_2.2) [SUSv4]	wcsncat(GLIBC_2.2) [SUSv4]	wcsncmp(GLIBC_2.2) [SUSv4]
wcsncpy(GLIBC_2.2) [SUSv4]	wcsnlen(GLIBC_2.2) [SUSv4]	wcsnrtombs(GLIBC_2.2) [SUSv4]	wcspbrk(GLIBC_2.2) [SUSv4]
wcsrchr(GLIBC_2.2) [SUSv4]	wcsrtombs(GLIBC_2.2) [SUSv4]	wcsspn(GLIBC_2.2) [SUSv4]	wcsstr(GLIBC_2.2) [SUSv4]
wcstod(GLIBC_2.2) [SUSv4]	wcstof(GLIBC_2.2) [SUSv4]	wcstoi(max(GLIBC_2.2)) [SUSv4]	wcstok(GLIBC_2.2) [SUSv4]
wcstol(GLIBC_2.2) [SUSv4]	wcstold(GLIBC_2.2) [SUSv4]	westold(GLIBC_2.4) [SUSv4]	westoll(GLIBC_2.2) [SUSv4]
wcstombs(GLIBC_2.2) [SUSv4]	wcstoq(GLIBC_2.2) [LSB]	westoul(GLIBC_2.2) [SUSv4]	westoull(GLIBC_2.2) [SUSv4]
wcstoumax(GLIBC_2.2) [SUSv4]	wcstouq(GLIBC_2.2) [LSB]	wcswcs(GLIBC_2.2) [SUSv3]	wcswidth(GLIBC_2.2) [SUSv4]
wcsxfrm(GLIBC_2.2) [SUSv4]	wctob(GLIBC_2.2) [SUSv4]	wctomb(GLIBC_2.2) [SUSv4]	wctrans(GLIBC_2.2) [SUSv4]
wctype(GLIBC_2.2) [SUSv4]	wcwidth(GLIBC_2.2) [SUSv4]	wmemchr(GLIBC_2.2) [SUSv4]	wmemcmp(GLIBC_2.2) [SUSv4]
wmemcpy(GLIBC_2.2) [SUSv4]	wmemmove(GLIBC_2.2) [SUSv4]	wmemset(GLIBC_2.2) [SUSv4]	wprintf(GLIBC_2.2) [SUSv4]
wprintf(GLIBC_2.4) [SUSv4]	wscanf(GLIBC_2.2) [LSB]	wscanf(GLIBC_2.4) [LSB]	

An LSB conforming implementation shall provide the architecture specific deprecated functions for Wide Characters specified in [Table 10-19](#), with the full mandatory functionality as described in the referenced underlying specification.

**Note:** These interfaces are deprecated, and applications should avoid using them. These interfaces may be withdrawn in future releases of this specification.

**Table 10-19 libc - Wide Characters Deprecated Function Interfaces**

<code>__wcstold_interna l(GLIBC_2.2) [LSB]</code>	<code>fwprintf(GLIBC_ 2.2) [SUSv4]</code>	<code>fwscanf(GLIBC_2 .2) [LSB]</code>	<code>swprintf(GLIBC_ 2.2) [SUSv4]</code>
<code>swscanf(GLIBC_2 .2) [LSB]</code>	<code>vfwprintf(GLIBC 2.2) [SUSv4]</code>	<code>vfwscanf(GLIBC_ 2.2) [LSB]</code>	<code>vswprintf(GLIBC 2.2) [SUSv4]</code>
<code>vswscanf(GLIBC_ 2.2) [LSB]</code>	<code>vwprintf(GLIBC_ 2.2) [SUSv4]</code>	<code>vwscanf(GLIBC_2 .2) [LSB]</code>	<code>wcstold(GLIBC_2 .2) [SUSv4]</code>
<code>wprintf(GLIBC_2. 2) [SUSv4]</code>	<code>wscanf(GLIBC_2. 2) [LSB]</code>		

## 10.2.11 String Functions

### 10.2.11.1 Interfaces for String Functions

An LSB conforming implementation shall provide the architecture specific functions for String Functions specified in [Table 10-20](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-20 libc - String Functions Function Interfaces**

<code>__mempcpy(GLI BC_2.2) [LSB]</code>	<code>__rawmemchr(GL IBC_2.2) [LSB]</code>	<code>__stpcpy(GLIBC_ 2.2) [LSB]</code>	<code>__strdup(GLIBC_ 2.2) [LSB]</code>
<code>__strtod_internal( GLIBC_2.2) [LSB]</code>	<code>__strtodf_internal( GLIBC_2.2) [LSB]</code>	<code>__strtok_r(GLIBC 2.2) [LSB]</code>	<code>__ strtol_internal( GLIBC_2.2) [LSB]</code>
<code>__strtold_internal( GLIBC_2.2) [LSB]</code>	<code>__strtoldf_internal( GLIBC_2.4) [LSB]</code>	<code>__strtollf_internal( GLIBC_2.2) [LSB]</code>	<code>__strtoulf_internal( GLIBC_2.2) [LSB]</code>
<code>__strtoullf_internal( GLIBC_2.2) [LSB]</code>	<code>__xpg_strerror_r( GLIBC_2.3.4) [LSB]</code>	<code>bcmp(GLIBC_2.2 ) [SUSv3]</code>	<code>bcopy(GLIBC_2.2 ) [SUSv3]</code>
<code>bzero(GLIBC_2.2 ) [SUSv3]</code>	<code>ffs(GLIBC_2.2) [SUSv4]</code>	<code>index(GLIBC_2.2 ) [SUSv3]</code>	<code>memccpy(GLIBC 2.2) [SUSv4]</code>
<code>memchr(GLIBC_ 2.2) [SUSv4]</code>	<code>memcmp(GLIBC_ 2.2) [SUSv4]</code>	<code>memcpy(GLIBC_2. 2) [SUSv4]</code>	<code>memmove(GLIBC 2.2) [SUSv4]</code>
<code>memrchr(GLIBC_ 2.2) [LSB]</code>	<code>memset(GLIBC_2. 2) [SUSv4]</code>	<code>rindex(GLIBC_2. 2) [SUSv3]</code>	<code>stpcpy(GLIBC_2. 2) [SUSv4]</code>
<code>stpcpy(GLIBC_2. 2) [SUSv4]</code>	<code>strcasecmp(GLIB C_2.2) [SUSv4]</code>	<code>strcasestr(GLIB C_2.2) [LSB]</code>	<code>strcat(GLIBC_2.2 ) [SUSv4]</code>
<code>strchr(GLIBC_2. 2) [SUSv4]</code>	<code>strcmp(GLIBC_2. 2) [SUSv4]</code>	<code>strcoll(GLIBC_2. 2) [SUSv4]</code>	<code>strcpy(GLIBC_2.2 ) [SUSv4]</code>
<code>strcspn(GLIBC_2. 2) [SUSv4]</code>	<code>strdup(GLIBC_2.2 ) [SUSv4]</code>	<code>strerror(GLIBC_2. 2) [SUSv4]</code>	<code>strerror_r(GLIBC 2.2) [LSB]</code>
<code>strfmon(GLIBC_2. 2) [SUSv4]</code>	<code>strfmon(GLIBC_2. 4) [SUSv4]</code>	<code>strftime(GLIBC_2. .2) [SUSv4]</code>	<code>strlen(GLIBC_2.2 ) [SUSv4]</code>
<code>strncasecmp(GLI BC_2.2) [SUSv4]</code>	<code>strncat(GLIBC_2. 2) [SUSv4]</code>	<code>strncmp(GLIBC_2. .2) [SUSv4]</code>	<code>strncpy(GLIBC_2. .2) [SUSv4]</code>
<code>strndup(GLIBC_2. 2) [SUSv4]</code>	<code>strnlen(GLIBC_2. .2) [SUSv4]</code>	<code>strpbrk(GLIBC_2. .2) [SUSv4]</code>	<code>strptime(GLIBC_ 2.2) [LSB]</code>
<code>strrchr(GLIBC_2. .2) [SUSv4]</code>	<code>strsep(GLIBC_2.2 ) [LSB]</code>	<code>strsignal(GLIBC_ 2.2) [SUSv4]</code>	<code>strspn(GLIBC_2.2 ) [SUSv4]</code>
<code>strstr(GLIBC_2.2)</code>	<code>strtof(GLIBC_2.2)</code>	<code>strtoimax(GLIBC)</code>	<code>strtok(GLIBC_2.2)</code>

[SUSv4]	[SUSv4]	2.2) [SUSv4]	) [SUSv4]
strtok_r(GLIBC_2.2) [SUSv4]	strtold(GLIBC_2.2) [SUSv4]	strtold(GLIBC_2.2.4) [SUSv4]	strtoll(GLIBC_2.2) [SUSv4]
strtoq(GLIBC_2.2) [LSB]	strtoull(GLIBC_2.2) [SUSv4]	strtoumax(GLIBC_2.2.2) [SUSv4]	strtouq(GLIBC_2.2) [LSB]
strxfrm(GLIBC_2.2) [SUSv4]	swab(GLIBC_2.2) [SUSv4]		

An LSB conforming implementation shall provide the architecture specific deprecated functions for String Functions specified in [Table 10-21](#), with the full mandatory functionality as described in the referenced underlying specification.

**Note:** These interfaces are deprecated, and applications should avoid using them. These interfaces may be withdrawn in future releases of this specification.

**Table 10-21 libc - String Functions Deprecated Function Interfaces**

__strtold_internal(GLIBC_2.2) [LSB]	strerror_r(GLIBC_2.2) [LSB]	strfmon(GLIBC_2.2) [SUSv4]	strtold(GLIBC_2.2) [SUSv4]
-------------------------------------	-----------------------------	----------------------------	----------------------------

## 10.2.12 IPC Functions

### 10.2.12.1 Interfaces for IPC Functions

An LSB conforming implementation shall provide the architecture specific functions for IPC Functions specified in [Table 10-22](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-22 libc - IPC Functions Function Interfaces**

ftok(GLIBC_2.2) [SUSv4]	msgctl(GLIBC_2.2) [SUSv4]	msgget(GLIBC_2.2) [SUSv4]	msgrev(GLIBC_2.2) [SUSv4]
msgsnd(GLIBC_2.2) [SUSv4]	semctl(GLIBC_2.2) [SUSv4]	semget(GLIBC_2.2) [SUSv4]	semop(GLIBC_2.2) [SUSv4]
shmat(GLIBC_2.2) [SUSv4]	shmctl(GLIBC_2.2) [SUSv4]	shmdt(GLIBC_2.2) [SUSv4]	shmget(GLIBC_2.2) [SUSv4]

## 10.2.13 Regular Expressions

### 10.2.13.1 Interfaces for Regular Expressions

An LSB conforming implementation shall provide the architecture specific functions for Regular Expressions specified in [Table 10-23](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-23 libc - Regular Expressions Function Interfaces**

regcomp(GLIBC_2.2) [SUSv4]	regerror(GLIBC_2.2) [SUSv4]	regexec(GLIBC_2.3.4) [LSB]	regfree(GLIBC_2.2) [SUSv4]
----------------------------	-----------------------------	----------------------------	----------------------------

## 10.2.14 Character Type Functions

### 10.2.14.1 Interfaces for Character Type Functions

An LSB conforming implementation shall provide the architecture specific functions for Character Type Functions specified in [Table 10-24](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-24 libc - Character Type Functions Function Interfaces**

<code>__ctype_get_mb_cur_max(GLIBC_2.2) [LSB]</code>	<code>_tolower(GLIBC_2.2) [SUSv4]</code>	<code>_toupper(GLIBC_2.2) [SUSv4]</code>	<code>isalnum(GLIBC_2.2) [SUSv4]</code>
<code>isalpha(GLIBC_2.2) [SUSv4]</code>	<code>isascii(GLIBC_2.2) [SUSv4]</code>	<code>iscntrl(GLIBC_2.2) [SUSv4]</code>	<code>isdigit(GLIBC_2.2) [SUSv4]</code>
<code>isgraph(GLIBC_2.2) [SUSv4]</code>	<code>islower(GLIBC_2.2) [SUSv4]</code>	<code>isprint(GLIBC_2.2) [SUSv4]</code>	<code>ispunct(GLIBC_2.2) [SUSv4]</code>
<code>isspace(GLIBC_2.2) [SUSv4]</code>	<code>isupper(GLIBC_2.2) [SUSv4]</code>	<code>iswalnum(GLIBC_2.2) [SUSv4]</code>	<code>iswalpha(GLIBC_2.2) [SUSv4]</code>
<code>iswblank(GLIBC_2.2) [SUSv4]</code>	<code>iswcntrl(GLIBC_2.2) [SUSv4]</code>	<code>iswctype(GLIBC_2.2) [SUSv4]</code>	<code>iswdigit(GLIBC_2.2) [SUSv4]</code>
<code>iswgraph(GLIBC_2.2) [SUSv4]</code>	<code>iswlower(GLIBC_2.2) [SUSv4]</code>	<code>iswprint(GLIBC_2.2) [SUSv4]</code>	<code>iswpunct(GLIBC_2.2) [SUSv4]</code>
<code>iswspace(GLIBC_2.2) [SUSv4]</code>	<code>iswupper(GLIBC_2.2) [SUSv4]</code>	<code>iswdxdigit(GLIBC_2.2) [SUSv4]</code>	<code>isxdigit(GLIBC_2.2) [SUSv4]</code>
<code>toascii(GLIBC_2.2) [SUSv4]</code>	<code>tolower(GLIBC_2.2) [SUSv4]</code>	<code>toupper(GLIBC_2.2) [SUSv4]</code>	

## 10.2.15 Time Manipulation

### 10.2.15.1 Interfaces for Time Manipulation

An LSB conforming implementation shall provide the architecture specific functions for Time Manipulation specified in [Table 10-25](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-25 libc - Time Manipulation Function Interfaces**

<code>adjtime(GLIBC_2.2) [LSB]</code>	<code>asctime(GLIBC_2.2) [SUSv4]</code>	<code>asctime_r(GLIBC_2.2) [SUSv4]</code>	<code>ctime(GLIBC_2.2) [SUSv4]</code>
<code>ctime_r(GLIBC_2.2) [SUSv4]</code>	<code>difftime(GLIBC_2.2) [SUSv4]</code>	<code>gmtime(GLIBC_2.2) [SUSv4]</code>	<code>gmtime_r(GLIBC_2.2) [SUSv4]</code>
<code>localtime(GLIBC_2.2) [SUSv4]</code>	<code>localtime_r(GLIBC_2.2) [SUSv4]</code>	<code>mktime(GLIBC_2.2) [SUSv4]</code>	<code>tzset(GLIBC_2.2) [SUSv4]</code>
<code>ualarm(GLIBC_2.2) [SUSv3]</code>			

An LSB conforming implementation shall provide the architecture specific data interfaces for Time Manipulation specified in [Table 10-26](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-26 libc - Time Manipulation Data Interfaces**

<code>__daylight(GLIBC_2.2) [LSB]</code>	<code>__timezone(GLIBC_2.2) [LSB]</code>	<code>__tzname(GLIBC_2.2) [LSB]</code>	<code>daylight(GLIBC_2.2) [SUSv4]</code>
<code>timezone(GLIBC_2.2) [SUSv4]</code>	<code>tzname(GLIBC_2.2) [SUSv4]</code>		

## 10.2.16 Terminal Interface Functions

### 10.2.16.1 Interfaces for Terminal Interface Functions

An LSB conforming implementation shall provide the architecture specific functions for Terminal Interface Functions specified in [Table 10-27](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-27 libc - Terminal Interface Functions Function Interfaces**

cfgetispeed(GLIB C_2.2) [SUSv4]	cfgetospeed(GLIB C_2.2) [SUSv4]	cfmakeraw(GLIB C_2.2) [LSB]	cfsetispeed(GLIB C_2.2) [SUSv4]
cfsetspeed(GLIB C_2.2) [SUSv4]	cfsetspeed(GLIBC _2.2) [LSB]	tcdrain(GLIBC_2. 2) [SUSv4]	tcflow(GLIBC_2. 2) [SUSv4]
tcflush(GLIBC_2. 2) [SUSv4]	tcgetattr(GLIBC_ 2.2) [SUSv4]	tcgetpgrp(GLIBC_ 2.2) [SUSv4]	tcgetsid(GLIBC_2 .2) [SUSv4]
tcsendbreak(GLIB C_2.2) [SUSv4]	tcsetattr(GLIBC_2 .2) [SUSv4]	tcsetpgrp(GLIBC_ 2.2) [SUSv4]	

## 10.2.17 System Database Interface

### 10.2.17.1 Interfaces for System Database Interface

An LSB conforming implementation shall provide the architecture specific functions for System Database Interface specified in [Table 10-28](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-28 libc - System Database Interface Function Interfaces**

endgrent(GLIBC_ 2.2) [SUSv4]	endprotoent(GLIB C_2.2) [SUSv4]	endpwent(GLIBC_ 2.2) [SUSv4]	endservent(GLIB C_2.2) [SUSv4]
endutent(GLIBC_ 2.2) [LSB]	endutxent(GLIBC_ 2.2) [SUSv4]	getrent(GLIBC_2.2) [SUSv4]	getrent_r(GLIBC_ 2.2) [LSB]
getgrgid(GLIBC_ 2.2) [SUSv4]	getgrgid_r(GLIBC_ 2.2) [SUSv4]	getgrnam(GLIBC_ 2.2) [SUSv4]	getgrnam_r(GLIB C_2.2) [SUSv4]
getgrouplist(GLIB C_2.2.4) [LSB]	gethostbyaddr(GL IBC_2.2) [SUSv3]	gethostbyaddr_r(G LIBC_2.2) [LSB]	gethostbyname(G LIBC_2.2) [SUSv3]
gethostbyname2(GLIBC_2.2) [LSB]	gethostbyname2_r(GLIBC_2.2) [LSB]	gethostbyname_r(GLIBC_2.2) [LSB]	getprotobynam(G LIBC_2.2) [SUSv4]
getprotobynam_r(GLIBC_2.2) [LSB]	getprotobynumber(GLIBC_2.2) [SUSv4]	getprotobynumber_r(GLIBC_2.2) [LSB]	getprotoent(GLIB C_2.2) [SUSv4]
getprotoent_r(GLI BC_2.2) [LSB]	getpwent(GLIBC_ 2.2) [SUSv4]	getpwent_r(GLIB C_2.2) [LSB]	getpwnam(GLIBC_ 2.2) [SUSv4]
getpwnam_r(GLI BC_2.2) [SUSv4]	getpwuid(GLIBC_ 2.2) [SUSv4]	getpwuid_r(GLIB C_2.2) [SUSv4]	getservbyname(G LIBC_2.2) [SUSv4]
getservbyname_r(GLIBC_2.2) [LSB]	getservbyport(GLI BC_2.2) [SUSv4]	getservbyport_r(G LIBC_2.2) [LSB]	getservent(GLIBC_ 2.2) [SUSv4]
getservent_r(GLI BC_2.2) [LSB]	getutent(GLIBC_2 .2) [LSB]	getutent_r(GLIBC_ 2.2) [LSB]	getutxent(GLIBC_ 2.2) [SUSv4]
getutxid(GLIBC_ 2.2) [SUSv4]	getutxline(GLIBC_ 2.2) [SUSv4]	pututxline(GLIBC_ 2.2) [SUSv4]	setgrent(GLIBC_2 .2) [SUSv4]
setgroups(GLIBC_ 2.2) [LSB]	setprotoent(GLIB C_2.2) [SUSv4]	setpwent(GLIBC_ 2.2) [SUSv4]	setservent(GLIBC_ 2.2) [SUSv4]
setutent(GLIBC_2 .2) [LSB]	setutxent(GLIBC_ 2.2) [SUSv4]	utmpname(GLIBC_ 2.2) [LSB]	

An LSB conforming implementation shall provide the architecture specific deprecated functions for System Database Interface specified in [Table 10-29](#), with the full mandat-

ory functionality as described in the referenced underlying specification.

**Note:** These interfaces are deprecated, and applications should avoid using them. These interfaces may be withdrawn in future releases of this specification.

**Table 10-29** libc - System Database Interface Deprecated Function Interfaces

gethostbyaddr(GLIBC_2.2) <a href="#">[SUSv3]</a>	gethostbyaddr_r(GLIBC_2.2) <a href="#">[LSB]</a>	gethostbyname(GLIBC_2.2) <a href="#">[SUSv3]</a>	gethostbyname2(GLIBC_2.2) <a href="#">[LSB]</a>
gethostbyname2_r(GLIBC_2.2) <a href="#">[LSB]</a>	gethostbyname_r(GLIBC_2.2) <a href="#">[LSB]</a>		

## 10.2.18 Language Support

### 10.2.18.1 Interfaces for Language Support

An LSB conforming implementation shall provide the architecture specific functions for Language Support specified in [Table 10-30](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-30** libc - Language Support Function Interfaces

__libc_start_main(GLIBC_2.2) <a href="#">[LSB]</a>			
----------------------------------------------------	--	--	--

## 10.2.19 Large File Support

### 10.2.19.1 Interfaces for Large File Support

An LSB conforming implementation shall provide the architecture specific functions for Large File Support specified in [Table 10-31](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-31** libc - Large File Support Function Interfaces

__fxstat64(GLIBC_2.2) <a href="#">[LSB]</a>	__lxstat64(GLIBC_2.2) <a href="#">[LSB]</a>	__xstat64(GLIBC_2.2) <a href="#">[LSB]</a>	creat64(GLIBC_2.2) <a href="#">[LFS]</a>
fgetpos64(GLIBC_2.2) <a href="#">[LFS]</a>	fopen64(GLIBC_2.2) <a href="#">[LFS]</a>	freopen64(GLIBC_2.2) <a href="#">[LFS]</a>	fseeko64(GLIBC_2.2) <a href="#">[LFS]</a>
fsetpos64(GLIBC_2.2) <a href="#">[LFS]</a>	fstatfs64(GLIBC_2.2) <a href="#">[LSB]</a>	fstatvfs64(GLIBC_2.2) <a href="#">[LFS]</a>	ftello64(GLIBC_2.2) <a href="#">[LFS]</a>
ftruncate64(GLIBC_2.2) <a href="#">[LFS]</a>	ftw64(GLIBC_2.2) <a href="#">[LFS]</a>	getrlimit64(GLIBC_2.2) <a href="#">[LFS]</a>	lockf64(GLIBC_2.2) <a href="#">[LFS]</a>
lseek64(GLIBC_2.2) <a href="#">[LFS]</a>	mkstemp64(GLIBC_2.2) <a href="#">[LSB]</a>	mmap64(GLIBC_2.2) <a href="#">[LFS]</a>	nftw64(GLIBC_2.3.3) <a href="#">[LFS]</a>
open64(GLIBC_2.2) <a href="#">[LFS]</a>	posix_fadvise64(GLIBC_2.2) <a href="#">[LSB]</a>	posix_fallocate64(GLIBC_2.2) <a href="#">[LSB]</a>	pread64(GLIBC_2.2) <a href="#">[LSB]</a>
pwrite64(GLIBC_2.2) <a href="#">[LSB]</a>	readdir64(GLIBC_2.2) <a href="#">[LFS]</a>	readdir64_r(GLIBC_2.2) <a href="#">[LSB]</a>	statfs64(GLIBC_2.2) <a href="#">[LSB]</a>
statvfs64(GLIBC_2.2) <a href="#">[LFS]</a>	tmpfile64(GLIBC_2.2) <a href="#">[LFS]</a>	truncate64(GLIBC_2.2) <a href="#">[LFS]</a>	

An LSB conforming implementation shall provide the architecture specific deprecated functions for Large File Support specified in [Table 10-32](#), with the full mandatory functionality as described in the referenced underlying specification.

**Note:** These interfaces are deprecated, and applications should avoid using them. These interfaces may be withdrawn in future releases of this specification.

**Table 10-32 libc - Large File Support Deprecated Function Interfaces**

fstatfs64(GLIBC_2.2) <a href="#">[LSB]</a>	statfs64(GLIBC_2.2) <a href="#">[LSB]</a>		
--------------------------------------------	-------------------------------------------	--	--

## 10.2.20 Inotify

### 10.2.20.1 Interfaces for Inotify

No external functions are defined for libc - Inotify in this part of the specification. See also the generic specification.

## 10.2.21 Standard Library

### 10.2.21.1 Interfaces for Standard Library

An LSB conforming implementation shall provide the architecture specific functions for Standard Library specified in [Table 10-33](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-33 libc - Standard Library Function Interfaces**

<code>_Exit(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>__assert_fail(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>__cxa_atexit(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>__cxa_finalize(GLIBC_2.2)</code> <a href="#">[LSB]</a>
<code>__errno_location(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>__fpending(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>__getpagesize(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>__isinf(GLIBC_2.2)</code> <a href="#">[LSB]</a>
<code>__isinff(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>__isinfl(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>__isinfl(GLIBC_2.4)</code> <a href="#">[LSB]</a>	<code>__isnan(GLIBC_2.2)</code> <a href="#">[LSB]</a>
<code>__isnanf(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>__isnanl(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>__isnanl(GLIBC_2.4)</code> <a href="#">[LSB]</a>	<code>__sysconf(GLIBC_2.2)</code> <a href="#">[LSB]</a>
<code>__xpg_basename(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>_exit(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>_longjmp(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>_setjmp(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>a64l(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>abort(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>abs(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>alphasort(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>alphasort64(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>argz_add(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>argz_add_sep(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>argz_append(GLIBC_2.2)</code> <a href="#">[LSB]</a>
<code>argz_count(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>argz_create(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>argz_create_sep(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>argz_delete(GLIBC_2.2)</code> <a href="#">[LSB]</a>
<code>argz_extract(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>argz_insert(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>argz_next(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>argz_replace(GLIBC_2.2)</code> <a href="#">[LSB]</a>
<code>argz_stringify(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>atof(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>atoi(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>atol(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>atoll(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>basename(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>bsearch(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>calloc(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>closelog(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>confstr(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>cuserid(GLIBC_2.2)</code> <a href="#">[SUSv2]</a>	<code>daemon(GLIBC_2.2)</code> <a href="#">[LSB]</a>
<code>dirfd(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>dirname(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>div(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>dl_iterate_phdr(GLIBC_2.2.4)</code> <a href="#">[LSB]</a>
<code>drand48(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>drand48_r(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>ecvt(GLIBC_2.2)</code> <a href="#">[SUSv3]</a>	<code>envz_add(GLIBC_2.2)</code> <a href="#">[LSB]</a>

envz_entry(GLIBC_C_2.2) [LSB]	envz_get(GLIBC_2.2) [LSB]	envz_merge(GLIBC_C_2.2) [LSB]	envz_remove(GLIBC_2.2) [LSB]
envz_strip(GLIBC_2.2) [LSB]	erand48(GLIBC_2.2) [SUSv4]	erand48_r(GLIBC_2.2) [LSB]	err(GLIBC_2.2) [LSB]
error(GLIBC_2.2) [LSB]	errx(GLIBC_2.2) [LSB]	fcvt(GLIBC_2.2) [SUSv3]	fmemopen(GLIBC_C_2.2) [SUSv4]
fmtmsg(GLIBC_2.2) [SUSv4]	fnmatch(GLIBC_2.2.3) [LSB]	fpathconf(GLIBC_2.2) [SUSv4]	free(GLIBC_2.2) [SUSv4]
freeaddrinfo(GLIBC_2.2) [SUSv4]	ftrylockfile(GLIBC_C_2.2) [SUSv4]	ftw(GLIBC_2.2) [SUSv4]	funlockfile(GLIBC_C_2.2) [SUSv4]
gai_strerror(GLIBC_C_2.2) [SUSv4]	gcvt(GLIBC_2.2) [SUSv3]	getaddrinfo(GLIBC_C_2.2) [SUSv4]	getcwd(GLIBC_2.2) [LSB]
getdate(GLIBC_2.2) [SUSv4]	getdomainname(GLIBC_2.2) [LSB]	getenv(GLIBC_2.2) [SUSv4]	getlogin(GLIBC_2.2) [SUSv4]
getlogin_r(GLIBC_2.2) [SUSv4]	getnameinfo(GLIBC_2.2) [SUSv4]	getopt(GLIBC_2.2) [LSB]	getopt_long(GLIBC_C_2.2) [LSB]
getopt_long_only(GLIBC_2.2) [LSB]	getsubopt(GLIBC_2.2) [SUSv4]	gettimeofday(GLIBC_2.2) [SUSv4]	glob(GLIBC_2.2) [SUSv4]
glob64(GLIBC_2.2) [LSB]	globfree(GLIBC_2.2) [SUSv4]	globfree64(GLIBC_C_2.2) [LSB]	grantpt(GLIBC_2.2) [SUSv4]
hcreate(GLIBC_2.2) [SUSv4]	hcreate_r(GLIBC_2.2) [LSB]	hdestroy(GLIBC_2.2) [SUSv4]	hdestroy_r(GLIBC_C_2.2) [LSB]
hsearch(GLIBC_2.2) [SUSv4]	hsearch_r(GLIBC_2.2) [LSB]	htonl(GLIBC_2.2) [SUSv4]	htonl(GLIBC_2.2) [SUSv4]
imaxabs(GLIBC_2.2) [SUSv4]	imaxdiv(GLIBC_2.2) [SUSv4]	inet_addr(GLIBC_2.2) [SUSv4]	inet_aton(GLIBC_2.2) [LSB]
inet_ntoa(GLIBC_2.2) [SUSv4]	inet_ntop(GLIBC_2.2) [SUSv4]	inet_pton(GLIBC_2.2) [SUSv4]	initstate(GLIBC_2.2) [SUSv4]
initstate_r(GLIBC_2.2) [LSB]	insque(GLIBC_2.2) [SUSv4]	isatty(GLIBC_2.2) [SUSv4]	isblank(GLIBC_2.2) [SUSv4]
jrand48(GLIBC_2.2) [SUSv4]	jrand48_r(GLIBC_2.2) [LSB]	l64a(GLIBC_2.2) [SUSv4]	labs(GLIBC_2.2) [SUSv4]
lcng48(GLIBC_2.2) [SUSv4]	lcng48_r(GLIBC_2.2) [LSB]	ldiv(GLIBC_2.2) [SUSv4]	lfind(GLIBC_2.2) [SUSv4]
llabs(GLIBC_2.2) [SUSv4]	lldiv(GLIBC_2.2) [SUSv4]	longjmp(GLIBC_2.2) [SUSv4]	lrand48(GLIBC_2.2) [SUSv4]
lrand48_r(GLIBC_2.2) [LSB]	lsearch(GLIBC_2.2) [SUSv4]	makecontext(GLIBC_2.2) [SUSv3]	malloc(GLIBC_2.2) [SUSv4]
memmem(GLIBC_2.2) [LSB]	mkdtemp(GLIBC_2.2) [SUSv4]	mkstemp(GLIBC_2.2) [SUSv4]	mktemp(GLIBC_2.2) [SUSv3]
mrand48(GLIBC_2.2) [SUSv4]	mrand48_r(GLIBC_C_2.2) [LSB]	nftw(GLIBC_2.3.3) [SUSv4]	nrnd48(GLIBC_2.2) [SUSv4]
nrnd48_r(GLIBC_2.2) [LSB]	ntohl(GLIBC_2.2) [SUSv4]	ntohs(GLIBC_2.2) [SUSv4]	open_memstream(GLIBC_2.2) [SUSv4]
openlog(GLIBC_2.2) [SUSv4]	perror(GLIBC_2.2) [SUSv4]	posix_openpt(GLIBC_2.2.1) [SUSv4]	ptsname(GLIBC_2.2) [SUSv4]
putenv(GLIBC_2.	qsort(GLIBC_2.2)	rand(GLIBC_2.2)	rand_r(GLIBC_2.

2) [SUSv4]	[SUSv4]	[SUSv4]	2) [SUSv4]
random(GLIBC_2.2) [SUSv4]	random_r(GLIBC_2.2) [LSB]	realloc(GLIBC_2.2) [SUSv4]	realpath(GLIBC_2.3) [SUSv4]
remque(GLIBC_2.2) [SUSv4]	scandir(GLIBC_2.2) [SUSv4]	scandir64(GLIBC_2.2) [LSB]	seed48(GLIBC_2.2) [SUSv4]
seed48_r(GLIBC_2.2) [LSB]	sendfile(GLIBC_2.2) [LSB]	setenv(GLIBC_2.2) [SUSv4]	sethostname(GLIBC_2.2) [LSB]
setlogmask(GLIBC_2.2) [SUSv4]	setstate(GLIBC_2.2) [SUSv4]	setstate_r(GLIBC_2.2) [LSB]	srand(GLIBC_2.2) [SUSv4]
srand48(GLIBC_2.2) [SUSv4]	srand48_r(GLIBC_2.2) [LSB]	random(GLIBC_2.2) [SUSv4]	srandom_r(GLIBC_2.2) [LSB]
strtod(GLIBC_2.2) [SUSv4]	strtol(GLIBC_2.2) [SUSv4]	strtoul(GLIBC_2.2) [SUSv4]	swapcontext(GLIBC_2.2) [SUSv3]
syslog(GLIBC_2.2) [SUSv4]	syslog(GLIBC_2.4) [SUSv4]	system(GLIBC_2.2) [LSB]	tdelete(GLIBC_2.2) [SUSv4]
tfind(GLIBC_2.2) [SUSv4]	tmpfile(GLIBC_2.2) [SUSv4]	tmpnam(GLIBC_2.2) [SUSv4]	tsearch(GLIBC_2.2) [SUSv4]
ttynname(GLIBC_2.2) [SUSv4]	ttynname_r(GLIBC_2.2) [SUSv4]	twalk(GLIBC_2.2) [SUSv4]	unlockpt(GLIBC_2.2) [SUSv4]
unsetenv(GLIBC_2.2) [SUSv4]	usleep(GLIBC_2.2) [SUSv3]	verrx(GLIBC_2.2) [LSB]	vfscanf(GLIBC_2.2) [LSB]
vfscanf(GLIBC_2.4) [LSB]	vscanf(GLIBC_2.2) [LSB]	vscanf(GLIBC_2.4) [LSB]	vsscanf(GLIBC_2.2) [LSB]
vsscanf(GLIBC_2.4) [LSB]	vsyslog(GLIBC_2.2) [LSB]	vsyslog(GLIBC_2.4) [LSB]	warn(GLIBC_2.2) [LSB]
warnx(GLIBC_2.2) [LSB]	wordexp(GLIBC_2.2) [SUSv4]	wordfree(GLIBC_2.2) [SUSv4]	

An LSB conforming implementation shall provide the architecture specific deprecated functions for Standard Library specified in [Table 10-34](#), with the full mandatory functionality as described in the referenced underlying specification.

**Note:** These interfaces are deprecated, and applications should avoid using them. These interfaces may be withdrawn in future releases of this specification.

**Table 10-34 libc - Standard Library Deprecated Function Interfaces**

__isinfl(GLIBC_2.2) [LSB]	__isnanl(GLIBC_2.2) [LSB]	basename(GLIBC_2.2) [LSB]	getdomainname(GLIBC_2.2) [LSB]
inet_aton(GLIBC_2.2) [LSB]	syslog(GLIBC_2.2) [SUSv4]	tmpnam(GLIBC_2.2) [SUSv4]	vfscanf(GLIBC_2.2) [LSB]
vscanf(GLIBC_2.2) [LSB]	vsscanf(GLIBC_2.2) [LSB]	vsyslog(GLIBC_2.2) [LSB]	

An LSB conforming implementation shall provide the architecture specific data interfaces for Standard Library specified in [Table 10-35](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-35 libc - Standard Library Data Interfaces**

__environ(GLIBC_2.2) [LSB]	__environ(GLIBC_2.2) [LSB]	__sys_errlist(GLIBC_2.12) [LSB]	environ(GLIBC_2.2) [SUSv4]
getdate_err(GLIBC_2.2) [SUSv4]	optarg(GLIBC_2.2) [SUSv4]	opterr(GLIBC_2.2) [SUSv4]	optind(GLIBC_2.2) [SUSv4]

optopt(GLIBC_2.2) [SUSv4]			
---------------------------	--	--	--

## 10.2.22 GNU Extensions for libc

### 10.2.22.1 Interfaces for GNU Extensions for libc

An LSB conforming implementation shall provide the architecture specific functions for GNU Extensions for libc specified in [Table 10-36](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-36 libc - GNU Extensions for libc Function Interfaces**

gnu_get_libc_release(GLIBC_2.2) [LSB]	gnu_get_libc_version(GLIBC_2.2) [LSB]		
---------------------------------------	---------------------------------------	--	--

## 10.3 Data Definitions for libc

This section defines global identifiers and their values that are associated with interfaces contained in libc. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the [ISO C \(1999\)](#) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

### 10.3.1 argz.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.2 assert.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.3 cpio.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.4 ctype.h

```
enum {
    _ISupper = 1,
    _ISlower = 2,
    _ISalpha = 4,
    _ISdigit = 8,
    _ISxdigit = 16,
    _ISspace = 32,
    _ISPprint = 64,
    _ISgraph = 128,
    _ISblank = 256,
    _IScntrl = 512,
    _ISPunct = 1024,
    _ISalnum = 2048
};
```

### 10.3.5 dirent.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.6 elf.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.7 endian.h

```
#define __BYTE_ORDER      __BIG_ENDIAN
```

### 10.3.8 errno.h

```
#define EDEADLOCK      35
```

### 10.3.9 fcntl.h

```
#define O_LARGEFILE      0
#define O_DIRECTORY       02000000
#define O_NOFOLLOW        04000000
#define POSIX_FADV_DONTNEED   6
#define POSIX_FADV_NOREUSE     7

#define F_GETLK64         5
#define F_SETLK64         6
#define F_SETLKW64        7
```

### 10.3.10 fmtmsg.h

```
/*
 * This header is architecture neutral
```

```
/* Please refer to the generic specification for details
 */
```

### 10.3.11 fnmatch.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.12 ftw.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.13 getopt.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.14 glob.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.15 iconv.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.16 ifaddrs.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.17 inttypes.h

```
#define __PRI64_PREFIX "l"
#define __PRIPTR_PREFIX "l"

typedef ldiv_t imaxdiv_t;
```

### 10.3.18 langinfo.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.19 limits.h

```
#define ULONG_MAX      0xFFFFFFFFFFFFFFFUL
#define LONG_BIT        64
#define LONG_MAX        9223372036854775807L

#define CHAR_MIN        0
#define CHAR_MAX        255

#define PTHREAD_STACK_MIN    16384
```

### 10.3.20 link.h

```
struct dl_phdr_info {
    Elf64_Addr dlpi_addr;
    const char *dlpi_name;
    const Elf64_Phdr *dlpi_phdr;
    Elf64_Half dlpi_phnum;
    unsigned long long int dlpi_adds;
    unsigned long long int dlpi_subs;
    size_t dlpi_tls_modid;
    void *dlpi_tls_data;
};
```

### 10.3.21 locale.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.22 lsb/time.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.23 lsb/types.h

```
typedef int64_t ssize_t;
```

### 10.3.24 lsb/wchar.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

**10.3.25 net/if.h**

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

**10.3.26 netdb.h**

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

**10.3.27 netinet/icmp6.h**

```
#define ICMP6_RR_RESULT_FLAGS_FORBIDDEN 0x1000
#define ICMP6_RR_RESULT_FLAGS_OOB        0x2000
#define ND_NA_FLAG_OVERRIDE            0x20000000
#define ND_NA_FLAG_SOLICITED          0x40000000
#define ND_NA_FLAG_ROUTER             0x80000000
```

**10.3.28 netinet/igmp.h**

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

**10.3.29 netinet/in.h**

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

**10.3.30 netinet/in\_systm.h**

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

**10.3.31 netinet/ip.h**

```
struct timestamp {
    u_int8_t len;
    u_int8_t ptr;
    unsigned int overflow:4;
    unsigned int flags:4;
    u_int32_t data[9];
};

struct iphdr {
    unsigned int version:4;
    unsigned int ihl:4;
```

```

    u_int8_t tos;
    u_int16_t tot_len;
    u_int16_t id;
    u_int16_t frag_off;
    u_int8_t ttl;
    u_int8_t protocol;
    u_int16_t check;
    u_int32_t saddr;
    u_int32_t daddr;
};

struct ip {
    unsigned int ip_v:4;
    unsigned int ip_hl:4;
    u_int8_t ip_tos;
    u_short ip_len;
    u_short ip_id;
    u_short ip_off;
    u_int8_t ip_ttl;
    u_int8_t ip_p;
    u_short ip_sum;
    struct in_addr ip_src;
    struct in_addr ip_dst;
};

struct ip_timestamp {
    u_int8_t ipt_len;
    u_int8_t ipt_code;
    u_int8_t ipt_ptr;
    unsigned int ipt_flg:4;
    unsigned int ipt_oflw:4;
    u_int32_t data[9];
};

```

### 10.3.32 netinet/ip6.h

```

#define IP6_ALERT_MLD      0x0000
#define IP6F_MORE_FRAG    0x0001
#define IP6_ALERT_RSVP    0x0001
#define IP6_ALERT_AN      0x0002
#define IP6F_RESERVED_MASK 0x0006
#define IP6F_OFF_MASK     0xffff8

```

### 10.3.33 netinet/ip\_icmp.h

```

/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */

```

### 10.3.34 netinet/tcp.h

```

struct tcphdr {
    uint16_t source;
    uint16_t dest;
    uint32_t seq;
    uint32_t ack_seq;
    uint16_t doff:4;
    uint16_t res1:4;
    uint16_t res2:2;
    uint16_t urg:1;
    uint16_t ack:1;
    uint16_t psh:1;
    uint16_t rst:1;
}

```

```
    uint16_t syn:1;
    uint16_t fin:1;
    uint16_t window;
    uint16_t check;
    uint16_t urg_ptr;
};
```

### 10.3.35 netinet/udp.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.36 nl\_types.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.37 pwd.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.38 regex.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.39 rpc/auth.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.40 rpc/clnt.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.41 rpc/rpc\_msg.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.42 rpc/svc.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.43 rpc/types.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.44 rpc/xdr.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.45 sched.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.46 search.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.47 setjmp.h

```
typedef long int __jmp_buf[18];
```

### 10.3.48 signal.h

```
#define __NUM_ACRS      16
#define __NUM_FPRS      16
#define __NUM_GPRS      16

typedef struct {
    unsigned long int mask;
    unsigned long int addr;
} __attribute__((aligned(8))) _psw_t;
typedef struct {
    _psw_t psw;
    unsigned long int gprs[16];
    unsigned int acrs[16];
} _s390_regs_common;
```

```
#define SIGEV_PAD_SIZE ((SIGEV_MAX_SIZE/sizeof(int))-4)
#define SI_PAD_SIZE ((SI_MAX_SIZE/sizeof(int))-4)

struct sigaction {
    union {
        sighandler_t _sa_handler;
        void (*_sa_sigaction) (int, siginfo_t *, void *);
    } __sigaction_handler;
    unsigned long int sa_flags;
    void (*sa_restorer) (void);
    sigset_t sa_mask;
};

#define MINSIGSTKSZ      2048      /* Minimum stack size for a
signal handler. */
#define SIGSTKSZ         8192      /* System default stack size. */

typedef struct {
    unsigned int fpc;
    double fprs[___NUM_FPRS];
} _s390_fp_regs;
typedef struct {
    _s390_REGS_COMMON regs;
    _s390_fp_regs fpregs;
} _sigregs;

struct sigcontext {
    unsigned long int oldmask;
    _sigregs *sregs;
};
```

### **10.3.49 spawn.h**

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### **10.3.50 stddef.h**

```
typedef int wchar_t;
typedef unsigned long int size_t;
typedef long int ptrdiff_t;
```

### **10.3.51 stdint.h**

```
#define INT64_C(c)      c ## L
#define INTMAX_C(c)      c ## L
#define __INT64_C(c)     c ## L
#define UINT64_C(c)      c ## UL
#define UINTMAX_C(c)     c ## UL
#define __UINT64_C(c)    c ## UL

#define INTPTR_MIN        (-9223372036854775807L-1)
#define INT_FAST16_MIN    (-9223372036854775807L-1)
#define INT_FAST32_MIN    (-9223372036854775807L-1)
#define PTRDIFF_MIN       (-9223372036854775807L-1)
#define SIZE_MAX          (18446744073709551615UL)
#define UINTPTR_MAX       (18446744073709551615UL)
#define UINT_FAST16_MAX   (18446744073709551615UL)
#define UINT_FAST32_MAX   (18446744073709551615UL)
```

```
#define INTPTR_MAX      (9223372036854775807L)
#define INT_FAST16_MAX   (9223372036854775807L)
#define INT_FAST32_MAX   (9223372036854775807L)
#define PTRDIFF_MAX       (9223372036854775807L)

typedef long int int64_t;
typedef long int intmax_t;
typedef unsigned long int uintmax_t;
typedef long int intptr_t;
typedef unsigned long int uintptr_t;
typedef unsigned long int uint64_t;
typedef long int int_least64_t;
typedef unsigned long int uint_least64_t;
typedef long int int_fast16_t;
typedef long int int_fast32_t;
typedef long int int_fast64_t;
typedef unsigned long int uint_fast16_t;
typedef unsigned long int uint_fast32_t;
typedef unsigned long int uint_fast64_t;
```

### 10.3.52 stdio.h

```
#define __IO_FILE_SIZE 216
```

### 10.3.53 stdlib.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.54 string.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.55 sys/epoll.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.56 sys/file.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.57 sys/inotify.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

```
 */
```

### **10.3.58 sys/ioctl.h**

```
#define TIOCGWINSZ      0x5413
#define TIOCSWINSZ      0x5414
#define FIONREAD        21531
#define TIOCNOTTY       21538
```

### **10.3.59 sys/ipc.h**

```
struct ipc_perm {
    key_t __key;
    uid_t uid;
    gid_t gid;
    uid_t cuid;
    gid_t cgid;
    mode_t mode;
    unsigned short __seq;
    unsigned short __pad2;
    unsigned long int __unused1;
    unsigned long int __unused2;
};
```

### **10.3.60 sys/mman.h**

```
#define MCL_CURRENT     1
#define MCL_FUTURE      2
```

### **10.3.61 sys/msg.h**

```
typedef unsigned long int msgqnum_t;
typedef unsigned long int msglen_t;

struct msqid_ds {
    struct ipc_perm msg_perm;
    time_t msg_stime;
    time_t msg_rtime;
    time_t msg_ctime;
    unsigned long int __msg_cbytes;
    msgqnum_t msg_qnum;
    msglen_t msg_qbytes;
    pid_t msg_lspid;
    pid_t msg_lrpid;
    unsigned long int __unused4;
    unsigned long int __unused5;
};
```

### **10.3.62 sys/param.h**

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### **10.3.63 sys/poll.h**

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.64 sys/ptrace.h

```
enum __ptrace_request {
    PTTRACE_TRACEME = 0,
    PTTRACE_PEEKTEXT = 1,
    PTTRACE_PEEKDATA = 2,
    PTTRACE_PEEKUSER = 3,
    PTTRACE_POKETEXT = 4,
    PTTRACE_POKEDATA = 5,
    PTTRACE_POKEUSER = 6,
    PTTRACE_CONT = 7,
    PTTRACE_KILL = 8,
    PTTRACE_SINGLESTEP = 9,
    PTTRACE_ATTACH = 16,
    PTTRACE_DETACH = 17,
    PTTRACE_SYSCALL = 24,
    PTTRACE_SETOPTIONS = 0x4200,
    PTTRACE_GETEVENTMSG = 0x4201,
    PTTRACE_GETSIGINFO = 0x4202,
    PTTRACE_SETSIGINFO = 0x4203
};
```

### 10.3.65 sys/resource.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.66 sys/select.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.67 sys/sem.h

```
struct semid_ds {
    struct ipc_perm sem_perm;
    time_t sem_otime;
    time_t sem_ctime;
    unsigned long int sem_nsems;
    unsigned long int __unused3;
    unsigned long int __unused4;
};
```

### 10.3.68 sys/shm.h

```
#define SHMLBA  (__getpagesize())
typedef unsigned long int shmat_t;
```

```

struct shmid_ds {
    struct ipc_perm shm_perm;
    size_t shm_segsz;
    time_t shm_atime;
    time_t shm_dtime;
    time_t shm_ctime;
    pid_t shm_cpid;
    pid_t shm_lpid;
    shmat_t shm_nattch;
    unsigned long int __unused4;
    unsigned long int __unused5;
};

```

### 10.3.69 sys/socket.h

```

typedef uint64_t __ss_aligntype;

#define SO_RCVLOWAT      18
#define SO SNDLOWAT      19
#define SO_RCVTIMEO      20
#define SO SNDTIMEO      21

```

### 10.3.70 sys/stat.h

```

#define _MKNOD_VER       0
#define _STAT_VER        1

struct stat {
    dev_t st_dev;
    ino_t st_ino;
    nlink_t st_nlink;
    mode_t st_mode;
    uid_t st_uid;
    gid_t st_gid;
    int pad0;
    dev_t st_rdev;
    off_t st_size;
    struct timespec st_atim; /* Time of last access. */
    struct timespec st_mtim; /* Time of last modification. */
    struct timespec st_ctim; /* Time of last status change. */
    blksize_t st_blksize;
    blkcnt_t st_blocks;
    long int __unused[3];
};

struct stat64 {
    dev_t st_dev;
    ino64_t st_ino;
    nlink_t st_nlink;
    mode_t st_mode;
    uid_t st_uid;
    gid_t st_gid;
    int pad0;
    dev_t st_rdev;
    off_t st_size;
    struct timespec st_atim; /* Time of last access. */
    struct timespec st_mtim; /* Time of last modification. */
    struct timespec st_ctim; /* Time of last status change. */
    blksize_t st_blksize;
    blkcnt64_t st_blocks;
    long int __unused[3];
};

```

### 10.3.71 sys/statfs.h

```

struct statfs {
    int f_type;                      /* type of filesystem */
    int f_bsize;                     /* optimal transfer block size */
    fsblkcnt_t f_blocks;             /* total data blocks in file
system */
    fsblkcnt_t f_bfree;              /* free blocks in fs */
    fsblkcnt_t f_bavail;             /* free blocks avail to non-
superuser */
    fsfilcnt_t f_files;              /* total file nodes in file
system */
    fsfilcnt_t f_ffree;              /* free file nodes in file system
*/
    fsid_t f_fsid;                  /* file system id */
    int f_namelen;                  /* maximum length of filenames */
    int f_frsize;                   /* fragment size */
    int f_spare[5];                 /* spare for later */
};

struct statfs64 {
    int f_type;                      /* type of filesystem */
    int f_bsize;                     /* optimal transfer block size */
    fsblkcnt64_t f_blocks;            /* total data blocks in file
system */
    fsblkcnt64_t f_bfree;              /* free blocks in fs */
    fsblkcnt64_t f_bavail;             /* free blocks avail to non-
superuser */
    fsfilcnt64_t f_files;              /* total file nodes in file
system */
    fsfilcnt64_t f_ffree;              /* free file nodes in file system
*/
    fsid_t f_fsid;                  /* file system id */
    int f_namelen;                  /* maximum length of filenames */
    int f_frsize;                   /* fragment size */
    int f_spare[5];                 /* spare for later */
};

```

### 10.3.72 sys/statvfs.h

```

struct statvfs {
    unsigned long int f_bsize;
    unsigned long int f_frsize;
    fsblkcnt64_t f_blocks;
    fsblkcnt64_t f_bfree;
    fsblkcnt64_t f_bavail;
    fsfilcnt64_t f_files;
    fsfilcnt64_t f_ffree;
    fsfilcnt64_t f_favail;
    unsigned long int f_fsid;
    unsigned long int f_flag;
    unsigned long int f_namemax;
    int __f_spare[6];
};

struct statvfs64 {
    unsigned long int f_bsize;
    unsigned long int f_frsize;
    fsblkcnt64_t f_blocks;
    fsblkcnt64_t f_bfree;
    fsblkcnt64_t f_bavail;
    fsfilcnt64_t f_files;
    fsfilcnt64_t f_ffree;
    fsfilcnt64_t f_favail;
    unsigned long int f_fsid;

```

```
    unsigned long int f_flag;
    unsigned long int f_namemax;
    int __f_spare[6];
};
```

### 10.3.73 sys/sysinfo.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.74 sys/time.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.75 sys/timeb.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.76 sys/times.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.77 sys/un.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.78 sys/utsname.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.79 sys/wait.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.80 syssexits.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.81 syslog.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.82 tar.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.83 termios.h

```
#define CR2      1024
#define CR3      1536
#define CRDLY    1536
#define VT1      16384
#define VTDLY    16384
#define OLCUC     2
#define TAB1     2048
#define NLDLY    256
#define FF1      32768
#define FFDLY    32768
#define ONLCR     4
#define XCASE     4
#define TAB2     4096
#define CR1      512
#define IUCLC     512
#define TAB3     6144
#define TABDLY   6144
#define BS1      8192
#define BSDLY   8192

#define VSUSP    10
#define VEOL     11
#define VREPRINT 12
#define VDISCARD 13
#define VWERASE  14
#define VEOL2    16
#define VMIN     6
#define VSWTC    7
#define VSTART   8
#define VSTOP    9

#define IXON     1024
#define IXOFF   4096

#define HUPCL    1024
#define CREAD   128
#define CS6     16
```

```
#define CLOCAL 2048
#define PARENB 256
#define CS7 32
#define CS8 48
#define CSIZE 48
#define VTIME 5
#define PARODD 512
#define CSTOPB 64

#define ISIG 1
#define ECHOPRT 1024
#define NOFLSH 128
#define ECHOE 16
#define PENDIN 16384
#define ICANON 2
#define ECHOKE 2048
#define TOSTOP 256
#define ECHOK 32
#define IEXTEN 32768
#define FLUSHO 4096
#define ECHOCTL 512
#define ECHONL 64
```

### 10.3.84 time.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.3.85 ucontext.h

```
#define NGREG 27

typedef union {
    double d;
    float f;
} fpreg_t;

typedef struct {
    unsigned int fpc;
    fpreg_t fprs[16];
} fpregset_t;

typedef struct {
    _psw_t psw;
    unsigned long int gregs[16];
    unsigned int aregs[16];
    fpregset_t fpregs;
} mcontext_t;

typedef struct ucontext {
    unsigned long int uc_flags;
    struct ucontext *uc_link;
    stack_t uc_stack;
    mcontext_t uc_mcontext;
    sigset_t uc_sigmask;
} ucontext_t;
```

### 10.3.86 ulimit.h

```
/*
```

```

* This header is architecture neutral
* Please refer to the generic specification for details
*/

```

### 10.3.87 unistd.h

```

/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
*/

```

### 10.3.88 utime.h

```

/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
*/

```

### 10.3.89 utmp.h

```

struct lastlog {
    time_t ll_time;
    char ll_line[UT_LINESIZE];
    char ll_host[UT_HOSTSIZE];
};

struct utmp {
    short ut_type;           /* Type of login. */
    pid_t ut_pid;            /* Process ID of login process.
*/                           /* Devicename. */
    char ut_id[4];           /* Inittab ID. */
    char ut_user[UT_NAMESIZE]; /* Username. */
    char ut_host[UT_HOSTSIZE]; /* Hostname for remote login. */
    struct exit_status ut_exit; /* Exit status of a process
marked as DEAD_PROCESS. */
    long int ut_session;      /* Session ID, used for
windowing. */
    struct timeval ut_tv;     /* Time entry was made. */
    int32_t ut_addr_v6[4];    /* Internet address of remote
host. */
    char __unused[20];         /* Reserved for future use. */
};

```

### 10.3.90 utmpx.h

```

struct utmpx {
    short ut_type;           /* Type of login. */
    pid_t ut_pid;            /* Process ID of login process.
*/                           /* Devicename. */
    char ut_id[4];           /* Inittab ID. */
    char ut_user[UT_NAMESIZE]; /* Username. */
    char ut_host[UT_HOSTSIZE]; /* Hostname for remote login. */
    struct exit_status ut_exit; /* Exit status of a process
marked as DEAD_PROCESS. */
    long int ut_session;      /* Session ID, used for
windowing. */
    struct timeval ut_tv;     /* Time entry was made. */
    int32_t ut_addr_v6[4];    /* Internet address of remote
*/

```

```
host. */
    char __unused[20];           /* Reserved for future use. */
};
```

### 10.3.91 wordexp.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

## 10.4 Interfaces for libm

[Table 10-37](#) defines the library name and shared object name for the libm library

**Table 10-37 libm Definition**

Library:	libm
SONAME:	libm.so.6

The behavior of the interfaces in this library is specified by the following specifications:

[LSB] [LSB Core - Generic](#)

[SUSv3] [POSIX 1003.1-2001 \(ISO/IEC 9945-2003\)](#)

[SUSv4] [POSIX 1003.1-2008 \(ISO/IEC 9945-2009\)](#)

### 10.4.1 Math

#### 10.4.1.1 Interfaces for Math

An LSB conforming implementation shall provide the architecture specific functions for Math specified in [Table 10-38](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-38 libm - Math Function Interfaces**

<a href="#">__finite(GLIBC_2.2) [LSB]</a>	<a href="#">__finitef(GLIBC_2.2) [LSB]</a>	<a href="#">__finitel(GLIBC_2.2) [LSB]</a>	<a href="#">__finitel(GLIBC_2.4) [LSB]</a>
<a href="#">__fpclassify(GLIBC_2.2) [LSB]</a>	<a href="#">__fpclassifyf(GLIBC_2.2) [LSB]</a>	<a href="#">__fpclassifyl(GLIBC_2.4) [LSB]</a>	<a href="#">__signbit(GLIBC_2.2) [LSB]</a>
<a href="#">__signbitf(GLIBC_2.2) [LSB]</a>	<a href="#">__signbitl(GLIBC_2.4) [LSB]</a>	<a href="#">acos(GLIBC_2.2) [SUSv4]</a>	<a href="#">acosf(GLIBC_2.2) [SUSv4]</a>
<a href="#">acosh(GLIBC_2.2) [SUSv4]</a>	<a href="#">acoshf(GLIBC_2.2) [SUSv4]</a>	<a href="#">acoshl(GLIBC_2.2) [SUSv4]</a>	<a href="#">acoshl(GLIBC_2.4) [SUSv4]</a>
<a href="#">acosl(GLIBC_2.2) [SUSv4]</a>	<a href="#">acosl(GLIBC_2.4) [SUSv4]</a>	<a href="#">asin(GLIBC_2.2) [SUSv4]</a>	<a href="#">asinf(GLIBC_2.2) [SUSv4]</a>
<a href="#">asinh(GLIBC_2.2) [SUSv4]</a>	<a href="#">asinhf(GLIBC_2.2) [SUSv4]</a>	<a href="#">asinhl(GLIBC_2.2) [SUSv4]</a>	<a href="#">asinhl(GLIBC_2.4) [SUSv4]</a>
<a href="#">asinl(GLIBC_2.2) [SUSv4]</a>	<a href="#">asinl(GLIBC_2.4) [SUSv4]</a>	<a href="#">atan(GLIBC_2.2) [SUSv4]</a>	<a href="#">atan2(GLIBC_2.2) [SUSv4]</a>
<a href="#">atan2f(GLIBC_2.2) [SUSv4]</a>	<a href="#">atan2l(GLIBC_2.2) [SUSv4]</a>	<a href="#">atan2l(GLIBC_2.4) [SUSv4]</a>	<a href="#">atanf(GLIBC_2.2) [SUSv4]</a>
<a href="#">atanh(GLIBC_2.2) [SUSv4]</a>	<a href="#">atanhf(GLIBC_2.2) [SUSv4]</a>	<a href="#">atanhl(GLIBC_2.2) [SUSv4]</a>	<a href="#">atanhl(GLIBC_2.4) [SUSv4]</a>
<a href="#">atanl(GLIBC_2.2) [SUSv4]</a>	<a href="#">atanl(GLIBC_2.4) [SUSv4]</a>	<a href="#">cabs(GLIBC_2.2) [SUSv4]</a>	<a href="#">cabsf(GLIBC_2.2) [SUSv4]</a>
<a href="#">cabsl(GLIBC_2.2)</a>	<a href="#">cabsl(GLIBC_2.4)</a>	<a href="#">cacos(GLIBC_2.2)</a>	<a href="#">cacosf(GLIBC_2.2)</a>

<a href="#">[SUSv4]</a>	<a href="#">[SUSv4]</a>	<a href="#">[SUSv4]</a>	2) <a href="#">[SUSv4]</a>
cacosh(GLIBC_2.2) <a href="#">[SUSv4]</a>	cacoshf(GLIBC_2.2) <a href="#">[SUSv4]</a>	cacoshl(GLIBC_2.2) <a href="#">[SUSv4]</a>	cacoshl(GLIBC_2.4) <a href="#">[SUSv4]</a>
cacosl(GLIBC_2.2) <a href="#">[SUSv4]</a>	cacosl(GLIBC_2.4) <a href="#">[SUSv4]</a>	carg(GLIBC_2.2) <a href="#">[SUSv4]</a>	cargf(GLIBC_2.2) <a href="#">[SUSv4]</a>
cargl(GLIBC_2.2) <a href="#">[SUSv4]</a>	cargl(GLIBC_2.4) <a href="#">[SUSv4]</a>	casin(GLIBC_2.2) <a href="#">[SUSv4]</a>	casinf(GLIBC_2.2) <a href="#">[SUSv4]</a>
casinh(GLIBC_2.2) <a href="#">[SUSv4]</a>	casinhf(GLIBC_2.2) <a href="#">[SUSv4]</a>	casinhl(GLIBC_2.2) <a href="#">[SUSv4]</a>	casinhl(GLIBC_2.4) <a href="#">[SUSv4]</a>
casinl(GLIBC_2.2) <a href="#">[SUSv4]</a>	casinl(GLIBC_2.4) <a href="#">[SUSv4]</a>	catan(GLIBC_2.2) <a href="#">[SUSv4]</a>	catanf(GLIBC_2.2) <a href="#">[SUSv4]</a>
catanh(GLIBC_2.2) <a href="#">[SUSv4]</a>	catanhf(GLIBC_2.2) <a href="#">[SUSv4]</a>	catanhl(GLIBC_2.2) <a href="#">[SUSv4]</a>	catanhl(GLIBC_2.4) <a href="#">[SUSv4]</a>
catanl(GLIBC_2.2) <a href="#">[SUSv4]</a>	catanl(GLIBC_2.4) <a href="#">[SUSv4]</a>	cbrt(GLIBC_2.2) <a href="#">[SUSv4]</a>	cbrtf(GLIBC_2.2) <a href="#">[SUSv4]</a>
cbrtl(GLIBC_2.2) <a href="#">[SUSv4]</a>	cbrtl(GLIBC_2.4) <a href="#">[SUSv4]</a>	ccos(GLIBC_2.2) <a href="#">[SUSv4]</a>	ccosf(GLIBC_2.2) <a href="#">[SUSv4]</a>
ccosh(GLIBC_2.2) <a href="#">[SUSv4]</a>	ccoshf(GLIBC_2.2) <a href="#">[SUSv4]</a>	ccoshl(GLIBC_2.2) <a href="#">[SUSv4]</a>	ccoshl(GLIBC_2.4) <a href="#">[SUSv4]</a>
ccosl(GLIBC_2.2) <a href="#">[SUSv4]</a>	ccosl(GLIBC_2.4) <a href="#">[SUSv4]</a>	ceil(GLIBC_2.2) <a href="#">[SUSv4]</a>	ceilf(GLIBC_2.2) <a href="#">[SUSv4]</a>
ceill(GLIBC_2.2) <a href="#">[SUSv4]</a>	ceill(GLIBC_2.4) <a href="#">[SUSv4]</a>	cexp(GLIBC_2.2) <a href="#">[SUSv4]</a>	cexpf(GLIBC_2.2) <a href="#">[SUSv4]</a>
cexpl(GLIBC_2.2) <a href="#">[SUSv4]</a>	cexpl(GLIBC_2.4) <a href="#">[SUSv4]</a>	cimag(GLIBC_2.2) <a href="#">[SUSv4]</a>	cimagf(GLIBC_2.2) <a href="#">[SUSv4]</a>
cimidl(GLIBC_2.2) <a href="#">[SUSv4]</a>	cimidl(GLIBC_2.4) <a href="#">[SUSv4]</a>	clog(GLIBC_2.2) <a href="#">[SUSv4]</a>	clog10(GLIBC_2.2) <a href="#">[LSB]</a>
clog10f(GLIBC_2.2) <a href="#">[LSB]</a>	clog10l(GLIBC_2.2) <a href="#">[LSB]</a>	clog10l(GLIBC_2.4) <a href="#">[LSB]</a>	clogf(GLIBC_2.2) <a href="#">[SUSv4]</a>
clogl(GLIBC_2.2) <a href="#">[SUSv4]</a>	clogl(GLIBC_2.4) <a href="#">[SUSv4]</a>	conj(GLIBC_2.2) <a href="#">[SUSv4]</a>	conjf(GLIBC_2.2) <a href="#">[SUSv4]</a>
conjl(GLIBC_2.2) <a href="#">[SUSv4]</a>	conjl(GLIBC_2.4) <a href="#">[SUSv4]</a>	copysign(GLIBC_2.2) <a href="#">[SUSv4]</a>	copysignf(GLIBC_2.2) <a href="#">[SUSv4]</a>
copysignl(GLIBC_2.2) <a href="#">[SUSv4]</a>	copysignl(GLIBC_2.4) <a href="#">[SUSv4]</a>	cos(GLIBC_2.2) <a href="#">[SUSv4]</a>	cosf(GLIBC_2.2) <a href="#">[SUSv4]</a>
cosh(GLIBC_2.2) <a href="#">[SUSv4]</a>	coshf(GLIBC_2.2) <a href="#">[SUSv4]</a>	coshl(GLIBC_2.2) <a href="#">[SUSv4]</a>	coshl(GLIBC_2.4) <a href="#">[SUSv4]</a>
cosl(GLIBC_2.2) <a href="#">[SUSv4]</a>	cosl(GLIBC_2.4) <a href="#">[SUSv4]</a>	cpow(GLIBC_2.2) <a href="#">[SUSv4]</a>	cpowf(GLIBC_2.2) <a href="#">[SUSv4]</a>
cpowl(GLIBC_2.2) <a href="#">[SUSv4]</a>	cpowl(GLIBC_2.4) <a href="#">[SUSv4]</a>	cproj(GLIBC_2.2) <a href="#">[SUSv4]</a>	cprojf(GLIBC_2.2) <a href="#">[SUSv4]</a>
cprojl(GLIBC_2.2) <a href="#">[SUSv4]</a>	cprojl(GLIBC_2.4) <a href="#">[SUSv4]</a>	creal(GLIBC_2.2) <a href="#">[SUSv4]</a>	crealf(GLIBC_2.2) <a href="#">[SUSv4]</a>
creall(GLIBC_2.2) <a href="#">[SUSv4]</a>	creall(GLIBC_2.4) <a href="#">[SUSv4]</a>	csin(GLIBC_2.2) <a href="#">[SUSv4]</a>	csinf(GLIBC_2.2) <a href="#">[SUSv4]</a>
csinh(GLIBC_2.2) <a href="#">[SUSv4]</a>	csinhf(GLIBC_2.2) <a href="#">[SUSv4]</a>	csinhl(GLIBC_2.2) <a href="#">[SUSv4]</a>	csinhl(GLIBC_2.4) <a href="#">[SUSv4]</a>
csinl(GLIBC_2.2) <a href="#">[SUSv4]</a>	csinl(GLIBC_2.4) <a href="#">[SUSv4]</a>	csqrt(GLIBC_2.2) <a href="#">[SUSv4]</a>	csqrtf(GLIBC_2.2) <a href="#">[SUSv4]</a>

<code>csqrts(GLIBC_2.2 ) [SUSv4]</code>	<code>csqrts(GLIBC_2.4 ) [SUSv4]</code>	<code>ctan(GLIBC_2.2) [SUSv4]</code>	<code>ctanf(GLIBC_2.2) [SUSv4]</code>
<code>ctanh(GLIBC_2.2) [SUSv4]</code>	<code>ctanhf(GLIBC_2.2 ) [SUSv4]</code>	<code>ctanhf(GLIBC_2.2 ) [SUSv4]</code>	<code>ctanhf(GLIBC_2.4 ) [SUSv4]</code>
<code>ctanl(GLIBC_2.2) [SUSv4]</code>	<code>ctanl(GLIBC_2.4) [SUSv4]</code>	<code>drem(GLIBC_2.2) [LSB]</code>	<code>dremf(GLIBC_2.2) [LSB]</code>
<code>dreml(GLIBC_2.2 ) [LSB]</code>	<code>dreml(GLIBC_2.4 ) [LSB]</code>	<code>erf(GLIBC_2.2) [SUSv4]</code>	<code>erfc(GLIBC_2.2) [SUSv4]</code>
<code>erfcf(GLIBC_2.2) [SUSv4]</code>	<code>erfcf(GLIBC_2.2) [SUSv4]</code>	<code>erfcf(GLIBC_2.4) [SUSv4]</code>	<code>erff(GLIBC_2.2) [SUSv4]</code>
<code>erfl(GLIBC_2.2) [SUSv4]</code>	<code>erfl(GLIBC_2.4) [SUSv4]</code>	<code>exp(GLIBC_2.2) [SUSv4]</code>	<code>exp10(GLIBC_2.2 ) [LSB]</code>
<code>exp10f(GLIBC_2.2) [LSB]</code>	<code>exp10l(GLIBC_2.2) [LSB]</code>	<code>exp10l(GLIBC_2.4) [LSB]</code>	<code>exp2(GLIBC_2.2) [SUSv4]</code>
<code>exp2f(GLIBC_2.2 ) [SUSv4]</code>	<code>exp2l(GLIBC_2.4 ) [SUSv4]</code>	<code>expf(GLIBC_2.2) [SUSv4]</code>	<code>expl(GLIBC_2.2) [SUSv4]</code>
<code>expl(GLIBC_2.4) [SUSv4]</code>	<code>expm1(GLIBC_2.2) [SUSv4]</code>	<code>expm1f(GLIBC_2.2) [SUSv4]</code>	<code>expm1l(GLIBC_2.2) [SUSv4]</code>
<code>expm1l(GLIBC_2.4) [SUSv4]</code>	<code>fabs(GLIBC_2.2) [SUSv4]</code>	<code>fabsf(GLIBC_2.2) [SUSv4]</code>	<code>fabsl(GLIBC_2.2) [SUSv4]</code>
<code>fabsl(GLIBC_2.4) [SUSv4]</code>	<code>fdim(GLIBC_2.2) [SUSv4]</code>	<code>fdimf(GLIBC_2.2) [SUSv4]</code>	<code>fdiml(GLIBC_2.2) [SUSv4]</code>
<code>fdiml(GLIBC_2.4) [SUSv4]</code>	<code>feclearexcept(GLIBC_2.2) [SUSv4]</code>	<code>fedisableexcept(GLIBC_2.2) [LSB]</code>	<code>feenableexcept(GLIBC_2.2) [LSB]</code>
<code>fegetenv(GLIBC_2.2) [SUSv4]</code>	<code>fegetexcept(GLIBC_2.2) [LSB]</code>	<code>fegetexceptflag(GLIBC_2.2) [SUSv4]</code>	<code>fegetround(GLIBC_2.2) [SUSv4]</code>
<code>feholdexcept(GLIBC_2.2) [SUSv4]</code>	<code>feraiseexcept(GLIBC_2.2) [SUSv4]</code>	<code>fesetenv(GLIBC_2.2) [SUSv4]</code>	<code>fesetexceptflag(GLIBC_2.2) [SUSv4]</code>
<code>fesetround(GLIBC_2.2) [SUSv4]</code>	<code>fetestexcept(GLIBC_2.2) [SUSv4]</code>	<code>feupdateenv(GLIBC_2.2) [SUSv4]</code>	<code>finite(GLIBC_2.2) [LSB]</code>
<code>finitef(GLIBC_2.2 ) [LSB]</code>	<code>finitel(GLIBC_2.2) [LSB]</code>	<code>finitel(GLIBC_2.4) [LSB]</code>	<code>floor(GLIBC_2.2) [SUSv4]</code>
<code>floorf(GLIBC_2.2 ) [SUSv4]</code>	<code>floorl(GLIBC_2.2) [SUSv4]</code>	<code>floorl(GLIBC_2.4) [SUSv4]</code>	<code>fma(GLIBC_2.2) [SUSv4]</code>
<code>fmaf(GLIBC_2.2) [SUSv4]</code>	<code>fmal(GLIBC_2.2) [SUSv4]</code>	<code>fmal(GLIBC_2.4) [SUSv4]</code>	<code>fmax(GLIBC_2.2) [SUSv4]</code>
<code>fmaxf(GLIBC_2.2) [SUSv4]</code>	<code>fmaxl(GLIBC_2.2) [SUSv4]</code>	<code>fmaxl(GLIBC_2.4) [SUSv4]</code>	<code>fmin(GLIBC_2.2) [SUSv4]</code>
<code>fminf(GLIBC_2.2) [SUSv4]</code>	<code>fminl(GLIBC_2.2) [SUSv4]</code>	<code>fminl(GLIBC_2.4) [SUSv4]</code>	<code>fmod(GLIBC_2.2) [SUSv4]</code>
<code>fmodf(GLIBC_2.2) [SUSv4]</code>	<code>fmodl(GLIBC_2.2) [SUSv4]</code>	<code>fmodl(GLIBC_2.4) [SUSv4]</code>	<code>frexp(GLIBC_2.2) [SUSv4]</code>
<code>frexpf(GLIBC_2.2) [SUSv4]</code>	<code>frexpl(GLIBC_2.2) [SUSv4]</code>	<code>frexpl(GLIBC_2.4) [SUSv4]</code>	<code>gamma(GLIBC_2.2) [LSB]</code>
<code>gammaf(GLIBC_2.2) [LSB]</code>	<code>gammal(GLIBC_2.2) [LSB]</code>	<code>gammal(GLIBC_2.4) [LSB]</code>	<code>hypot(GLIBC_2.2) [SUSv4]</code>
<code>hypotf(GLIBC_2.2) [SUSv4]</code>	<code>hypotl(GLIBC_2.2) [SUSv4]</code>	<code>hypotl(GLIBC_2.4) [SUSv4]</code>	<code>ilogb(GLIBC_2.2) [SUSv4]</code>

<code>ilogbf(GLIBC_2.2 ) [SUSv4]</code>	<code>ilogbl(GLIBC_2.2 ) [SUSv4]</code>	<code>ilogbl(GLIBC_2.4 ) [SUSv4]</code>	<code>j0(GLIBC_2.2) [SUSv4]</code>
<code>j0f(GLIBC_2.2) [LSB]</code>	<code>j0l(GLIBC_2.2) [LSB]</code>	<code>j0l(GLIBC_2.4) [LSB]</code>	<code>j1(GLIBC_2.2) [SUSv4]</code>
<code>j1f(GLIBC_2.2) [LSB]</code>	<code>j1l(GLIBC_2.2) [LSB]</code>	<code>j1l(GLIBC_2.4) [LSB]</code>	<code>jn(GLIBC_2.2) [SUSv4]</code>
<code>jnf(GLIBC_2.2) [LSB]</code>	<code>jnl(GLIBC_2.2) [LSB]</code>	<code>jnl(GLIBC_2.4) [LSB]</code>	<code>ldexp(GLIBC_2.2 ) [SUSv4]</code>
<code>ldexpf(GLIBC_2.2) [SUSv4]</code>	<code>ldexpl(GLIBC_2.2 ) [SUSv4]</code>	<code>ldexpl(GLIBC_2.4 ) [SUSv4]</code>	<code>lgamma(GLIBC_2.2) [SUSv4]</code>
<code>lgamma_r(GLIBC_2.2) [LSB]</code>	<code>lgammaf(GLIBC_2.2) [SUSv4]</code>	<code>lgammaf_r(GLIBC_2.2) [LSB]</code>	<code>lgammal(GLIBC_2.2) [SUSv4]</code>
<code>lgammal(GLIBC_2.4) [SUSv4]</code>	<code>lgammal_r(GLIBC_2.2) [LSB]</code>	<code>lgammal_r(GLIBC_2.4) [LSB]</code>	<code>llrint(GLIBC_2.2) [SUSv4]</code>
<code>llrintf(GLIBC_2.2 ) [SUSv4]</code>	<code>llrintl(GLIBC_2.2 ) [SUSv4]</code>	<code>llrintl(GLIBC_2.4 ) [SUSv4]</code>	<code>llround(GLIBC_2.2) [SUSv4]</code>
<code>llroundf(GLIBC_2.2 ) [SUSv4]</code>	<code>llroundl(GLIBC_2.2 ) [SUSv4]</code>	<code>llroundl(GLIBC_2.4 ) [SUSv4]</code>	<code>log(GLIBC_2.2) [SUSv4]</code>
<code>log10(GLIBC_2.2 ) [SUSv4]</code>	<code>log10f(GLIBC_2.2 ) [SUSv4]</code>	<code>log10l(GLIBC_2.2 ) [SUSv4]</code>	<code>log10l(GLIBC_2.4) [SUSv4]</code>
<code>log1p(GLIBC_2.2 ) [SUSv4]</code>	<code>log1pf(GLIBC_2.2 ) [SUSv4]</code>	<code>log1pl(GLIBC_2.2 ) [SUSv4]</code>	<code>log1pl(GLIBC_2.4) [SUSv4]</code>
<code>log2(GLIBC_2.2) [SUSv4]</code>	<code>log2f(GLIBC_2.2) [SUSv4]</code>	<code>log2l(GLIBC_2.2) [SUSv4]</code>	<code>log2l(GLIBC_2.4) [SUSv4]</code>
<code>logb(GLIBC_2.2) [SUSv4]</code>	<code>logbf(GLIBC_2.2) [SUSv4]</code>	<code>logbl(GLIBC_2.2) [SUSv4]</code>	<code>logbl(GLIBC_2.4) [SUSv4]</code>
<code>logf(GLIBC_2.2) [SUSv4]</code>	<code>logl(GLIBC_2.2) [SUSv4]</code>	<code>logl(GLIBC_2.4) [SUSv4]</code>	<code>lrint(GLIBC_2.2) [SUSv4]</code>
<code>lrintf(GLIBC_2.2) [SUSv4]</code>	<code>lrintl(GLIBC_2.2) [SUSv4]</code>	<code>lrintl(GLIBC_2.4) [SUSv4]</code>	<code>lround(GLIBC_2.2) [SUSv4]</code>
<code>lroundf(GLIBC_2.2 ) [SUSv4]</code>	<code>lroundl(GLIBC_2.2 ) [SUSv4]</code>	<code>lroundl(GLIBC_2.4) [SUSv4]</code>	<code>matherr(GLIBC_2.2) [LSB]</code>
<code>modf(GLIBC_2.2) [SUSv4]</code>	<code>modff(GLIBC_2.2 ) [SUSv4]</code>	<code>modfl(GLIBC_2.2 ) [SUSv4]</code>	<code>modfl(GLIBC_2.4) [SUSv4]</code>
<code>nan(GLIBC_2.2) [SUSv4]</code>	<code>nanf(GLIBC_2.2) [SUSv4]</code>	<code>nanl(GLIBC_2.2) [SUSv4]</code>	<code>nanl(GLIBC_2.4) [SUSv4]</code>
<code>nearbyint(GLIBC_2.2) [SUSv4]</code>	<code>nearbyintf(GLIBC_2.2) [SUSv4]</code>	<code>nearbyintl(GLIBC_2.2) [SUSv4]</code>	<code>nearbyintl(GLIBC_2.4) [SUSv4]</code>
<code>nextafter(GLIBC_2.2) [SUSv4]</code>	<code>nextafterf(GLIBC_2.2) [SUSv4]</code>	<code>nextafterl(GLIBC_2.2) [SUSv4]</code>	<code>nextafterl(GLIBC_2.4) [SUSv4]</code>
<code>nexttoward(GLIBC_2.2) [SUSv4]</code>	<code>nexttoward(GLIBC_2.4) [SUSv4]</code>	<code>nexttowardf(GLIBC_2.2) [SUSv4]</code>	<code>nexttowardf(GLIBC_2.4) [SUSv4]</code>
<code>nexttowardl(GLIBC_2.2) [SUSv4]</code>	<code>nexttowardl(GLIBC_2.4) [SUSv4]</code>	<code>pow(GLIBC_2.2) [SUSv4]</code>	<code>pow10(GLIBC_2.2) [LSB]</code>
<code>pow10f(GLIBC_2.2 ) [LSB]</code>	<code>pow10l(GLIBC_2.2 ) [LSB]</code>	<code>pow10l(GLIBC_2.4) [LSB]</code>	<code>powf(GLIBC_2.2) [SUSv4]</code>
<code>powl(GLIBC_2.2) [SUSv4]</code>	<code>powl(GLIBC_2.4) [SUSv4]</code>	<code>remainder(GLIBC_2.2) [SUSv4]</code>	<code>remainderf(GLIBC_2.2) [SUSv4]</code>
<code>remainderl(GLIBC_2.2) [SUSv4]</code>	<code>remainderl(GLIBC_2.4) [SUSv4]</code>	<code>remquo(GLIBC_2.2) [SUSv4]</code>	<code>remquof(GLIBC_2.2) [SUSv4]</code>

remquo(GLIBC_2.2) [SUSv4]	remquo(GLIBC_2.4) [SUSv4]	rint(GLIBC_2.2) [SUSv4]	rintf(GLIBC_2.2) [SUSv4]
rintl(GLIBC_2.2) [SUSv4]	rintl(GLIBC_2.4) [SUSv4]	round(GLIBC_2.2) [SUSv4]	roundf(GLIBC_2.2) [SUSv4]
roundl(GLIBC_2.2) [SUSv4]	roundl(GLIBC_2.4) [SUSv4]	scalb(GLIBC_2.2) [SUSv3]	scalbf(GLIBC_2.2) [LSB]
scalbl(GLIBC_2.2) [LSB]	scalbl(GLIBC_2.4) [LSB]	scalbln(GLIBC_2.2) [SUSv4]	scalblnf(GLIBC_2.2) [SUSv4]
scalblnl(GLIBC_2.2) [SUSv4]	scalblnl(GLIBC_2.4) [SUSv4]	scalbn(GLIBC_2.2) [SUSv4]	scalbnf(GLIBC_2.2) [SUSv4]
scalbnl(GLIBC_2.2) [SUSv4]	scalbnl(GLIBC_2.4) [SUSv4]	significand(GLIBC_2.2) [LSB]	significandf(GLIBC_2.2) [LSB]
significndl(GLIBC_2.2) [LSB]	significndl(GLIBC_2.4) [LSB]	sin(GLIBC_2.2) [SUSv4]	sincos(GLIBC_2.2) [LSB]
sincosf(GLIBC_2.2) [LSB]	sincosl(GLIBC_2.2) [LSB]	sincosl(GLIBC_2.4) [LSB]	sinf(GLIBC_2.2) [SUSv4]
sinh(GLIBC_2.2) [SUSv4]	sinhf(GLIBC_2.2) [SUSv4]	sinhl(GLIBC_2.2) [SUSv4]	sinhl(GLIBC_2.4) [SUSv4]
sinl(GLIBC_2.2) [SUSv4]	sinl(GLIBC_2.4) [SUSv4]	sqrt(GLIBC_2.2) [SUSv4]	sqrtf(GLIBC_2.2) [SUSv4]
sqrtl(GLIBC_2.2) [SUSv4]	sqrtl(GLIBC_2.4) [SUSv4]	tan(GLIBC_2.2) [SUSv4]	tanf(GLIBC_2.2) [SUSv4]
tanh(GLIBC_2.2) [SUSv4]	tanhf(GLIBC_2.2) [SUSv4]	tanhl(GLIBC_2.2) [SUSv4]	tanhl(GLIBC_2.4) [SUSv4]
tanl(GLIBC_2.2) [SUSv4]	tanl(GLIBC_2.4) [SUSv4]	tgamma(GLIBC_2.2) [SUSv4]	tgammaf(GLIBC_2.2) [SUSv4]
tgammal(GLIBC_2.2) [SUSv4]	tgammal(GLIBC_2.4) [SUSv4]	trunc(GLIBC_2.2) [SUSv4]	truncf(GLIBC_2.2) [SUSv4]
truncl(GLIBC_2.2) [SUSv4]	truncl(GLIBC_2.4) [SUSv4]	y0(GLIBC_2.2) [SUSv4]	y0f(GLIBC_2.2) [LSB]
y0l(GLIBC_2.2) [LSB]	y0l(GLIBC_2.4) [LSB]	y1(GLIBC_2.2) [SUSv4]	y1f(GLIBC_2.2) [LSB]
y1l(GLIBC_2.2) [LSB]	y1l(GLIBC_2.4) [LSB]	yn(GLIBC_2.2) [SUSv4]	ynf(GLIBC_2.2) [LSB]
ynl(GLIBC_2.2) [LSB]	ynl(GLIBC_2.4) [LSB]		

An LSB conforming implementation shall provide the architecture specific deprecated functions for Math specified in [Table 10-39](#), with the full mandatory functionality as described in the referenced underlying specification.

**Note:** These interfaces are deprecated, and applications should avoid using them. These interfaces may be withdrawn in future releases of this specification.

**Table 10-39 libm - Math Deprecated Function Interfaces**

__finitel(GLIBC_2.2) [LSB]	acoshl(GLIBC_2.2) [SUSv4]	acosl(GLIBC_2.2) [SUSv4]	asinhl(GLIBC_2.2) [SUSv4]
asinl(GLIBC_2.2) [SUSv4]	atan2l(GLIBC_2.2) [SUSv4]	atanhl(GLIBC_2.2) [SUSv4]	atanl(GLIBC_2.2) [SUSv4]
cabsl(GLIBC_2.2) [SUSv4]	cacoshl(GLIBC_2.2) [SUSv4]	cacosl(GLIBC_2.2) [SUSv4]	cargl(GLIBC_2.2) [SUSv4]

<code>casinh(GLIBC_2.2) [SUSv4]</code>	<code>casinl(GLIBC_2.2) [SUSv4]</code>	<code>catanhl(GLIBC_2.2) [SUSv4]</code>	<code>catanl(GLIBC_2.2) [SUSv4]</code>
<code>cbtrl(GLIBC_2.2) [SUSv4]</code>	<code>ccoshl(GLIBC_2.2) [SUSv4]</code>	<code>ccosl(GLIBC_2.2) [SUSv4]</code>	<code>ceil(GLIBC_2.2) [SUSv4]</code>
<code>cexpl(GLIBC_2.2) [SUSv4]</code>	<code>cimagl(GLIBC_2.2) [SUSv4]</code>	<code>clog10l(GLIBC_2.2) [SUSv4]</code>	<code>clogl(GLIBC_2.2) [SUSv4]</code>
<code>conjl(GLIBC_2.2) [SUSv4]</code>	<code>copysignl(GLIBC_2.2) [SUSv4]</code>	<code>coshl(GLIBC_2.2) [SUSv4]</code>	<code>cosl(GLIBC_2.2) [SUSv4]</code>
<code>cpowl(GLIBC_2.2) [SUSv4]</code>	<code>cprojl(GLIBC_2.2) [SUSv4]</code>	<code>creall(GLIBC_2.2) [SUSv4]</code>	<code>csinhl(GLIBC_2.2) [SUSv4]</code>
<code>csinl(GLIBC_2.2) [SUSv4]</code>	<code>csqrtl(GLIBC_2.2) [SUSv4]</code>	<code>ctanhl(GLIBC_2.2) [SUSv4]</code>	<code>ctanl(GLIBC_2.2) [SUSv4]</code>
<code>drem(GLIBC_2.2) [LSB]</code>	<code>dremf(GLIBC_2.2) [LSB]</code>	<code>dreml(GLIBC_2.2) [LSB]</code>	<code>dreml(GLIBC_2.4) [LSB]</code>
<code>erfc1l(GLIBC_2.2) [SUSv4]</code>	<code>erfl(GLIBC_2.2) [SUSv4]</code>	<code>exp10l(GLIBC_2.2) [LSB]</code>	<code>expl(GLIBC_2.2) [SUSv4]</code>
<code>expm1l(GLIBC_2.2) [SUSv4]</code>	<code>fabsl(GLIBC_2.2) [SUSv4]</code>	<code>fdiml(GLIBC_2.2) [SUSv4]</code>	<code>finite(GLIBC_2.2) [LSB]</code>
<code>finitef(GLIBC_2.2) [LSB]</code>	<code>finitel(GLIBC_2.2) [LSB]</code>	<code>finitel(GLIBC_2.4) [LSB]</code>	<code>floorl(GLIBC_2.2) [SUSv4]</code>
<code>fmal(GLIBC_2.2) [SUSv4]</code>	<code>fmaxl(GLIBC_2.2) [SUSv4]</code>	<code>fminl(GLIBC_2.2) [SUSv4]</code>	<code>fmodl(GLIBC_2.2) [SUSv4]</code>
<code>freexpl(GLIBC_2.2) [SUSv4]</code>	<code>gamma(GLIBC_2.2) [LSB]</code>	<code>gammal(GLIBC_2.2) [LSB]</code>	<code>gammal(GLIBC_2.2) [LSB]</code>
<code>gammal(GLIBC_2.4) [LSB]</code>	<code>hypotl(GLIBC_2.2) [SUSv4]</code>	<code>ilogbl(GLIBC_2.2) [SUSv4]</code>	<code>j0l(GLIBC_2.2) [LSB]</code>
<code>j1l(GLIBC_2.2) [LSB]</code>	<code>jnl(GLIBC_2.2) [LSB]</code>	<code>ldexpl(GLIBC_2.2) [SUSv4]</code>	<code>lgammal(GLIBC_2.2) [SUSv4]</code>
<code>lgamma_r(GLIBC_2.2) [LSB]</code>	<code>llrintl(GLIBC_2.2) [SUSv4]</code>	<code>llroundl(GLIBC_2.2) [SUSv4]</code>	<code>log10l(GLIBC_2.2) [SUSv4]</code>
<code>log1pl(GLIBC_2.2) [SUSv4]</code>	<code>log2l(GLIBC_2.2) [SUSv4]</code>	<code>logbl(GLIBC_2.2) [SUSv4]</code>	<code>logl(GLIBC_2.2) [SUSv4]</code>
<code>lrintl(GLIBC_2.2) [SUSv4]</code>	<code>lroundl(GLIBC_2.2) [SUSv4]</code>	<code>matherr(GLIBC_2.2) [LSB]</code>	<code>modfl(GLIBC_2.2) [SUSv4]</code>
<code>nanl(GLIBC_2.2) [SUSv4]</code>	<code>nearbyintl(GLIBC_2.2) [SUSv4]</code>	<code>nextafterl(GLIBC_2.2) [SUSv4]</code>	<code>nexttoward(GLIBC_2.2) [SUSv4]</code>
<code>nexttowardf(GLIBC_2.2) [SUSv4]</code>	<code>nexttowardl(GLIBC_2.2) [SUSv4]</code>	<code>pow10l(GLIBC_2.2) [LSB]</code>	<code>powl(GLIBC_2.2) [SUSv4]</code>
<code>remainderl(GLIBC_2.2) [SUSv4]</code>	<code>remquol(GLIBC_2.2) [SUSv4]</code>	<code>rintl(GLIBC_2.2) [SUSv4]</code>	<code>roundl(GLIBC_2.2) [SUSv4]</code>
<code>scalbl(GLIBC_2.2) [LSB]</code>	<code>scalblnl(GLIBC_2.2) [SUSv4]</code>	<code>scalbnl(GLIBC_2.2) [SUSv4]</code>	<code>significndl(GLIBC_2.2) [LSB]</code>
<code>sincosl(GLIBC_2.2) [LSB]</code>	<code>sinhl(GLIBC_2.2) [SUSv4]</code>	<code>sinl(GLIBC_2.2) [SUSv4]</code>	<code>sqrtl(GLIBC_2.2) [SUSv4]</code>
<code>tanhl(GLIBC_2.2) [SUSv4]</code>	<code>tanl(GLIBC_2.2) [SUSv4]</code>	<code>tgammal(GLIBC_2.2) [SUSv4]</code>	<code>trunc1(GLIBC_2.2) [SUSv4]</code>
<code>y0l(GLIBC_2.2) [LSB]</code>	<code>y1l(GLIBC_2.2) [LSB]</code>	<code>ynl(GLIBC_2.2) [LSB]</code>	

An LSB conforming implementation shall provide the architecture specific data inter-

faces for Math specified in [Table 10-40](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-40 libm - Math Data Interfaces**

signgam(GLIBC_2.2) [ <a href="#">SUSv4</a> ]			
----------------------------------------------	--	--	--

## 10.5 Data Definitions for libm

This section defines global identifiers and their values that are associated with interfaces contained in libm. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the [ISO C \(1999\)](#) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

### 10.5.1 complex.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 10.5.2 fenv.h

```
#define FE_INEXACT      0x08
#define FE_UNDERFLOW    0x10
#define FE_OVERFLOW      0x20
#define FE_DIVBYZERO    0x40
#define FE_INVALID       0x80

#define FE_ALL_EXCEPT   \
    (FE_INEXACT | FE_DIVBYZERO | FE_UNDERFLOW | FE_OVERFLOW | \
     FE_INVALID)

#define FE_TONEAREST     0
#define FE_TOWARDZERO   0x1
#define FE_UPWARD        0x2
#define FE_DOWNWARD      0x3

typedef unsigned int fexcept_t;

typedef struct {
    fexcept_t fpc;
    void *ieee_instruction_pointer;
} fenv_t;

#define FE_DFL_ENV      ((const fenv_t *) -1)
```

### 10.5.3 math.h

```

typedef double float_t;
typedef double double_t;

#define isfinite(x)      \
    (sizeof (x) == sizeof (float) ? __finitef (x) : sizeof (x) == \
     sizeof (double)? __finite (x) : __finitel (x)) /* Return nonzero \
value if X is not +-Inf or NaN. */
#define fpclassify(x)   \
    (sizeof (x) == sizeof (float) ? __fpclassifyf (x) : sizeof (x) == \
     sizeof (double) ? __fpclassify (x) : __fpclassifyl \
    (x)) /* Return number of classification appropriate for X. \
*/
#define isinf(x)        \
    (sizeof (x) == sizeof (float) ? __isnaf (x) : sizeof (x) == \
     sizeof (double) ? __isnan (x) : __isnanl (x))
#define isnan(x)         \
    (sizeof (x) == sizeof (float) ? __isnanf (x) : sizeof (x) == \
     sizeof (double) ? __isnan (x) : __isnanl (x))
#define signbit(x)       \
    (sizeof (x) == sizeof (float)? __signbitf (x): sizeof (x) == \
     sizeof (double)? __signbit (x) : __signbitl (x) /* Return \
nonzero value if sign of X is negative. */

#define HUGE_VALL        0x1.0p2047L
#define FP_ILOGB0        -2147483647
#define FP_ILOGBNAN      2147483647

extern int __fpclassifyl(long double);
extern int __signbitl(long double);
extern long double exp2l(long double);

```

## 10.6 Interface Definitions for libm

The interfaces defined on the following pages are included in libm and are defined by this specification. Unless otherwise noted, these interfaces shall be included in the source standard.

Other interfaces listed in [Section 10.4](#) shall behave as described in the referenced base document. For interfaces referencing LSB and not listed below, please see the generic part of the specification.

### **\_\_fpclassifyl**

#### **Name**

**\_\_fpclassifyl** — Classify real floating type

#### **Synopsis**

```
int __fpclassifyl(long double arg);
```

#### **Description**

**\_\_fpclassifyl()** has the same specification as **fpclassify()** in [POSIX 1003.1-2008 \(ISO/IEC 9945-2009\)](#), except that the argument type for **\_\_fpclassifyl()** is known to be long double.

**\_\_fpclassifyl()** is not in the source standard; it is only in the binary standard.

## **\_\_signbitl**

### **Name**

`__signbitl` — test sign of floating point value

### **Synopsis**

```
#include <math.h>
int __signbitl(long double arg);
```

### **Description**

`__signbitl()` has the same specification as `signbit()` in [POSIX 1003.1-2008 \(ISO/IEC 9945-2009\)](#), except that the argument type for `__signbitl()` is known to be long double.

`__signbitl()` is not in the source standard; it is only in the binary standard.

## **10.7 Interfaces for libpthread**

[Table 10-41](#) defines the library name and shared object name for the libpthread library

**Table 10-41 libpthread Definition**

Library:	libpthread
SONAME:	libpthread.so.0

The behavior of the interfaces in this library is specified by the following specifications:

[LFS] [Large File Support](#)

[LSB] [LSB Core - Generic](#)

[SUSv3] [POSIX 1003.1-2001 \(ISO/IEC 9945-2003\)](#)

[SUSv4] [POSIX 1003.1-2008 \(ISO/IEC 9945-2009\)](#)

### **10.7.1 Realtime Threads**

#### **10.7.1.1 Interfaces for Realtime Threads**

An LSB conforming implementation shall provide the architecture specific functions for Realtime Threads specified in [Table 10-42](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-42 libpthread - Realtime Threads Function Interfaces**

<code>pthread_attr_getinheritsched(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_attr_getschedpolicy(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_attr_getscopelist(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_attr_setscheduler(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>pthread_attr_setschedpolicy(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_attr_setscheduleparam(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_getschedulingparam(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_setscheduleparam(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>

### **10.7.2 Advanced Realtime Threads**

#### **10.7.2.1 Interfaces for Advanced Realtime Threads**

An LSB conforming implementation shall provide the architecture specific functions for Advanced Realtime Threads specified in [Table 10-43](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-43 libpthread - Advanced Realtime Threads Function Interfaces**

<code>pthread_barrier_destroy(GLIBC_2.2) [SUSv4]</code>	<code>pthread_barrier_init(GLIBC_2.2) [SUSv4]</code>	<code>pthread_barrier_wait(GLIBC_2.2) [SUSv4]</code>	<code>pthread_barrierattr_destroy(GLIBC_2.2) [SUSv4]</code>
<code>pthread_barrierattr_init(GLIBC_2.2) [SUSv4]</code>	<code>pthread_barrierattr_setpshared(GLIBC_2.2) [SUSv4]</code>	<code>pthread_getcpulockid(GLIBC_2.2) [SUSv4]</code>	<code>pthread_spin_destroy(GLIBC_2.2) [SUSv4]</code>
<code>pthread_spin_init(GLIBC_2.2) [SUSv4]</code>	<code>pthread_spin_lock(GLIBC_2.2) [SUSv4]</code>	<code>pthread_spin_trylock(GLIBC_2.2) [SUSv4]</code>	<code>pthread_spin_unlock(GLIBC_2.2) [SUSv4]</code>

## 10.7.3 Posix Threads

### 10.7.3.1 Interfaces for Posix Threads

An LSB conforming implementation shall provide the architecture specific functions for Posix Threads specified in [Table 10-44](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-44 libpthread - Posix Threads Function Interfaces**

<code>_pthread_cleanup_pop(GLIBC_2.2) [LSB]</code>	<code>_pthread_cleanup_push(GLIBC_2.2) [LSB]</code>	<code>pthread_attr_destroy(GLIBC_2.2) [SUSv4]</code>	<code>pthread_attr_getdetachstate(GLIBC_2.2) [SUSv4]</code>
<code>pthread_attr_getguardsize(GLIBC_2.2) [SUSv4]</code>	<code>pthread_attr_getschedparam(GLIBC_2.2) [SUSv4]</code>	<code>pthread_attr_getstackaddr(GLIBC_2.2) [SUSv4]</code>	<code>pthread_attr_getstackaddraddr(GLIBC_2.2) [SUSv3]</code>
<code>pthread_attr_getstacksize(GLIBC_2.2) [SUSv4]</code>	<code>pthread_attr_init(GLIBC_2.2) [SUSv4]</code>	<code>pthread_attr_setdetachstate(GLIBC_2.2) [SUSv4]</code>	<code>pthread_attr_setguardsize(GLIBC_2.2) [SUSv4]</code>
<code>pthread_attr_setschedparam(GLIBC_2.2) [SUSv4]</code>	<code>pthread_attr_setstackaddr(GLIBC_2.2) [SUSv4]</code>	<code>pthread_attr_setstackaddraddr(GLIBC_2.2) [SUSv3]</code>	<code>pthread_attr_setstacksize(GLIBC_2.2) [SUSv4]</code>
<code>pthread_cancel(GLIBC_2.2) [SUSv4]</code>	<code>pthread_cond_broadcast(GLIBC_2.3.2) [SUSv4]</code>	<code>pthread_cond_destroy(GLIBC_2.3.2) [SUSv4]</code>	<code>pthread_cond_init(GLIBC_2.3.2) [SUSv4]</code>
<code>pthread_cond_signal(GLIBC_2.3.2) [SUSv4]</code>	<code>pthread_cond_timedwait(GLIBC_2.3.2) [SUSv4]</code>	<code>pthread_cond_wait(GLIBC_2.3.2) [SUSv4]</code>	<code>pthread_condattr_destroy(GLIBC_2.2) [SUSv4]</code>
<code>pthread_condattr_getpshared(GLIBC_2.2) [SUSv4]</code>	<code>pthread_condattr_init(GLIBC_2.2) [SUSv4]</code>	<code>pthread_condattr_setpshared(GLIBC_2.2) [SUSv4]</code>	<code>pthread_create(GLIBC_2.2) [SUSv4]</code>
<code>pthread_detach(GLIBC_2.2) [SUSv4]</code>	<code>pthread_equal(GLIBC_2.2) [SUSv4]</code>	<code>pthread_exit(GLIBC_2.2) [SUSv4]</code>	<code>pthread_getconcurrency(GLIBC_2.2) [SUSv4]</code>
<code>pthread_getspecific(GLIBC_2.2) [SUSv4]</code>	<code>pthread_join(GLIBC_2.2) [SUSv4]</code>	<code>pthread_key_create(GLIBC_2.2) [SUSv4]</code>	<code>pthread_key_delete(GLIBC_2.2) [SUSv4]</code>
<code>pthread_kill(GLIBC_2.2) [SUSv4]</code>	<code>pthread_mutex_destroy(GLIBC_2.2) [SUSv4]</code>	<code>pthread_mutex_init(GLIBC_2.2) [SUSv4]</code>	<code>pthread_mutex_lock(GLIBC_2.2) [SUSv4]</code>
<code>pthread_mutex_timedlock(GLIBC_2.2) [SUSv4]</code>	<code>pthread_mutex_trylock(GLIBC_2.2) [SUSv4]</code>	<code>pthread_mutex_unlock(GLIBC_2.2) [SUSv4]</code>	<code>pthread_mutexattr_destroy(GLIBC_2.2) [SUSv4]</code>

pthread_mutexattr_getpshared(GLIBC_2.2) [SUSv4]	pthread_mutexattr_gettype(GLIBC_2.2) [SUSv4]	pthread_mutexattr_init(GLIBC_2.2) [SUSv4]	pthread_mutexattr_setpshared(GLIBC_2.2) [SUSv4]
pthread_mutexattr_settype(GLIBC_2.2) [SUSv4]	pthread_once(GLIBC_2.2) [SUSv4]	pthread_rwlock_destroy(GLIBC_2.2) [SUSv4]	pthread_rwlock_init(GLIBC_2.2) [SUSv4]
pthread_rwlock_rdlock(GLIBC_2.2) [SUSv4]	pthread_rwlock_timedrdlock(GLIBC_2.2) [SUSv4]	pthread_rwlock_timedwrlock(GLIBC_2.2) [SUSv4]	pthread_rwlock_tryrdlock(GLIBC_2.2) [SUSv4]
pthread_rwlock_trywrlock(GLIBC_2.2) [SUSv4]	pthread_rwlock_untlock(GLIBC_2.2) [SUSv4]	pthread_rwlock_wlock(GLIBC_2.2) [SUSv4]	pthread_rwlockattr_destroy(GLIBC_2.2) [SUSv4]
pthread_rwlockattr_getpshared(GLIBC_2.2) [SUSv4]	pthread_rwlockattr_init(GLIBC_2.2) [SUSv4]	pthread_rwlockattr_setpshared(GLIBC_2.2) [SUSv4]	pthread_self(GLIBC_2.2) [SUSv4]
pthread_setscanceltate(GLIBC_2.2) [SUSv4]	pthread_setscanceltype(GLIBC_2.2) [SUSv4]	pthread_setconcurrency(GLIBC_2.2) [SUSv4]	pthread_setspecific(GLIBC_2.2) [SUSv4]
pthread_sigmask(GLIBC_2.2) [SUSv4]	pthread_testcancel(GLIBC_2.2) [SUSv4]	sem_close(GLIBC_2.2) [SUSv4]	sem_destroy(GLIBC_2.2) [SUSv4]
sem_getvalue(GLIBC_2.2) [SUSv4]	sem_init(GLIBC_2.2) [SUSv4]	sem_open(GLIBC_2.2) [SUSv4]	sem_post(GLIBC_2.2) [SUSv4]
sem_timedwait(GLIBC_2.2) [SUSv4]	sem_trywait(GLIBC_2.2) [SUSv4]	sem_unlink(GLIBC_2.2) [SUSv4]	sem_wait(GLIBC_2.2) [SUSv4]

An LSB conforming implementation shall provide the architecture specific deprecated functions for Posix Threads specified in [Table 10-45](#), with the full mandatory functionality as described in the referenced underlying specification.

**Note:** These interfaces are deprecated, and applications should avoid using them. These interfaces may be withdrawn in future releases of this specification.

**Table 10-45 libpthread - Posix Threads Deprecated Function Interfaces**

pthread_attr_getstackaddr(GLIBC_2.2) [SUSv3]	pthread_attr_setstackaddr(GLIBC_2.2) [SUSv3]		
----------------------------------------------	----------------------------------------------	--	--

## 10.7.4 Thread aware versions of libc interfaces

### 10.7.4.1 Interfaces for Thread aware versions of libc interfaces

An LSB conforming implementation shall provide the architecture specific functions for Thread aware versions of libc interfaces specified in [Table 10-46](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-46 libpthread - Thread aware versions of libc interfaces Function Interfaces**

lseek64(GLIBC_2.2) [LFS]	open64(GLIBC_2.2) [LFS]	pread(GLIBC_2.2) [SUSv4]	pread64(GLIBC_2.2) [LSB]
pwrite(GLIBC_2.2) [SUSv4]	pwrite64(GLIBC_2.2) [LSB]		

## 10.7.5 GNU Extensions for libpthread

### 10.7.5.1 Interfaces for GNU Extensions for libpthread

An LSB conforming implementation shall provide the architecture specific functions for GNU Extensions for libpthread specified in [Table 10-47](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-47 libpthread - GNU Extensions for libpthread Function Interfaces**

pthread_getattr_np (GLIBC_2.2.3) <a href="#">[LSB]</a>	pthread_mutex_consistent_np(GLIBC_2.4) <a href="#">[LSB]</a>	pthread_mutexattr_getrobust_np(GLIBC_2.4) <a href="#">[LSB]</a>	pthread_mutexattr_setrobust_np(GLIBC_2.4) <a href="#">[LSB]</a>
pthread_rwlockattr_getkind_np(GLIBC_2.2) <a href="#">[LSB]</a>	pthread_rwlockattr_setkind_np(GLIBC_2.2) <a href="#">[LSB]</a>		

## 10.7.6 System Calls

### 10.7.6.1 Interfaces for System Calls

An LSB conforming implementation shall provide the architecture specific functions for System Calls specified in [Table 10-48](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-48 libpthread - System Calls Function Interfaces**

close(GLIBC_2.2) <a href="#">[SUSv4]</a>	fcntl(GLIBC_2.2) <a href="#">[LSB]</a>	fork(GLIBC_2.2) <a href="#">[SUSv4]</a>	fsync(GLIBC_2.2) <a href="#">[SUSv4]</a>
lseek(GLIBC_2.2) <a href="#">[SUSv4]</a>	msync(GLIBC_2.2) <a href="#">[SUSv4]</a>	nanosleep(GLIBC_2.2) <a href="#">[SUSv4]</a>	open(GLIBC_2.2) <a href="#">[SUSv4]</a>
pause(GLIBC_2.2) <a href="#">[SUSv4]</a>	read(GLIBC_2.2) <a href="#">[SUSv4]</a>	vfork(GLIBC_2.2) <a href="#">[SUSv3]</a>	wait(GLIBC_2.2) <a href="#">[SUSv4]</a>
waitpid(GLIBC_2.2) <a href="#">[LSB]</a>	write(GLIBC_2.2) <a href="#">[SUSv4]</a>		

## 10.7.7 Standard I/O

### 10.7.7.1 Interfaces for Standard I/O

An LSB conforming implementation shall provide the architecture specific functions for Standard I/O specified in [Table 10-49](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-49 libpthread - Standard I/O Function Interfaces**

flockfile(GLIBC_2.2) <a href="#">[SUSv4]</a>			
-------------------------------------------------	--	--	--

## 10.7.8 Signal Handling

### 10.7.8.1 Interfaces for Signal Handling

An LSB conforming implementation shall provide the architecture specific functions for Signal Handling specified in [Table 10-50](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-50 libpthread - Signal Handling Function Interfaces**

__libc_current_sigrtmax(GLIBC_2.2)	__libc_current_sigrtmin(GLIBC_2.2)	raise(GLIBC_2.2) <a href="#">[SUSv4]</a>	sigaction(GLIBC_2.2) <a href="#">[SUSv4]</a>
------------------------------------	------------------------------------	---------------------------------------------	-------------------------------------------------

) <a href="#">[LSB]</a>	<a href="#">[LSB]</a>		
siglongjmp(GLIBC_C_2.2) <a href="#">[SUSv4]</a>	sigwait(GLIBC_2.2) <a href="#">[SUSv4]</a>		

## 10.7.9 Standard Library

### 10.7.9.1 Interfaces for Standard Library

An LSB conforming implementation shall provide the architecture specific functions for Standard Library specified in [Table 10-51](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-51 libpthread - Standard Library Function Interfaces**

__errno_location(GLIBC_2.2) <a href="#">[LSB]</a>	ftrylockfile(GLIBC_C_2.2) <a href="#">[SUSv4]</a>	funlockfile(GLIBC_C_2.2) <a href="#">[SUSv4]</a>	longjmp(GLIBC_2.2) <a href="#">[SUSv4]</a>
system(GLIBC_2.2) <a href="#">[LSB]</a>			

## 10.7.10 Socket Interface

### 10.7.10.1 Interfaces for Socket Interface

An LSB conforming implementation shall provide the architecture specific functions for Socket Interface specified in [Table 10-52](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-52 libpthread - Socket Interface Function Interfaces**

__h_errno_locatio n(GLIBC_2.2) <a href="#">[LSB]</a>	accept(GLIBC_2.2) <a href="#">[SUSv4]</a>	connect(GLIBC_2.2) <a href="#">[SUSv4]</a>	recv(GLIBC_2.2) <a href="#">[SUSv4]</a>
recvfrom(GLIBC_2.2) <a href="#">[SUSv4]</a>	recvmsg(GLIBC_2.2) <a href="#">[SUSv4]</a>	send(GLIBC_2.2) <a href="#">[SUSv4]</a>	sendmsg(GLIBC_2.2) <a href="#">[SUSv4]</a>
sendto(GLIBC_2.2) <a href="#">[SUSv4]</a>			

## 10.7.11 Terminal Interface Functions

### 10.7.11.1 Interfaces for Terminal Interface Functions

An LSB conforming implementation shall provide the architecture specific functions for Terminal Interface Functions specified in [Table 10-53](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-53 libpthread - Terminal Interface Functions Function Interfaces**

tcdrain(GLIBC_2.2) <a href="#">[SUSv4]</a>			
--------------------------------------------	--	--	--

## 10.8 Data Definitions for libpthread

This section defines global identifiers and their values that are associated with interfaces contained in libpthread. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the [ISO C \(1999\)](#) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

## 10.8.1 lsb/pthread.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

## 10.8.2 pthread.h

```
#define __SIZEOF_PTHREAD_BARRIER_T      32
#define __SIZEOF_PTHREAD_MUTEX_T         40
#define __SIZEOF_PTHREAD_ATTR_T         56
#define __SIZEOF_PTHREAD_RWLOCK_T       56
#define PTHREAD_RWLOCK_INITIALIZER     { { 0, 0, 0, 0, 0, 0, 0, 0,
0, 0, 0, 0 } }
#define PTHREAD_MUTEX_INITIALIZER       { { 0, 0, 0, 0, 0, 0, 0, 0,
{ 0, 0 } } }

typedef union {
    char __size[__SIZEOF_PTHREAD_BARRIER_T];
    long int __align;
} pthread_barrier_t;

typedef struct __pthread_internal_list __pthread_list_t;
struct __pthread_mutex_s {
    int __lock;
    unsigned int __count;
    int __owner;
    unsigned int __nusers;
    int __kind;
    int __spins;
    __pthread_list_t __list;
};

typedef union {
    struct {
        int __lock;
        unsigned int __nr_readers;
        unsigned int __readers_wakeup;
        unsigned int __writer_wakeup;
        unsigned int __nr_readers_queued;
        unsigned int __nr_writers_queued;
        int __writer;
        int __pad1;
        unsigned long int __pad2;
        unsigned long int __pad3;
        unsigned int __flags;
    } __data;
    char __size[__SIZEOF_PTHREAD_RWLOCK_T];
    long int __align;
} pthread_rwlock_t;
```

### 10.8.3 semaphore.h

```
#define __SIZEOF_SEM_T 32
```

## 10.9 Interfaces for libgcc\_s

[Table 10-54](#) defines the library name and shared object name for the libgcc\_s library

**Table 10-54 libgcc\_s Definition**

Library:	libgcc_s
SONAME:	libgcc_s.so.1

The behavior of the interfaces in this library is specified by the following specifications:  
[\[LSB\] LSB Core - Generic](#)

## 10.9.1 Unwind Library

### 10.9.1.1 Interfaces for Unwind Library

An LSB conforming implementation shall provide the architecture specific functions for Unwind Library specified in [Table 10-55](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-55 libgcc\_s - Unwind Library Function Interfaces**

_Unwind_Backtrace(GCC_3.3) [LSB]	_Unwind_DeleteException(GCC_3.0) [LSB]	_Unwind_FindEnclosingFunction(GCC_3.3) [LSB]	_Unwind_Find_FDE(GCC_3.0) [LSB]
_Unwind_ForcedUnwind(GCC_3.0) [LSB]	_Unwind_GetCFA(GCC_3.3) [LSB]	_Unwind_GetDataRelBase(GCC_3.0) [LSB]	_Unwind_GetGR(GCC_3.0) [LSB]
_Unwind_GetIP(GCC_3.0) [LSB]	_Unwind_GetLanguageSpecificData(GCC_3.0) [LSB]	_Unwind_GetRegiOnStart(GCC_3.0) [LSB]	_Unwind_GetTextRelBase(GCC_3.0) [LSB]
_Unwind_RaiseException(GCC_3.0) [LSB]	_Unwind_Resume(GCC_3.0) [LSB]	_Unwind_ResumeOrRethrow(GCC_3.3) [LSB]	_Unwind_SetGR(GCC_3.0) [LSB]
_Unwind_SetIP(GCC_3.0) [LSB]			

## 10.10 Data Definitions for libgcc\_s

This section defines global identifiers and their values that are associated with interfaces contained in libgcc\_s. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the [ISO C \(1999\)](#) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

## 10.10.1 unwind.h

```
extern _Unwind_Ptr _Unwind_GetDataRelBase(struct _Unwind_Context *);
extern _Unwind_Ptr _Unwind_GetTextRelBase(struct _Unwind_Context *);
```

## 10.11 Interface Definitions for libgcc\_s

The interfaces defined on the following pages are included in libgcc\_s and are defined by this specification. Unless otherwise noted, these interfaces shall be included in the source standard.

Other interfaces listed in [Section 10.9](#) shall behave as described in the referenced base document. For interfaces referencing LSB and not listed below, please see the generic part of the specification.

### \_Unwind\_Find\_FDE

#### **Name**

`_Unwind_Find_FDE` — private C++ error handling method

#### **Synopsis**

```
fde * _Unwind_Find_FDE(void * pc, struct dwarf_eh_bases * bases);
```

#### **Description**

`_Unwind_Find_FDE()` looks for the object containing `pc`, then inserts into `bases`.

### \_Unwind\_GetDataRelBase

#### **Name**

`_Unwind_GetDataRelBase` — private IA64 C++ error handling method

#### **Synopsis**

```
_Unwind_Ptr _Unwind_GetDataRelBase(struct _Unwind_Context * context);
```

#### **Description**

`_Unwind_GetDataRelBase()` returns the global pointer in register one for `context`.

### \_Unwind\_GetTextRelBase

#### **Name**

`_Unwind_GetTextRelBase` — private IA64 C++ error handling method

#### **Synopsis**

```
_Unwind_Ptr _Unwind_GetTextRelBase(struct _Unwind_Context * context);
```

#### **Description**

`_Unwind_GetTextRelBase()` calls the abort method, then returns.

## 10.12 Interfaces for libdl

[Table 10-56](#) defines the library name and shared object name for the libdl library

**Table 10-56 libdl Definition**

Library:	libdl
SONAME:	libdl.so.2

The behavior of the interfaces in this library is specified by the following specifications:

[LSB] [LSB Core - Generic](#)

[SUSv4] [POSIX 1003.1-2008 \(ISO/IEC 9945-2009\)](#)

### 10.12.1 Dynamic Loader

#### 10.12.1.1 Interfaces for Dynamic Loader

An LSB conforming implementation shall provide the architecture specific functions for Dynamic Loader specified in [Table 10-57](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-57 libdl - Dynamic Loader Function Interfaces**

dladdr(GLIBC_2.2) <a href="#">[LSB]</a>	dlclose(GLIBC_2.2) <a href="#">[SUSv4]</a>	dlerror(GLIBC_2.2) <a href="#">[SUSv4]</a>	dlopen(GLIBC_2.2) <a href="#">[LSB]</a>
dlsym(GLIBC_2.2) <a href="#">[LSB]</a>	dlvsym(GLIBC_2.2) <a href="#">[LSB]</a>		

## 10.13 Data Definitions for libdl

This section defines global identifiers and their values that are associated with interfaces contained in libdl. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the [ISO C \(1999\)](#) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

### 10.13.1 dlfcn.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

## 10.14 Interfaces for libcrypt

[Table 10-58](#) defines the library name and shared object name for the libcrypt library

**Table 10-58 libcrypt Definition**

Library:	libcrypt
----------	----------

SONAME:	libcrypt.so.1
---------	---------------

The behavior of the interfaces in this library is specified by the following specifications:

[LSB] [LSB Core - Generic](#)

[SUSv4] [POSIX 1003.1-2008 \(ISO/IEC 9945-2009\)](#)

## 10.14.1 Encryption

### 10.14.1.1 Interfaces for Encryption

An LSB conforming implementation shall provide the architecture specific functions for Encryption specified in [Table 10-59](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 10-59 libcrypt - Encryption Function Interfaces**

crypt(GLIBC_2.2) [SUSv4]	crypt_r(GLIBC_2.2) [LSB]	encrypt(GLIBC_2.2) [SUSv4]	encrypt_r(GLIBC_2.2) [LSB]
setkey(GLIBC_2.2) [SUSv4]	setkey_r(GLIBC_2.2) [LSB]		

## 10.15 Data Definitions for libcrypt

This section defines global identifiers and their values that are associated with interfaces contained in libcrypt. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the [ISO C \(1999\)](#) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

### 10.15.1 crypt.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

## **IV Utility Libraries**

## 11 Libraries

An LSB-conforming implementation shall also support the following utility libraries which are built on top of the interfaces provided by the base libraries. These libraries implement common functionality, and hide additional system dependent information such as file formats and device names.

### 11.1 Interfaces for libz

[Table 11-1](#) defines the library name and shared object name for the libz library

**Table 11-1 libz Definition**

Library:	libz
SONAME:	libz.so.1

#### 11.1.1 Compression Library

##### 11.1.1.1 Interfaces for Compression Library

No external functions are defined for libz - Compression Library in this part of the specification. See also the generic specification.

### 11.2 Data Definitions for libz

This section defines global identifiers and their values that are associated with interfaces contained in libz. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the [ISO C \(1999\)](#) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

#### 11.2.1 zconf.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

#### 11.2.2 zlib.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 11.3 Interfaces for libncurses

[Table 11-2](#) defines the library name and shared object name for the libncurses library

**Table 11-2 libncurses Definition**

Library:	libncurses
SONAME:	libncurses.so.5

## 11.3.1 Curses

### 11.3.1.1 Interfaces for Curses

No external functions are defined for libncurses - Curses in this part of the specification. See also the generic specification.

## 11.4 Data Definitions for libncurses

This section defines global identifiers and their values that are associated with interfaces contained in libncurses. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the [ISO C \(1999\)](#) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

## 11.4.1 curses.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

## 11.5 Interfaces for libcursesw

[Table 11-3](#) defines the library name and shared object name for the libcursesw library

**Table 11-3 libcursesw Definition**

Library:	libcursesw
SONAME:	libcursesw.so.5

## 11.5.1 Curses Wide

### 11.5.1.1 Interfaces for Curses Wide

No external functions are defined for libcursesw - Curses Wide in this part of the specification. See also the generic specification.

## 11.6 Data Definitions for libcursesw

This section defines global identifiers and their values that are associated with interfaces contained in libcursesw. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header

file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the [ISO C \(1999\)](#) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

### **11.6.1 ncursesw/curses.h**

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### **11.6.2 ncursesw/ncurses\_dll.h**

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### **11.6.3 ncursesw/term.h**

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### **11.6.4 ncursesw/unctrl.h**

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

## **11.7 Interfaces for libutil**

[Table 11-4](#) defines the library name and shared object name for the libutil library

**Table 11-4 libutil Definition**

Library:	libutil
SONAME:	libutil.so.1

The behavior of the interfaces in this library is specified by the following specifications:  
[LSB] [LSB Core - Generic](#)

### **11.7.1 Utility Functions**

#### **11.7.1.1 Interfaces for Utility Functions**

An LSB conforming implementation shall provide the architecture specific functions for Utility Functions specified in [Table 11-5](#), with the full mandatory functionality as de-

scribed in the referenced underlying specification.

**Table 11-5 libutil - Utility Functions Function Interfaces**

forkpty(GLIBC_2.2) <a href="#">[LSB]</a>	login(GLIBC_2.2) <a href="#">[LSB]</a>	login_tty(GLIBC_2.2) <a href="#">[LSB]</a>	logout(GLIBC_2.2) <a href="#">[LSB]</a>
logwtmp(GLIBC_2.2) <a href="#">[LSB]</a>	openpty(GLIBC_2.2) <a href="#">[LSB]</a>		

## **V Base Libraries**

## 12 Libraries

An LSB-conforming implementation shall support base libraries which provide interfaces for accessing the operating system, processor and other hardware in the system.

Only those interfaces that are unique to the z/Architecture platform are defined here. This section should be used in conjunction with the corresponding section in the Linux Standard Base Specification.

### 12.1 Interfaces for libstdc++

[Table 12-1](#) defines the library name and shared object name for the libstdc++ library

**Table 12-1 libstdc++ Definition**

Library:	libstdc++
SONAME:	libstdc++.so.6

The behavior of the interfaces in this library is specified by the following specifications:

- [CXXABI-1.86] [Itanium™ C++ ABI](#)
- [ISOCXX] [ISO/IEC 14882: 2003 C++ Language](#)
- [LSB] [LSB Core - Generic](#)

#### 12.1.1 C++ Runtime Support

##### 12.1.1.1 Interfaces for C++ Runtime Support

An LSB conforming implementation shall provide the architecture specific methods for C++ Runtime Support specified in [Table 12-2](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-2 libstdc++ - C++ Runtime Support Function Interfaces**

operator new[](unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
operator new[](unsigned long, nothrow_t const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
operator new(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
operator new(unsigned long, nothrow_t const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

#### 12.1.2 C++ type descriptors for built-in types

##### 12.1.2.1 Interfaces for C++ type descriptors for built-in types

No external methods are defined for libstdc++ - C++ type descriptors for built-in types in this part of the specification. See also the generic specification.

#### 12.1.3 C++ \_Rb\_tree

##### 12.1.3.1 Interfaces for C++ \_Rb\_tree

No external methods are defined for libstdc++ - C++ \_Rb\_tree in this part of the specification. See also the generic specification.

#### 12.1.4 Class type\_info

##### 12.1.4.1 Class data for type\_info

The virtual table for the std::type\_info class is described in the generic part of this specification.

The Run Time Type Information for the std::type\_info class is described by [Table 12-3](#)

**Table 12-3 typeinfo for type\_info**

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for type_info

### 12.1.4.2 Interfaces for Class type\_info

No external methods are defined for libstdcxx - Class std::type\_info in this part of the specification. See also the generic specification.

## 12.1.5 Class \_\_cxxabiv1::\_\_enum\_type\_info

### 12.1.5.1 Class data for \_\_cxxabiv1::\_\_enum\_type\_info

The virtual table for the \_\_cxxabiv1::\_\_enum\_type\_info class is described in the generic part of this specification.

The Run Time Type Information for the \_\_cxxabiv1::\_\_enum\_type\_info class is described by [Table 12-4](#)

**Table 12-4 typeinfo for \_\_cxxabiv1::\_\_enum\_type\_info**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for __cxxabiv1::__enum_type_info

### 12.1.5.2 Interfaces for Class \_\_cxxabiv1::\_\_enum\_type\_info

No external methods are defined for libstdcxx - Class \_\_cxxabiv1::\_\_enum\_type\_info in this part of the specification. See also the generic specification.

## 12.1.6 Class \_\_cxxabiv1::\_\_array\_type\_info

### 12.1.6.1 Class data for \_\_cxxabiv1::\_\_array\_type\_info

The virtual table for the \_\_cxxabiv1::\_\_array\_type\_info class is described in the generic part of this specification.

The Run Time Type Information for the \_\_cxxabiv1::\_\_array\_type\_info class is described by [Table 12-5](#)

**Table 12-5 typeinfo for \_\_cxxabiv1::\_\_array\_type\_info**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for __cxxabiv1::__array_type_info

### 12.1.6.2 Interfaces for Class \_\_cxxabiv1::\_\_array\_type\_info

No external methods are defined for libstdcxx - Class \_\_cxxabiv1::\_\_array\_type\_info in this part of the specification. See also the generic specification.

## 12.1.7 Class \_\_cxxabiv1::\_\_class\_type\_info

### 12.1.7.1 Class data for \_\_cxxabiv1::\_\_class\_type\_info

The virtual table for the \_\_cxxabiv1::\_\_class\_type\_info class is described by [Table 12-6](#)

**Table 12-6 Primary vtable for \_\_cxxabiv1::\_\_class\_type\_info**

Base Offset	0
-------------	---

Virtual Base Offset	0
RTTI	typeinfo for __cxxabiv1::__class_type_info
vfunc[0]:	__cxxabiv1::__class_type_info::~_class_type_info()
vfunc[1]:	__cxxabiv1::__class_type_info::~_class_type_info()
vfunc[2]:	type_info::__is_pointer_p() const
vfunc[3]:	type_info::__is_function_p() const
vfunc[4]:	__cxxabiv1::__class_type_info::__do_catch(type_info const*, void**, unsigned int) const
vfunc[5]:	__cxxabiv1::__class_type_info::__do_upcast(__cxxabiv1::__class_type_info const*, void**) const
vfunc[6]:	__cxxabiv1::__class_type_info::__do_upcast(__cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info::__upcast_result&) const
vfunc[7]:	__cxxabiv1::__class_type_info::__do_dyncast(long, __cxxabiv1::__class_type_info::__sub_kind, __cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info const*, __cxxabiv1::__class_type_info::__dyncast_result&) const
vfunc[8]:	__cxxabiv1::__class_type_info::__do_find_public_src(long, void const*, __cxxabiv1::__class_type_info const*, void const*) const

The Run Time Type Information for the \_\_cxxabiv1::\_\_class\_type\_info class is described by [Table 12-7](#)

**Table 12-7 typeinfo for \_\_cxxabiv1::\_\_class\_type\_info**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for __cxxabiv1::__class_type_info

### 12.1.7.2 Interfaces for Class \_\_cxxabiv1::\_\_class\_type\_info

An LSB conforming implementation shall provide the architecture specific methods for Class \_\_cxxabiv1::\_\_class\_type\_info specified in [Table 12-8](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-8 libstdcxx - Class \_\_cxxabiv1::\_\_class\_type\_info Function Interfaces**

```
__cxxabiv1::__class_type_info::__do_dyncast(long,
__cxxabiv1::__class_type_info::__sub_kind, __cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info::__dyncast_result&) const(CXXABI_1.3)
```

**[CXXABI-1.86]**

`__cxxabiv1::__class_type_info::__do_find_public_src(long, void const*,  
 __cxxabiv1::__class_type_info const*, void const*) const(CXXABI_1.3)` [\[CXXABI-1.86\]](#)

## 12.1.8 Class `__cxxabiv1::__pbase_type_info`

### 12.1.8.1 Class data for `__cxxabiv1::__pbase_type_info`

The virtual table for the `__cxxabiv1::__pbase_type_info` class is described in the generic part of this specification.

The Run Time Type Information for the `__cxxabiv1::__pbase_type_info` class is described by [Table 12-9](#)

**Table 12-9 typeinfo for `__cxxabiv1::__pbase_type_info`**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>__cxxabiv1::__pbase_type_info</code>

### 12.1.8.2 Interfaces for Class `__cxxabiv1::__pbase_type_info`

No external methods are defined for libstdcxx - Class `__cxxabiv1::__pbase_type_info` in this part of the specification. See also the generic specification.

## 12.1.9 Class `__cxxabiv1::__pointer_type_info`

### 12.1.9.1 Class data for `__cxxabiv1::__pointer_type_info`

The virtual table for the `__cxxabiv1::__pointer_type_info` class is described in the generic part of this specification.

The Run Time Type Information for the `__cxxabiv1::__pointer_type_info` class is described by [Table 12-10](#)

**Table 12-10 typeinfo for `__cxxabiv1::__pointer_type_info`**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>__cxxabiv1::__pointer_type_info</code>

### 12.1.9.2 Interfaces for Class `__cxxabiv1::__pointer_type_info`

No external methods are defined for libstdcxx - Class `__cxxabiv1::__pointer_type_info` in this part of the specification. See also the generic specification.

## 12.1.10 Class `__cxxabiv1::__function_type_info`

### 12.1.10.1 Class data for `__cxxabiv1::__function_type_info`

The virtual table for the `__cxxabiv1::__function_type_info` class is described in the generic part of this specification.

The Run Time Type Information for the `__cxxabiv1::__function_type_info` class is described by [Table 12-11](#)

**Table 12-11 typeinfo for `__cxxabiv1::__function_type_info`**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>
-------------	-------------------------------------------------------------

Name	typeinfo name for __cxxabiv1::__function_type_info
------	-------------------------------------------------------

### 12.1.10.2 Interfaces for Class \_\_cxxabiv1::\_\_function\_type\_info

No external methods are defined for libstdcxx - Class \_\_cxxabiv1::\_\_function\_type\_info in this part of the specification. See also the generic specification.

## 12.1.11 Class \_\_cxxabiv1::\_\_si\_class\_type\_info

### 12.1.11.1 Class data for \_\_cxxabiv1::\_\_si\_class\_type\_info

The virtual table for the \_\_cxxabiv1::\_\_si\_class\_type\_info class is described by [Table 12-12](#)

**Table 12-12 Primary vtable for \_\_cxxabiv1::\_\_si\_class\_type\_info**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for __cxxabiv1::__si_class_type_info
vfunc[0]:	__cxxabiv1::__si_class_type_info::__~__si_class_type_info()
vfunc[1]:	__cxxabiv1::__si_class_type_info::__~__si_class_type_info()
vfunc[2]:	type_info::__is_pointer_p() const
vfunc[3]:	type_info::__is_function_p() const
vfunc[4]:	__cxxabiv1::__class_type_info::__do_catch(type_info const*, void**, unsigned int) const
vfunc[5]:	__cxxabiv1::__class_type_info::__do_upcast(__cxxabiv1::__class_type_info const*, void**) const
vfunc[6]:	__cxxabiv1::__si_class_type_info::__do_upcast(__cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info::__upcast_result&) const
vfunc[7]:	__cxxabiv1::__si_class_type_info::__do_dyncast(long, __cxxabiv1::__class_type_info::__sub_k ind, __cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info::__dynca st_result&) const
vfunc[8]:	__cxxabiv1::__si_class_type_info::__do _find_public_src(long, void const*, __cxxabiv1::__class_type_info const*, void const*) const

The Run Time Type Information for the \_\_cxxabiv1::\_\_si\_class\_type\_info class is described by [Table 12-13](#)

**Table 12-13 typeinfo for \_\_cxxabiv1::\_\_si\_class\_type\_info**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for __cxxabiv1::__si_class_type_info

### 12.1.11.2 Interfaces for Class \_\_cxxabiv1::\_\_si\_class\_type\_info

An LSB conforming implementation shall provide the architecture specific methods for Class \_\_cxxabiv1::\_\_si\_class\_type\_info specified in [Table 12-14](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-14 libstdc++ - Class \_\_cxxabiv1::\_\_si\_class\_type\_info Function Interfaces**

<code>__cxxabiv1::__si_class_type_info::__do_dyncast(long, __cxxabiv1::__class_type_info::__sub_kind, __cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info::__dyncast_result&amp;) const(CXXABI_1.3)</code> <b>[CXXABI-1.86]</b>
<code>__cxxabiv1::__si_class_type_info::__do_find_public_src(long, void const*, __cxxabiv1::__class_type_info const*, void const*) const(CXXABI_1.3)</code> <b>[CXXABI-1.86]</b>

### 12.1.12 Class \_\_cxxabiv1::\_\_vmi\_class\_type\_info

#### 12.1.12.1 Class data for \_\_cxxabiv1::\_\_vmi\_class\_type\_info

The virtual table for the \_\_cxxabiv1::\_\_vmi\_class\_type\_info class is described by [Table 12-15](#)

**Table 12-15 Primary vtable for \_\_cxxabiv1::\_\_vmi\_class\_type\_info**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for __cxxabiv1::__vmi_class_type_info
vfunc[0]:	<code>__cxxabiv1::__vmi_class_type_info::__~_vmi_class_type_info()</code>
vfunc[1]:	<code>__cxxabiv1::__vmi_class_type_info::__~_vmi_class_type_info()</code>
vfunc[2]:	<code>type_info::__is_pointer_p() const</code>
vfunc[3]:	<code>type_info::__is_function_p() const</code>
vfunc[4]:	<code>__cxxabiv1::__class_type_info::__do_catch(type_info const*, void**, unsigned int) const</code>
vfunc[5]:	<code>__cxxabiv1::__class_type_info::__do_upcast(__cxxabiv1::__class_type_info const*, void**) const</code>
vfunc[6]:	<code>__cxxabiv1::__vmi_class_type_info::__do_upcast(__cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info::__upcast_result&amp;) const</code>
vfunc[7]:	<code>__cxxabiv1::__vmi_class_type_info::__do_dyncast(long, __cxxabiv1::__class_type_info::__sub_k</code>

	ind, __cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info::__dyncast_result&) const
vfunc[8]:	__cxxabiv1::__vmi_class_type_info::__do_find_public_src(long, void const*, __cxxabiv1::__class_type_info const*, void const*) const

The Run Time Type Information for the \_\_cxxabiv1::\_\_vmi\_class\_type\_info class is described by [Table 12-16](#)

**Table 12-16 typeinfo for \_\_cxxabiv1::\_\_vmi\_class\_type\_info**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for __cxxabiv1::__vmi_class_type_info

### 12.1.12.2 Interfaces for Class \_\_cxxabiv1::\_\_vmi\_class\_type\_info

An LSB conforming implementation shall provide the architecture specific methods for Class \_\_cxxabiv1::\_\_vmi\_class\_type\_info specified in [Table 12-17](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-17 libstdcxx - Class \_\_cxxabiv1::\_\_vmi\_class\_type\_info Function Interfaces**

__cxxabiv1::__vmi_class_type_info::__do_dyncast(long, __cxxabiv1::__class_type_info::__sub_kind, __cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info::__dyncast_result&) const(CXXABI_1.3) <a href="#">[CXXABI-1.86]</a>
__cxxabiv1::__vmi_class_type_info::__do_find_public_src(long, void const*, __cxxabiv1::__class_type_info const*, void const*) const(CXXABI_1.3) <a href="#">[CXXABI-1.86]</a>

### 12.1.13 Class \_\_cxxabiv1::\_\_fundamental\_type\_info

#### 12.1.13.1 Class data for \_\_cxxabiv1::\_\_fundamental\_type\_info

The virtual table for the \_\_cxxabiv1::\_\_fundamental\_type\_info class is described in the generic part of this specification.

The Run Time Type Information for the \_\_cxxabiv1::\_\_fundamental\_type\_info class is described by [Table 12-18](#)

**Table 12-18 typeinfo for \_\_cxxabiv1::\_\_fundamental\_type\_info**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for __cxxabiv1::__fundamental_type_info

#### 12.1.13.2 Interfaces for Class \_\_cxxabiv1::\_\_fundamental\_type\_info

No external methods are defined for libstdcxx - Class \_\_cxxabiv1::\_\_fundamental\_type\_info in this part of the specification. See also the generic specification.

## 12.1.14 Class

### `__cxxabiv1::__pointer_to_member_type_info`

#### 12.1.14.1 Class data for

##### `__cxxabiv1::__pointer_to_member_type_info`

The virtual table for the `__cxxabiv1::__pointer_to_member_type_info` class is described in the generic part of this specification.

The Run Time Type Information for the `__cxxabiv1::__pointer_to_member_type_info` class is described by [Table 12-19](#)

**Table 12-19 typeinfo for `__cxxabiv1::__pointer_to_member_type_info`**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>__cxxabiv1::__pointer_to_member_type_info</code>

#### 12.1.14.2 Interfaces for Class

##### `__cxxabiv1::__pointer_to_member_type_info`

No external methods are defined for libstdcxx - Class `__cxxabiv1::__pointer_to_member_type_info` in this part of the specification. See also the generic specification.

## 12.1.15 Class `__gnu_cxx::stdio_filebuf<char, char_traits<char> >`

#### 12.1.15.1 Interfaces for Class `__gnu_cxx::stdio_filebuf<char, char_traits<char> >`

No external methods are defined for libstdcxx - Class `__gnu_cxx::stdio_filebuf<char, std::char_traits<char> >` in this part of the specification. See also the generic specification.

## 12.1.16 Class `__gnu_cxx::stdio_filebuf<wchar_t, char_traits<wchar_t> >`

#### 12.1.16.1 Interfaces for Class `__gnu_cxx::stdio_filebuf<wchar_t, char_traits<wchar_t> >`

No external methods are defined for libstdcxx - Class `__gnu_cxx::stdio_filebuf<wchar_t, std::char_traits<wchar_t> >` in this part of the specification. See also the generic specification.

## 12.1.17 Class `__gnu_cxx::__pool_alloc_base`

#### 12.1.17.1 Interfaces for Class `__gnu_cxx::__pool_alloc_base`

An LSB conforming implementation shall provide the architecture specific methods for Class `__gnu_cxx::__pool_alloc_base` specified in [Table 12-20](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-20 libstdcxx - Class `__gnu_cxx::__pool_alloc_base` Function Interfaces**

<code>__gnu_cxx::__pool_alloc_base::__M_get_free_list(unsigned long)</code> (GLIBCXX_3.4.2) [LSB]
<code>__gnu_cxx::__pool_alloc_base::__M_refill(unsigned long)</code> (GLIBCXX_3.4.2) [LSB]

## 12.1.18 Class `__gnu_cxx::stdio_sync_filebuf<char, char_traits<char> >`

### 12.1.18.1 Class data for `__gnu_cxx::stdio_sync_filebuf<char, char_traits<char> >`

The virtual table for the `__gnu_cxx::stdio_sync_filebuf<char, std::char_traits<char> >` class is described by [Table 12-21](#)

**Table 12-21 Primary vtable for `__gnu_cxx::stdio_sync_filebuf<char, char_traits<char> >`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt; &gt;</code>
vfunc[0]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt; &gt;::~stdio_sync_filebuf()</code>
vfunc[1]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt; &gt;::~stdio_sync_filebuf()</code>
vfunc[2]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt; &gt;::imbue(locale const&amp;)</code>
vfunc[3]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt; &gt;::setbuf(char*, long)</code>
vfunc[4]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt; &gt;::seekoff(long, _Ios_Seekdir, _Ios_Openmode)</code>
vfunc[5]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt; &gt;::seekpos(fpos&lt;__mbstate_t&gt;, _Ios_Openmode)</code>
vfunc[6]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt; &gt;::sync()</code>
vfunc[7]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt; &gt;::showmany()</code>
vfunc[8]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt; &gt;::xsgetn(char*, long)</code>
vfunc[9]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt; &gt;::underflow()</code>
vfunc[10]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt; &gt;::uflow()</code>
vfunc[11]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt; &gt;::pbackfail(int)</code>
vfunc[12]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt; &gt;::xsputn(char const*, long)</code>
vfunc[13]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt; &gt;::overflow(int)</code>

### 12.1.18.2 Interfaces for Class `__gnu_cxx::stdio_sync_filebuf<char, char_traits<char> >`

No external methods are defined for libstdcxx - Class `__gnu_cxx::stdio_sync_filebuf<char, std::char_traits<char> >` in this part of the specification. See also the generic specification.

### 12.1.19 Class

#### `__gnu_cxx::stdio_sync_filebuf<wchar_t, char_traits<wchar_t> >`

##### 12.1.19.1 Class data for `__gnu_cxx::stdio_sync_filebuf<wchar_t, char_traits<wchar_t> >`

The virtual table for the `__gnu_cxx::stdio_sync_filebuf<wchar_t, std::char_traits<wchar_t> >` class is described by [Table 12-22](#)

**Table 12-22 Primary vtable for `__gnu_cxx::stdio_sync_filebuf<wchar_t, char_traits<wchar_t> >`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;</code>
vfunc[0]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::~stdio_sync_filebuf()</code>
vfunc[1]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::~stdio_sync_filebuf()</code>
vfunc[2]:	<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::imbue(locale const&amp;)</code>
vfunc[3]:	<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::setbuf(wchar_t*, long)</code>
vfunc[4]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::seekoff(long, _Ios_Seekdir, _Ios_Openmode)</code>
vfunc[5]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::seekpos(fpos&lt;_mbstate_t&gt;, _Ios_Openmode)</code>
vfunc[6]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::sync()</code>
vfunc[7]:	<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::showmanyc()</code>
vfunc[8]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::xsgetn(wchar_t*, long)</code>
vfunc[9]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::underflow()</code>
vfunc[10]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t,</code>

	<code>char_traits&lt;wchar_t&gt;::uflow()</code>
vfunc[11]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::pbackfail(unsigned int)</code>
vfunc[12]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::xspputn(wchar_t const*, long)</code>
vfunc[13]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::overflow(unsigned int)</code>

### 12.1.19.2 Interfaces for Class

#### `__gnu_cxx::stdio_sync_filebuf<wchar_t, char_traits<wchar_t> >`

No external methods are defined for libstdcxx - Class `__gnu_cxx::stdio_sync_filebuf<wchar_t, std::char_traits<wchar_t> >` in this part of the specification. See also the generic specification.

## 12.1.20 Class exception

### 12.1.20.1 Class data for exception

The virtual table for the `std::exception` class is described in the generic part of this specification.

The Run Time Type Information for the `std::exception` class is described by [Table 12-23](#)

**Table 12-23 typeinfo for exception**

Base Vtable	vtable for <code>__cxxabiv1::__class_type_info</code>
Name	typeinfo name for exception

### 12.1.20.2 Interfaces for Class exception

No external methods are defined for libstdcxx - Class `std::exception` in this part of the specification. See also the generic specification.

## 12.1.21 Class bad\_typeid

### 12.1.21.1 Class data for bad\_typeid

The virtual table for the `std::bad_typeid` class is described in the generic part of this specification.

The Run Time Type Information for the `std::bad_typeid` class is described by [Table 12-24](#)

**Table 12-24 typeinfo for bad\_typeid**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>bad_typeid</code>

### 12.1.21.2 Interfaces for Class bad\_typeid

No external methods are defined for libstdcxx - Class `std::bad_typeid` in this part of the specification. See also the generic specification.

## 12.1.22 Class logic\_error

### 12.1.22.1 Class data for logic\_error

The virtual table for the std::logic\_error class is described in the generic part of this specification.

The Run Time Type Information for the std::logic\_error class is described by [Table 12-25](#)

**Table 12-25 typeinfo for logic\_error**

Base Vtable	vtable for _cxxabiv1::_si_class_type_info
Name	typeinfo name for logic_error

### 12.1.22.2 Interfaces for Class logic\_error

No external methods are defined for libstdcxx - Class std::logic\_error in this part of the specification. See also the generic specification.

## 12.1.23 Class range\_error

### 12.1.23.1 Class data for range\_error

The virtual table for the std::range\_error class is described in the generic part of this specification.

The Run Time Type Information for the std::range\_error class is described by [Table 12-26](#)

**Table 12-26 typeinfo for range\_error**

Base Vtable	vtable for _cxxabiv1::_si_class_type_info
Name	typeinfo name for range_error

### 12.1.23.2 Interfaces for Class range\_error

No external methods are defined for libstdcxx - Class std::range\_error in this part of the specification. See also the generic specification.

## 12.1.24 Class domain\_error

### 12.1.24.1 Class data for domain\_error

The virtual table for the std::domain\_error class is described in the generic part of this specification.

The Run Time Type Information for the std::domain\_error class is described by [Table 12-27](#)

**Table 12-27 typeinfo for domain\_error**

Base Vtable	vtable for _cxxabiv1::_si_class_type_info
Name	typeinfo name for domain_error

### 12.1.24.2 Interfaces for Class domain\_error

No external methods are defined for libstdcxx - Class std::domain\_error in this part of the specification. See also the generic specification.

## 12.1.25 Class length\_error

### 12.1.25.1 Class data for length\_error

The virtual table for the std::length\_error class is described in the generic part of this specification.

The Run Time Type Information for the std::length\_error class is described by [Table 12-28](#)

**Table 12-28 typeinfo for length\_error**

Base Vtable	vtable for _cxxabiv1::_si_class_type_info
Name	typeinfo name for length_error

### 12.1.25.2 Interfaces for Class length\_error

No external methods are defined for libstdcxx - Class std::length\_error in this part of the specification. See also the generic specification.

## 12.1.26 Class out\_of\_range

### 12.1.26.1 Class data for out\_of\_range

The virtual table for the std::out\_of\_range class is described in the generic part of this specification.

The Run Time Type Information for the std::out\_of\_range class is described by [Table 12-29](#)

**Table 12-29 typeinfo for out\_of\_range**

Base Vtable	vtable for _cxxabiv1::_si_class_type_info
Name	typeinfo name for out_of_range

### 12.1.26.2 Interfaces for Class out\_of\_range

No external methods are defined for libstdcxx - Class std::out\_of\_range in this part of the specification. See also the generic specification.

## 12.1.27 Class bad\_exception

### 12.1.27.1 Class data for bad\_exception

The virtual table for the std::bad\_exception class is described in the generic part of this specification.

The Run Time Type Information for the std::bad\_exception class is described by [Table 12-30](#)

**Table 12-30 typeinfo for bad\_exception**

Base Vtable	vtable for _cxxabiv1::_si_class_type_info
Name	typeinfo name for bad_exception

### 12.1.27.2 Interfaces for Class bad\_exception

No external methods are defined for libstdcxx - Class std::bad\_exception in this part of the specification. See also the generic specification.

## 12.1.28 Class runtime\_error

### 12.1.28.1 Class data for runtime\_error

The virtual table for the std::runtime\_error class is described in the generic part of this specification.

The Run Time Type Information for the std::runtime\_error class is described by [Table 12-31](#)

**Table 12-31 typeinfo for runtime\_error**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for runtime_error

### 12.1.28.2 Interfaces for Class runtime\_error

No external methods are defined for libstdcxx - Class std::runtime\_error in this part of the specification. See also the generic specification.

## 12.1.29 Class overflow\_error

### 12.1.29.1 Class data for overflow\_error

The virtual table for the std::overflow\_error class is described in the generic part of this specification.

The Run Time Type Information for the std::overflow\_error class is described by [Table 12-32](#)

**Table 12-32 typeinfo for overflow\_error**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for overflow_error

### 12.1.29.2 Interfaces for Class overflow\_error

No external methods are defined for libstdcxx - Class std::overflow\_error in this part of the specification. See also the generic specification.

## 12.1.30 Class underflow\_error

### 12.1.30.1 Class data for underflow\_error

The virtual table for the std::underflow\_error class is described in the generic part of this specification.

The Run Time Type Information for the std::underflow\_error class is described by [Table 12-33](#)

**Table 12-33 typeinfo for underflow\_error**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for underflow_error

### 12.1.30.2 Interfaces for Class underflow\_error

No external methods are defined for libstdcxx - Class std::underflow\_error in this part of the specification. See also the generic specification.

## 12.1.31 Class invalid\_argument

### 12.1.31.1 Class data for invalid\_argument

The virtual table for the std::invalid\_argument class is described in the generic part of this specification.

The Run Time Type Information for the std::invalid\_argument class is described by [Table 12-34](#)

**Table 12-34 typeinfo for invalid\_argument**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for invalid_argument

### 12.1.31.2 Interfaces for Class invalid\_argument

No external methods are defined for libstdcxx - Class std::invalid\_argument in this part of the specification. See also the generic specification.

## 12.1.32 Class bad\_cast

### 12.1.32.1 Class data for bad\_cast

The virtual table for the std::bad\_cast class is described in the generic part of this specification.

The Run Time Type Information for the std::bad\_cast class is described by [Table 12-35](#)

**Table 12-35 typeinfo for bad\_cast**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for bad_cast

### 12.1.32.2 Interfaces for Class bad\_cast

No external methods are defined for libstdcxx - Class std::bad\_cast in this part of the specification. See also the generic specification.

## 12.1.33 Class bad\_alloc

### 12.1.33.1 Class data for bad\_alloc

The virtual table for the std::bad\_alloc class is described in the generic part of this specification.

The Run Time Type Information for the std::bad\_alloc class is described by [Table 12-36](#)

**Table 12-36 typeinfo for bad\_alloc**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for bad_alloc

### 12.1.33.2 Interfaces for Class bad\_alloc

No external methods are defined for libstdcxx - Class std::bad\_alloc in this part of the specification. See also the generic specification.

## 12.1.34 struct \_\_numeric\_limits\_base

### 12.1.34.1 Interfaces for struct \_\_numeric\_limits\_base

No external methods are defined for libstdcxx - struct \_\_numeric\_limits\_base in this part of the specification. See also the generic specification.

## 12.1.35 struct numeric\_limits<long double>

### 12.1.35.1 Interfaces for struct numeric\_limits<long double>

No external methods are defined for libstdcxx - struct numeric\_limits<long double> in this part of the specification. See also the generic specification.

## 12.1.36 struct numeric\_limits<long long>

### 12.1.36.1 Interfaces for struct numeric\_limits<long long>

No external methods are defined for libstdcxx - struct numeric\_limits<long long> in this part of the specification. See also the generic specification.

## 12.1.37 struct numeric\_limits<unsigned long long>

### 12.1.37.1 Interfaces for struct numeric\_limits<unsigned long long>

No external methods are defined for libstdcxx - struct numeric\_limits<unsigned long long> in this part of the specification. See also the generic specification.

## 12.1.38 struct numeric\_limits<float>

### 12.1.38.1 Interfaces for struct numeric\_limits<float>

No external methods are defined for libstdcxx - struct numeric\_limits<float> in this part of the specification. See also the generic specification.

## 12.1.39 struct numeric\_limits<double>

### 12.1.39.1 Interfaces for struct numeric\_limits<double>

No external methods are defined for libstdcxx - struct numeric\_limits<double> in this part of the specification. See also the generic specification.

## 12.1.40 struct numeric\_limits<short>

### 12.1.40.1 Interfaces for struct numeric\_limits<short>

No external methods are defined for libstdcxx - struct numeric\_limits<short> in this part of the specification. See also the generic specification.

## 12.1.41 struct numeric\_limits<unsigned short>

### 12.1.41.1 Interfaces for struct numeric\_limits<unsigned short>

No external methods are defined for libstdcxx - struct numeric\_limits<unsigned short> in this part of the specification. See also the generic specification.

## 12.1.42 struct numeric\_limits<int>

### 12.1.42.1 Interfaces for struct numeric\_limits<int>

No external methods are defined for libstdcxx - struct numeric\_limits<int> in this part

of the specification. See also the generic specification.

## **12.1.43 struct numeric\_limits<unsigned int>**

### **12.1.43.1 Interfaces for struct numeric\_limits<unsigned int>**

No external methods are defined for libstdcxx - struct numeric\_limits<unsigned int> in this part of the specification. See also the generic specification.

## **12.1.44 struct numeric\_limits<long>**

### **12.1.44.1 Interfaces for struct numeric\_limits<long>**

No external methods are defined for libstdcxx - struct numeric\_limits<long> in this part of the specification. See also the generic specification.

## **12.1.45 struct numeric\_limits<unsigned long>**

### **12.1.45.1 Interfaces for struct numeric\_limits<unsigned long>**

No external methods are defined for libstdcxx - struct numeric\_limits<unsigned long> in this part of the specification. See also the generic specification.

## **12.1.46 struct numeric\_limits<wchar\_t>**

### **12.1.46.1 Interfaces for struct numeric\_limits<wchar\_t>**

No external methods are defined for libstdcxx - struct numeric\_limits<wchar\_t> in this part of the specification. See also the generic specification.

## **12.1.47 struct numeric\_limits<unsigned char>**

### **12.1.47.1 Interfaces for struct numeric\_limits<unsigned char>**

No external methods are defined for libstdcxx - struct numeric\_limits<unsigned char> in this part of the specification. See also the generic specification.

## **12.1.48 struct numeric\_limits<signed char>**

### **12.1.48.1 Interfaces for struct numeric\_limits<signed char>**

No external methods are defined for libstdcxx - struct numeric\_limits<signed char> in this part of the specification. See also the generic specification.

## **12.1.49 struct numeric\_limits<char>**

### **12.1.49.1 Interfaces for struct numeric\_limits<char>**

No external methods are defined for libstdcxx - struct numeric\_limits<char> in this part of the specification. See also the generic specification.

## **12.1.50 struct numeric\_limits<bool>**

### **12.1.50.1 Interfaces for struct numeric\_limits<bool>**

No external methods are defined for libstdcxx - struct numeric\_limits<bool> in this part of the specification. See also the generic specification.

## 12.1.51 struct numeric\_limits<\_\_float128>

### 12.1.51.1 Interfaces for struct numeric\_limits<\_\_float128>

No external methods are defined for libstdcxx - struct numeric\_limits<\_\_float128> in this part of the specification. See also the generic specification.

An LSB conforming implementation shall provide the architecture specific data interfaces for struct numeric\_limits<\_\_float128> specified in [Table 12-37](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-37 libstdcxx - struct numeric\_limits<\_\_float128> Data Interfaces**

numeric_limits<__float128>::has_denorm(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<__float128>::is_bounded(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<__float128>::is_integer(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<__float128>::round_style(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<__float128>::has_infinity(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<__float128>::max_exponent(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<__float128>::min_exponent(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<__float128>::has_quiet_NaN(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<__float128>::is_specialized(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<__float128>::max_exponent10(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<__float128>::min_exponent10(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<__float128>::has_denorm_loss(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<__float128>::tinyness_before(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<__float128>::has_signaling_NaN(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<__float128>::radix(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<__float128>::traps(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<__float128>::digits(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<__float128>::digits10(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<__float128>::is_exact(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<__float128>::is_iec559(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<__float128>::is_modulo(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<__float128>::is_signed(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
typeinfo for __float128 const*(CXXABI_LDBL_1.3) <a href="#">[CXXABI-1.86]</a>
typeinfo for __float128*(CXXABI_LDBL_1.3) <a href="#">[CXXABI-1.86]</a>
typeinfo for __float128(CXXABI_LDBL_1.3) <a href="#">[CXXABI-1.86]</a>
typeinfo name for __float128 const*(CXXABI_LDBL_1.3) <a href="#">[CXXABI-1.86]</a>
typeinfo name for __float128*(CXXABI_LDBL_1.3) <a href="#">[CXXABI-1.86]</a>
typeinfo name for __float128(CXXABI_LDBL_1.3) <a href="#">[CXXABI-1.86]</a>

## 12.1.52 Class ctype\_base

### 12.1.52.1 Class data for ctype\_base

The Run Time Type Information for the std::ctype\_base class is described by [Table 12-38](#).

**Table 12-38 typeinfo for ctype\_base**

Base Vtable	vtable for _cxxabiv1::__class_type_info
Name	typeinfo name for ctype_base

### 12.1.52.2 Interfaces for Class ctype\_base

No external methods are defined for libstdcxx - Class std::ctype\_base in this part of the specification. See also the generic specification.

## 12.1.53 Class \_\_ctype\_abstract\_base<char>

### 12.1.53.1 Class data for \_\_ctype\_abstract\_base<char>

The virtual table for the std::\_\_ctype\_abstract\_base<char> class is described in the generic part of this specification.

### 12.1.53.2 Interfaces for Class \_\_ctype\_abstract\_base<char>

No external methods are defined for libstdcxx - Class std::\_\_ctype\_abstract\_base<char> in this part of the specification. See also the generic specification.

## 12.1.54 Class \_\_ctype\_abstract\_base<wchar\_t>

### 12.1.54.1 Class data for \_\_ctype\_abstract\_base<wchar\_t>

The virtual table for the std::\_\_ctype\_abstract\_base<wchar\_t> class is described in the generic part of this specification.

### 12.1.54.2 Interfaces for Class \_\_ctype\_abstract\_base<wchar\_t>

No external methods are defined for libstdcxx - Class std::\_\_ctype\_abstract\_base<wchar\_t> in this part of the specification. See also the generic specification.

## 12.1.55 Class ctype<char>

### 12.1.55.1 Class data for ctype<char>

The virtual table for the std::ctype<char> class is described in the generic part of this specification.

### 12.1.55.2 Interfaces for Class ctype<char>

An LSB conforming implementation shall provide the architecture specific methods for Class std::ctype<char> specified in [Table 12-39](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-39 libstdcxx - Class ctype<char> Function Interfaces**

ctype<char>::ctype(__locale_struct*, unsigned short const*, bool, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<char>::ctype(unsigned short const*, bool, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<char>::ctype(__locale_struct*, unsigned short const*, bool, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<char>::ctype(unsigned short const*, bool, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 12.1.56 Class ctype<wchar\_t>

### 12.1.56.1 Class data for ctype<wchar\_t>

The virtual table for the std::ctype<wchar\_t> class is described in the generic part of this specification.

The Run Time Type Information for the std::ctype<wchar\_t> class is described by [Table 12-40](#)

**Table 12-40 typeinfo for ctype<wchar\_t>**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for ctype<wchar_t>

### 12.1.56.2 Interfaces for Class ctype<wchar\_t>

An LSB conforming implementation shall provide the architecture specific methods for Class std::ctype<wchar\_t> specified in [Table 12-41](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-41 libstdc++ - Class ctype<wchar\_t> Function Interfaces**

ctype<wchar_t>::ctype(__locale_struct*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<wchar_t>::ctype(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<wchar_t>::ctype(__locale_struct*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<wchar_t>::ctype(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 12.1.57 Class ctype\_byname<char>

### 12.1.57.1 Class data for ctype\_byname<char>

The virtual table for the std::ctype\_byname<char> class is described in the generic part of this specification.

The Run Time Type Information for the std::ctype\_byname<char> class is described by [Table 12-42](#)

**Table 12-42 typeinfo for ctype\_byname<char>**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for ctype_byname<char>

### 12.1.57.2 Interfaces for Class ctype\_byname<char>

An LSB conforming implementation shall provide the architecture specific methods for Class std::ctype\_byname<char> specified in [Table 12-43](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-43 libstdc++ - Class ctype\_byname<char> Function Interfaces**

ctype_byname<char>::ctype_byname(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype_byname<char>::ctype_byname(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 12.1.58 Class `ctype_byname<wchar_t>`

### 12.1.58.1 Class data for `ctype_byname<wchar_t>`

The virtual table for the `std::ctype_byname<wchar_t>` class is described in the generic part of this specification.

The Run Time Type Information for the `std::ctype_byname<wchar_t>` class is described by [Table 12-44](#)

**Table 12-44 typeinfo for `ctype_byname<wchar_t>`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>ctype_byname&lt;wchar_t&gt;</code>

### 12.1.58.2 Interfaces for Class `ctype_byname<wchar_t>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::ctype_byname<wchar_t>` specified in [Table 12-45](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-45 libstdc++ - Class `ctype_byname<wchar_t>` Function Interfaces**

<code>ctype_byname&lt;wchar_t&gt;::ctype_byname(char const*, unsigned long)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>ctype_byname&lt;wchar_t&gt;::ctype_byname(char const*, unsigned long)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 12.1.59 Class `basic_string<char, char_traits<char>, allocator<char> >`

### 12.1.59.1 Interfaces for Class `basic_string<char, char_traits<char>, allocator<char> >`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::basic_string<char, std::char_traits<char>, std::allocator<char> >` specified in [Table 12-46](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-46 libstdc++ - Class `basic_string<char, char_traits<char>, allocator<char> >` Function Interfaces**

<code>basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt;::find_last_of(char const*, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt;::find_last_of(char const*, unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt;::find_last_of(basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt; const&amp;, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt;::find_last_of(char, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt;::find_first_of(char const*, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt;::find_first_of(char const*, unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt;::find_first_of(basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt; const&amp;, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>

unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::find_first_of(char, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_M_check_length(unsigned long, unsigned long, char const*) const(GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::find_last_not_of(char const*, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::find_last_not_of(char const*, unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::find_last_not_of(basic_string<char, char_traits<char>, allocator<char>> const&, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::find_last_not_of(char, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::find_first_not_of(char const*, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::find_first_not_of(char const*, unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::find_first_not_of(basic_string<char, char_traits<char>, allocator<char>> const&, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::find_first_not_of(char, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::at(unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::copy(char*, unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::find(char const*, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::find(char const*, unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::find(basic_string<char, char_traits<char>, allocator<char>> const&, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::find(char, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::rfind(char const*, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::rfind(char const*, unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::rfind(basic_string<char, char_traits<char>, allocator<char>> const&, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::rfind(char, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::substr(unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::compare(unsigned long, unsigned long, char const*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::compare(unsigned long,

unsigned long, char const*, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::compare(unsigned long, unsigned long, basic_string<char, char_traits<char>, allocator<char>> const&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::compare(unsigned long, unsigned long, basic_string<char, char_traits<char>, allocator<char>> const&, unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_M_check(unsigned long, char const*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_M_limit(unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::operator[](unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_S_construct(unsigned long, char, allocator<char> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_M_replace_aux(unsigned long, unsigned long, unsigned long, char)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_M_replace_safe(unsigned long, unsigned long, char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::at(unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_Rep::_M_set_length_and_sharable(unsigned long)(GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_Rep::_M_clone(allocator<char> const&, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_Rep::_S_create(unsigned long, unsigned long, allocator<char> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::erase(unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::append(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::append(basic_string<char, char_traits<char>, allocator<char>> const&, unsigned long, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::append(unsigned long, char)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::assign(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::assign(basic_string<char, char_traits<char>, allocator<char>> const&, unsigned long, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::assign(unsigned long, char) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_insert(__gnu_cxx::__normal_iterator<char*>, basic_string<char, char_traits<char>, allocator<char>> >, unsigned long, char)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::insert(unsigned long, char const*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::insert(unsigned long, char)

const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::insert(unsigned long, basic_string<char, char_traits<char>, allocator<char>> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::insert(unsigned long, basic_string<char, char_traits<char>, allocator<char>> const&, unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::insert(unsigned long, unsigned long, char)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::resize(unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::resize(unsigned long, char) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_M_copy(char*, char const*, unsigned long)(GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_M_move(char*, char const*, unsigned long)(GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::replace(_gnu_cxx::__normal_iterator<char*>, basic_string<char, char_traits<char>, allocator<char>> >, __gnu_cxx::__normal_iterator<char*>, basic_string<char, char_traits<char>, allocator<char>> >, char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::replace(_gnu_cxx::__normal_iterator<char*>, basic_string<char, char_traits<char>, allocator<char>> >, __gnu_cxx::__normal_iterator<char*>, basic_string<char, char_traits<char>, allocator<char>> >, unsigned long, char) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::replace(unsigned long, unsigned long, char const*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::replace(unsigned long, unsigned long, char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::replace(unsigned long, unsigned long, basic_string<char, char_traits<char>, allocator<char>> const&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::replace(unsigned long, unsigned long, basic_string<char, char_traits<char>, allocator<char>> const&, unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::replace(unsigned long, unsigned long, unsigned long, char)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::reserve(unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_M_assign(char*, unsigned long, char)(GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_M_mutate(unsigned long, unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::basic_string(char const*, unsigned long, allocator<char> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::basic_string(basic_string<char, char_traits<char>, allocator<char>> const&, unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>

>::basic_string(basic_string<char, char_traits<char>, allocator<char> > const&, unsigned long, unsigned long, allocator<char> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::basic_string(unsigned long, char, allocator<char> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::basic_string(char const*, unsigned long, allocator<char> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::basic_string(basic_string<char, char_traits<char>, allocator<char> > const&, unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::basic_string(basic_string<char, char_traits<char>, allocator<char> > const&, unsigned long, unsigned long, allocator<char> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::basic_string(unsigned long, char, allocator<char> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::operator[](unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 12.1.60 Class basic\_string<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> >

### 12.1.60.1 Interfaces for Class basic\_string<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> >

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_string<wchar\_t, std::char\_traits<wchar\_t>, std::allocator<wchar\_t> > specified in [Table 12-47](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-47 libstdcxx - Class basic\_string<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> > Function Interfaces**

basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::find_last_of(wchar_t const*, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::find_last_of(wchar_t const*, unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::find_last_of(basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> > const&, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::find_last_of(wchar_t, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::find_first_of(wchar_t const*, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::find_first_of(wchar_t const*, unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::find_first_of(basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> > const&, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::find_first_of(wchar_t, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::_M_check_length(unsigned long, unsigned long, char const*) const(GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a>



const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::compare(unsigned long, unsigned long, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>> const&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::compare(unsigned long, unsigned long, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>> const&, unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::M_check(unsigned long, char const*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_M_limit(unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::operator[] (unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_S_construct(unsigned long, wchar_t, allocator<wchar_t> const&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_M_replace_aux(unsigned long, unsigned long, unsigned long, wchar_t) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_M_replace_safe(unsigned long, unsigned long, wchar_t const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::at(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_Rep::_M_set_length_and_sharable(unsigned long)(GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_Rep::_M_clone(allocator<wchar_t> const&, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_Rep::_S_create(unsigned long, unsigned long, allocator<wchar_t> const&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::erase(unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::append(wchar_t const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::append(basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>> const&, unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::append(unsigned long, wchar_t)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::assign(wchar_t const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::assign(basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>> const&, unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::assign(unsigned long, wchar_t)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>

>::insert(__gnu_cxx::__normal_iterator<wchar_t*, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>, unsigned long, wchar_t) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::insert(unsigned long, wchar_t const*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::insert(unsigned long, wchar_t const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::insert(unsigned long, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>> const&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::insert(unsigned long, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>> const&, unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::insert(unsigned long, unsigned long, wchar_t)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::resize(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::resize(unsigned long, wchar_t)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>:: >::_M_copy(wchar_t*, wchar_t const*, unsigned long)(GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>:: >::_M_move(wchar_t*, wchar_t const*, unsigned long)(GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>:: >::_replace(__gnu_cxx::__normal_iterator<wchar_t*, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>>, __gnu_cxx::__normal_iterator<wchar_t*, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>>, wchar_t const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>:: >::_replace(__gnu_cxx::__normal_iterator<wchar_t*, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>>, __gnu_cxx::__normal_iterator<wchar_t*, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>>, unsigned long, wchar_t) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::replace(unsigned long, unsigned long, wchar_t const*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::replace(unsigned long, unsigned long, wchar_t const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::replace(unsigned long, unsigned long, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::replace(unsigned long, unsigned long, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>> const&, unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::replace(unsigned long, unsigned long, unsigned long, wchar_t)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::reserve(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_M_assign(wchar_t*, unsigned long, wchar_t)(GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_M_mutate(unsigned long, unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::basic_string(wchar_t const*, unsigned long, allocator<wchar_t> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::basic_string(basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>> const&, unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::basic_string(basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>> const&, unsigned long, unsigned long, allocator<wchar_t> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::basic_string(unsigned long, wchar_t, allocator<wchar_t> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::basic_string(wchar_t const*, unsigned long, allocator<wchar_t> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::basic_string(basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>> const&, unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::basic_string(basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>> const&, unsigned long, unsigned long, allocator<wchar_t> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::operator[](unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 12.1.61 Class basic\_stringstream<char, char\_traits<char>, allocator<char> >

### 12.1.61.1 Class data for basic\_stringstream<char, char\_traits<char>, allocator<char> >

The virtual table for the std::basic\_stringstream<char, std::char\_traits<char>, std::allocator<char> > class is described by [Table 12-48](#)

**Table 12-48 Primary vtable for basic\_stringstream<char, char\_traits<char>, allocator<char> >**

Base Offset	0
Virtual Base Offset	104
RTTI	typeinfo for basic_stringstream<char, char_traits<char>, allocator<char> >
vfunc[0]:	basic_stringstream<char, char_traits<char>, allocator<char> >::~basic_stringstream()
vfunc[1]:	basic_stringstream<char,

	char_traits<char>, allocator<char> >::~basic_stringstream()
--	----------------------------------------------------------------

**Table 12-49 Secondary vtable for basic\_stringstream<char, char\_traits<char>, allocator<char> >**

Base Offset	-16
Virtual Base Offset	88
RTTI	typeinfo for basic_stringstream<char, char_traits<char>, allocator<char> >
vfunc[0]:	non-virtual thunk to basic_stringstream<char, char_traits<char>, allocator<char> >::~basic_stringstream()
vfunc[1]:	non-virtual thunk to basic_stringstream<char, char_traits<char>, allocator<char> >::~basic_stringstream()

**Table 12-50 Secondary vtable for basic\_stringstream<char, char\_traits<char>, allocator<char> >**

Base Offset	-104
Virtual Base Offset	-104
RTTI	typeinfo for basic_stringstream<char, char_traits<char>, allocator<char> >
vfunc[0]:	virtual thunk to basic_stringstream<char, char_traits<char>, allocator<char> >::~basic_stringstream()
vfunc[1]:	virtual thunk to basic_stringstream<char, char_traits<char>, allocator<char> >::~basic_stringstream()

The VTT for the std::basic\_stringstream<char, std::char\_traits<char>, std::allocator<char> > class is described by [Table 12-51](#)

**Table 12-51 VTT for basic\_stringstream<char, char\_traits<char>, allocator<char> >**

VTT Name	_ZTTSt18basic_stringstreamIcSt11char_traitsIcESaIcEE
Number of Entries	10

### 12.1.61.2 Interfaces for Class basic\_stringstream<char, char\_traits<char>, allocator<char> >

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_stringstream<char, std::char\_traits<char>, std::allocator<char> > specified in [Table 12-52](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-52 libstdc++ - Class basic\_stringstream<char, char\_traits<char>, allocator<char> > Function Interfaces**

non-virtual thunk to basic_stringstream<char, char_traits<char>, allocator<char> >::~basic_stringstream()(GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>
non-virtual thunk to basic_stringstream<char, char_traits<char>, allocator<char> >::~basic_stringstream()(GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>

virtual thunk to basic_stringstream<char, char_traits<char>, allocator<char>>::~basic_stringstream()(GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>
-------------------------------------------------------------------------------------------------------------------------------------------------

virtual thunk to basic_stringstream<char, char_traits<char>, allocator<char>>::~basic_stringstream()(GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>
-------------------------------------------------------------------------------------------------------------------------------------------------

## 12.1.62 Class `basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`

### 12.1.62.1 Class data for `basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`

The virtual table for the `std::basic_stringstream<wchar_t, std::char_traits<wchar_t>, std::allocator<wchar_t>` class is described by [Table 12-53](#)

**Table 12-53 Primary vtable for `basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`**

Base Offset	0
Virtual Base Offset	104
RTTI	typeinfo for <code>basic_stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</code>
vfunc[0]:	<code>basic_stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::~basic_stringstream()</code>
vfunc[1]:	<code>basic_stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::~basic_stringstream()</code>

**Table 12-54 Secondary vtable for `basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`**

Base Offset	-16
Virtual Base Offset	88
RTTI	typeinfo for <code>basic_stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</code>
vfunc[0]:	non-virtual thunk to <code>basic_stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::~basic_stringstream()</code>
vfunc[1]:	non-virtual thunk to <code>basic_stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::~basic_stringstream()</code>

**Table 12-55 Secondary vtable for `basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`**

Base Offset	-104
-------------	------

Virtual Base Offset	-104
RTTI	typeinfo for basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>
vfunc[0]:	virtual thunk to basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::~basic_stringstream()
vfunc[1]:	virtual thunk to basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::~basic_stringstream()

The VTT for the std::basic\_stringstream<wchar\_t, std::char\_traits<wchar\_t>, std::allocator<wchar\_t>> class is described by [Table 12-56](#)

**Table 12-56 VTT for basic\_stringstream<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t>>**

VTT Name	_ZTTSt18basic_stringstreamIwSt11char_traitsIwESaIwEE
Number of Entries	10

### 12.1.62.2 Interfaces for Class basic\_stringstream<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t>>

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_stringstream<wchar\_t, std::char\_traits<wchar\_t>, std::allocator<wchar\_t>> specified in [Table 12-57](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-57 libstdc++ - Class basic\_stringstream<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t>> Function Interfaces**

non-virtual thunk to basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::~basic_stringstream()(GLIBCXX_3.4) <a href="#">[CXABI-1.86]</a>
non-virtual thunk to basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::~basic_stringstream()(GLIBCXX_3.4) <a href="#">[CXABI-1.86]</a>
virtual thunk to basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::~basic_stringstream()(GLIBCXX_3.4) <a href="#">[CXABI-1.86]</a>
virtual thunk to basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::~basic_stringstream()(GLIBCXX_3.4) <a href="#">[CXABI-1.86]</a>

### 12.1.63 Class basic\_istream<char, char\_traits<char>, allocator<char>>

#### 12.1.63.1 Class data for basic\_istream<char, char\_traits<char>, allocator<char>>

The virtual table for the std::basic\_istream<char, std::char\_traits<char>, std::allocator<char>> class is described by [Table 12-58](#)

**Table 12-58 Primary vtable for basic\_istream<char, char\_traits<char>, allocator<char> >**

Base Offset	0
Virtual Base Offset	96
RTTI	typeinfo for basic_istream<char, char_traits<char>, allocator<char> >
vfunc[0]:	basic_istream<char, char_traits<char>, allocator<char> >::~basic_istream()
vfunc[1]:	basic_istream<char, char_traits<char>, allocator<char> >::~basic_istream()

**Table 12-59 Secondary vtable for basic\_istream<char, char\_traits<char>, allocator<char> >**

Base Offset	-96
Virtual Base Offset	-96
RTTI	typeinfo for basic_istream<char, char_traits<char>, allocator<char> >
vfunc[0]:	virtual thunk to basic_istream<char, char_traits<char>, allocator<char> >::~basic_istream()
vfunc[1]:	virtual thunk to basic_istream<char, char_traits<char>, allocator<char> >::~basic_istream()

The VTT for the std::basic\_istream<char, std::char\_traits<char>, std::allocator<char> > class is described by [Table 12-60](#)

**Table 12-60 VTT for basic\_istream<char, char\_traits<char>, allocator<char> >**

VTT Name	_ZTTSt19basic_istreamIcSt11char_traitsIcESaIcEE
Number of Entries	4

### 12.1.63.2 Interfaces for Class basic\_istream<char, char\_traits<char>, allocator<char> >

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_istream<char, std::char\_traits<char>, std::allocator<char> > specified in [Table 12-61](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-61 libstdc++ - Class basic\_istream<char, char\_traits<char>, allocator<char> > Function Interfaces**

virtual thunk to basic_istream<char, char_traits<char>, allocator<char> >::~basic_istream()(GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>
virtual thunk to basic_istream<char, char_traits<char>, allocator<char> >::~basic_istream()(GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>

## 12.1.64 Class `basic_istream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`

### 12.1.64.1 Class data for `basic_istream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`

The virtual table for the `std::basic_istream<wchar_t, std::char_traits<wchar_t>, std::allocator<wchar_t>` class is described by [Table 12-62](#)

**Table 12-62 Primary vtable for `basic_istream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`**

Base Offset	0
Virtual Base Offset	96
RTTI	typeinfo for <code>basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</code>
vfunc[0]:	<code>basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::~basic_istream()</code>
vfunc[1]:	<code>basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::~basic_istream()</code>

**Table 12-63 Secondary vtable for `basic_istream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`**

Base Offset	-96
Virtual Base Offset	-96
RTTI	typeinfo for <code>basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</code>
vfunc[0]:	virtual thunk to <code>basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::~basic_istream()</code>
vfunc[1]:	virtual thunk to <code>basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::~basic_istream()</code>

The VTT for the `std::basic_istream<wchar_t, std::char_traits<wchar_t>, std::allocator<wchar_t>` class is described by [Table 12-64](#)

**Table 12-64 VTT for `basic_istream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`**

VTT Name	<code>_ZTTSt19basic_istreamIwSt11char_traitsIwESaIwEE</code>
Number of Entries	4

### 12.1.64.2 Interfaces for Class `basic_istringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::basic_istringstream<wchar_t, std::char_traits<wchar_t>, std::allocator<wchar_t>>` specified in [Table 12-65](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-65 libstdc++ - Class `basic_istringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>` Function Interfaces**

virtual thunk to <code>basic_istringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::~basic_istringstream()</code> (GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>
virtual thunk to <code>basic_istringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::~basic_istringstream()</code> (GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>

### 12.1.65 Class `basic_ostringstream<char, char_traits<char>, allocator<char>`

#### 12.1.65.1 Class data for `basic_ostringstream<char, char_traits<char>, allocator<char>`

The virtual table for the `std::basic_ostringstream<char, std::char_traits<char>, std::allocator<char>>` class is described by [Table 12-66](#)

**Table 12-66 Primary vtable for `basic_ostringstream<char, char_traits<char>, allocator<char>`**

Base Offset	0
Virtual Base Offset	88
RTTI	typeinfo for <code>basic_ostringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;</code>
vfunc[0]:	<code>basic_ostringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::~basic_ostringstream()</code>
vfunc[1]:	<code>basic_ostringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::~basic_ostringstream()</code>

**Table 12-67 Secondary vtable for `basic_ostringstream<char, char_traits<char>, allocator<char>`**

Base Offset	-88
Virtual Base Offset	-88
RTTI	typeinfo for <code>basic_ostringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;</code>
vfunc[0]:	virtual thunk to <code>basic_ostringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::~basic_ostringstream()</code>
vfunc[1]:	virtual thunk to <code>basic_ostringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::~basic_ostringstream()</code>

The VTT for the `std::basic_ostringstream<char, std::char_traits<char>, std::allocator<char>>` class is described by [Table 12-68](#)

**Table 12-68 VTT for basic\_ostringstream<char, char\_traits<char>, allocator<char> >**

VTT Name	_ZTTSt19basic_ostringstreamIcSt11cha r_traitsIcESaIcEE
Number of Entries	4

### 12.1.65.2 Interfaces for Class basic\_ostringstream<char, char\_traits<char>, allocator<char> >

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_ostringstream<char, std::char\_traits<char>, std::allocator<char> > specified in [Table 12-69](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-69 libstdc++ - Class basic\_ostringstream<char, char\_traits<char>, allocator<char> > Function Interfaces**

virtual thunk to basic_ostringstream<char, char_traits<char>, allocator<char> >::~basic_ostringstream()(GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>
virtual thunk to basic_ostringstream<char, char_traits<char>, allocator<char> >::~basic_ostringstream()(GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>

### 12.1.66 Class basic\_ostringstream<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> >

#### 12.1.66.1 Class data for basic\_ostringstream<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> >

The virtual table for the std::basic\_ostringstream<wchar\_t, std::char\_traits<wchar\_t>, std::allocator<wchar\_t> > class is described by [Table 12-70](#)

**Table 12-70 Primary vtable for basic\_ostringstream<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> >**

Base Offset	0
Virtual Base Offset	88
RTTI	typeinfo for basic_ostringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >
vfunc[0]:	basic_ostringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::~basic_ostringstream()
vfunc[1]:	basic_ostringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::~basic_ostringstream()

**Table 12-71 Secondary vtable for basic\_ostringstream<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> >**

Base Offset	-88
Virtual Base Offset	-88
RTTI	typeinfo for basic_ostringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >

vfunc[0]:	virtual thunk to basic_ostringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::~basic_ostringstream()
vfunc[1]:	virtual thunk to basic_ostringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::~basic_ostringstream()

The VTT for the std::basic\_ostringstream<wchar\_t, std::char\_traits<wchar\_t>, std::allocator<wchar\_t> > class is described by [Table 12-72](#)

**Table 12-72 VTT for basic\_ostringstream<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> >**

VTT Name	_ZTTSt19basic_ostringstreamIwSt11char_traitsIwESaIwEE
Number of Entries	4

### 12.1.66.2 Interfaces for Class basic\_ostringstream<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> >

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_ostringstream<wchar\_t, std::char\_traits<wchar\_t>, std::allocator<wchar\_t> > specified in [Table 12-73](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-73 libstdc++ - Class basic\_ostringstream<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> > Function Interfaces**

virtual thunk to basic_ostringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::~basic_ostringstream()(GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>
virtual thunk to basic_ostringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::~basic_ostringstream()(GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>

### 12.1.67 Class basic\_stringbuf<char, char\_traits<char>, allocator<char> >

#### 12.1.67.1 Class data for basic\_stringbuf<char, char\_traits<char>, allocator<char> >

The virtual table for the std::basic\_stringbuf<char, std::char\_traits<char>, std::allocator<char> > class is described by [Table 12-74](#)

**Table 12-74 Primary vtable for basic\_stringbuf<char, char\_traits<char>, allocator<char> >**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for basic_stringbuf<char, char_traits<char>, allocator<char> >
vfunc[0]:	basic_stringbuf<char, char_traits<char>, allocator<char> >::~basic_stringbuf()
vfunc[1]:	basic_stringbuf<char, char_traits<char>, allocator<char> >::~basic_stringbuf()
vfunc[2]:	basic_streambuf<char, char_traits<char>

	>::imbue(locale const&)
vfunc[3]:	basic_stringbuf<char, char_traits<char>, allocator<char> >::setbuf(char*, long)
vfunc[4]:	basic_stringbuf<char, char_traits<char>, allocator<char> >::seekoff(long, _Ios_Seekdir, _Ios_Openmode)
vfunc[5]:	basic_stringbuf<char, char_traits<char>, allocator<char> >::seekpos(fpos<__mbstate_t>, _Ios_Openmode)
vfunc[6]:	basic_streampbuf<char, char_traits<char> >::sync()
vfunc[7]:	basic_streampbuf<char, char_traits<char> >::showmany()
vfunc[8]:	basic_streampbuf<char, char_traits<char> >::xsgetn(char*, long)
vfunc[9]:	basic_stringbuf<char, char_traits<char>, allocator<char> >::underflow()
vfunc[10]:	basic_streampbuf<char, char_traits<char> >::uflow()
vfunc[11]:	basic_stringbuf<char, char_traits<char>, allocator<char> >::pbackfail(int)
vfunc[12]:	basic_streampbuf<char, char_traits<char> >::xsputn(char const*, long)
vfunc[13]:	basic_stringbuf<char, char_traits<char>, allocator<char> >::overflow(int)

The Run Time Type Information for the std::basic\_stringbuf<char, std::char\_traits<char>, std::allocator<char> > class is described by [Table 12-75](#)

**Table 12-75 typeinfo for basic\_stringbuf<char, char\_traits<char>, allocator<char> >**

Base Vtable	vtable for <u>__cxxabiv1::__si_class_type_info</u>
Name	typeinfo name for basic_stringbuf<char, char_traits<char>, allocator<char> >

### 12.1.67.2 Interfaces for Class basic\_stringbuf<char, char\_traits<char>, allocator<char> >

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_stringbuf<char, std::char\_traits<char>, std::allocator<char> > specified in [Table 12-76](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-76 libstdcxx - Class basic\_stringbuf<char, char\_traits<char>, allocator<char> > Function Interfaces**

basic_stringbuf<char, char_traits<char>, allocator<char> >::setbuf(char*, long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<char, char_traits<char>, allocator<char> >::_M_sync(char*, unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<char, char_traits<char>, allocator<char> >::seekoff(long, _Ios_Seekdir, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 12.1.68 Class `basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`

### 12.1.68.1 Class data for `basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`

The virtual table for the `std::basic_stringbuf<wchar_t, std::char_traits<wchar_t>, std::allocator<wchar_t>` class is described by [Table 12-77](#)

**Table 12-77 Primary vtable for `basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</code>
vfunc[0]:	<code>basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::~basic_stringbuf()</code>
vfunc[1]:	<code>basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::~basic_stringbuf()</code>
vfunc[2]:	<code>basic_streampbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::imbue(locale const&amp;)</code>
vfunc[3]:	<code>basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::setbuf(wchar_t*, long)</code>
vfunc[4]:	<code>basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::seekoff(long, _Ios_Seekdir, _Ios_Openmode)</code>
vfunc[5]:	<code>basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::seekpos(fpos&lt;__mbstate_t&gt;, _Ios_Openmode)</code>
vfunc[6]:	<code>basic_streampbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::sync()</code>
vfunc[7]:	<code>basic_streampbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::showmanyc()</code>
vfunc[8]:	<code>basic_streampbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::xsgetn(wchar_t*, long)</code>
vfunc[9]:	<code>basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::underflow()</code>
vfunc[10]:	<code>basic_streampbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::uflow()</code>
vfunc[11]:	<code>basic_stringbuf&lt;wchar_t,</code>

	char_traits<wchar_t>, allocator<wchar_t> >::pbackfail(unsigned int)
vfunc[12]:	basic_streambuf<wchar_t, char_traits<wchar_t>>::xsputn(wchar_t const*, long)
vfunc[13]:	basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::overflow(unsigned int)

The Run Time Type Information for the std::basic\_stringbuf<wchar\_t, std::char\_traits<wchar\_t>, std::allocator<wchar\_t>> class is described by [Table 12-78](#)

**Table 12-78 typeinfo for basic\_stringbuf<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> >**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>

### 12.1.68.2 Interfaces for Class basic\_stringbuf<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> >

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_stringbuf<wchar\_t, std::char\_traits<wchar\_t>, std::allocator<wchar\_t>> specified in [Table 12-79](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-79 libstdcxx - Class basic\_stringbuf<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> > Function Interfaces**

basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::setbuf(wchar_t*, long)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_M_sync(wchar_t*, unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::seekoff(long, _Ios_Seekdir, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>

### 12.1.69 Class basic\_iostream<char, char\_traits<char> >

#### 12.1.69.1 Class data for basic\_iostream<char, char\_traits<char> >

The virtual table for the std::basic\_iostream<char, std::char\_traits<char>> class is described by [Table 12-80](#)

**Table 12-80 Primary vtable for basic\_iostream<char, char\_traits<char> >**

Base Offset	0
Virtual Base Offset	24
RTTI	typeinfo for basic_iostream<char, char_traits<char>>
vfunc[0]:	basic_iostream<char, char_traits<char>>::~basic_iostream()

vfunc[1]:	basic_iostream<char, char_traits<char>>::~basic_iostream()
-----------	------------------------------------------------------------

**Table 12-81 Secondary vtable for basic\_iostream<char, char\_traits<char>>**

Base Offset	-16
Virtual Base Offset	8
RTTI	typeinfo for basic_iostream<char, char_traits<char>>
vfunc[0]:	non-virtual thunk to basic_iostream<char, char_traits<char>>::~basic_iostream()
vfunc[1]:	non-virtual thunk to basic_iostream<char, char_traits<char>>::~basic_iostream()

**Table 12-82 Secondary vtable for basic\_iostream<char, char\_traits<char>>**

Base Offset	-24
Virtual Base Offset	-24
RTTI	typeinfo for basic_iostream<char, char_traits<char>>
vfunc[0]:	virtual thunk to basic_iostream<char, char_traits<char>>::~basic_iostream()
vfunc[1]:	virtual thunk to basic_iostream<char, char_traits<char>>::~basic_iostream()

The VTT for the std::basic\_iostream<char, std::char\_traits<char>> class is described by [Table 12-83](#)

**Table 12-83 VTT for basic\_iostream<char, char\_traits<char>>**

VTT Name	ZTTSd
Number of Entries	7

### 12.1.69.2 Interfaces for Class basic\_iostream<char, char\_traits<char>>

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_iostream<char, std::char\_traits<char>> specified in [Table 12-84](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-84 libstdcxx - Class basic\_iostream<char, char\_traits<char>> Function Interfaces**

non-virtual thunk to basic_iostream<char, char_traits<char>>::~basic_iostream() (GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>
non-virtual thunk to basic_iostream<char, char_traits<char>>::~basic_iostream() (GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>
virtual thunk to basic_iostream<char, char_traits<char>>::~basic_iostream() (GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>
virtual thunk to basic_iostream<char, char_traits<char>>::~basic_iostream() (GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>

## 12.1.70 Class `basic_iostream<wchar_t, char_traits<wchar_t>>`

### 12.1.70.1 Class data for `basic_iostream<wchar_t, char_traits<wchar_t>>`

The virtual table for the `std::basic_iostream<wchar_t, std::char_traits<wchar_t>>` class is described by [Table 12-85](#)

**Table 12-85 Primary vtable for `basic_iostream<wchar_t, char_traits<wchar_t>>`**

Base Offset	0
Virtual Base Offset	24
RTTI	typeinfo for <code>basic_iostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code>
vfunc[0]:	<code>basic_iostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_iostream()</code>
vfunc[1]:	<code>basic_iostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_iostream()</code>

**Table 12-86 Secondary vtable for `basic_iostream<wchar_t, char_traits<wchar_t>>`**

Base Offset	-16
Virtual Base Offset	8
RTTI	typeinfo for <code>basic_iostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code>
vfunc[0]:	non-virtual thunk to <code>basic_iostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_iostream()</code>
vfunc[1]:	non-virtual thunk to <code>basic_iostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_iostream()</code>

**Table 12-87 Secondary vtable for `basic_iostream<wchar_t, char_traits<wchar_t>>`**

Base Offset	-24
Virtual Base Offset	-24
RTTI	typeinfo for <code>basic_iostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code>
vfunc[0]:	virtual thunk to <code>basic_iostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_iostream()</code>
vfunc[1]:	virtual thunk to <code>basic_iostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_iostream()</code>

The VTT for the `std::basic_iostream<wchar_t, std::char_traits<wchar_t>>` class is described by [Table 12-88](#)

**Table 12-88 VTT for basic\_iostream<wchar\_t, char\_traits<wchar\_t> >**

VTT Name	_ZTTSSt14basic_iostreamIwSt11char_traitsIwEE
Number of Entries	7

### 12.1.70.2 Interfaces for Class basic\_iostream<wchar\_t, char\_traits<wchar\_t> >

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_iostream<wchar\_t, std::char\_traits<wchar\_t> > specified in [Table 12-89](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-89 libstdc++ - Class basic\_iostream<wchar\_t, char\_traits<wchar\_t> > Function Interfaces**

non-virtual thunk to basic_iostream<wchar_t, char_traits<wchar_t> >::~basic_iostream()(GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>
non-virtual thunk to basic_iostream<wchar_t, char_traits<wchar_t> >::~basic_iostream()(GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>
virtual thunk to basic_iostream<wchar_t, char_traits<wchar_t> >::~basic_iostream()(GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>
virtual thunk to basic_iostream<wchar_t, char_traits<wchar_t> >::~basic_iostream()(GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>

### 12.1.71 Class basic\_istream<char, char\_traits<char> >

#### 12.1.71.1 Class data for basic\_istream<char, char\_traits<char> >

The virtual table for the std::basic\_istream<char, std::char\_traits<char> > class is described by [Table 12-90](#)

**Table 12-90 Primary vtable for basic\_istream<char, char\_traits<char> >**

Base Offset	0
Virtual Base Offset	16
RTTI	typeinfo for basic_istream<char, char_traits<char> >
vfunc[0]:	basic_istream<char, char_traits<char> >::~basic_istream()
vfunc[1]:	basic_istream<char, char_traits<char> >::~basic_istream()

**Table 12-91 Secondary vtable for basic\_istream<char, char\_traits<char> >**

Base Offset	-16
Virtual Base Offset	-16
RTTI	typeinfo for basic_istream<char, char_traits<char> >
vfunc[0]:	virtual thunk to basic_istream<char, char_traits<char> >::~basic_istream()
vfunc[1]:	virtual thunk to basic_istream<char, char_traits<char> >::~basic_istream()

The VTT for the std::basic\_istream<char, std::char\_traits<char> > class is described by

[Table 12-92](#)**Table 12-92 VTT for basic\_istream<char, char\_traits<char> >**

VTT Name	ZTTSi
Number of Entries	2

### 12.1.71.2 Interfaces for Class basic\_istream<char, char\_traits<char> >

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_istream<char, std::char\_traits<char> > specified in [Table 12-93](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-93 libstdcxx - Class basic\_istream<char, char\_traits<char> > Function Interfaces**

basic_istream<char, char_traits<char> >& basic_istream<char, char_traits<char> >:: M_extract<__float128>(__float128&)(GLIBCXX_LDBL_3.4.7) <a href="#">[LSB]</a>
basic_istream<char, char_traits<char> >::get(char*, long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::get(char*, long, char)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::read(char*, long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::seekg(long, _Ios_Seekdir)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::ignore(long)(GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::ignore(long, int)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::getline(char*, long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::getline(char*, long, char)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::readsome(char*, long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::operator>>(__float128&)(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >& operator>><__float128, char, char_traits<char> >(basic_istream<char, char_traits<char> >&, complex<__float128>&)(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
virtual thunk to basic_istream<char, char_traits<char> >::~basic_istream()(GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>
virtual thunk to basic_istream<char, char_traits<char> >::~basic_istream()(GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>

### 12.1.72 Class basic\_istream<wchar\_t, char\_traits<wchar\_t> >

#### 12.1.72.1 Class data for basic\_istream<wchar\_t, char\_traits<wchar\_t> >

The virtual table for the std::basic\_istream<wchar\_t, std::char\_traits<wchar\_t> > class is described by [Table 12-94](#)

**Table 12-94 Primary vtable for basic\_istream<wchar\_t, char\_traits<wchar\_t> >**

Base Offset	0
Virtual Base Offset	16
RTTI	typeinfo for basic_istream<wchar_t, char_traits<wchar_t> >
vfunc[0]:	basic_istream<wchar_t, char_traits<wchar_t> >::~basic_istream()
vfunc[1]:	basic_istream<wchar_t, char_traits<wchar_t> >::~basic_istream()

**Table 12-95 Secondary vtable for basic\_istream<wchar\_t, char\_traits<wchar\_t> >**

Base Offset	-16
Virtual Base Offset	-16
RTTI	typeinfo for basic_istream<wchar_t, char_traits<wchar_t> >
vfunc[0]:	virtual thunk to basic_istream<wchar_t, char_traits<wchar_t> >::~basic_istream()
vfunc[1]:	virtual thunk to basic_istream<wchar_t, char_traits<wchar_t> >::~basic_istream()

The VTT for the std::basic\_istream<wchar\_t, std::char\_traits<wchar\_t> > class is described by [Table 12-96](#)

**Table 12-96 VTT for basic\_istream<wchar\_t, char\_traits<wchar\_t> >**

VTT Name	_ZTTSt13basic_istreamIwSt11char_trait_sIwEE
Number of Entries	2

### 12.1.72.2 Interfaces for Class basic\_istream<wchar\_t, char\_traits<wchar\_t> >

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_istream<wchar\_t, std::char\_traits<wchar\_t> > specified in [Table 12-97](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-97 libstdcxx - Class basic\_istream<wchar\_t, char\_traits<wchar\_t> > Function Interfaces**

basic_istream<wchar_t, char_traits<wchar_t> >& basic_istream<wchar_t, char_traits<wchar_t> >::__M_extract<__float128>(__float128&) (GLIBCXX_LDBL_3.4.7) <a href="#">[LSB]</a>
basic_istream<wchar_t, char_traits<wchar_t> >::get(wchar_t*, long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t> >::get(wchar_t*, long, wchar_t) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t> >::read(wchar_t*, long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t> >::seekg(long, _Ios_Seekdir) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

basic_istream<wchar_t, char_traits<wchar_t>>::ignore(long)(GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>::ignore(long, unsigned int)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>::getline(wchar_t*, long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>::getline(wchar_t*, long, wchar_t)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>::readsome(wchar_t*, long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>::operator>>(_float128&)(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>& operator>><_float128, wchar_t, char_traits<wchar_t>>(basic_istream<wchar_t, char_traits<wchar_t>>&, complex<_float128>&)(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
virtual thunk to basic_istream<wchar_t, char_traits<wchar_t>>::~basic_istream()(GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>
virtual thunk to basic_istream<wchar_t, char_traits<wchar_t>>::~basic_istream()(GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>

## 12.1.73 Class istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> >

### 12.1.73.1 Interfaces for Class istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> >

No external methods are defined for libstdcxx - Class std::istreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t>> in this part of the specification. See also the generic specification.

## 12.1.74 Class istreambuf\_iterator<char, char\_traits<char> >

### 12.1.74.1 Interfaces for Class istreambuf\_iterator<char, char\_traits<char> >

No external methods are defined for libstdcxx - Class std::istreambuf\_iterator<char, std::char\_traits<char>> in this part of the specification. See also the generic specification.

## 12.1.75 Class basic\_ostream<char, char\_traits<char> >

### 12.1.75.1 Class data for basic\_ostream<char, char\_traits<char> >

The virtual table for the std::basic\_ostream<char, std::char\_traits<char>> class is described by [Table 12-98](#)

**Table 12-98 Primary vtable for basic\_ostream<char, char\_traits<char> >**

Base Offset	0
Virtual Base Offset	8
RTTI	typeinfo for basic_ostream<char, char_traits<char>>

vfunc[0]:	basic_ostream<char, char_traits<char>>::~basic_ostream()
vfunc[1]:	basic_ostream<char, char_traits<char>>::~basic_ostream()

**Table 12-99 Secondary vtable for basic\_ostream<char, char\_traits<char> >**

Base Offset	-8
Virtual Base Offset	-8
RTTI	typeinfo for basic_ostream<char, char_traits<char> >
vfunc[0]:	virtual thunk to basic_ostream<char, char_traits<char>>::~basic_ostream()
vfunc[1]:	virtual thunk to basic_ostream<char, char_traits<char>>::~basic_ostream()

The VTT for the std::basic\_ostream<char, std::char\_traits<char> > class is described by [Table 12-100](#)

**Table 12-100 VTT for basic\_ostream<char, char\_traits<char> >**

VTT Name	_ZTTSo
Number of Entries	2

### 12.1.75.2 Interfaces for Class basic\_ostream<char, char\_traits<char> >

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_ostream<char, std::char\_traits<char> > specified in [Table 12-101](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-101 libstdcxx - Class basic\_ostream<char, char\_traits<char> > Function Interfaces**

basic_ostream<char, char_traits<char> >::seekp(long, _Ios_Seekdir) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<char, char_traits<char> >::write(char const*, long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<char, char_traits<char> >::_M_write(char const*, long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<char, char_traits<char> >& basic_ostream<char, char_traits<char> >::_M_insert<__float128>(__float128)(GLIBCXX_LDBL_3.4.7) <a href="#">[LSB]</a>
basic_ostream<char, char_traits<char> >::operator<<(__float128) (GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<char, char_traits<char> >& operator<<<__float128, char, char_traits<char> >(basic_ostream<char, char_traits<char> >&, complex<__float128> const&)(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
virtual thunk to basic_ostream<char, char_traits<char> >::~basic_ostream() (GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>
virtual thunk to basic_ostream<char, char_traits<char> >::~basic_ostream() (GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>

## 12.1.76 Class `basic_ostream<wchar_t, char_traits<wchar_t>>`

### 12.1.76.1 Class data for `basic_ostream<wchar_t, char_traits<wchar_t>>`

The virtual table for the `std::basic_ostream<wchar_t, std::char_traits<wchar_t>>` class is described by [Table 12-102](#)

**Table 12-102 Primary vtable for `basic_ostream<wchar_t, char_traits<wchar_t>>`**

Base Offset	0
Virtual Base Offset	8
RTTI	typeinfo for <code>basic_ostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code>
vfunc[0]:	<code>basic_ostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_ostream()</code>
vfunc[1]:	<code>basic_ostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_ostream()</code>

**Table 12-103 Secondary vtable for `basic_ostream<wchar_t, char_traits<wchar_t>>`**

Base Offset	-8
Virtual Base Offset	-8
RTTI	typeinfo for <code>basic_ostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code>
vfunc[0]:	virtual thunk to <code>basic_ostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_ostream()</code>
vfunc[1]:	virtual thunk to <code>basic_ostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_ostream()</code>

The VTT for the `std::basic_ostream<wchar_t, std::char_traits<wchar_t>>` class is described by [Table 12-104](#)

**Table 12-104 VTT for `basic_ostream<wchar_t, char_traits<wchar_t>>`**

VTT Name	_ZTTSt13basic_ostreamIwSt11char_trai tsIwEE
Number of Entries	2

### 12.1.76.2 Interfaces for Class `basic_ostream<wchar_t, char_traits<wchar_t>>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::basic_ostream<wchar_t, std::char_traits<wchar_t>>` specified in [Table 12-105](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-105 libstdc++ - Class `basic_ostream<wchar_t, char_traits<wchar_t>>` Function Interfaces**

<code>basic_ostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::seekp(long, _Ios_Seekdir)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
--------------------------------------------------------------------------------------------------------------------------------------------

basic_ostream<wchar_t, char_traits<wchar_t>>::write(wchar_t const*, long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>& basic_ostream<wchar_t, char_traits<wchar_t>>::_M_insert<__float128>(__float128) (GLIBCXX_LDBL_3.4.7) <a href="#">[LSB]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::operator<<(__float128) (GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>& operator<<<__float128, wchar_t, char_traits<wchar_t>>(basic_ostream<wchar_t, char_traits<wchar_t>>&, complex<__float128> const&)(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
virtual thunk to basic_ostream<wchar_t, char_traits<wchar_t>>::~basic_ostream() (GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>
virtual thunk to basic_ostream<wchar_t, char_traits<wchar_t>>::~basic_ostream() (GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>

## 12.1.77 Class `basic_fstream<char, char_traits<char>>`

### 12.1.77.1 Class data for `basic_fstream<char, char_traits<char>>`

The virtual table for the `std::basic_fstream<char, std::char_traits<char>>` class is described by [Table 12-106](#)

**Table 12-106 Primary vtable for `basic_fstream<char, char_traits<char>>`**

Base Offset	0
Virtual Base Offset	264
RTTI	typeinfo for <code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;</code>
vfunc[0]:	<code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;::~basic_fstream()</code>
vfunc[1]:	<code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;::~basic_fstream()</code>

**Table 12-107 Secondary vtable for `basic_fstream<char, char_traits<char>>`**

Base Offset	-16
Virtual Base Offset	248
RTTI	typeinfo for <code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;</code>
vfunc[0]:	non-virtual thunk to <code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;::~basic_fstream()</code>
vfunc[1]:	non-virtual thunk to <code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;::~basic_fstream()</code>

**Table 12-108 Secondary vtable for `basic_fstream<char, char_traits<char>>`**

Base Offset	-264
Virtual Base Offset	-264
RTTI	typeinfo for <code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;</code>
vfunc[0]:	virtual thunk to <code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;::~basic_fstream()</code>
vfunc[1]:	virtual thunk to <code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;::~basic_fstream()</code>

	char_traits<char> >::~basic_fstream()
--	---------------------------------------

The VTT for the std::basic\_fstream<char, std::char\_traits<char> > class is described by [Table 12-109](#)

**Table 12-109 VTT for basic\_fstream<char, char\_traits<char> >**

VTT Name	_ZTTSt13basic_fstreamIcSt11char_trait_sIcEE
Number of Entries	10

### 12.1.77.2 Interfaces for Class basic\_fstream<char, char\_traits<char> >

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_fstream<char, std::char\_traits<char> > specified in [Table 12-110](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-110 libstdcxx - Class basic\_fstream<char, char\_traits<char> > Function Interfaces**

non-virtual thunk to basic_fstream<char, char_traits<char> >::~basic_fstream() (GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>
non-virtual thunk to basic_fstream<char, char_traits<char> >::~basic_fstream() (GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>
virtual thunk to basic_fstream<char, char_traits<char> >::~basic_fstream() (GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>
virtual thunk to basic_fstream<char, char_traits<char> >::~basic_fstream() (GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>

### 12.1.78 Class basic\_fstream<wchar\_t, char\_traits<wchar\_t> >

#### 12.1.78.1 Class data for basic\_fstream<wchar\_t, char\_traits<wchar\_t> >

The virtual table for the std::basic\_fstream<wchar\_t, std::char\_traits<wchar\_t> > class is described by [Table 12-111](#)

**Table 12-111 Primary vtable for basic\_fstream<wchar\_t, char\_traits<wchar\_t> >**

Base Offset	0
Virtual Base Offset	264
RTTI	typeinfo for basic_fstream<wchar_t, char_traits<wchar_t> >
vfunc[0]:	basic_fstream<wchar_t, char_traits<wchar_t> >::~basic_fstream()
vfunc[1]:	basic_fstream<wchar_t, char_traits<wchar_t> >::~basic_fstream()

**Table 12-112 Secondary vtable for basic\_fstream<wchar\_t, char\_traits<wchar\_t> >**

Base Offset	-16
Virtual Base Offset	248
RTTI	typeinfo for basic_fstream<wchar_t,

	char_traits<wchar_t> >
vfunc[0]:	non-virtual thunk to basic_fstream<wchar_t, char_traits<wchar_t> >::~basic_fstream()
vfunc[1]:	non-virtual thunk to basic_fstream<wchar_t, char_traits<wchar_t> >::~basic_fstream()

**Table 12-113 Secondary vtable for basic\_fstream<wchar\_t, char\_traits<wchar\_t> >**

Base Offset	-264
Virtual Base Offset	-264
RTTI	typeinfo for basic_fstream<wchar_t, char_traits<wchar_t> >
vfunc[0]:	virtual thunk to basic_fstream<wchar_t, char_traits<wchar_t> >::~basic_fstream()
vfunc[1]:	virtual thunk to basic_fstream<wchar_t, char_traits<wchar_t> >::~basic_fstream()

The VTT for the std::basic\_fstream<wchar\_t, std::char\_traits<wchar\_t> > class is described by [Table 12-114](#)

**Table 12-114 VTT for basic\_fstream<wchar\_t, char\_traits<wchar\_t> >**

VTT Name	ZTTSt13basic_fstreamIwSt11char_trait_sIwEE
Number of Entries	10

### 12.1.78.2 Interfaces for Class basic\_fstream<wchar\_t, char\_traits<wchar\_t> >

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_fstream<wchar\_t, std::char\_traits<wchar\_t> > specified in [Table 12-115](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-115 libstdc++ - Class basic\_fstream<wchar\_t, char\_traits<wchar\_t> > Function Interfaces**

non-virtual thunk to basic_fstream<wchar_t, char_traits<wchar_t> >::~basic_fstream()(GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>
non-virtual thunk to basic_fstream<wchar_t, char_traits<wchar_t> >::~basic_fstream()(GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>
virtual thunk to basic_fstream<wchar_t, char_traits<wchar_t> >::~basic_fstream() (GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>

### 12.1.79 Class basic\_ifstream<char, char\_traits<char> >

#### 12.1.79.1 Class data for basic\_ifstream<char, char\_traits<char> >

The virtual table for the std::basic\_ifstream<char, std::char\_traits<char> > class is de-

scribed by [Table 12-116](#)

**Table 12-116 Primary vtable for basic\_ifstream<char, char\_traits<char> >**

Base Offset	0
Virtual Base Offset	256
RTTI	typeinfo for basic_ifstream<char, char_traits<char> >
vfunc[0]:	basic_ifstream<char, char_traits<char> >::~basic_ifstream()
vfunc[1]:	basic_ifstream<char, char_traits<char> >::~basic_ifstream()

**Table 12-117 Secondary vtable for basic\_ifstream<char, char\_traits<char> >**

Base Offset	-256
Virtual Base Offset	-256
RTTI	typeinfo for basic_ifstream<char, char_traits<char> >
vfunc[0]:	virtual thunk to basic_ifstream<char, char_traits<char> >::~basic_ifstream()
vfunc[1]:	virtual thunk to basic_ifstream<char, char_traits<char> >::~basic_ifstream()

The VTT for the std::basic\_ifstream<char, std::char\_traits<char> > class is described by [Table 12-118](#)

**Table 12-118 VTT for basic\_ifstream<char, char\_traits<char> >**

VTT Name	_ZTTSt14basic_ifstreamIcSt11char_trait_s1cEE
Number of Entries	4

### 12.1.79.2 Interfaces for Class basic\_ifstream<char, char\_traits<char> >

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_ifstream<char, std::char\_traits<char> > specified in [Table 12-119](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-119 libstdc++ - Class basic\_ifstream<char, char\_traits<char> > Function Interfaces**

virtual thunk to basic_ifstream<char, char_traits<char> >::~basic_ifstream() (GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>
virtual thunk to basic_ifstream<char, char_traits<char> >::~basic_ifstream() (GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>

### 12.1.80 Class basic\_ifstream<wchar\_t, char\_traits<wchar\_t> >

#### 12.1.80.1 Class data for basic\_ifstream<wchar\_t, char\_traits<wchar\_t> >

The virtual table for the std::basic\_ifstream<wchar\_t, std::char\_traits<wchar\_t> > class is described by [Table 12-120](#)

**Table 12-120 Primary vtable for basic\_ifstream<wchar\_t, char\_traits<wchar\_t>>**

Base Offset	0
Virtual Base Offset	256
RTTI	typeinfo for basic_ifstream<wchar_t, char_traits<wchar_t>>
vfunc[0]:	basic_ifstream<wchar_t, char_traits<wchar_t>>::~basic_ifstream()
vfunc[1]:	basic_ifstream<wchar_t, char_traits<wchar_t>>::~basic_ifstream()

**Table 12-121 Secondary vtable for basic\_ifstream<wchar\_t, char\_traits<wchar\_t>>**

Base Offset	-256
Virtual Base Offset	-256
RTTI	typeinfo for basic_ifstream<wchar_t, char_traits<wchar_t>>
vfunc[0]:	virtual thunk to basic_ifstream<wchar_t, char_traits<wchar_t>>::~basic_ifstream()
vfunc[1]:	virtual thunk to basic_ifstream<wchar_t, char_traits<wchar_t>>::~basic_ifstream()

The VTT for the std::basic\_ifstream<wchar\_t, std::char\_traits<wchar\_t>> class is described by [Table 12-122](#)

**Table 12-122 VTT for basic\_ifstream<wchar\_t, char\_traits<wchar\_t>>**

VTT Name	_ZTTSt14basic_ifstreamIwSt11char_traitsIwEE
Number of Entries	4

### 12.1.80.2 Interfaces for Class basic\_ifstream<wchar\_t, char\_traits<wchar\_t>>

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_ifstream<wchar\_t, std::char\_traits<wchar\_t>> specified in [Table 12-123](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-123 libstdc++ - Class basic\_ifstream<wchar\_t, char\_traits<wchar\_t>> Function Interfaces**

virtual thunk to basic_ifstream<wchar_t, char_traits<wchar_t>>::~basic_ifstream() (GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>
virtual thunk to basic_ifstream<wchar_t, char_traits<wchar_t>>::~basic_ifstream() (GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>

### 12.1.81 Class basic\_ofstream<char, char\_traits<char>>

#### 12.1.81.1 Class data for basic\_ofstream<char, char\_traits<char>>

The virtual table for the std::basic\_ofstream<char, std::char\_traits<char>> class is de-

scribed by [Table 12-124](#)

**Table 12-124 Primary vtable for basic\_ofstream<char, char\_traits<char> >**

Base Offset	0
Virtual Base Offset	248
RTTI	typeinfo for basic_ofstream<char, char_traits<char> >
vfunc[0]:	basic_ofstream<char, char_traits<char> >::~basic_ofstream()
vfunc[1]:	basic_ofstream<char, char_traits<char> >::~basic_ofstream()

**Table 12-125 Secondary vtable for basic\_ofstream<char, char\_traits<char> >**

Base Offset	-248
Virtual Base Offset	-248
RTTI	typeinfo for basic_ofstream<char, char_traits<char> >
vfunc[0]:	virtual thunk to basic_ofstream<char, char_traits<char> >::~basic_ofstream()
vfunc[1]:	virtual thunk to basic_ofstream<char, char_traits<char> >::~basic_ofstream()

The VTT for the std::basic\_ofstream<char, std::char\_traits<char> > class is described by [Table 12-126](#)

**Table 12-126 VTT for basic\_ofstream<char, char\_traits<char> >**

VTT Name	_ZTTSt14basic_ofstreamIcSt11char_trai tsIcEE
Number of Entries	4

### 12.1.81.2 Interfaces for Class basic\_ofstream<char, char\_traits<char> >

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_ofstream<char, std::char\_traits<char> > specified in [Table 12-127](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-127 libstdc++ - Class basic\_ofstream<char, char\_traits<char> > Function Interfaces**

virtual thunk to basic_ofstream<char, char_traits<char> >::~basic_ofstream() (GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>
virtual thunk to basic_ofstream<char, char_traits<char> >::~basic_ofstream() (GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>

### 12.1.82 Class basic\_ofstream<wchar\_t, char\_traits<wchar\_t> >

#### 12.1.82.1 Class data for basic\_ofstream<wchar\_t, char\_traits<wchar\_t> >

The virtual table for the std::basic\_ofstream<wchar\_t, std::char\_traits<wchar\_t> > class is described by [Table 12-128](#)

**Table 12-128 Primary vtable for basic\_ofstream<wchar\_t, char\_traits<wchar\_t>>**

Base Offset	0
Virtual Base Offset	248
RTTI	typeinfo for basic_ofstream<wchar_t, char_traits<wchar_t>>
vfunc[0]:	basic_ofstream<wchar_t, char_traits<wchar_t>>::~basic_ofstream()
vfunc[1]:	basic_ofstream<wchar_t, char_traits<wchar_t>>::~basic_ofstream()

**Table 12-129 Secondary vtable for basic\_ofstream<wchar\_t, char\_traits<wchar\_t>>**

Base Offset	-248
Virtual Base Offset	-248
RTTI	typeinfo for basic_ofstream<wchar_t, char_traits<wchar_t>>
vfunc[0]:	virtual thunk to basic_ofstream<wchar_t, char_traits<wchar_t>>::~basic_ofstream()
vfunc[1]:	virtual thunk to basic_ofstream<wchar_t, char_traits<wchar_t>>::~basic_ofstream()

The VTT for the std::basic\_ofstream<wchar\_t, std::char\_traits<wchar\_t>> class is described by [Table 12-130](#)

**Table 12-130 VTT for basic\_ofstream<wchar\_t, char\_traits<wchar\_t>>**

VTT Name	_ZTTSt14basic_ofstreamIwSt11char_traitsIwEE
Number of Entries	4

### 12.1.82.2 Interfaces for Class basic\_ofstream<wchar\_t, char\_traits<wchar\_t>>

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_ofstream<wchar\_t, std::char\_traits<wchar\_t>> specified in [Table 12-131](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-131 libstdc++ - Class basic\_ofstream<wchar\_t, char\_traits<wchar\_t>> Function Interfaces**

virtual thunk to basic_ofstream<wchar_t, char_traits<wchar_t>>::~basic_ofstream() (GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>
virtual thunk to basic_ofstream<wchar_t, char_traits<wchar_t>>::~basic_ofstream() (GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>

## 12.1.83 Class `basic_streambuf<char, char_traits<char>>`

### 12.1.83.1 Class data for `basic_streambuf<char, char_traits<char>>`

The virtual table for the `std::basic_streambuf<char, std::char_traits<char>>` class is described by [Table 12-132](#)

**Table 12-132 Primary vtable for `basic_streambuf<char, char_traits<char>>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;</code>
vfunc[0]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;::~basic_streambuf()</code>
vfunc[1]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;::~basic_streambuf()</code>
vfunc[2]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;::imbue(locale const&amp;)</code>
vfunc[3]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;::setbuf(char*, long)</code>
vfunc[4]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;::seekoff(long, _Ios_Seekdir, _Ios_Openmode)</code>
vfunc[5]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;::seekpos(fpos&lt;__mbstate_t&gt;, _Ios_Openmode)</code>
vfunc[6]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;::sync()</code>
vfunc[7]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;::showmany()</code>
vfunc[8]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;::xsgetn(char*, long)</code>
vfunc[9]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;::underflow()</code>
vfunc[10]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;::uflow()</code>
vfunc[11]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;::pbackfail(int)</code>
vfunc[12]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;::xsputn(char const*, long)</code>
vfunc[13]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;::overflow(int)</code>

The Run Time Type Information for the `std::basic_streambuf<char, std::char_traits<char>>` class is described by [Table 12-133](#)

**Table 12-133 typeinfo for `basic_streambuf<char, char_traits<char>>`**

Base Vtable	vtable for <code>__cxxabiv1::__class_type_info</code>
Name	typeinfo name for <code>basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;</code>

	>
--	---

### 12.1.83.2 Interfaces for Class `basic_streambuf<char, char_traits<char>>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::basic_streambuf<char, std::char_traits<char>>` specified in [Table 12-134](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-134 libstdcxx - Class `basic_streambuf<char, char_traits<char>>` Function Interfaces**

<code>basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;::pubseekoff(long, _Ios_Seekdir, _Ios_Openmode)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;::sgetn(char*, long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;::sputn(char const*, long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;::setbuf(char*, long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;::xsgetn(char*, long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;::xsputn(char const*, long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;::seekoff(long, _Ios_Seekdir, _Ios_Openmode)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;::pubsetbuf(char*, long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

### 12.1.84 Class `basic_streambuf<wchar_t, char_traits<wchar_t>>`

#### 12.1.84.1 Class data for `basic_streambuf<wchar_t, char_traits<wchar_t>>`

The virtual table for the `std::basic_streambuf<wchar_t, std::char_traits<wchar_t>>` class is described by [Table 12-135](#)

**Table 12-135 Primary vtable for `basic_streambuf<wchar_t, char_traits<wchar_t>>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code>
vfunc[0]:	<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_streambuf()</code>
vfunc[1]:	<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_streambuf()</code>
vfunc[2]:	<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::imbue(locale const&amp;)</code>

vfunc[3]:	basic_streambuf<wchar_t, char_traits<wchar_t> >::setbuf(wchar_t*, long)
vfunc[4]:	basic_streambuf<wchar_t, char_traits<wchar_t>>::seekoff(long, _Ios_Seekdir, _Ios_Openmode)
vfunc[5]:	basic_streambuf<wchar_t, char_traits<wchar_t> >::seekpos(fpos<__mbstate_t>, _Ios_Openmode)
vfunc[6]:	basic_streambuf<wchar_t, char_traits<wchar_t>>::sync()
vfunc[7]:	basic_streambuf<wchar_t, char_traits<wchar_t>>::showmany()
vfunc[8]:	basic_streambuf<wchar_t, char_traits<wchar_t> >::xsgetn(wchar_t*, long)
vfunc[9]:	basic_streambuf<wchar_t, char_traits<wchar_t>>::underflow()
vfunc[10]:	basic_streambuf<wchar_t, char_traits<wchar_t>>::uflow()
vfunc[11]:	basic_streambuf<wchar_t, char_traits<wchar_t> >::pbackfail(unsigned int)
vfunc[12]:	basic_streambuf<wchar_t, char_traits<wchar_t>>::xsputn(wchar_t const*, long)
vfunc[13]:	basic_streambuf<wchar_t, char_traits<wchar_t> >::overflow(unsigned int)

The Run Time Type Information for the std::basic\_streambuf<wchar\_t, std::char\_traits<wchar\_t>> class is described by [Table 12-136](#)

**Table 12-136 typeinfo for basic\_streambuf<wchar\_t, char\_traits<wchar\_t>>**

Base Vtable	vtable for <u>__cxxabiv1::__class_type_info</u>
Name	typeinfo name for basic_streambuf<wchar_t, char_traits<wchar_t>>

### 12.1.84.2 Interfaces for Class basic\_streambuf<wchar\_t, char\_traits<wchar\_t>>

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_streambuf<wchar\_t, std::char\_traits<wchar\_t>> specified in [Table 12-137](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-137 libstdc++ - Class basic\_streambuf<wchar\_t, char\_traits<wchar\_t>> Function Interfaces**

basic_streambuf<wchar_t, char_traits<wchar_t>>::pubseekoff(long, _Ios_Seekdir, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t>>::sgetn(wchar_t*, long)

(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t>>::sputn(wchar_t const*, long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t>>::setbuf(wchar_t*, long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t>>::xsgetn(wchar_t*, long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t>>::xsputn(wchar_t const*, long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t>>::seekoff(long, _Ios_Seekdir, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t>>::pubsetbuf(wchar_t*, long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 12.1.85 Class basic\_filebuf<char, char\_traits<char> >

### 12.1.85.1 Class data for basic\_filebuf<char, char\_traits<char> >

The virtual table for the std::basic\_filebuf<char, std::char\_traits<char> > class is described by [Table 12-138](#)

**Table 12-138 Primary vtable for basic\_filebuf<char, char\_traits<char> >**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for basic_filebuf<char, char_traits<char> >
vfunc[0]:	basic_filebuf<char, char_traits<char> >::~basic_filebuf()
vfunc[1]:	basic_filebuf<char, char_traits<char> >::~basic_filebuf()
vfunc[2]:	basic_filebuf<char, char_traits<char> >::imbue(locale const&)
vfunc[3]:	basic_filebuf<char, char_traits<char> >::setbuf(char*, long)
vfunc[4]:	basic_filebuf<char, char_traits<char> >::seekoff(long, _Ios_Seekdir, _Ios_Openmode)
vfunc[5]:	basic_filebuf<char, char_traits<char> >::seekpos(fpos<__mbstate_t>, _Ios_Openmode)
vfunc[6]:	basic_filebuf<char, char_traits<char> >::sync()
vfunc[7]:	basic_filebuf<char, char_traits<char> >::showmany()
vfunc[8]:	basic_filebuf<char, char_traits<char> >::xsgetn(char*, long)
vfunc[9]:	basic_filebuf<char, char_traits<char> >::underflow()
vfunc[10]:	basic_streambuf<char, char_traits<char> >::uflow()
vfunc[11]:	basic_filebuf<char, char_traits<char> >

	>::pbackfail(int)
vfunc[12]:	basic_filebuf<char, char_traits<char>>::xspputn(char const*, long)
vfunc[13]:	basic_filebuf<char, char_traits<char>>::overflow(int)

The Run Time Type Information for the std::basic\_filebuf<char, std::char\_traits<char>> class is described by [Table 12-139](#)

**Table 12-139 typeinfo for basic\_filebuf<char, char\_traits<char>>**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for basic_filebuf<char, char_traits<char>>

### 12.1.85.2 Interfaces for Class basic\_filebuf<char, char\_traits<char>>

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_filebuf<char, std::char\_traits<char>> specified in [Table 12-140](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-140 libstdc++ - Class basic\_filebuf<char, char\_traits<char>> Function Interfaces**

basic_filebuf<char, char_traits<char>>::_M_set_buffer(long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char>>::_M_convert_to_external(char*, long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char>>::setbuf(char*, long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char>>::xsgetn(char*, long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char>>::xspputn(char const*, long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char>>::_M_seek(long, _Ios_Seekdir, __mbstate_t)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char>>::seekoff(long, _Ios_Seekdir, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

### 12.1.86 Class basic\_filebuf<wchar\_t, char\_traits<wchar\_t>>

#### 12.1.86.1 Class data for basic\_filebuf<wchar\_t, char\_traits<wchar\_t>>

The virtual table for the std::basic\_filebuf<wchar\_t, std::char\_traits<wchar\_t>> class is described by [Table 12-141](#)

**Table 12-141 Primary vtable for basic\_filebuf<wchar\_t, char\_traits<wchar\_t>>**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for basic_filebuf<wchar_t, char_traits<wchar_t>>

vfunc[0]:	basic_filebuf<wchar_t, char_traits<wchar_t>>::~basic_filebuf()
vfunc[1]:	basic_filebuf<wchar_t, char_traits<wchar_t>>::~basic_filebuf()
vfunc[2]:	basic_filebuf<wchar_t, char_traits<wchar_t>>::imbue(locale const&)
vfunc[3]:	basic_filebuf<wchar_t, char_traits<wchar_t>>::setbuf(wchar_t*, long)
vfunc[4]:	basic_filebuf<wchar_t, char_traits<wchar_t>>::seekoff(long, _Ios_Seekdir, _Ios_Openmode)
vfunc[5]:	basic_filebuf<wchar_t, char_traits<wchar_t>>::seekpos(fpos<__mbstate_t>, _Ios_Openmode)
vfunc[6]:	basic_filebuf<wchar_t, char_traits<wchar_t>>::sync()
vfunc[7]:	basic_filebuf<wchar_t, char_traits<wchar_t>>::showmanyc()
vfunc[8]:	basic_filebuf<wchar_t, char_traits<wchar_t>>::xsgetn(wchar_t*, long)
vfunc[9]:	basic_filebuf<wchar_t, char_traits<wchar_t>>::underflow()
vfunc[10]:	basic_streambuf<wchar_t, char_traits<wchar_t>>::uflow()
vfunc[11]:	basic_filebuf<wchar_t, char_traits<wchar_t>>::pbackfail(unsigned int)
vfunc[12]:	basic_filebuf<wchar_t, char_traits<wchar_t>>::xsputn(wchar_t const*, long)
vfunc[13]:	basic_filebuf<wchar_t, char_traits<wchar_t>>::overflow(unsigned int)

The Run Time Type Information for the std::basic\_filebuf<wchar\_t, std::char\_traits<wchar\_t>> class is described by [Table 12-142](#)

**Table 12-142 typeinfo for basic\_filebuf<wchar\_t, char\_traits<wchar\_t>>**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for basic_filebuf<wchar_t, char_traits<wchar_t>>

### 12.1.86.2 Interfaces for Class basic\_filebuf<wchar\_t, char\_traits<wchar\_t>>

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_filebuf<wchar\_t, std::char\_traits<wchar\_t>> specified in [Table 12-143](#),

with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-143 libstdc++ - Class `basic_filebuf<wchar_t, char_traits<wchar_t>` > Function Interfaces**

basic_filebuf<wchar_t, char_traits<wchar_t>>::_M_set_buffer(long) (GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_filebuf<wchar_t, char_traits<wchar_t>>::_M_convert_to_external(wchar_t*, long)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_filebuf<wchar_t, char_traits<wchar_t>>::setbuf(wchar_t*, long) (GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_filebuf<wchar_t, char_traits<wchar_t>>::xsgetn(wchar_t*, long) (GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_filebuf<wchar_t, char_traits<wchar_t>>::xsputn(wchar_t const*, long) (GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_filebuf<wchar_t, char_traits<wchar_t>>::_M_seek(long, _Ios_Seekdir, __mbstate_t)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_filebuf<wchar_t, char_traits<wchar_t>>::seekoff(long, _Ios_Seekdir, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::_M_write(wchar_t const*, long) (GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
virtual thunk to basic_fstream<wchar_t, char_traits<wchar_t>>::~basic_fstream() (GLIBCXX_3.4) <a href="#">[CXXABI-1.86]</a>

## 12.1.87 Class `ios_base`

### 12.1.87.1 Class data for `ios_base`

The virtual table for the `std::ios_base` class is described in the generic part of this specification.

The Run Time Type Information for the `std::ios_base` class is described by [Table 12-144](#)

**Table 12-144 typeinfo for `ios_base`**

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for <code>ios_base</code>

### 12.1.87.2 Interfaces for Class `ios_base`

No external methods are defined for libstdc++ - Class `std::ios_base` in this part of the specification. See also the generic specification.

## 12.1.88 Class `basic_ios<char, char_traits<char>>`

### 12.1.88.1 Class data for `basic_ios<char, char_traits<char>>`

The virtual table for the `std::basic_ios<char, std::char_traits<char>>` class is described in the generic part of this specification.

### 12.1.88.2 Interfaces for Class `basic_ios<char, char_traits<char>>`

No external methods are defined for libstdc++ - Class `std::basic_ios<char, std::char_traits<char>>` in this part of the specification. See also the generic specification.

## 12.1.89 Class `basic_ios<wchar_t, char_traits<wchar_t>>`

### 12.1.89.1 Class data for `basic_ios<wchar_t, char_traits<wchar_t>>`

The virtual table for the `std::basic_ios<wchar_t, std::char_traits<wchar_t>>` class is described in the generic part of this specification.

The Run Time Type Information for the `std::basic_ios<wchar_t, std::char_traits<wchar_t>>` class is described by [Table 12-145](#)

**Table 12-145 typeinfo for `basic_ios<wchar_t, char_traits<wchar_t>>`**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>	
Name	typeinfo name for <code>basic_ios&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code>	
flags:	8	
basetype:	typeinfo for <code>ios_base</code>	

### 12.1.89.2 Interfaces for Class `basic_ios<wchar_t, char_traits<wchar_t>>`

No external methods are defined for libstdcxx - Class `std::basic_ios<wchar_t, std::char_traits<wchar_t>>` in this part of the specification. See also the generic specification.

## 12.1.90 Class `ios_base::failure`

### 12.1.90.1 Class data for `ios_base::failure`

The virtual table for the `std::ios_base::failure` class is described in the generic part of this specification.

The Run Time Type Information for the `std::ios_base::failure` class is described by [Table 12-146](#)

**Table 12-146 typeinfo for `ios_base::failure`**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>ios_base::failure</code>

### 12.1.90.2 Interfaces for Class `ios_base::failure`

No external methods are defined for libstdcxx - Class `std::ios_base::failure` in this part of the specification. See also the generic specification.

## 12.1.91 Class `__timepunct<char>`

### 12.1.91.1 Class data for `__timepunct<char>`

The virtual table for the `std::__timepunct<char>` class is described in the generic part of this specification.

The Run Time Type Information for the `std::__timepunct<char>` class is described by [Table 12-147](#)

**Table 12-147 typeinfo for \_\_timepunct<char>**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for __timepunct<char>

### 12.1.91.2 Interfaces for Class \_\_timepunct<char>

An LSB conforming implementation shall provide the architecture specific methods for Class std::\_\_timepunct<char> specified in [Table 12-148](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-148 libstdc++ - Class \_\_timepunct<char> Function Interfaces**

__timepunct<char>::__M_put(char*, unsigned long, char const*, tm const*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
__timepunct<char>::__timepunct(__locale_struct*, char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
__timepunct<char>::__timepunct(__timepunct_cache<char>*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
__timepunct<char>::__timepunct(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
__timepunct<char>::__timepunct(__locale_struct*, char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
__timepunct<char>::__timepunct(__timepunct_cache<char>*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
__timepunct<char>::__timepunct(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

### 12.1.92 Class \_\_timepunct<wchar\_t>

#### 12.1.92.1 Class data for \_\_timepunct<wchar\_t>

The virtual table for the std::\_\_timepunct<wchar\_t> class is described in the generic part of this specification.

The Run Time Type Information for the std::\_\_timepunct<wchar\_t> class is described by [Table 12-149](#)

**Table 12-149 typeinfo for \_\_timepunct<wchar\_t>**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for __timepunct<wchar_t>

#### 12.1.92.2 Interfaces for Class \_\_timepunct<wchar\_t>

An LSB conforming implementation shall provide the architecture specific methods for Class std::\_\_timepunct<wchar\_t> specified in [Table 12-150](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-150 libstdc++ - Class \_\_timepunct<wchar\_t> Function Interfaces**

__timepunct<wchar_t>::__M_put(wchar_t*, unsigned long, wchar_t const*, tm const*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
__timepunct<wchar_t>::__timepunct(__locale_struct*, char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
__timepunct<wchar_t>::__timepunct(__timepunct_cache<wchar_t>*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
__timepunct<wchar_t>::__timepunct(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

<code>__timepunct&lt;wchar_t&gt;::__timepunct(__locale_struct*, char const*, unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>
<code>__timepunct&lt;wchar_t&gt;::__timepunct(__timepunct_cache&lt;wchar_t&gt;*, unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>
<code>__timepunct&lt;wchar_t&gt;::__timepunct(unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>

## 12.1.93 Class messages\_base

### 12.1.93.1 Class data for messages\_base

The Run Time Type Information for the std::messages\_base class is described by [Table 12-151](#)

**Table 12-151 typeinfo for messages\_base**

Base Vtable	vtable for <code>__cxxabiv1::__class_type_info</code>
Name	typeinfo name for messages_base

### 12.1.93.2 Interfaces for Class messages\_base

No external methods are defined for libstdcxx - Class std::messages\_base in this part of the specification. See also the generic specification.

## 12.1.94 Class messages<char>

### 12.1.94.1 Class data for messages<char>

The virtual table for the std::messages<char> class is described in the generic part of this specification.

### 12.1.94.2 Interfaces for Class messages<char>

An LSB conforming implementation shall provide the architecture specific methods for Class std::messages<char> specified in [Table 12-152](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-152 libstdcxx - Class messages<char> Function Interfaces**

<code>messages&lt;char&gt;::messages(__locale_struct*, char const*, unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>
<code>messages&lt;char&gt;::messages(unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>
<code>messages&lt;char&gt;::messages(__locale_struct*, char const*, unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>
<code>messages&lt;char&gt;::messages(unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>

## 12.1.95 Class messages<wchar\_t>

### 12.1.95.1 Class data for messages<wchar\_t>

The virtual table for the std::messages<wchar\_t> class is described in the generic part of this specification.

### 12.1.95.2 Interfaces for Class messages<wchar\_t>

An LSB conforming implementation shall provide the architecture specific methods for Class std::messages<wchar\_t> specified in [Table 12-153](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-153 libstdc++ - Class messages<wchar\_t> Function Interfaces**

messages<wchar_t>::messages(__locale_struct*, char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<wchar_t>::messages(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<wchar_t>::messages(__locale_struct*, char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<wchar_t>::messages(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 12.1.96 Class messages\_byname<char>

### 12.1.96.1 Class data for messages\_byname<char>

The virtual table for the std::messages\_byname<char> class is described in the generic part of this specification.

The Run Time Type Information for the std::messages\_byname<char> class is described by [Table 12-154](#)

**Table 12-154 typeinfo for messages\_byname<char>**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for messages_byname<char>

### 12.1.96.2 Interfaces for Class messages\_byname<char>

An LSB conforming implementation shall provide the architecture specific methods for Class std::messages\_byname<char> specified in [Table 12-155](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-155 libstdc++ - Class messages\_byname<char> Function Interfaces**

messages_byname<char>::messages_byname(char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages_byname<char>::messages_byname(char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 12.1.97 Class messages\_byname<wchar\_t>

### 12.1.97.1 Class data for messages\_byname<wchar\_t>

The virtual table for the std::messages\_byname<wchar\_t> class is described in the generic part of this specification.

The Run Time Type Information for the std::messages\_byname<wchar\_t> class is described by [Table 12-156](#)

**Table 12-156 typeinfo for messages\_byname<wchar\_t>**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for messages_byname<wchar_t>

### 12.1.97.2 Interfaces for Class messages\_byname<wchar\_t>

An LSB conforming implementation shall provide the architecture specific methods for Class std::messages\_byname<wchar\_t> specified in [Table 12-157](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-157 libstdc++ - Class messages\_byname<wchar\_t> Function Interfaces**

messages_byname<wchar_t>::messages_byname(char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages_byname<wchar_t>::messages_byname(char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 12.1.98 Class numpunct<char>

### 12.1.98.1 Class data for numpunct<char>

The virtual table for the std::numpunct<char> class is described in the generic part of this specification.

The Run Time Type Information for the std::numpunct<char> class is described by [Table 12-158](#)

**Table 12-158 typeinfo for numpunct<char>**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for numpunct<char>

### 12.1.98.2 Interfaces for Class numpunct<char>

An LSB conforming implementation shall provide the architecture specific methods for Class std::numpunct<char> specified in [Table 12-159](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-159 libstdc++ - Class numpunct<char> Function Interfaces**

numpunct<char>::numpunct(__locale_struct*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<char>::numpunct(__numpunct_cache<char>*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<char>::numpunct(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<char>::numpunct(__locale_struct*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<char>::numpunct(__numpunct_cache<char>*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<char>::numpunct(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 12.1.99 Class numpunct<wchar\_t>

### 12.1.99.1 Class data for numpunct<wchar\_t>

The virtual table for the std::numpunct<wchar\_t> class is described in the generic part of this specification.

The Run Time Type Information for the std::numpunct<wchar\_t> class is described by [Table 12-160](#)

**Table 12-160 typeinfo for numpunct<wchar\_t>**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for numpunct<wchar_t>

### 12.1.99.2 Interfaces for Class numpunct<wchar\_t>

An LSB conforming implementation shall provide the architecture specific methods for

Class std::numpunct<wchar\_t> specified in [Table 12-161](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-161 libstdcxx - Class numpunct<wchar\_t> Function Interfaces**

numpunct<wchar_t>::numpunct(__locale_struct*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<wchar_t>::numpunct(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<wchar_t>::numpunct(__locale_struct*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<wchar_t>::numpunct(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 12.1.100 Class numpunct\_byname<char>

### 12.1.100.1 Class data for numpunct\_byname<char>

The virtual table for the std::numpunct\_byname<char> class is described in the generic part of this specification.

The Run Time Type Information for the std::numpunct\_byname<char> class is described by [Table 12-162](#)

**Table 12-162 typeinfo for numpunct\_byname<char>**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for numpunct_byname<char>

### 12.1.100.2 Interfaces for Class numpunct\_byname<char>

An LSB conforming implementation shall provide the architecture specific methods for Class std::numpunct\_byname<char> specified in [Table 12-163](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-163 libstdcxx - Class numpunct\_byname<char> Function Interfaces**

numpunct_byname<char>::numpunct_byname(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct_byname<char>::numpunct_byname(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 12.1.101 Class numpunct\_byname<wchar\_t>

### 12.1.101.1 Class data for numpunct\_byname<wchar\_t>

The virtual table for the std::numpunct\_byname<wchar\_t> class is described in the generic part of this specification.

The Run Time Type Information for the std::numpunct\_byname<wchar\_t> class is described by [Table 12-164](#)

**Table 12-164 typeinfo for numpunct\_byname<wchar\_t>**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for numpunct_byname<wchar_t>

### 12.1.101.2 Interfaces for Class numpunct\_byname<wchar\_t>

An LSB conforming implementation shall provide the architecture specific methods for

Class std::numpunct\_byname<wchar\_t> specified in [Table 12-165](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-165 libstdcxx - Class numpunct\_byname<wchar\_t> Function Interfaces**

numpunct_byname<wchar_t>::numpunct_byname(char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
-----------------------------------------------------------------------------------------------------------------

numpunct_byname<wchar_t>::numpunct_byname(char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
-----------------------------------------------------------------------------------------------------------------

## **12.1.102 Class \_\_codecvt\_abstract\_base<char, char, \_\_mbstate\_t>**

### **12.1.102.1 Class data for \_\_codecvt\_abstract\_base<char, char, \_\_mbstate\_t>**

The virtual table for the std::\_\_codecvt\_abstract\_base<char, char, \_\_mbstate\_t> class is described in the generic part of this specification.

### **12.1.102.2 Interfaces for Class \_\_codecvt\_abstract\_base<char, char, \_\_mbstate\_t>**

No external methods are defined for libstdcxx - Class std::\_\_codecvt\_abstract\_base<char, char, \_\_mbstate\_t> in this part of the specification. See also the generic specification.

## **12.1.103 Class \_\_codecvt\_abstract\_base<wchar\_t, char, \_\_mbstate\_t>**

### **12.1.103.1 Class data for \_\_codecvt\_abstract\_base<wchar\_t, char, \_\_mbstate\_t>**

The virtual table for the std::\_\_codecvt\_abstract\_base<wchar\_t, char, \_\_mbstate\_t> class is described in the generic part of this specification.

### **12.1.103.2 Interfaces for Class \_\_codecvt\_abstract\_base<wchar\_t, char, \_\_mbstate\_t>**

No external methods are defined for libstdcxx - Class std::\_\_codecvt\_abstract\_base<wchar\_t, char, \_\_mbstate\_t> in this part of the specification. See also the generic specification.

## **12.1.104 Class codecvt\_base**

### **12.1.104.1 Class data for codecvt\_base**

The Run Time Type Information for the std::codecvt\_base class is described by [Table 12-166](#)

**Table 12-166 typeinfo for codecvt\_base**

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for codecvt_base

### **12.1.104.2 Interfaces for Class codecvt\_base**

No external methods are defined for libstdcxx - Class std::codecvt\_base in this part of the specification. See also the generic specification.

## 12.1.105 Class `codecvt<char, char, __mbstate_t>`

### 12.1.105.1 Class data for `codecvt<char, char, __mbstate_t>`

The virtual table for the `std::codecvt<char, char, __mbstate_t>` class is described by [Table 12-167](#)

**Table 12-167 Primary vtable for `codecvt<char, char, __mbstate_t>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>codecvt&lt;char, char, __mbstate_t&gt;</code>
vfunc[0]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::~codecvt()</code>
vfunc[1]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::~codecvt()</code>
vfunc[2]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_out(__mbstate_t&amp;, char const*, char const*, char const*&amp;, char*, char*, char*&amp;) const</code>
vfunc[3]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_unshift(__mbstate_t&amp;, char*, char*, char*) const</code>
vfunc[4]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_in(__mbstate_t&amp;, char const*, char const*, char const*&amp;, char*, char*, char*&amp;) const</code>
vfunc[5]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_encoding() const</code>
vfunc[6]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_always_noconv() const</code>
vfunc[7]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_length(__mbstate_t&amp;, char const*, char const*, unsigned long) const</code>
vfunc[8]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_max_length() const</code>

The Run Time Type Information for the `std::codecvt<char, char, __mbstate_t>` class is described by [Table 12-168](#)

**Table 12-168 typeinfo for `codecvt<char, char, __mbstate_t>`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>codecvt&lt;char, char, __mbstate_t&gt;</code>

### 12.1.105.2 Interfaces for Class `codecvt<char, char, __mbstate_t>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::codecvt<char, char, __mbstate_t>` specified in [Table 12-169](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-169 libstdc++ - Class codecvt<char, char, \_\_mbstate\_t> Function Interfaces**

codecvt<char, char, __mbstate_t>::do_length(__mbstate_t&, char const*, char const*, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
codecvt<char, char, __mbstate_t>::codecvt(__locale_struct*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
codecvt<char, char, __mbstate_t>::codecvt(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
codecvt<char, char, __mbstate_t>::codecvt(__locale_struct*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
codecvt<char, char, __mbstate_t>::codecvt(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 12.1.106 Class `codecvt<wchar_t, char, __mbstate_t>`

### 12.1.106.1 Class data for `codecvt<wchar_t, char, __mbstate_t>`

The virtual table for the std::codecvt<wchar\_t, char, \_\_mbstate\_t> class is described by [Table 12-170](#)

**Table 12-170 Primary vtable for `codecvt<wchar_t, char, __mbstate_t>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for codecvt<wchar_t, char, __mbstate_t>
vfunc[0]:	codecvt<wchar_t, char, __mbstate_t>::~codecvt()
vfunc[1]:	codecvt<wchar_t, char, __mbstate_t>::~codecvt()
vfunc[2]:	codecvt<wchar_t, char, __mbstate_t>::do_out(__mbstate_t&, wchar_t const*, wchar_t const*, wchar_t const*&, char*, char*&, char*&) const
vfunc[3]:	codecvt<wchar_t, char, __mbstate_t>::do_unshift(__mbstate_t&, char*, char*, char*&) const
vfunc[4]:	codecvt<wchar_t, char, __mbstate_t>::do_in(__mbstate_t&, char const*, char const*, char const*&, wchar_t*, wchar_t*, wchar_t*&) const
vfunc[5]:	codecvt<wchar_t, char, __mbstate_t>::do_encoding() const
vfunc[6]:	codecvt<wchar_t, char, __mbstate_t>::do_always_noconv() const
vfunc[7]:	codecvt<wchar_t, char, __mbstate_t>::do_length(__mbstate_t&, char const*, char const*, unsigned long) const
vfunc[8]:	codecvt<wchar_t, char, __mbstate_t>::do_max_length() const

The Run Time Type Information for the std::codecvt<wchar\_t, char, \_\_mbstate\_t> class

is described by [Table 12-171](#)

**Table 12-171 typeinfo for codecvt<wchar\_t, char, \_\_mbstate\_t>**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for codecvt<wchar_t, char, __mbstate_t>

### 12.1.106.2 Interfaces for Class `codecvt<wchar_t, char, __mbstate_t>`

An LSB conforming implementation shall provide the architecture specific methods for Class std::codecvt<wchar\_t, char, \_\_mbstate\_t> specified in [Table 12-172](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-172 libstdc++ - Class `codecvt<wchar_t, char, __mbstate_t>` Function Interfaces**

codecvt<wchar_t, char, __mbstate_t>::do_length(__mbstate_t&, char const*, char const*, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
codecvt<wchar_t, char, __mbstate_t>::codecvt(__locale_struct*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
codecvt<wchar_t, char, __mbstate_t>::codecvt(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
codecvt<wchar_t, char, __mbstate_t>::codecvt(__locale_struct*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
codecvt<wchar_t, char, __mbstate_t>::codecvt(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

### 12.1.107 Class `codecvt_byname<char, char, __mbstate_t>`

#### 12.1.107.1 Class data for `codecvt_byname<char, char, __mbstate_t>`

The virtual table for the std::codecvt\_byname<char, char, \_\_mbstate\_t> class is described by [Table 12-173](#)

**Table 12-173 Primary vtable for `codecvt_byname<char, char, __mbstate_t>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>codecvt_byname&lt;char, char, __mbstate_t&gt;</code>
vfunc[0]:	<code>codecvt_byname&lt;char, char, __mbstate_t&gt;::~codecvt_byname()</code>
vfunc[1]:	<code>codecvt_byname&lt;char, char, __mbstate_t&gt;::~codecvt_byname()</code>
vfunc[2]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_out(__mbstate_t&amp;, char const*, char const*, char const*&amp;, char*, char*&amp;) const</code>
vfunc[3]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_unshift(__mbstate_t&amp;, char*, char*, char*&amp;) const</code>
vfunc[4]:	<code>codecvt&lt;char, char,</code>

	<code>__mbstate_t&gt;::do_in(__mbstate_t&amp;, char const*, char const*, char const*&amp;, char*, char*, char*) const</code>
vfunc[5]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_encoding() const</code>
vfunc[6]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_always_noconv() const</code>
vfunc[7]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_length(__mbstate_t&amp;, char const*, char const*, unsigned long) const</code>
vfunc[8]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_max_length() const</code>

The Run Time Type Information for the `std::codecvt_byname<char, char, __mbstate_t>` class is described by [Table 12-174](#)

**Table 12-174 typeinfo for `codecvt_byname<char, char, __mbstate_t>`**

Base Vtable	vtable for <code>_cxxabiv1::_si_class_type_info</code>
Name	typeinfo name for <code>codecvt_byname&lt;char, char, __mbstate_t&gt;</code>

### 12.1.107.2 Interfaces for Class `codecvt_byname<char, char, __mbstate_t>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::codecvt_byname<char, char, __mbstate_t>` specified in [Table 12-175](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-175 libstdc++ - Class `codecvt_byname<char, char, __mbstate_t>` Function Interfaces**

<code>codecvt_byname&lt;char, char, __mbstate_t&gt;::codecvt_byname(char const*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>codecvt_byname&lt;char, char, __mbstate_t&gt;::codecvt_byname(char const*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

### 12.1.108 Class `codecvt_byname<wchar_t, char, __mbstate_t>`

#### 12.1.108.1 Class data for `codecvt_byname<wchar_t, char, __mbstate_t>`

The virtual table for the `std::codecvt_byname<wchar_t, char, __mbstate_t>` class is described by [Table 12-176](#)

**Table 12-176 Primary vtable for `codecvt_byname<wchar_t, char, __mbstate_t>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>codecvt_byname&lt;wchar_t, char, __mbstate_t&gt;</code>
vfunc[0]:	<code>codecvt_byname&lt;wchar_t, char,</code>

	<code>__mbstate_t&gt;::~codecvt_byname()</code>
vfunc[1]:	<code>codecvt_byname&lt;wchar_t, char, __mbstate_t&gt;::~codecvt_byname()</code>
vfunc[2]:	<code>codecvt&lt;wchar_t, char, __mbstate_t&gt;::do_out(__mbstate_t&amp;, wchar_t const*, wchar_t const*, wchar_t const*&amp;, char*, char*, char*&amp;) const</code>
vfunc[3]:	<code>codecvt&lt;wchar_t, char, __mbstate_t&gt;::do_unshift(__mbstate_t&amp;, char*, char*, char*&amp;) const</code>
vfunc[4]:	<code>codecvt&lt;wchar_t, char, __mbstate_t&gt;::do_in(__mbstate_t&amp;, char const*, char const*, char const*&amp;, wchar_t*, wchar_t*, wchar_t*&amp;) const</code>
vfunc[5]:	<code>codecvt&lt;wchar_t, char, __mbstate_t&gt;::do_encoding() const</code>
vfunc[6]:	<code>codecvt&lt;wchar_t, char, __mbstate_t&gt;::do_always_noconv() const</code>
vfunc[7]:	<code>codecvt&lt;wchar_t, char, __mbstate_t&gt;::do_length(__mbstate_t&amp;, char const*, char const*, unsigned long) const</code>
vfunc[8]:	<code>codecvt&lt;wchar_t, char, __mbstate_t&gt;::do_max_length() const</code>

The Run Time Type Information for the `std::codecvt_byname<wchar_t, char, __mbstate_t>` class is described by [Table 12-177](#)

**Table 12-177 typeinfo for `codecvt_byname<wchar_t, char, __mbstate_t>`**

Base Vtable	vtable for <code>_cxxabiv1::_si_class_type_info</code>
Name	typeinfo name for <code>codecvt_byname&lt;wchar_t, char, __mbstate_t&gt;</code>

### 12.1.108.2 Interfaces for Class `codecvt_byname<wchar_t, char, __mbstate_t>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::codecvt_byname<wchar_t, char, __mbstate_t>` specified in [Table 12-178](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-178 libstdc++ - Class `codecvt_byname<wchar_t, char, __mbstate_t>` Function Interfaces**

<code>codecvt_byname&lt;wchar_t, char, __mbstate_t&gt;::codecvt_byname(char const*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>codecvt_byname&lt;wchar_t, char, __mbstate_t&gt;::codecvt_byname(char const*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

## 12.1.109 Class `collate<char>`

### 12.1.109.1 Class data for `collate<char>`

The virtual table for the `std::collate<char>` class is described in the generic part of this specification.

The Run Time Type Information for the `std::collate<char>` class is described by [Table 12-179](#)

**Table 12-179 typeinfo for `collate<char>`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>collate&lt;char&gt;</code>

### 12.1.109.2 Interfaces for Class `collate<char>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::collate<char>` specified in [Table 12-180](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-180 libstdc++ - Class `collate<char>` Function Interfaces**

<code>collate&lt;char&gt;::_M_transform(char*, char const*, unsigned long)</code> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>collate&lt;char&gt;::collate(__locale_struct*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>collate&lt;char&gt;::collate(unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>collate&lt;char&gt;::collate(__locale_struct*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>collate&lt;char&gt;::collate(unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

## 12.1.110 Class `collate<wchar_t>`

### 12.1.110.1 Class data for `collate<wchar_t>`

The virtual table for the `std::collate<wchar_t>` class is described in the generic part of this specification.

The Run Time Type Information for the `std::collate<wchar_t>` class is described by [Table 12-181](#)

**Table 12-181 typeinfo for `collate<wchar_t>`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>collate&lt;wchar_t&gt;</code>

### 12.1.110.2 Interfaces for Class `collate<wchar_t>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::collate<wchar_t>` specified in [Table 12-182](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-182 libstdc++ - Class `collate<wchar_t>` Function Interfaces**

<code>collate&lt;wchar_t&gt;::_M_transform(wchar_t*, wchar_t const*, unsigned long)</code> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>collate&lt;wchar_t&gt;::collate(__locale_struct*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>collate&lt;wchar_t&gt;::collate(unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>collate&lt;wchar_t&gt;::collate(__locale_struct*, unsigned long)(GLIBCXX_3.4)</code>

<a href="#">[ISOCXX]</a>
--------------------------

collate<wchar_t>::collate(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
--------------------------------------------------------------------------------

## 12.1.111 Class `collate_byname<char>`

### 12.1.111.1 Class data for `collate_byname<char>`

The virtual table for the std::collate\_byname<char> class is described in the generic part of this specification.

The Run Time Type Information for the std::collate\_byname<char> class is described by [Table 12-183](#)

**Table 12-183 typeinfo for `collate_byname<char>`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>collate_byname&lt;char&gt;</code>

### 12.1.111.2 Interfaces for Class `collate_byname<char>`

An LSB conforming implementation shall provide the architecture specific methods for Class std::collate\_byname<char> specified in [Table 12-184](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-184 libstdc++ - Class `collate_byname<char>` Function Interfaces**

collate_byname<char>::collate_byname(char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
------------------------------------------------------------------------------------------------------------

collate_byname<char>::collate_byname(char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
------------------------------------------------------------------------------------------------------------

## 12.1.112 Class `collate_byname<wchar_t>`

### 12.1.112.1 Class data for `collate_byname<wchar_t>`

The virtual table for the std::collate\_byname<wchar\_t> class is described in the generic part of this specification.

The Run Time Type Information for the std::collate\_byname<wchar\_t> class is described by [Table 12-185](#)

**Table 12-185 typeinfo for `collate_byname<wchar_t>`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>collate_byname&lt;wchar_t&gt;</code>

### 12.1.112.2 Interfaces for Class `collate_byname<wchar_t>`

An LSB conforming implementation shall provide the architecture specific methods for Class std::collate\_byname<wchar\_t> specified in [Table 12-186](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-186 libstdc++ - Class `collate_byname<wchar_t>` Function Interfaces**

collate_byname<wchar_t>::collate_byname(char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
---------------------------------------------------------------------------------------------------------------

collate_byname<wchar_t>::collate_byname(char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
---------------------------------------------------------------------------------------------------------------

## 12.1.113 Class time\_base

### 12.1.113.1 Class data for time\_base

The Run Time Type Information for the std::time\_base class is described by [Table 12-187](#)

**Table 12-187 typeinfo for time\_base**

Base Vtable	vtable for _cxxabiv1::__class_type_info
Name	typeinfo name for time_base

### 12.1.113.2 Interfaces for Class time\_base

No external methods are defined for libstdcxx - Class std::time\_base in this part of the specification. See also the generic specification.

## 12.1.114 Class time\_get\_byname<char, istreambuf\_iterator<char, char\_traits<char>>>

### 12.1.114.1 Class data for time\_get\_byname<char, istreambuf\_iterator<char, char\_traits<char>>>

The virtual table for the std::time\_get\_byname<char, std::istreambuf\_iterator<char, std::char\_traits<char>>> class is described in the generic part of this specification.

The Run Time Type Information for the std::time\_get\_byname<char, std::istreambuf\_iterator<char, std::char\_traits<char>>> class is described by [Table 12-188](#)

**Table 12-188 typeinfo for time\_get\_byname<char, istreambuf\_iterator<char, char\_traits<char>>>**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for time_get_byname<char, istreambuf_iterator<char, char_traits<char>>>

### 12.1.114.2 Interfaces for Class time\_get\_byname<char, istreambuf\_iterator<char, char\_traits<char>>>

An LSB conforming implementation shall provide the architecture specific methods for Class std::time\_get\_byname<char, std::istreambuf\_iterator<char, std::char\_traits<char>>> specified in [Table 12-189](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-189 libstdcxx - Class time\_get\_byname<char, istreambuf\_iterator<char, char\_traits<char>>> Function Interfaces**

time_get_byname<char, istreambuf_iterator<char, char_traits<char>>>::time_get_byname(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
time_get_byname<char, istreambuf_iterator<char, char_traits<char>>>::time_get_byname(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## **12.1.115 Class `time_get_byname<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>`**

### **12.1.115.1 Class data for `time_get_byname<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>`**

The virtual table for the `std::time_get_byname<wchar_t, std::istreambuf_iterator<wchar_t, std::char_traits<wchar_t>>` class is described in the generic part of this specification.

The Run Time Type Information for the `std::time_get_byname<wchar_t, std::istreambuf_iterator<wchar_t, std::char_traits<wchar_t>>` class is described by [Table 12-190](#)

**Table 12-190 typeinfo for `time_get_byname<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>time_get_byname&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code>

### **12.1.115.2 Interfaces for Class `time_get_byname<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>`**

An LSB conforming implementation shall provide the architecture specific methods for Class `std::time_get_byname<wchar_t, std::istreambuf_iterator<wchar_t, std::char_traits<wchar_t>>` specified in [Table 12-191](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-191 libstdcxx - Class `time_get_byname<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>` Function Interfaces**

<code>time_get_byname&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::time_get_byname(char const*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>time_get_byname&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::time_get_byname(char const*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

## **12.1.116 Class `time_put_byname<char, ostreambuf_iterator<char, char_traits<char>>`**

### **12.1.116.1 Class data for `time_put_byname<char, ostreambuf_iterator<char, char_traits<char>>`**

The virtual table for the `std::time_put_byname<char, std::ostreambuf_iterator<char, std::char_traits<char>>` class is described in the generic part of this specification.

The Run Time Type Information for the `std::time_put_byname<char, std::ostreambuf_iterator<char, std::char_traits<char>>` class is described by [Table 12-192](#)

**Table 12-192 typeinfo for `time_put_byname<char, ostreambuf_iterator<char, char_traits<char>>`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>time_put_byname&lt;char,</code>

	ostreambuf_iterator<char, char_traits<char> > >
--	----------------------------------------------------

### 12.1.116.2 Interfaces for Class `time_put_byname<char, ostreambuf_iterator<char, char_traits<char> > >`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::time_put_byname<char, std::ostreambuf_iterator<char, std::char_traits<char> > >` specified in [Table 12-193](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-193 libstdc++ - Class `time_put_byname<char, ostreambuf_iterator<char, char_traits<char> > >` Function Interfaces**

time_put_byname<char, ostreambuf_iterator<char, char_traits<char> > >::time_put_byname(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
time_put_byname<char, ostreambuf_iterator<char, char_traits<char> > >::time_put_byname(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

### 12.1.117 Class `time_put_byname<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> > >`

#### 12.1.117.1 Class data for `time_put_byname<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> > >`

The virtual table for the `std::time_put_byname<wchar_t, std::ostreambuf_iterator<wchar_t, std::char_traits<wchar_t> > >` class is described in the generic part of this specification.

The Run Time Type Information for the `std::time_put_byname<wchar_t, std::ostreambuf_iterator<wchar_t, std::char_traits<wchar_t> > >` class is described by [Table 12-194](#)

**Table 12-194 typeinfo for `time_put_byname<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> > >`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>time_put_byname&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;</code>

#### 12.1.117.2 Interfaces for Class `time_put_byname<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> > >`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::time_put_byname<wchar_t, std::ostreambuf_iterator<wchar_t, std::char_traits<wchar_t> > >` specified in [Table 12-195](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-195 libstdc++ - Class `time_put_byname<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> > >` Function Interfaces**

time_put_byname<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> > >::time_put_byname(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
time_put_byname<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> > >::time_put_byname(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 12.1.118 Class `time_get<char, istreambuf_iterator<char, char_traits<char>>>`

### 12.1.118.1 Class data for `time_get<char, istreambuf_iterator<char, char_traits<char>>>`

The virtual table for the `std::time_get<char, std::istreambuf_iterator<char, std::char_traits<char>>>` class is described in the generic part of this specification.

### 12.1.118.2 Interfaces for Class `time_get<char, istreambuf_iterator<char, char_traits<char>>>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::time_get<char, std::istreambuf_iterator<char, std::char_traits<char>>>` specified in [Table 12-196](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-196 libstdc++ - Class `time_get<char, istreambuf_iterator<char, char_traits<char>>>` Function Interfaces**

<code>time_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;::_M_extract_num(istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, int&amp;, int, int, unsigned long, ios_base&amp;, _Ios_Iostate&amp;) const(GLIBCXX_3.4)</code> <a href="#">[ISO CXX]</a>
<code>time_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;::_M_extract_name(istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, int&amp;, char const**, unsigned long, ios_base&amp;, _Ios_Iostate&amp;) const(GLIBCXX_3.4)</code> <a href="#">[ISO CXX]</a>
<code>time_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;::time_get(unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISO CXX]</a>
<code>time_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;::time_get(unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISO CXX]</a>

## 12.1.119 Class `time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>`

### 12.1.119.1 Class data for `time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>`

The virtual table for the `std::time_get<wchar_t, std::istreambuf_iterator<wchar_t, std::char_traits<wchar_t>>>` class is described in the generic part of this specification.

### 12.1.119.2 Interfaces for Class `time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::time_get<wchar_t, std::istreambuf_iterator<wchar_t, std::char_traits<wchar_t>>>` specified in [Table 12-197](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-197 libstdc++ - Class `time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>` Function Interfaces**

<code>time_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;::_M_extract_num(istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, int&amp;, int, int, unsigned long, ios_base&amp;, _Ios_Iostate&amp;) const(GLIBCXX_3.4)</code> <a href="#">[ISO CXX]</a>
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>> >::_M_extract_name(istreambuf_iterator<wchar_t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, int&, wchar_t const**, unsigned long, ios_base&, _Ios_Iostate&) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>> >::time_get(unsigned long)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
-------------------------------------------------------------------------------------------------------------------------------------------

time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>> >::time_get(unsigned long)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
-------------------------------------------------------------------------------------------------------------------------------------------

## 12.1.120 Class time\_put<char, ostreambuf\_iterator<char, char\_traits<char>>>

### 12.1.120.1 Class data for time\_put<char, ostreambuf\_iterator<char, char\_traits<char>>>

The virtual table for the std::time\_put<char, std::ostreambuf\_iterator<char, std::char\_traits<char>>> class is described in the generic part of this specification.

The Run Time Type Information for the std::time\_put<char, std::ostreambuf\_iterator<char, std::char\_traits<char>>> class is described by [Table 12-198](#)

**Table 12-198 typeinfo for time\_put<char, ostreambuf\_iterator<char, char\_traits<char>>>**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info	
Name	typeinfo name for time_put<char, ostreambuf_iterator<char, char_traits<char>>>	
flags:	8	
basetype:	typeinfo for locale::facet	2
basetype:	typeinfo for time_base	2

### 12.1.120.2 Interfaces for Class time\_put<char, ostreambuf\_iterator<char, char\_traits<char>>>

An LSB conforming implementation shall provide the architecture specific methods for Class std::time\_put<char, std::ostreambuf\_iterator<char, std::char\_traits<char>>> specified in [Table 12-199](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-199 libstdc++ - Class time\_put<char, ostreambuf\_iterator<char, char\_traits<char>>> Function Interfaces**

time_put<char, ostreambuf_iterator<char, char_traits<char>>>::time_put(unsigned long)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
------------------------------------------------------------------------------------------------------------------------------

time_put<char, ostreambuf_iterator<char, char_traits<char>>>::time_put(unsigned long)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
------------------------------------------------------------------------------------------------------------------------------

## 12.1.121 Class `time_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>`

>

### 12.1.121.1 Class data for `time_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>`

The virtual table for the `std::time_put<wchar_t, std::ostreambuf_iterator<wchar_t, std::char_traits<wchar_t>>>` class is described in the generic part of this specification.

The Run Time Type Information for the `std::time_put<wchar_t, std::ostreambuf_iterator<wchar_t, std::char_traits<wchar_t>>>` class is described by [Table 12-200](#)

**Table 12-200 typeinfo for `time_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>`**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>	
Name	typeinfo name for <code>time_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;</code>	
flags:	8	
basetype:	typeinfo for <code>locale::facet</code>	2
basetype:	typeinfo for <code>time_base</code>	2

### 12.1.121.2 Interfaces for Class `time_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::time_put<wchar_t, std::ostreambuf_iterator<wchar_t, std::char_traits<wchar_t>>>` specified in [Table 12-201](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-201 libstdc++ - Class `time_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>` Function Interfaces**

<code>time_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;::time_put(unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>time_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;::time_put(unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

## 12.1.122 Class `moneypunct<char, false>`

### 12.1.122.1 Class data for `moneypunct<char, false>`

The virtual table for the `std::moneypunct<char, false>` class is described in the generic part of this specification.

### 12.1.122.2 Interfaces for Class `moneypunct<char, false>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::moneypunct<char, false>` specified in [Table 12-202](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-202 libstdc++ - Class `moneypunct<char, false>` Function Interfaces**

<code>moneypunct&lt;char, false&gt;::moneypunct(__locale_struct*, char const*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>moneypunct&lt;char, false&gt;::moneypunct(__moneypunct_cache&lt;char, false&gt;*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>moneypunct&lt;char, false&gt;::moneypunct(unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>moneypunct&lt;char, false&gt;::moneypunct(__locale_struct*, char const*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>moneypunct&lt;char, false&gt;::moneypunct(__moneypunct_cache&lt;char, false&gt;*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>moneypunct&lt;char, false&gt;::moneypunct(unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

## 12.1.123 Class `moneypunct<char, true>`

### 12.1.123.1 Class data for `moneypunct<char, true>`

The virtual table for the `std::moneypunct<char, true>` class is described in the generic part of this specification.

### 12.1.123.2 Interfaces for Class `moneypunct<char, true>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::moneypunct<char, true>` specified in [Table 12-203](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-203 libstdc++ - Class `moneypunct<char, true>` Function Interfaces**

<code>moneypunct&lt;char, true&gt;::moneypunct(__locale_struct*, char const*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>moneypunct&lt;char, true&gt;::moneypunct(__moneypunct_cache&lt;char, true&gt;*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>moneypunct&lt;char, true&gt;::moneypunct(unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>moneypunct&lt;char, true&gt;::moneypunct(__locale_struct*, char const*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>moneypunct&lt;char, true&gt;::moneypunct(__moneypunct_cache&lt;char, true&gt;*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>moneypunct&lt;char, true&gt;::moneypunct(unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

## 12.1.124 Class `moneypunct<wchar_t, false>`

### 12.1.124.1 Class data for `moneypunct<wchar_t, false>`

The virtual table for the `std::moneypunct<wchar_t, false>` class is described in the generic part of this specification.

### 12.1.124.2 Interfaces for Class `moneypunct<wchar_t, false>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::moneypunct<wchar_t, false>` specified in [Table 12-204](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-204 libstdc++ - Class `moneypunct<wchar_t, false>` Function Interfaces**

<code>moneypunct&lt;wchar_t, false&gt;::moneypunct(__locale_struct*, char const*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>moneypunct&lt;wchar_t, false&gt;::moneypunct(__moneypunct_cache&lt;wchar_t, false&gt;*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

moneypunct<wchar_t, false>::moneypunct(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, false>::moneypunct(__locale_struct*, char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, false>::moneypunct(__moneypunct_cache<wchar_t, false>*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, false>::moneypunct(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 12.1.125 Class `moneypunct<wchar_t, true>`

### 12.1.125.1 Class data for `moneypunct<wchar_t, true>`

The virtual table for the `std::moneypunct<wchar_t, true>` class is described in the generic part of this specification.

### 12.1.125.2 Interfaces for Class `moneypunct<wchar_t, true>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::moneypunct<wchar_t, true>` specified in [Table 12-205](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-205 libstdcxx - Class `moneypunct<wchar_t, true>` Function Interfaces**

moneypunct<wchar_t, true>::moneypunct(__locale_struct*, char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true>::moneypunct(__moneypunct_cache<wchar_t, true>*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true>::moneypunct(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true>::moneypunct(__locale_struct*, char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true>::moneypunct(__moneypunct_cache<wchar_t, true>*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true>::moneypunct(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 12.1.126 Class `moneypunct_byname<char, false>`

### 12.1.126.1 Class data for `moneypunct_byname<char, false>`

The virtual table for the `std::moneypunct_byname<char, false>` class is described in the generic part of this specification.

The Run Time Type Information for the `std::moneypunct_byname<char, false>` class is described by [Table 12-206](#)

**Table 12-206 typeinfo for `moneypunct_byname<char, false>`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>moneypunct_byname&lt;char, false&gt;</code>

### 12.1.126.2 Interfaces for Class `moneypunct_byname<char, false>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::moneypunct_byname<char, false>` specified in [Table 12-207](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-207 libstdc++ - Class moneypunct\_byname<char, false> Function Interfaces**

moneypunct_byname<char, false>::moneypunct_byname(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
---------------------------------------------------------------------------------------------------------------------

moneypunct_byname<char, false>::moneypunct_byname(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
---------------------------------------------------------------------------------------------------------------------

## 12.1.127 Class moneypunct\_byname<char, true>

### 12.1.127.1 Class data for moneypunct\_byname<char, true>

The virtual table for the std::moneypunct\_byname<char, true> class is described in the generic part of this specification.

The Run Time Type Information for the std::moneypunct\_byname<char, true> class is described by [Table 12-208](#)

**Table 12-208 typeinfo for moneypunct\_byname<char, true>**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for moneypunct_byname<char, true>

### 12.1.127.2 Interfaces for Class moneypunct\_byname<char, true>

An LSB conforming implementation shall provide the architecture specific methods for Class std::moneypunct\_byname<char, true> specified in [Table 12-209](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-209 libstdc++ - Class moneypunct\_byname<char, true> Function Interfaces**

moneypunct_byname<char, true>::moneypunct_byname(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
--------------------------------------------------------------------------------------------------------------------

moneypunct_byname<char, true>::moneypunct_byname(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
--------------------------------------------------------------------------------------------------------------------

## 12.1.128 Class moneypunct\_byname<wchar\_t, false>

### 12.1.128.1 Class data for moneypunct\_byname<wchar\_t, false>

The virtual table for the std::moneypunct\_byname<wchar\_t, false> class is described in the generic part of this specification.

The Run Time Type Information for the std::moneypunct\_byname<wchar\_t, false> class is described by [Table 12-210](#)

**Table 12-210 typeinfo for moneypunct\_byname<wchar\_t, false>**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for moneypunct_byname<wchar_t, false>

### 12.1.128.2 Interfaces for Class moneypunct\_byname<wchar\_t, false>

An LSB conforming implementation shall provide the architecture specific methods for Class std::moneypunct\_byname<wchar\_t, false> specified in [Table 12-211](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-211 libstdc++ - Class moneypunct\_byname<wchar\_t, false> Function Interfaces**

moneypunct_byname<wchar_t, false>::moneypunct_byname(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct_byname<wchar_t, false>::moneypunct_byname(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 12.1.129 Class moneypunct\_byname<wchar\_t, true>

### 12.1.129.1 Class data for moneypunct\_byname<wchar\_t, true>

The virtual table for the std::moneypunct\_byname<wchar\_t, true> class is described in the generic part of this specification.

The Run Time Type Information for the std::moneypunct\_byname<wchar\_t, true> class is described by [Table 12-212](#)

**Table 12-212 typeinfo for moneypunct\_byname<wchar\_t, true>**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for moneypunct_byname<wchar_t, true>

### 12.1.129.2 Interfaces for Class moneypunct\_byname<wchar\_t, true>

An LSB conforming implementation shall provide the architecture specific methods for Class std::moneypunct\_byname<wchar\_t, true> specified in [Table 12-213](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-213 libstdc++ - Class moneypunct\_byname<wchar\_t, true> Function Interfaces**

moneypunct_byname<wchar_t, true>::moneypunct_byname(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct_byname<wchar_t, true>::moneypunct_byname(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 12.1.130 Class money\_base

### 12.1.130.1 Class data for money\_base

The Run Time Type Information for the std::money\_base class is described by [Table 12-214](#)

**Table 12-214 typeinfo for money\_base**

Base Vtable	vtable for <code>_cxxabiv1::__class_type_info</code>
Name	typeinfo name for money_base

### 12.1.130.2 Interfaces for Class money\_base

No external methods are defined for libstdc++ - Class std::money\_base in this part of the specification. See also the generic specification.

## 12.1.131 Class `money_get<char, istreambuf_iterator<char, char_traits<char>>>`

### 12.1.131.1 Class data for `money_get<char, istreambuf_iterator<char, char_traits<char>>>`

The virtual table for the `std::money_get<char, std::istreambuf_iterator<char, std::char_traits<char>>>` class is described in the generic part of this specification.

The Run Time Type Information for the `std::money_get<char, std::istreambuf_iterator<char, std::char_traits<char>>>` class is described by [Table 12-215](#)

**Table 12-215 typeinfo for `money_get<char, istreambuf_iterator<char, char_traits<char>>>`**

Base Vtable	vtable for <code>_cxxabiv1::_si_class_type_info</code>
Name	typeinfo name for <code>money_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;</code>

### 12.1.131.2 Interfaces for Class `money_get<char, istreambuf_iterator<char, char_traits<char>>>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::money_get<char, std::istreambuf_iterator<char, std::char_traits<char>>>` specified in [Table 12-216](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-216 libstdcxx - Class `money_get<char, istreambuf_iterator<char, char_traits<char>>>` Function Interfaces**

<code>istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; __gnu_cxx_ldbl128::money_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;::__M_extract&lt;false&gt;(istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, ios_base&amp;, _Ios_Iostate&amp;, basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;&amp;)</code> const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
<code>istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; __gnu_cxx_ldbl128::money_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;::__M_extract&lt;true&gt;(istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, ios_base&amp;, _Ios_Iostate&amp;, basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;&amp;)</code> const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
<code>__gnu_cxx_ldbl128::money_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;::get(istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, bool, ios_base&amp;, _Ios_Iostate&amp;, basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;&amp;)</code> const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
<code>__gnu_cxx_ldbl128::money_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;::get(istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, bool, ios_base&amp;, _Ios_Iostate&amp;, __float128&amp;)</code> const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
<code>__gnu_cxx_ldbl128::money_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;::money_get(unsigned long)(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>
<code>__gnu_cxx_ldbl128::money_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;::money_get(unsigned long)(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>
<code>money_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;</code>

>::money_get(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
-------------------------------------------------------------------

money_get<char, istreambuf_iterator<char, char_traits<char>> >::money_get(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
-----------------------------------------------------------------------------------------------------------------------------------

An LSB conforming implementation shall provide the architecture specific data interfaces for Class std::money\_get<char, std::istreambuf\_iterator<char, std::char\_traits<char>>> specified in [Table 12-217](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-217 libstdcxx - Class money\_get<char, istreambuf\_iterator<char, char\_traits<char>>> Data Interfaces**

typeinfo for __gnu_cxx_ldbl128::money_get<char, istreambuf_iterator<char, char_traits<char>>>(GLIBCXX_LDBL_3.4) <a href="#">[CXXABI-1.86]</a>
-----------------------------------------------------------------------------------------------------------------------------------------------

typeinfo name for __gnu_cxx_ldbl128::money_get<char, istreambuf_iterator<char, char_traits<char>>>(GLIBCXX_LDBL_3.4) <a href="#">[CXXABI-1.86]</a>
----------------------------------------------------------------------------------------------------------------------------------------------------

### 12.1.132 Class money\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>>

#### 12.1.132.1 Class data for money\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>>

The virtual table for the std::money\_get<wchar\_t, std::istreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t>>> class is described in the generic part of this specification.

The Run Time Type Information for the std::money\_get<wchar\_t, std::istreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t>>> class is described by [Table 12-218](#)

**Table 12-218 typeinfo for money\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>>**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>

#### 12.1.132.2 Interfaces for Class money\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>>

An LSB conforming implementation shall provide the architecture specific methods for Class std::money\_get<wchar\_t, std::istreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t>>> specified in [Table 12-219](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-219 libstdcxx - Class money\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>> Function Interfaces**

istreambuf_iterator<wchar_t, char_traits<wchar_t>>> __gnu_cxx_ldbl128::money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>::_M_extract<false>(istreambuf_iterator<wchar_t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, _Ios_Iostate&, basic_string<char, char_traits<char>, allocator<char>>&) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

istreambuf_iterator<wchar_t, char_traits<wchar_t>>> __gnu_cxx_ldbl128::money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>::_M_extract<true>(istreambuf_iterator<wchar_t,
-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

char_traits<wchar_t>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, _Ios_Iostate&, basic_string<char, char_traits<char>, allocator<char>>&) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
__gnu_cxx_ldbl128::money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>::get(istreambuf_iterator<wchar_t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, bool, ios_base&, _Ios_Iostate&, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>&) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
__gnu_cxx_ldbl128::money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>::get(istreambuf_iterator<wchar_t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, bool, ios_base&, _Ios_Iostate&, __float128&) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
__gnu_cxx_ldbl128::money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>::do_get(istreambuf_iterator<wchar_t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, bool, ios_base&, _Ios_Iostate&, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>&) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
__gnu_cxx_ldbl128::money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>::do_get(istreambuf_iterator<wchar_t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, bool, ios_base&, _Ios_Iostate&, __float128&) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
__gnu_cxx_ldbl128::money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>::__do_get(istreambuf_iterator<wchar_t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, bool, ios_base&, _Ios_Iostate&, double&) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
__gnu_cxx_ldbl128::money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>::money_get(unsigned long)(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
__gnu_cxx_ldbl128::money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>::money_get(unsigned long)(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
__gnu_cxx_ldbl128::money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>::~money_get()(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
__gnu_cxx_ldbl128::money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>::~money_get()(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
__gnu_cxx_ldbl128::money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>::~money_get()(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>::money_get(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>::money_get(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the architecture specific data interfaces for Class std::money\_get<wchar\_t, std::istreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t>>> specified in [Table 12-220](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-220 libstdc++ - Class money\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>> Data Interfaces**

typeinfo for __gnu_cxx_ldbl128::money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>(GLIBCXX_LDBL_3.4) <a href="#">[CXXABI-1.86]</a>
typeinfo name for __gnu_cxx_ldbl128::money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>(GLIBCXX_LDBL_3.4) <a href="#">[CXXABI-1.86]</a>
vtable for __gnu_cxx_ldbl128::money_get<wchar_t, istreambuf_iterator<wchar_t,

char_traits<wchar_t> >>(GLIBCXX_LDBL_3.4) <a href="#">[CXXABI-1.86]</a>
-------------------------------------------------------------------------

## 12.1.133 Class `money_put<char, ostreambuf_iterator<char, char_traits<char> > >`

### 12.1.133.1 Class data for `money_put<char, ostreambuf_iterator<char, char_traits<char> > >`

The virtual table for the `std::money_put<char, std::ostreambuf_iterator<char, std::char_traits<char> > >` class is described in the generic part of this specification.

The Run Time Type Information for the `std::money_put<char, std::ostreambuf_iterator<char, std::char_traits<char> > >` class is described by [Table 12-221](#)

**Table 12-221 typeinfo for `money_put<char, ostreambuf_iterator<char, char_traits<char> > >`**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;</code>

### 12.1.133.2 Interfaces for Class `money_put<char, ostreambuf_iterator<char, char_traits<char> > >`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::money_put<char, std::ostreambuf_iterator<char, std::char_traits<char> > >` specified in [Table 12-222](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-222 libstdcxx - Class `money_put<char, ostreambuf_iterator<char, char_traits<char> > >` Function Interfaces**

<code>__gnu_cxx_ldbl128::money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::put(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, bool, ios_base&amp;, char, basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt; const&amp;)</code> const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
<code>__gnu_cxx_ldbl128::money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::put(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, bool, ios_base&amp;, char, float128) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
<code>__gnu_cxx_ldbl128::money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::do_put(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, bool, ios_base&amp;, char, basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt; const&amp;)</code> const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
<code>__gnu_cxx_ldbl128::money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::do_put(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, bool, ios_base&amp;, char, float128) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
<code>__gnu_cxx_ldbl128::money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::_do_put(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, bool, ios_base&amp;, char, double) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
<code>ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;</code> <code>__gnu_cxx_ldbl128::money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::_M_insert&lt;false&gt;(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, char, basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt; const&amp;)</code> const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
<code>ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;</code>

<code>__gnu_cxx_ldbl128::money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; &gt;::_M_insert&lt;true&gt;(ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, ios_base&amp;, char, basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt; const&amp;)</code>
<code>const(GLIBCXX_LDBL_3.4) [LSB]</code>
<code>__gnu_cxx_ldbl128::money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; &gt;::money_put(unsigned long)(GLIBCXX_LDBL_3.4) [LSB]</code>
<code>__gnu_cxx_ldbl128::money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; &gt;::money_put(unsigned long)(GLIBCXX_LDBL_3.4) [LSB]</code>
<code>money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; &gt;::money_put(unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>
<code>money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; &gt;::money_put(unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>

An LSB conforming implementation shall provide the architecture specific data interfaces for Class `std::money_put<char, std::ostreambuf_iterator<char, std::char_traits<char>> >` specified in [Table 12-223](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-223 libstdcxx - Class `money_put<char, ostreambuf_iterator<char, char_traits<char>> >` Data Interfaces**

<code>typeinfo for __gnu_cxx_ldbl128::money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; &gt; (GLIBCXX_LDBL_3.4) [CXXABI-1.86]</code>
<code>typeinfo name for __gnu_cxx_ldbl128::money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; &gt; (GLIBCXX_LDBL_3.4) [CXXABI-1.86]</code>

## 12.1.134 Class `money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>> >`

### 12.1.134.1 Class data for `money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>> >`

The virtual table for the `std::money_put<wchar_t, std::ostreambuf_iterator<wchar_t, std::char_traits<wchar_t>> >` class is described in the generic part of this specification.

The Run Time Type Information for the `std::money_put<wchar_t, std::ostreambuf_iterator<wchar_t, std::char_traits<wchar_t>> >` class is described by [Table 12-224](#)

**Table 12-224 typeinfo for `money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>> >`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	<code>typeinfo name for money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;</code>

### 12.1.134.2 Interfaces for Class `money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>> >`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::money_put<wchar_t, std::ostreambuf_iterator<wchar_t, std::char_traits<wchar_t>> >` specified in [Table 12-225](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-225 libstdc++ - Class `money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>` Function Interfaces**

<code>__gnu_cxx_ldbl128::money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::put(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, bool, ios_base&amp;, wchar_t, basic_string&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, allocator&lt;wchar_t&gt; const&amp;) const(GLIBCXX_LDBL_3.4) [ISOCXX]</code>
<code>__gnu_cxx_ldbl128::money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::put(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, bool, ios_base&amp;, wchar_t, __float128) const(GLIBCXX_LDBL_3.4) [ISOCXX]</code>
<code>__gnu_cxx_ldbl128::money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::do_put(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, bool, ios_base&amp;, wchar_t, basic_string&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, allocator&lt;wchar_t&gt; const&amp;) const(GLIBCXX_LDBL_3.4) [ISOCXX]</code>
<code>__gnu_cxx_ldbl128::money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::do_put(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, bool, ios_base&amp;, wchar_t, __float128) const(GLIBCXX_LDBL_3.4) [ISOCXX]</code>
<code>__gnu_cxx_ldbl128::money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::_do_put(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, bool, ios_base&amp;, wchar_t, double) const(GLIBCXX_LDBL_3.4) [ISOCXX]</code>
<code>ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; __gnu_cxx_ldbl128::money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::_M_insert&lt;false&gt;(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, ios_base&amp;, wchar_t, basic_string&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, allocator&lt;wchar_t&gt; const&amp;) const(GLIBCXX_LDBL_3.4) [LSB]</code>
<code>ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; __gnu_cxx_ldbl128::money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::_M_insert&lt;true&gt;(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, ios_base&amp;, wchar_t, basic_string&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, allocator&lt;wchar_t&gt; const&amp;) const(GLIBCXX_LDBL_3.4) [LSB]</code>
<code>__gnu_cxx_ldbl128::money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::money_put(unsigned long)(GLIBCXX_LDBL_3.4) [LSB]</code>
<code>__gnu_cxx_ldbl128::money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::money_put(unsigned long)(GLIBCXX_LDBL_3.4) [LSB]</code>
<code>__gnu_cxx_ldbl128::money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::~money_put()(GLIBCXX_LDBL_3.4) [LSB]</code>
<code>__gnu_cxx_ldbl128::money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::~money_put()(GLIBCXX_LDBL_3.4) [LSB]</code>
<code>__gnu_cxx_ldbl128::money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::~money_put()(GLIBCXX_LDBL_3.4) [LSB]</code>
<code>money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::money_put(unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>
<code>money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::money_put(unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>

An LSB conforming implementation shall provide the architecture specific data interfaces for Class `std::money_put<wchar_t, std::ostreambuf_iterator<wchar_t, std::char_traits<wchar_t>>>` specified in [Table 12-226](#), with the full mandatory func-

tionality as described in the referenced underlying specification.

**Table 12-226 libstdc++ - Class `money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>` Data Interfaces**

typeinfo for <code>__gnu_cxx_ldbl128::money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code> (GLIBCXX_LDBL_3.4) [CXXABI-1.86]
typeinfo name for <code>__gnu_cxx_ldbl128::money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code> (GLIBCXX_LDBL_3.4) [CXXABI-1.86]
vtable for <code>__gnu_cxx_ldbl128::money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code> (GLIBCXX_LDBL_3.4) [CXXABI-1.86]

## 12.1.135 Class locale

### 12.1.135.1 Interfaces for Class locale

An LSB conforming implementation shall provide the architecture specific methods for Class std::locale specified in [Table 12-227](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-227 libstdc++ - Class locale Function Interfaces**

locale::Impl::Impl(char const*, unsigned long)(GLIBCXX_3.4) [LSB]
locale::Impl::Impl(locale::Impl const&, unsigned long)(GLIBCXX_3.4) [LSB]
locale::Impl::Impl(unsigned long)(GLIBCXX_3.4) [LSB]
locale::Impl::Impl(char const*, unsigned long)(GLIBCXX_3.4) [LSB]
locale::Impl::Impl(locale::Impl const&, unsigned long)(GLIBCXX_3.4) [LSB]
locale::Impl::Impl(unsigned long)(GLIBCXX_3.4) [LSB]

## 12.1.136 Class locale::facet

### 12.1.136.1 Class data for locale::facet

The virtual table for the std::locale::facet class is described in the generic part of this specification.

The Run Time Type Information for the std::locale::facet class is described by [Table 12-228](#).

**Table 12-228 typeinfo for locale::facet**

Base Vtable	vtable for <code>__cxxabiv1::__class_type_info</code>
Name	typeinfo name for locale::facet

### 12.1.136.2 Interfaces for Class locale::facet

No external methods are defined for libstdc++ - Class std::locale::facet in this part of the specification. See also the generic specification.

## 12.1.137 facet functions

### 12.1.137.1 Interfaces for facet functions

An LSB conforming implementation shall provide the architecture specific methods for facet functions specified in [Table 12-229](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-229 libstdc++ - facet functions Function Interfaces**

<code>void __convert_to_v&lt;__float128&gt;(char const*, __float128&amp;, _Ios_Iostate&amp;, __locale_struct* const&amp;)(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
<code>bool has_facet&lt;__gnu_cxx_ldbl128::num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;&gt;(locale const&amp;)(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>
<code>bool has_facet&lt;__gnu_cxx_ldbl128::num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;&gt;(locale const&amp;)(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>
<code>bool has_facet&lt;__gnu_cxx_ldbl128::num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;&gt;(locale const&amp;)(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>
<code>bool has_facet&lt;__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;&gt;(locale const&amp;)(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>
<code>bool has_facet&lt;__gnu_cxx_ldbl128::money_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;&gt;(locale const&amp;)(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>
<code>bool has_facet&lt;__gnu_cxx_ldbl128::money_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;&gt;(locale const&amp;)(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>
<code>bool has_facet&lt;__gnu_cxx_ldbl128::money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;&gt;(locale const&amp;)(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>
<code>bool has_facet&lt;__gnu_cxx_ldbl128::money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;&gt;(locale const&amp;)(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>
<code>__gnu_cxx_ldbl128::num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt; const&amp; use_facet&lt;__gnu_cxx_ldbl128::num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;&gt;(locale const&amp;)(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>
<code>__gnu_cxx_ldbl128::num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt; const&amp; use_facet&lt;__gnu_cxx_ldbl128::num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;&gt;(locale const&amp;)(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>
<code>__gnu_cxx_ldbl128::num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt; const&amp; use_facet&lt;__gnu_cxx_ldbl128::num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;&gt;(locale const&amp;)(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>
<code>__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt; const&amp; use_facet&lt;__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;&gt;(locale const&amp;)(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>
<code>__gnu_cxx_ldbl128::money_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt; const&amp; use_facet&lt;__gnu_cxx_ldbl128::money_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;&gt;(locale const&amp;)(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>
<code>__gnu_cxx_ldbl128::money_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt; const&amp; use_facet&lt;__gnu_cxx_ldbl128::money_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;&gt;(locale const&amp;)(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>
<code>__gnu_cxx_ldbl128::money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt; const&amp; use_facet&lt;__gnu_cxx_ldbl128::money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;&gt;(locale const&amp;)(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>
<code>__gnu_cxx_ldbl128::money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt; const&amp; use_facet&lt;__gnu_cxx_ldbl128::money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;&gt;(locale const&amp;)(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>

char_traits<wchar_t> >> >(locale const&)(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
----------------------------------------------------------------------------------

## 12.1.138 Class \_\_num\_base

### 12.1.138.1 Class data for \_\_num\_base

### 12.1.138.2 Interfaces for Class \_\_num\_base

No external methods are defined for libstdc++ - Class std::\_\_num\_base in this part of the specification. See also the generic specification.

## 12.1.139 Class num\_get<char, istreambuf\_iterator<char, char\_traits<char> > >

### 12.1.139.1 Class data for num\_get<char, istreambuf\_iterator<char, char\_traits<char> > >

The virtual table for the std::num\_get<char, std::istreambuf\_iterator<char, std::char\_traits<char> > > class is described in the generic part of this specification.

The Run Time Type Information for the std::num\_get<char, std::istreambuf\_iterator<char, std::char\_traits<char> > > class is described by [Table 12-230](#)

**Table 12-230 typeinfo for num\_get<char, istreambuf\_iterator<char, char\_traits<char> > >**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for num_get<char, istreambuf_iterator<char, char_traits<char> > >
basetype:	typeinfo for locale::facet

### 12.1.139.2 Interfaces for Class num\_get<char, istreambuf\_iterator<char, char\_traits<char> > >

An LSB conforming implementation shall provide the architecture specific methods for Class std::num\_get<char, std::istreambuf\_iterator<char, std::char\_traits<char> > > specified in [Table 12-231](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-231 libstdc++ - Class num\_get<char, istreambuf\_iterator<char, char\_traits<char> > > Function Interfaces**

istreambuf_iterator<char, char_traits<char> > __gnu_cxx_ldbl128::num_get<char, istreambuf_iterator<char, char_traits<char> > >::M_extract_int<unsigned int>(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, unsigned int&) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
istreambuf_iterator<char, char_traits<char> > __gnu_cxx_ldbl128::num_get<char, istreambuf_iterator<char, char_traits<char> > >::M_extract_int<long>(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, long&) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
istreambuf_iterator<char, char_traits<char> > __gnu_cxx_ldbl128::num_get<char, istreambuf_iterator<char, char_traits<char> > >::M_extract_int<unsigned long>(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, unsigned long&)

<code>const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>
<code>istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; __gnu_cxx_ldbl128::num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::__M_extract_int&lt;unsigned short&gt;(istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, unsigned short&amp;)</code> <code>const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>
<code>istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; __gnu_cxx_ldbl128::num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::__M_extract_int&lt;long long&gt;(istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, long long&amp;)</code> <code>const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>
<code>istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; __gnu_cxx_ldbl128::num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::__M_extract_int&lt;unsigned long long&gt;(istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, unsigned long long&amp;)</code> <code>const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>
<code>__gnu_cxx_ldbl128::num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::__M_extract_float(istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt;&amp;)</code> <code>const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>
<code>__gnu_cxx_ldbl128::num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::__get(istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, void*&amp;)</code> <code>const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
<code>__gnu_cxx_ldbl128::num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::__get(istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, bool&amp;)</code> <code>const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
<code>__gnu_cxx_ldbl128::num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::__get(istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, double&amp;)</code> <code>const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
<code>__gnu_cxx_ldbl128::num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::__get(istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, float&amp;)</code> <code>const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
<code>__gnu_cxx_ldbl128::num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::__get(istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, __float128&amp;)</code> <code>const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
<code>__gnu_cxx_ldbl128::num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::__get(istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, unsigned int&amp;)</code> <code>const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
<code>__gnu_cxx_ldbl128::num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::__get(istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, long&amp;)</code> <code>const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
<code>__gnu_cxx_ldbl128::num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::__get(istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, unsigned long&amp;)</code> <code>const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>



>::do_get(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, unsigned long long&) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOcxx]</a>
__gnu_cxx_ldbl128::num_get<char, istreambuf_iterator<char, char_traits<char> >>::__do_get(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, double&) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOcxx]</a>
__gnu_cxx_ldbl128::num_get<char, istreambuf_iterator<char, char_traits<char> >>::num_get(unsigned long)(GLIBCXX_LDBL_3.4) <a href="#">[ISOcxx]</a>
__gnu_cxx_ldbl128::num_get<char, istreambuf_iterator<char, char_traits<char> >>::num_get(unsigned long)(GLIBCXX_LDBL_3.4) <a href="#">[ISOcxx]</a>
__gnu_cxx_ldbl128::num_get<char, istreambuf_iterator<char, char_traits<char> >>::~num_get()(GLIBCXX_LDBL_3.4) <a href="#">[ISOcxx]</a>
__gnu_cxx_ldbl128::num_get<char, istreambuf_iterator<char, char_traits<char> >>::~num_get()(GLIBCXX_LDBL_3.4) <a href="#">[ISOcxx]</a>
__gnu_cxx_ldbl128::num_get<char, istreambuf_iterator<char, char_traits<char> >>::~num_get()(GLIBCXX_LDBL_3.4) <a href="#">[ISOcxx]</a>
num_get<char, istreambuf_iterator<char, char_traits<char> >>::num_get(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
num_get<char, istreambuf_iterator<char, char_traits<char> >>::num_get(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>

An LSB conforming implementation shall provide the architecture specific data interfaces for Class std::num\_get<char, std::istreambuf\_iterator<char, std::char\_traits<char> >> specified in [Table 12-232](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-232 libstdcxx - Class num\_get<char, istreambuf\_iterator<char, char\_traits<char> >> Data Interfaces**

typeinfo for __gnu_cxx_ldbl128::num_get<char, istreambuf_iterator<char, char_traits<char> >>(GLIBCXX_LDBL_3.4) <a href="#">[CXXABI-1.86]</a>
typeinfo name for __gnu_cxx_ldbl128::num_get<char, istreambuf_iterator<char, char_traits<char> >>(GLIBCXX_LDBL_3.4) <a href="#">[CXXABI-1.86]</a>

## 12.1.140 Class num\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> >>

### 12.1.140.1 Class data for num\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> >>

The virtual table for the std::num\_get<wchar\_t, std::istreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t> >> class is described in the generic part of this specification.

The Run Time Type Information for the std::num\_get<wchar\_t, std::istreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t> >> class is described by [Table 12-233](#)

**Table 12-233 typeinfo for num\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> >>**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for num_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> >>

basetype:	typeinfo for locale::facet
<b>12.1.140.2 Interfaces for Class num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;</b>	
An LSB conforming implementation shall provide the architecture specific methods for Class std::num_get<wchar_t, std::istreambuf_iterator<wchar_t, std::char_traits<wchar_t>>> specified in <a href="#">Table 12-234</a> , with the full mandatory functionality as described in the referenced underlying specification.	
<b>Table 12-234 libstdc++ - Class num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt; Function Interfaces</b>	
<pre>istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; __gnu_cxx_ldbl128::num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;::__M_extract_int&lt;unsigned int&gt;(istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, ios_base&amp;, _Ios_Iostate&amp;, unsigned int&amp;) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></pre>	
<pre>istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; __gnu_cxx_ldbl128::num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;::__M_extract_int&lt;long&gt;(istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, ios_base&amp;, _Ios_Iostate&amp;, long&amp;) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></pre>	
<pre>istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; __gnu_cxx_ldbl128::num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;::__M_extract_int&lt;unsigned long&gt;(istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, ios_base&amp;, _Ios_Iostate&amp;, unsigned long&amp;) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></pre>	
<pre>istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; __gnu_cxx_ldbl128::num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;::__M_extract_int&lt;unsigned short&gt;(istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, ios_base&amp;, _Ios_Iostate&amp;, unsigned short&amp;) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></pre>	
<pre>istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; __gnu_cxx_ldbl128::num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;::__M_extract_int&lt;long long&gt;(istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, ios_base&amp;, _Ios_Iostate&amp;, long long&amp;) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></pre>	
<pre>istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; __gnu_cxx_ldbl128::num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;::__M_extract_int&lt;unsigned long long&gt;(istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, ios_base&amp;, _Ios_Iostate&amp;, unsigned long long&amp;) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></pre>	
<pre>__gnu_cxx_ldbl128::num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;::__M_extract_float(istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, ios_base&amp;, _Ios_Iostate&amp;, basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt;&amp;) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></pre>	
<pre>__gnu_cxx_ldbl128::num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;::__get(istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, ios_base&amp;, _Ios_Iostate&amp;, void*&amp;) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></pre>	





>::num_get(unsigned long)(GLIBCXX_3.4) [ISOCXX]
-------------------------------------------------

An LSB conforming implementation shall provide the architecture specific data interfaces for Class std::num\_get<wchar\_t, std::istreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t>>> specified in [Table 12-235](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-235 libstdcxx - Class num\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>> Data Interfaces**

typeinfo for __gnu_cxx_ldbl128::num_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>(GLIBCXX_LDBL_3.4) [CXXABI-1.86]
--------------------------------------------------------------------------------------------------------------------------------------

typeinfo name for __gnu_cxx_ldbl128::num_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>(GLIBCXX_LDBL_3.4) [CXXABI-1.86]
-------------------------------------------------------------------------------------------------------------------------------------------

## 12.1.141 Class num\_put<char, ostreambuf\_iterator<char, char\_traits<char>>>

### 12.1.141.1 Class data for num\_put<char, ostreambuf\_iterator<char, char\_traits<char>>>

The virtual table for the std::num\_put<char, std::ostreambuf\_iterator<char, std::char\_traits<char>>> class is described in the generic part of this specification.

The Run Time Type Information for the std::num\_put<char, std::ostreambuf\_iterator<char, std::char\_traits<char>>> class is described by [Table 12-236](#)

**Table 12-236 typeinfo for num\_put<char, ostreambuf\_iterator<char, char\_traits<char>>>**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for num_put<char, ostreambuf_iterator<char, char_traits<char>>>
basetype:	typeinfo for locale::facet

### 12.1.141.2 Interfaces for Class num\_put<char, ostreambuf\_iterator<char, char\_traits<char>>>

An LSB conforming implementation shall provide the architecture specific methods for Class std::num\_put<char, std::ostreambuf\_iterator<char, std::char\_traits<char>>> specified in [Table 12-237](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-237 libstdcxx - Class num\_put<char, ostreambuf\_iterator<char, char\_traits<char>>> Function Interfaces**

__gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char>>>::__M_group_int(char const*, unsigned long, char, ios_base&, char*, char*, int&) const(GLIBCXX_LDBL_3.4) [LSB]
----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

ostreambuf_iterator<char, char_traits<char>> __gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char>>>::__M_insert_int<long>(ostreambuf_iterator<char, char_traits<char>>, ios_base&, char, long) const(GLIBCXX_LDBL_3.4) [LSB]
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

ostreambuf_iterator<char, char_traits<char>> __gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char>>>::__M_insert_int<unsigned>
-------------------------------------------------------------------------------------------------------------------------------------------------------

long>(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, unsigned long) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
ostreambuf_iterator<char, char_traits<char> > __gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> >>::__M_insert_int<long long>(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, long long) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
ostreambuf_iterator<char, char_traits<char> > __gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> >>::__M_insert_int<unsigned long long>(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, unsigned long long) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
__gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> >>::__M_group_float(char const*, unsigned long, char, char const*, char*, char*, int&) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
ostreambuf_iterator<char, char_traits<char> > __gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> >>::__M_insert_float<double>(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, char, double) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
ostreambuf_iterator<char, char_traits<char> > __gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> >>::__M_insert_float<__float128>(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, char, __float128) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
__gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> >>::put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, void const*) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
__gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> >>::put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, bool) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
__gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> >>::put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, double) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
__gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> >>::put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, __float128) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
__gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> >>::put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, long) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
__gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> >>::put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, unsigned long) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
__gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> >>::put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, long long) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
__gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> >>::put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, unsigned long long) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
__gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> >>::__M_pad(char, long, ios_base&, char*, char const*, int&) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
__gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> >>::do_put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, void const*) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
__gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> >

>::do_put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, bool) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
__gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> > >::do_put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, double) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
__gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> > >::do_put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, float128) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
__gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> > >::do_put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, long) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
__gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> > >::do_put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, unsigned long) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
__gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> > >::do_put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, long long) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
__gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> > >::do_put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, unsigned long long) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
__gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> > >::__do_put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, double) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
num_put<char, ostreambuf_iterator<char, char_traits<char> >>::_M_group_int(char const*, unsigned long, char, ios_base&, char*, char*, int&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
num_put<char, ostreambuf_iterator<char, char_traits<char> > >::_M_group_float(char const*, unsigned long, char, char const*, char*, char*, int&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
num_put<char, ostreambuf_iterator<char, char_traits<char> >>::_M_pad(char, long, ios_base&, char*, char const*, int&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
__gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> > >::num_put(unsigned long)(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
__gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> > >::num_put(unsigned long)(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
__gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> > >::~num_put()(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
__gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> > >::~num_put()(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
__gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char> > >::~num_put()(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a>
num_put<char, ostreambuf_iterator<char, char_traits<char> >>::num_put(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
num_put<char, ostreambuf_iterator<char, char_traits<char> >>::num_put(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the architecture specific data interfaces for Class std::num\_put<char, std::ostreambuf\_iterator<char, std::char\_traits<char> >> specified in [Table 12-238](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-238 libstdcxx - Class num\_put<char, ostreambuf\_iterator<char, char\_traits<char>>> Data Interfaces**

typeinfo for __gnu_cxx_ldb1128::num_put<char, ostreambuf_iterator<char, char_traits<char>>>(GLIBCXX_LDBL_3.4) <a href="#">[CXXABI-1.86]</a>
typeinfo name for __gnu_cxx_ldb1128::num_put<char, ostreambuf_iterator<char, char_traits<char>>>(GLIBCXX_LDBL_3.4) <a href="#">[CXXABI-1.86]</a>

## 12.1.142 Class num\_put<wchar\_t, ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>>

### 12.1.142.1 Class data for num\_put<wchar\_t, ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>>

The virtual table for the std::num\_put<wchar\_t, std::ostreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t>>> class is described in the generic part of this specification.

The Run Time Type Information for the std::num\_put<wchar\_t, std::ostreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t>>> class is described by [Table 12-239](#)

**Table 12-239 typeinfo for num\_put<wchar\_t, ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>>**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>
basetype:	typeinfo for locale::facet

### 12.1.142.2 Interfaces for Class num\_put<wchar\_t, ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>>

An LSB conforming implementation shall provide the architecture specific methods for Class std::num\_put<wchar\_t, std::ostreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t>>> specified in [Table 12-240](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-240 libstdcxx - Class num\_put<wchar\_t, ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>> Function Interfaces**

__gnu_cxx_ldb1128::num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>::__M_group_int(char const*, unsigned long, wchar_t, ios_base&, wchar_t*, wchar_t*, int&) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
ostreambuf_iterator<wchar_t, char_traits<wchar_t>> __gnu_cxx_ldb1128::num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>::__M_insert_int<long>(ostreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, wchar_t, long) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
ostreambuf_iterator<wchar_t, char_traits<wchar_t>> __gnu_cxx_ldb1128::num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>::__M_insert_int<unsigned long>(ostreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, wchar_t, unsigned long) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
ostreambuf_iterator<wchar_t, char_traits<wchar_t>> __gnu_cxx_ldb1128::num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>::__M_insert_int<long long>(ostreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, wchar_t, long long)

const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a>
<code>ostreampbuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;</code> <code>    &lt;__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t,</code> <code>    char_traits&lt;wchar_t&gt; &gt;&gt;:_M_insert_int&lt;unsigned long</code> <code>    long&gt;(ostreampbuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, wchar_t,</code> <code>    unsigned long long) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>
<code>    &lt;__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t,</code> <code>    char_traits&lt;wchar_t&gt; &gt;&gt;:_M_group_float(char const*, unsigned long, wchar_t,</code> <code>    wchar_t const*, wchar_t*, wchar_t*, int&amp;) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>
<code>ostreampbuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;</code> <code>    &lt;__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t,</code> <code>    char_traits&lt;wchar_t&gt; &gt;&gt;:_M_insert_float&lt;double&gt;(ostreampbuf_iterator&lt;wchar_t,</code> <code>    char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, wchar_t, char, double)</code> <code>    const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>
<code>ostreampbuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;</code> <code>    &lt;__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t,</code> <code>    char_traits&lt;wchar_t&gt; &gt;&gt;:_M_insert_float&lt;__float128&gt;(ostreampbuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, wchar_t, char, __float128) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>
<code>    &lt;__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t,</code> <code>    char_traits&lt;wchar_t&gt; &gt;&gt;:put(ostreampbuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, wchar_t, void const*) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
<code>    &lt;__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t,</code> <code>    char_traits&lt;wchar_t&gt; &gt;&gt;:put(ostreampbuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, wchar_t, bool) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
<code>    &lt;__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t,</code> <code>    char_traits&lt;wchar_t&gt; &gt;&gt;:put(ostreampbuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, wchar_t, double) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
<code>    &lt;__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t,</code> <code>    char_traits&lt;wchar_t&gt; &gt;&gt;:put(ostreampbuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, wchar_t, __float128) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
<code>    &lt;__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t,</code> <code>    char_traits&lt;wchar_t&gt; &gt;&gt;:put(ostreampbuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, wchar_t, long) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
<code>    &lt;__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t,</code> <code>    char_traits&lt;wchar_t&gt; &gt;&gt;:put(ostreampbuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, wchar_t, unsigned long) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
<code>    &lt;__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t,</code> <code>    char_traits&lt;wchar_t&gt; &gt;&gt;:put(ostreampbuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, wchar_t, long long) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
<code>    &lt;__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t,</code> <code>    char_traits&lt;wchar_t&gt; &gt;&gt;:put(ostreampbuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, wchar_t, unsigned long long) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
<code>    &lt;__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t,</code> <code>    char_traits&lt;wchar_t&gt; &gt;&gt;:_M_pad(wchar_t, long, ios_base&amp;, wchar_t*, wchar_t</code> <code>    const*, int&amp;) const(GLIBCXX_LDBL_3.4) <a href="#">[LSB]</a></code>
<code>    &lt;__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t,</code> <code>    char_traits&lt;wchar_t&gt; &gt;&gt;:do_put(ostreampbuf_iterator&lt;wchar_t,</code> <code>    char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, wchar_t, void const*)</code> <code>    const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
<code>    &lt;__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t,</code> <code>    char_traits&lt;wchar_t&gt; &gt;&gt;:do_put(ostreampbuf_iterator&lt;wchar_t,</code> <code>    char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, wchar_t, bool) const(GLIBCXX_LDBL_3.4)</code>

<a href="#">[ISOCXX]</a>	<pre>__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;::do_put(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, ios_base&amp;, wchar_t, double) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></pre>
	<pre>__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;::do_put(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, ios_base&amp;, wchar_t, __float128) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></pre>
	<pre>__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;::do_put(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, ios_base&amp;, wchar_t, long) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></pre>
	<pre>__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;::do_put(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, ios_base&amp;, wchar_t, unsigned long) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></pre>
	<pre>__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;::do_put(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, ios_base&amp;, wchar_t, long long) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></pre>
	<pre>__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;::do_put(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, ios_base&amp;, wchar_t, unsigned long long) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></pre>
	<pre>__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;::do_put(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, ios_base&amp;, wchar_t, double) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></pre>
	<pre>__gnu_cxx_ldbl128::money_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; &gt;::do_get(istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, bool, ios_base&amp;, _Ios_Iostate&amp;, basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></pre>
	<pre>__gnu_cxx_ldbl128::money_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; &gt;::do_get(istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, bool, ios_base&amp;, _Ios_Iostate&amp;, __float128&amp;) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></pre>
	<pre>__gnu_cxx_ldbl128::money_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; &gt;::do_get(istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, bool, ios_base&amp;, _Ios_Iostate&amp;, double&amp;) const(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></pre>
	<pre>num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::_M_group_int(char const*, unsigned long, wchar_t, ios_base&amp;, wchar_t*,  wchar_t*, int&amp;) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></pre>
	<pre>num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::_M_group_float(char const*, unsigned long, wchar_t, wchar_t const*, wchar_t*,  wchar_t*, int&amp;) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></pre>
	<pre>num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::_M_pad(wchar_t, long, ios_base&amp;, wchar_t*, wchar_t const*, int&amp;) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></pre>
	<pre>__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;::num_put(unsigned long)(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></pre>

__gnu_cxx_ldbl128::num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>::num_put(unsigned long)(GLIBCXX_LDBL_3.4) [ISOCXX]
__gnu_cxx_ldbl128::num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>::~num_put()(GLIBCXX_LDBL_3.4) [ISOCXX]
__gnu_cxx_ldbl128::num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>::~num_put()(GLIBCXX_LDBL_3.4) [ISOCXX]
__gnu_cxx_ldbl128::num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>::~num_put()(GLIBCXX_LDBL_3.4) [ISOCXX]
__gnu_cxx_ldbl128::money_get<char, ostreambuf_iterator<char, char_traits<char>>>::~money_get()(GLIBCXX_LDBL_3.4) [ISOCXX]
__gnu_cxx_ldbl128::money_get<char, ostreambuf_iterator<char, char_traits<char>>>::~money_get()(GLIBCXX_LDBL_3.4) [ISOCXX]
__gnu_cxx_ldbl128::money_get<char, ostreambuf_iterator<char, char_traits<char>>>::~money_get()(GLIBCXX_LDBL_3.4) [ISOCXX]
__gnu_cxx_ldbl128::money_put<char, ostreambuf_iterator<char, char_traits<char>>>::~money_put()(GLIBCXX_LDBL_3.4) [ISOCXX]
__gnu_cxx_ldbl128::money_put<char, ostreambuf_iterator<char, char_traits<char>>>::~money_put()(GLIBCXX_LDBL_3.4) [ISOCXX]
__gnu_cxx_ldbl128::money_put<char, ostreambuf_iterator<char, char_traits<char>>>::~money_put()(GLIBCXX_LDBL_3.4) [ISOCXX]
num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>::num_put(unsigned long)(GLIBCXX_3.4) [ISOCXX]
num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>::num_put(unsigned long)(GLIBCXX_3.4) [ISOCXX]

An LSB conforming implementation shall provide the architecture specific data interfaces for Class std::num\_put<wchar\_t, std::ostreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t>>> specified in [Table 12-241](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-241 libstdcxx - Class num\_put<wchar\_t, ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>> Data Interfaces**

guard variable for __gnu_cxx_ldbl128::num_get<char, ostreambuf_iterator<char, char_traits<char>>>::id(GLIBCXX_LDBL_3.4) [CXXABI-1.86]
guard variable for __gnu_cxx_ldbl128::num_get<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>::id(GLIBCXX_LDBL_3.4) [CXXABI-1.86]
guard variable for __gnu_cxx_ldbl128::num_put<char, ostreambuf_iterator<char, char_traits<char>>>::id(GLIBCXX_LDBL_3.4) [CXXABI-1.86]
guard variable for __gnu_cxx_ldbl128::num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>::id(GLIBCXX_LDBL_3.4) [CXXABI-1.86]
guard variable for __gnu_cxx_ldbl128::money_get<char, ostreambuf_iterator<char, char_traits<char>>>::id(GLIBCXX_LDBL_3.4) [CXXABI-1.86]
guard variable for __gnu_cxx_ldbl128::money_get<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>::id(GLIBCXX_LDBL_3.4) [CXXABI-1.86]
guard variable for __gnu_cxx_ldbl128::money_put<char, ostreambuf_iterator<char, char_traits<char>>>::id(GLIBCXX_LDBL_3.4) [CXXABI-1.86]
guard variable for __gnu_cxx_ldbl128::money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>::id(GLIBCXX_LDBL_3.4) [CXXABI-1.86]

<a href="#">[CXXABI-1.86]</a>
<code>__gnu_cxx_ldbl128::num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; &gt;::id(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
<code>__gnu_cxx_ldbl128::num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::id(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
<code>__gnu_cxx_ldbl128::num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; &gt;::id(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
<code>__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::id(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
<code>__gnu_cxx_ldbl128::money_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; &gt;::id(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
<code>__gnu_cxx_ldbl128::money_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::id(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
<code>__gnu_cxx_ldbl128::money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; &gt;::id(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
<code>__gnu_cxx_ldbl128::money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::id(GLIBCXX_LDBL_3.4) <a href="#">[ISOCXX]</a></code>
typeinfo for <code>__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;&gt;(GLIBCXX_LDBL_3.4) <a href="#">[CXXABI-1.86]</a></code>
typeinfo name for <code>__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;&gt;(GLIBCXX_LDBL_3.4) <a href="#">[CXXABI-1.86]</a></code>
vtable for <code>__gnu_cxx_ldbl128::num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; &gt;&gt;(GLIBCXX_LDBL_3.4) <a href="#">[CXXABI-1.86]</a></code>
vtable for <code>__gnu_cxx_ldbl128::num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;&gt;(GLIBCXX_LDBL_3.4) <a href="#">[CXXABI-1.86]</a></code>
vtable for <code>__gnu_cxx_ldbl128::num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; &gt;&gt;(GLIBCXX_LDBL_3.4) <a href="#">[CXXABI-1.86]</a></code>
vtable for <code>__gnu_cxx_ldbl128::num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;&gt;(GLIBCXX_LDBL_3.4) <a href="#">[CXXABI-1.86]</a></code>
vtable for <code>__gnu_cxx_ldbl128::money_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; &gt;&gt;(GLIBCXX_LDBL_3.4) <a href="#">[CXXABI-1.86]</a></code>
vtable for <code>__gnu_cxx_ldbl128::money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; &gt;&gt;(GLIBCXX_LDBL_3.4) <a href="#">[CXXABI-1.86]</a></code>

## 12.1.143 Class `gslice`

### 12.1.143.1 Class data for `gslice`

### 12.1.143.2 Interfaces for Class `gslice`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::gslice` specified in [Table 12-242](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-242 libstdcxx - Class `gslice` Function Interfaces**

<code>gslice::_Indexer::_Indexer(unsigned long, valarray&lt;unsigned long&gt; const&amp;, valarray&lt;unsigned long&gt; const&amp;)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>gslice::_Indexer::_Indexer(unsigned long, valarray&lt;unsigned long&gt; const&amp;, valarray&lt;unsigned long&gt; const&amp;)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>

## 12.1.144 Class `__basic_file<char>`

### 12.1.144.1 Class data for `__basic_file<char>`

### 12.1.144.2 Interfaces for Class `__basic_file<char>`

An LSB conforming implementation shall provide the architecture specific methods for Class std::\_\_basic\_file<char> specified in [Table 12-243](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-243 libstdcxx - Class `__basic_file<char>` Function Interfaces**

<code>__basic_file&lt;char&gt;::xsgetn(char*, long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>__basic_file&lt;char&gt;::xsputn(char const*, long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>__basic_file&lt;char&gt;::seekoff(long, _Ios_Seekdir)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>__basic_file&lt;char&gt;::xsputn_2(char const*, long, char const*, long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

## 12.1.145 Class `_List_node_base`

### 12.1.145.1 Interfaces for Class `_List_node_base`

No external methods are defined for libstdcxx - Class std::\_List\_node\_base in this part of the specification. See also the generic specification.

## 12.1.146 Class `valarray<unsigned int>`

### 12.1.146.1 Class data for `valarray<unsigned int>`

### 12.1.146.2 Interfaces for Class `valarray<unsigned int>`

An LSB conforming implementation shall provide the architecture specific methods for Class std::valarray<unsigned int> specified in [Table 12-244](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-244 libstdcxx - Class `valarray<unsigned int>` Function Interfaces**

<code>valarray&lt;unsigned long&gt;::size() const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>valarray&lt;unsigned long&gt;::valarray(valarray&lt;unsigned long&gt; const&amp;)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>valarray&lt;unsigned long&gt;::valarray(unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>valarray&lt;unsigned long&gt;::valarray(valarray&lt;unsigned long&gt; const&amp;)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>valarray&lt;unsigned long&gt;::valarray(unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>valarray&lt;unsigned long&gt;::~valarray()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>valarray&lt;unsigned long&gt;::~valarray()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>valarray&lt;unsigned long&gt;::operator[](unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

## 12.1.147 Class `allocator<char>`

### 12.1.147.1 Class data for `allocator<char>`

### 12.1.147.2 Interfaces for Class `allocator<char>`

No external methods are defined for libstdcxx - Class std::allocator<char> in this part of the specification. See also the generic specification.

## 12.1.148 Class allocator<wchar\_t>

### 12.1.148.1 Class data for allocator<wchar\_t>

### 12.1.148.2 Interfaces for Class allocator<wchar\_t>

No external methods are defined for libstdcxx - Class std::allocator<wchar\_t> in this part of the specification. See also the generic specification.

## 12.1.149 Class \_\_gnu\_cxx::\_\_pool<true>

### 12.1.149.1 Interfaces for Class \_\_gnu\_cxx::\_\_pool<true>

An LSB conforming implementation shall provide the architecture specific methods for Class \_\_gnu\_cxx::\_\_pool<true> specified in [Table 12-245](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-245 libstdcxx - Class \_\_gnu\_cxx::\_\_pool<true> Function Interfaces**

__gnu_cxx::__pool<true>::__M_reclaim_block(char*, unsigned long) (GLIBCXX_3.4.4) <a href="#">[LSB]</a>
__gnu_cxx::__pool<true>::__M_reserve_block(unsigned long, unsigned long) (GLIBCXX_3.4.4) <a href="#">[LSB]</a>

## 12.1.150 Class \_\_gnu\_cxx::\_\_pool<false>

### 12.1.150.1 Interfaces for Class \_\_gnu\_cxx::\_\_pool<false>

An LSB conforming implementation shall provide the architecture specific methods for Class \_\_gnu\_cxx::\_\_pool<false> specified in [Table 12-246](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-246 libstdcxx - Class \_\_gnu\_cxx::\_\_pool<false> Function Interfaces**

__gnu_cxx::__pool<false>::__M_reclaim_block(char*, unsigned long) (GLIBCXX_3.4.4) <a href="#">[LSB]</a>
__gnu_cxx::__pool<false>::__M_reserve_block(unsigned long, unsigned long) (GLIBCXX_3.4.4) <a href="#">[LSB]</a>

## 12.1.151 Class \_\_gnu\_cxx::free\_list

### 12.1.151.1 Interfaces for Class \_\_gnu\_cxx::free\_list

An LSB conforming implementation shall provide the architecture specific methods for Class \_\_gnu\_cxx::free\_list specified in [Table 12-247](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-247 libstdcxx - Class \_\_gnu\_cxx::free\_list Function Interfaces**

__gnu_cxx::free_list::__M_get(unsigned long)(GLIBCXX_3.4.4) <a href="#">[LSB]</a>
-----------------------------------------------------------------------------------

## 12.1.152 Class locale::\_\_Impl

### 12.1.152.1 Interfaces for Class locale::\_\_Impl

An LSB conforming implementation shall provide the architecture specific methods for Class std::locale::\_\_Impl specified in [Table 12-248](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-248 libstdcxx - Class locale::\_\_Impl Function Interfaces**

locale::__Impl::__M_install_cache(locale::facet const*, unsigned long)
------------------------------------------------------------------------

(GLIBCXX\_3.4.7) [\[ISOCXX\]](#)

## 12.1.153 Namespace std Functions

### 12.1.153.1 Interfaces for Namespace std Functions

An LSB conforming implementation shall provide the architecture specific methods for Namespace std Functions specified in [Table 12-249](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-249 libstdcxx - Namespace std Functions Function Interfaces**

long __copy_streambufs<char, char_traits<char>>(basic_streambuf<char, char_traits<char>>*, basic_streambuf<char, char_traits<char>>*) (GLIBCXX_3.4.8) <a href="#">[ISOCXX]</a>
-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

long __copy_streambufs<wchar_t, char_traits<wchar_t>>(basic_streambuf<wchar_t, char_traits<wchar_t>>*, basic_streambuf<wchar_t, char_traits<wchar_t>>*)(GLIBCXX_3.4.8) <a href="#">[ISOCXX]</a>
-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

## 12.1.154 Class char\_traits<char>

### 12.1.154.1 Interfaces for Class char\_traits<char>

No external methods are defined for libstdcxx - Class std::char\_traits<char> in this part of the specification. See also the generic specification.

## 12.1.155 Class char\_traits<wchar\_t>

### 12.1.155.1 Interfaces for Class char\_traits<wchar\_t>

No external methods are defined for libstdcxx - Class std::char\_traits<wchar\_t> in this part of the specification. See also the generic specification.

## 12.2 Interface Definitions for libstdcxx

The interfaces defined on the following pages are included in libstdcxx and are defined by this specification. Unless otherwise noted, these interfaces shall be included in the source standard.

Other interfaces listed in [Section 12.1](#) shall behave as described in the referenced base document. For interfaces referencing LSB and not listed below, please see the generic part of the specification.

## **VI Package Format and Installation**

## 13 Software Installation

### 13.1 Package Dependencies

The LSB runtime environment shall provide the following dependencies.

`lsb-core-s390x`

This dependency is used to indicate that the application is dependent on features contained in the LSB-Core specification.

This dependency shall have a version of 5.0.

Other LSB modules may add additional dependencies; such dependencies shall have the format `lsb-module-s390x`.

### 13.2 Package Architecture Considerations

All packages must specify an architecture of `s390x`. A LSB runtime environment must accept an architecture of `s390` even if the native architecture is different.

The `archnum` value in the Lead Section shall be `0x000E`.

## Annex A Alphabetical Listing of Interfaces by Library

### A.1 libc

The behavior of the interfaces in this library is specified by the following Standards.

[Large File Support](#) [LFS]

[LSB Core - Generic](#) [LSB]

[RFC 5531/4506 RPC & XDR](#) [RPC + XDR]

[SUSv2](#) [SUSv2]

[POSIX 1003.1-2001 \(ISO/IEC 9945-2003\)](#) [SUSv3]

[POSIX 1003.1-2008 \(ISO/IEC 9945-2009\)](#) [SUSv4]

[SVID Issue 4](#) [SVID.4]

**Table A-1 libc Function Interfaces**

<code>_Exit(GLIBC_2.2) [SUSv4]</code>	<code>getpagesize(GLIBC_2.2) [LSB]</code>	<code>setpriority(GLIBC_2.2) [SUSv4]</code>
<code>_IO_feof(GLIBC_2.2) [LSB]</code>	<code>getpeername(GLIBC_2.2) [SUSv4]</code>	<code>setprotoent(GLIBC_2.2) [SUSv4]</code>
<code>_IO_getc(GLIBC_2.2) [LSB]</code>	<code>getpgid(GLIBC_2.2) [SUSv4]</code>	<code>setpwent(GLIBC_2.2) [SUSv4]</code>
<code>_IO_putc(GLIBC_2.2) [LSB]</code>	<code>getpgrp(GLIBC_2.2) [SUSv4]</code>	<code>setregid(GLIBC_2.2) [SUSv4]</code>
<code>_IO_puts(GLIBC_2.2) [LSB]</code>	<code>getpid(GLIBC_2.2) [SUSv4]</code>	<code>setreuid(GLIBC_2.2) [SUSv4]</code>
<code>_assert_fail(GLIBC_2.2) [LSB]</code>	<code>getppid(GLIBC_2.2) [SUSv4]</code>	<code>setrlimit(GLIBC_2.2) [LSB]</code>
<code>_ctype_get_mb_cur_max(GLIBC_2.2)[LSB]</code>	<code>getpriority(GLIBC_2.2) [SUSv4]</code>	<code>setrlimit64(GLIBC_2.2) [LFS]</code>
<code>_cxa_atexit(GLIBC_2.2) [LSB]</code>	<code>getprotobynumber(GLIBC_2.2)[SUSv4]</code>	<code>setservent(GLIBC_2.2) [SUSv4]</code>
<code>_cxa_finalize(GLIBC_2.2)[LSB]</code>	<code>getprotobynumber_r(GLIBC_2.2)[LSB]</code>	<code>setsid(GLIBC_2.2) [SUSv4]</code>
<code>_errno_location(GLIBC_2.2)[LSB]</code>	<code>getprotobynumber_r(GLIBC_2.2)[SUSv4]</code>	<code>setsockopt(GLIBC_2.2) [LSB]</code>
<code>_fpending(GLIBC_2.2) [LSB]</code>	<code>getprotobynumber_r(GLIBC_2.2)[LSB]</code>	<code>setstate(GLIBC_2.2) [SUSv4]</code>
<code>_fprintf_chk(GLIBC_2.4)[LSB]</code>	<code>getprotoent(GLIBC_2.2) [SUSv4]</code>	<code>setstate_r(GLIBC_2.2) [LSB]</code>
<code>_fxstat(GLIBC_2.2) [LSB]</code>	<code>getprotoent_r(GLIBC_2.2) [LSB]</code>	<code>setuid(GLIBC_2.2) [SUSv4]</code>
<code>_fxstat64(GLIBC_2.2) [LSB]</code>	<code>getpwent(GLIBC_2.2) [SUSv4]</code>	<code>setutent(GLIBC_2.2) [LSB]</code>
<code>_getpagesize(GLIBC_2.2) [LSB]</code>	<code>getpwent_r(GLIBC_2.2) [LSB]</code>	<code>setutxent(GLIBC_2.2) [SUSv4]</code>
<code>_getpgid(GLIBC_2.2) [LSB]</code>	<code>getpwnam(GLIBC_2.2) [SUSv4]</code>	<code>setvbuf(GLIBC_2.2) [SUSv4]</code>
<code>_h_errno_location(GLIBC_2.2)[LSB]</code>	<code>getpwnam_r(GLIBC_2.2) [SUSv4]</code>	<code>shmat(GLIBC_2.2) [SUSv4]</code>
<code>_isinf(GLIBC_2.2) [LSB]</code>	<code>getpwuid(GLIBC_2.2) [SUSv4]</code>	<code>shmctl(GLIBC_2.2) [SUSv4]</code>
<code>_isinff(GLIBC_2.2)</code>	<code>getpwuid_r(GLIBC_2.2)</code>	<code>shmdt(GLIBC_2.2)</code>

<a href="#">[LSB]</a>	<a href="#">[SUSv4]</a>	<a href="#">[SUSv4]</a>
<code>__isinf(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>getrlimit(GLIBC_2.2)</code> <a href="#">[LFS]</a>	<code>shmget(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>__isinf(GLIBC_2.4)</code> <a href="#">[LSB]</a>	<code>getrlimit64(GLIBC_2.2)</code> <a href="#">[LFS]</a>	<code>shutdown(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>__isnan(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>getrusage(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>sigaction(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>__isnanf(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>getservbyname(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>sigaddset(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>__isnanl(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>getservbyname_r(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>sigaltstack(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>__isnanl(GLIBC_2.4)</code> <a href="#">[LSB]</a>	<code>getservbyport(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>sigandset(GLIBC_2.2)</code> <a href="#">[LSB]</a>
<code>__libc_current_sigrtmax(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>getservbyport_r(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>sigdelset(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>__libc_current_sigrtmin(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>getservent(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>sigemptyset(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>__libc_start_main(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>getservent_r(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>sigfillset(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>__lxstat(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>getsid(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>sighold(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>__lxstat64(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>getsockname(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>sigignore(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>__mempcpy(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>getsockopt(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>siginterrupt(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>__printf_chk(GLIBC_2.4)</code> <a href="#">[LSB]</a>	<code>getsockopt(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>sigisemptyset(GLIBC_2.2)</code> <a href="#">[LSB]</a>
<code>__rawmemchr(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>gettext(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>sigismember(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>__sigsetjmp(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>gettimeofday(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>siglongjmp(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>__snprintf_chk(GLIBC_2.4)</code> <a href="#">[LSB]</a>	<code>getuid(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>signal(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>__sprintf_chk(GLIBC_2.4)</code> <a href="#">[LSB]</a>	<code>getutent(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>sigorset(GLIBC_2.2)</code> <a href="#">[LSB]</a>
<code>__stpcpy(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>getutent_r(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>sigpause(GLIBC_2.2)</code> <a href="#">[LSB]</a>
<code>__strupdup(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>getutxent(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>sigpending(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>__strtod_internal(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>getutxid(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>sigprocmask(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>__strtodf_internal(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>getutxline(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>sigqueue(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>__strtok_r(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>getw(GLIBC_2.2)</code> <a href="#">[SUSv2]</a>	<code>sigrelse(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>__strtol_internal(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>getwc(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>sigreturn(GLIBC_2.2)</code> <a href="#">[LSB]</a>
<code>__strtold_internal(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>getwc_unlocked(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>sigset(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>

<code>__strtold_internal(GLIBC_2.4)[LSB]</code>	<code>getwchar(GLIBC_2.2)</code> [SUSv4]	<code>sigsuspend(GLIBC_2.2)</code> [SUSv4]
<code>__strtoll_internal(GLIBC_2.2)[LSB]</code>	<code>getwchar_unlocked(GLIBC_2.2)[LSB]</code>	<code>sigtimedwait(GLIBC_2.2)</code> [SUSv4]
<code>__strtoul_internal(GLIBC_2.2)[LSB]</code>	<code>getwd(GLIBC_2.2)</code> [SUSv3]	<code>sigwait(GLIBC_2.2)</code> [SUSv4]
<code>__strtoull_internal(GLIBC_2.2)[LSB]</code>	<code>glob(GLIBC_2.2)</code> [SUSv4]	<code>sigwaitinfo(GLIBC_2.2)</code> [SUSv4]
<code>__sysconf(GLIBC_2.2)[LSB]</code>	<code>glob64(GLIBC_2.2)</code> [LSB]	<code>sleep(GLIBC_2.2)</code> [SUSv4]
<code>__sysv_signal(GLIBC_2.2)[LSB]</code>	<code>globfree(GLIBC_2.2)</code> [SUSv4]	<code>snprintf(GLIBC_2.2)</code> [SUSv4]
<code>__vfprintf_chk(GLIBC_2.4)[LSB]</code>	<code>globfree64(GLIBC_2.2)</code> [LSB]	<code>snprintf(GLIBC_2.4)</code> [SUSv4]
<code>__vprintf_chk(GLIBC_2.4)[LSB]</code>	<code>gmtime(GLIBC_2.2)</code> [SUSv4]	<code>socketmark(GLIBC_2.2.4)</code> [SUSv4]
<code>__vsnprintf_chk(GLIBC_2.4)[LSB]</code>	<code>gmtime_r(GLIBC_2.2)</code> [SUSv4]	<code>socket(GLIBC_2.2)</code> [SUSv4]
<code>__vsprintf_chk(GLIBC_2.4)[LSB]</code>	<code>gnu_get_libc_release(GLIBC_2.2)</code> [LSB]	<code>socketpair(GLIBC_2.2)</code> [SUSv4]
<code>__wcstod_internal(GLIBC_2.2)[LSB]</code>	<code>gnu_get_libc_version(GLIBC_2.2)</code> [LSB]	<code>sprintf(GLIBC_2.2)</code> [SUSv4]
<code>__wcstof_internal(GLIBC_2.2)[LSB]</code>	<code>grantpt(GLIBC_2.2)</code> [SUSv4]	<code>sprintf(GLIBC_2.4)</code> [SUSv4]
<code>__wcstol_internal(GLIBC_2.2)[LSB]</code>	<code>hcreate(GLIBC_2.2)</code> [SUSv4]	<code>srand(GLIBC_2.2)</code> [SUSv4]
<code>__wcstold_internal(GLIBC_2.2)[LSB]</code>	<code>hcreate_r(GLIBC_2.2)</code> [LSB]	<code>srand48(GLIBC_2.2)</code> [SUSv4]
<code>__wcstold_internal(GLIBC_2.4)[LSB]</code>	<code>hdestroy(GLIBC_2.2)</code> [SUSv4]	<code>srand48_r(GLIBC_2.2)</code> [LSB]
<code>__wcstoul_internal(GLIBC_2.2)[LSB]</code>	<code>hdestroy_r(GLIBC_2.2)</code> [LSB]	<code>srandom(GLIBC_2.2)</code> [SUSv4]
<code>__xmknod(GLIBC_2.2)[LSB]</code>	<code>hsearch(GLIBC_2.2)</code> [SUSv4]	<code>srandom_r(GLIBC_2.2)</code> [LSB]
<code>__xpg_basename(GLIBC_2.2)[LSB]</code>	<code>hsearch_r(GLIBC_2.2)</code> [LSB]	<code>sscanf(GLIBC_2.2)</code> [LSB]
<code>__xpg_sigpause(GLIBC_2.2)[LSB]</code>	<code>htonl(GLIBC_2.2)</code> [SUSv4]	<code>sscanf(GLIBC_2.4)</code> [LSB]
<code>__xpg_strerror_r(GLIBC_2.3.4)[LSB]</code>	<code>htons(GLIBC_2.2)</code> [SUSv4]	<code>statfs(GLIBC_2.2)</code> [LSB]
<code>__xstat(GLIBC_2.2)[LSB]</code>	<code>iconv(GLIBC_2.2)</code> [SUSv4]	<code>statfs64(GLIBC_2.2)</code> [LSB]
<code>__xstat64(GLIBC_2.2)[LSB]</code>	<code>iconv_close(GLIBC_2.2)</code> [SUSv4]	<code>statvfs(GLIBC_2.2)</code> [SUSv4]
<code>_exit(GLIBC_2.2)</code> [SUSv4]	<code>iconv_open(GLIBC_2.2)</code> [SUSv4]	<code>statvfs64(GLIBC_2.2)</code> [LFS]
<code>_longjmp(GLIBC_2.2)</code> [SUSv4]	<code>if_freenameindex(GLIBC_2.2)</code> [SUSv4]	<code>stime(GLIBC_2.2)</code> [LSB]
<code>_setjmp(GLIBC_2.2)</code> [SUSv4]	<code>if_indextoname(GLIBC_2.2)</code> [SUSv4]	<code>stpcpy(GLIBC_2.2)</code> [SUSv4]

<code>_tolower(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>if_nameindex(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>stpcpy(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>_toupper(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>if_nametoindex(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>strcasecmp(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>a64l(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>imaxabs(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>strcasestr(GLIBC_2.2)</code> <a href="#">[LSB]</a>
<code>abort(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>imaxdiv(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>strcat(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>abs(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>index(GLIBC_2.2)</code> <a href="#">[SUSv3]</a>	<code>strchr(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>accept(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>inet_addr(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>strcmp(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>access(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>inet_aton(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>strcoll(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>acct(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>inet_ntoa(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>strcpy(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>adjtime(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>inet_ntop(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>strcspn(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>alarm(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>inet_pton(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>strupr(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>alphasort(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>initgroups(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>strerror(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>alphasort64(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>initstate(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>strerror_r(GLIBC_2.2)</code> <a href="#">[LSB]</a>
<code>argz_add(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>initstate_r(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>strfmon(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>argz_add_sep(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>insque(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>strfmon(GLIBC_2.4)</code> <a href="#">[SUSv4]</a>
<code>argz_append(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>ioctl(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>strftime(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>argz_count(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>isalnum(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>strlen(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>argz_create(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>isalpha(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>strncasecmp(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>argz_create_sep(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>isascii(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>strncat(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>argz_delete(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>isatty(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>strncmp(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>argz_extract(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>isblank(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>strncpy(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>argz_insert(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>iscntrl(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>strndup(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>argz_next(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>isdigit(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>strnlen(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>argz_replace(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>isgraph(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>strpbrk(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>argz_stringify(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>islower(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>strptime(GLIBC_2.2)</code> <a href="#">[LSB]</a>
<code>asctime(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>isprint(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>strrchr(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>

## LSB Core - S390X 5.0

asctime_r(GLIBC_2.2) [SUSv4]	ispunct(GLIBC_2.2) [SUSv4]	strsep(GLIBC_2.2)[LSB]
asprintf(GLIBC_2.2) [LSB]	isspace(GLIBC_2.2) [SUSv4]	strsignal(GLIBC_2.2) [SUSv4]
asprintf(GLIBC_2.4) [LSB]	isupper(GLIBC_2.2) [SUSv4]	strspn(GLIBC_2.2) [SUSv4]
atof(GLIBC_2.2)[SUSv4]	iswalnum(GLIBC_2.2) [SUSv4]	strstr(GLIBC_2.2) [SUSv4]
atoi(GLIBC_2.2)[SUSv4]	iswalpha(GLIBC_2.2) [SUSv4]	strtod(GLIBC_2.2) [SUSv4]
atol(GLIBC_2.2)[SUSv4]	iswblank(GLIBC_2.2) [SUSv4]	strtof(GLIBC_2.2) [SUSv4]
atoll(GLIBC_2.2) [SUSv4]	iswcntrl(GLIBC_2.2) [SUSv4]	strtoimax(GLIBC_2.2) [SUSv4]
authnone_create(GLIBC_2.2)[SVID.4]	iswctype(GLIBC_2.2) [SUSv4]	strtok(GLIBC_2.2) [SUSv4]
backtrace(GLIBC_2.2) [LSB]	iswdigit(GLIBC_2.2) [SUSv4]	strtok_r(GLIBC_2.2) [SUSv4]
backtrace_symbols(GLIBC_2.2)[LSB]	iswgraph(GLIBC_2.2) [SUSv4]	strtol(GLIBC_2.2) [SUSv4]
backtrace_symbols_fd(GLIBC_2.2)[LSB]	iswlower(GLIBC_2.2) [SUSv4]	strtold(GLIBC_2.2) [SUSv4]
basename(GLIBC_2.2) [LSB]	iswprint(GLIBC_2.2) [SUSv4]	strtold(GLIBC_2.4) [SUSv4]
bcmp(GLIBC_2.2) [SUSv3]	iswpunct(GLIBC_2.2) [SUSv4]	strtoll(GLIBC_2.2) [SUSv4]
bcopy(GLIBC_2.2) [SUSv3]	iswspace(GLIBC_2.2) [SUSv4]	strtoq(GLIBC_2.2)[LSB]
bind(GLIBC_2.2) [SUSv4]	iswupper(GLIBC_2.2) [SUSv4]	strtoul(GLIBC_2.2) [SUSv4]
bind_textdomain_codeset(GLIBC_2.2)[LSB]	iswdxigit(GLIBC_2.2) [SUSv4]	strtoull(GLIBC_2.2) [SUSv4]
bindresvport(GLIBC_2.2) [LSB]	isxdigit(GLIBC_2.2) [SUSv4]	strtoumax(GLIBC_2.2) [SUSv4]
bindtextdomain(GLIBC_2.2)[LSB]	jrand48(GLIBC_2.2) [SUSv4]	strtouq(GLIBC_2.2) [LSB]
brk(GLIBC_2.2)[SUSv2]	jrand48_r(GLIBC_2.2) [LSB]	strxfrm(GLIBC_2.2) [SUSv4]
bsd_signal(GLIBC_2.2) [SUSv3]	key_decryptsession(GLIBC_2.2)[SVID.4]	svc_getreqset(GLIBC_2.2) [SVID.4]
bsearch(GLIBC_2.2) [SUSv4]	kill(GLIBC_2.2)[LSB]	svc_register(GLIBC_2.2) [LSB]
btowc(GLIBC_2.2) [SUSv4]	killpg(GLIBC_2.2) [SUSv4]	svc_run(GLIBC_2.2) [LSB]
bzero(GLIBC_2.2) [SUSv3]	l64a(GLIBC_2.2) [SUSv4]	svc_sendreply(GLIBC_2.2)[LSB]
calloc(GLIBC_2.2) [SUSv4]	labs(GLIBC_2.2)[SUSv4]	svcerr_auth(GLIBC_2.2) [SVID.4]
callrpc(GLIBC_2.2)[RPC + XDR]	lchown(GLIBC_2.2) [SUSv4]	svcerr_decode(GLIBC_2.2)[SVID.4]

catclose(GLIBC_2.2) [SUSv4]	lcong48(GLIBC_2.2) [SUSv4]	svcerr_noproc(GLIBC_2.2)[SVID.4]
catgets(GLIBC_2.2) [SUSv4]	lcong48_r(GLIBC_2.2) [LSB]	svcerr_noprog(GLIBC_2.2)[SVID.4]
catopen(GLIBC_2.2) [SUSv4]	ldiv(GLIBC_2.2)[SUSv4]	svcerr_progvers(GLIBC_2.2)[SVID.4]
cfgetispeed(GLIBC_2.2) [SUSv4]	lfind(GLIBC_2.2) [SUSv4]	svcerr_systemerr(GLIBC_2.2)[SVID.4]
cfgetospeed(GLIBC_2.2) [SUSv4]	link(GLIBC_2.2)[LSB]	svcerr_weakauth(GLIBC_2.2)[SVID.4]
cfmakeraw(GLIBC_2.2) [LSB]	listen(GLIBC_2.2) [SUSv4]	svcfd_create(GLIBC_2.2) [RPC + XDR]
cfsetispeed(GLIBC_2.2) [SUSv4]	llabs(GLIBC_2.2) [SUSv4]	svcrw_create(GLIBC_2.2)[RPC + XDR]
cfsetospeed(GLIBC_2.2) [SUSv4]	lldiv(GLIBC_2.2) [SUSv4]	svctcp_create(GLIBC_2.2)[LSB]
cfsetspeed(GLIBC_2.2) [LSB]	localeconv(GLIBC_2.2) [SUSv4]	svcudp_create(GLIBC_2.2)[LSB]
chdir(GLIBC_2.2) [SUSv4]	localtime(GLIBC_2.2) [SUSv4]	swab(GLIBC_2.2) [SUSv4]
chmod(GLIBC_2.2) [SUSv4]	localtime_r(GLIBC_2.2) [SUSv4]	swapcontext(GLIBC_2.2) [SUSv3]
chown(GLIBC_2.2) [SUSv4]	lockf(GLIBC_2.2) [SUSv4]	swprintf(GLIBC_2.2) [SUSv4]
chroot(GLIBC_2.2) [SUSv2]	lockf64(GLIBC_2.2) [LFS]	swprintf(GLIBC_2.4) [SUSv4]
clearerr(GLIBC_2.2) [SUSv4]	longjmp(GLIBC_2.2) [SUSv4]	swscanf(GLIBC_2.2) [LSB]
clearerr_unlocked(GLIBC_2.2)[LSB]	lrand48(GLIBC_2.2) [SUSv4]	swscanf(GLIBC_2.4) [LSB]
clnt_create(GLIBC_2.2) [SVID.4]	lrand48_r(GLIBC_2.2) [LSB]	symlink(GLIBC_2.2) [SUSv4]
clnt_pcreateerror(GLIBC_2.2)[SVID.4]	lsearch(GLIBC_2.2) [SUSv4]	sync(GLIBC_2.2) [SUSv4]
clnt_perrno(GLIBC_2.2) [SVID.4]	lseek(GLIBC_2.2) [SUSv4]	sysconf(GLIBC_2.2) [LSB]
clnt_perror(GLIBC_2.2) [SVID.4]	lseek64(GLIBC_2.2) [LFS]	sysinfo(GLIBC_2.2) [LSB]
clnt_spcreateerror(GLIBC_2.2)[SVID.4]	makecontext(GLIBC_2.2) [SUSv3]	syslog(GLIBC_2.2) [SUSv4]
clnt_sperrno(GLIBC_2.2) [SVID.4]	malloc(GLIBC_2.2) [SUSv4]	syslog(GLIBC_2.4) [SUSv4]
clnt_sprror(GLIBC_2.2) [SVID.4]	mblen(GLIBC_2.2) [SUSv4]	system(GLIBC_2.2) [LSB]
clntraw_create(GLIBC_2.2)[RPC + XDR]	mbrlen(GLIBC_2.2) [SUSv4]	tcdrain(GLIBC_2.2) [SUSv4]
clnttcp_create(GLIBC_2.2)[RPC + XDR]	mbrtowc(GLIBC_2.2) [SUSv4]	tcflow(GLIBC_2.2) [SUSv4]
clntudp_bufcreate(GLIBC_2.2)[RPC + XDR]	mbsinit(GLIBC_2.2) [SUSv4]	tcflush(GLIBC_2.2) [SUSv4]

## LSB Core - S390X 5.0

clntudp_create(GLIBC_2.2) [RPC + XDR]	mbsnrtowcs(GLIBC_2.2) [SUSv4]	tcgetattr(GLIBC_2.2) [SUSv4]
clock(GLIBC_2.2) [SUSv4]	mbsrtowcs(GLIBC_2.2) [SUSv4]	tcgetpgrp(GLIBC_2.2) [SUSv4]
close(GLIBC_2.2) [SUSv4]	mbstowcs(GLIBC_2.2) [SUSv4]	tcgetsid(GLIBC_2.2) [SUSv4]
closedir(GLIBC_2.2) [SUSv4]	mbtowc(GLIBC_2.2) [SUSv4]	tcsendbreak(GLIBC_2.2) [SUSv4]
closelog(GLIBC_2.2) [SUSv4]	memccpy(GLIBC_2.2) [SUSv4]	tcsetattr(GLIBC_2.2) [SUSv4]
confstr(GLIBC_2.2) [SUSv4]	memchr(GLIBC_2.2) [SUSv4]	tcsetpgrp(GLIBC_2.2) [SUSv4]
connect(GLIBC_2.2) [SUSv4]	memcmp(GLIBC_2.2) [SUSv4]	tdelete(GLIBC_2.2) [SUSv4]
creat(GLIBC_2.2) [SUSv4]	memcpy(GLIBC_2.2) [SUSv4]	telldir(GLIBC_2.2) [SUSv4]
creat64(GLIBC_2.2) [LFS]	memmem(GLIBC_2.2) [LSB]	tempnam(GLIBC_2.2) [SUSv4]
ctermid(GLIBC_2.2) [SUSv4]	memmove(GLIBC_2.2) [SUSv4]	textdomain(GLIBC_2.2) [LSB]
ctime(GLIBC_2.2) [SUSv4]	memrchr(GLIBC_2.2) [LSB]	tfind(GLIBC_2.2) [SUSv4]
ctime_r(GLIBC_2.2) [SUSv4]	memset(GLIBC_2.2) [SUSv4]	time(GLIBC_2.2) [SUSv4]
cuserid(GLIBC_2.2) [SUSv2]	mkdir(GLIBC_2.2) [SUSv4]	times(GLIBC_2.2) [SUSv4]
daemon(GLIBC_2.2) [LSB]	mkdtemp(GLIBC_2.2) [SUSv4]	tmpfile(GLIBC_2.2) [SUSv4]
dcgettext(GLIBC_2.2) [LSB]	mkfifo(GLIBC_2.2) [SUSv4]	tmpfile64(GLIBC_2.2) [LFS]
dcngettext(GLIBC_2.2) [LSB]	mkstemp(GLIBC_2.2) [SUSv4]	tmpnam(GLIBC_2.2) [SUSv4]
dgettext(GLIBC_2.2) [LSB]	mkstemp64(GLIBC_2.2) [LSB]	toascii(GLIBC_2.2) [SUSv4]
difftime(GLIBC_2.2) [SUSv4]	mktemp(GLIBC_2.2) [SUSv3]	tolower(GLIBC_2.2) [SUSv4]
dirfd(GLIBC_2.2) [SUSv4]	mktimes(GLIBC_2.2) [SUSv4]	toupper(GLIBC_2.2) [SUSv4]
dirname(GLIBC_2.2) [SUSv4]	mlock(GLIBC_2.2) [SUSv4]	towctrans(GLIBC_2.2) [SUSv4]
div(GLIBC_2.2)[SUSv4]	mlockall(GLIBC_2.2) [SUSv4]	towlower(GLIBC_2.2) [SUSv4]
dl_iterate_phdr(GLIBC_2.2.4)[LSB]	mmap(GLIBC_2.2) [SUSv4]	towupper(GLIBC_2.2) [SUSv4]
dnggettext(GLIBC_2.2) [LSB]	mmap64(GLIBC_2.2) [LFS]	truncate(GLIBC_2.2) [SUSv4]
dprintf(GLIBC_2.4) [SUSv4]	mprotect(GLIBC_2.2) [SUSv4]	truncate64(GLIBC_2.2) [LFS]
drand48(GLIBC_2.2) [SUSv4]	mrand48(GLIBC_2.2) [SUSv4]	tsearch(GLIBC_2.2) [SUSv4]

drand48_r(GLIBC_2.2) [LSB]	mrand48_r(GLIBC_2.2) [LSB]	ttyname(GLIBC_2.2) [SUSv4]
dup(GLIBC_2.2)[SUSv4]	mremap(GLIBC_2.2) [LSB]	ttyname_r(GLIBC_2.2) [SUSv4]
dup2(GLIBC_2.2) [SUSv4]	msgctl(GLIBC_2.2) [SUSv4]	twalk(GLIBC_2.2) [SUSv4]
ecvt(GLIBC_2.2) [SUSv3]	msgget(GLIBC_2.2) [SUSv4]	tzset(GLIBC_2.2) [SUSv4]
endgrent(GLIBC_2.2) [SUSv4]	msgrcv(GLIBC_2.2) [SUSv4]	ualarm(GLIBC_2.2) [SUSv3]
endprotoent(GLIBC_2.2) [SUSv4]	msgsnd(GLIBC_2.2) [SUSv4]	ulimit(GLIBC_2.2) [SUSv4]
endpwent(GLIBC_2.2) [SUSv4]	msync(GLIBC_2.2) [SUSv4]	umask(GLIBC_2.2) [SUSv4]
endservent(GLIBC_2.2) [SUSv4]	munlock(GLIBC_2.2) [SUSv4]	uname(GLIBC_2.2) [SUSv4]
endutent(GLIBC_2.2) [LSB]	munlockall(GLIBC_2.2) [SUSv4]	ungetc(GLIBC_2.2) [SUSv4]
endutxent(GLIBC_2.2) [SUSv4]	munmap(GLIBC_2.2) [SUSv4]	ungetwc(GLIBC_2.2) [SUSv4]
envz_add(GLIBC_2.2) [LSB]	nanosleep(GLIBC_2.2) [SUSv4]	unlink(GLIBC_2.2)[LSB]
envz_entry(GLIBC_2.2) [LSB]	nftw(GLIBC_2.3.3) [SUSv4]	unlockpt(GLIBC_2.2) [SUSv4]
envz_get(GLIBC_2.2) [LSB]	nftw64(GLIBC_2.3.3) [LFS]	unsetenv(GLIBC_2.2) [SUSv4]
envz_merge(GLIBC_2.2) [LSB]	nggettext(GLIBC_2.2) [LSB]	usleep(GLIBC_2.2) [SUSv3]
envz_remove(GLIBC_2.2) [LSB]	nice(GLIBC_2.2) [SUSv4]	utime(GLIBC_2.2) [SUSv4]
envz_strip(GLIBC_2.2) [LSB]	nl_langinfo(GLIBC_2.2) [SUSv4]	utimes(GLIBC_2.2) [SUSv4]
erand48(GLIBC_2.2) [SUSv4]	nrand48(GLIBC_2.2) [SUSv4]	utmpname(GLIBC_2.2) [LSB]
erand48_r(GLIBC_2.2) [LSB]	nrand48_r(GLIBC_2.2) [LSB]	vasprintf(GLIBC_2.2) [LSB]
err(GLIBC_2.2)[LSB]	ntohl(GLIBC_2.2) [SUSv4]	vasprintf(GLIBC_2.4) [LSB]
error(GLIBC_2.2)[LSB]	ntohs(GLIBC_2.2) [SUSv4]	vdprintf(GLIBC_2.2) [SUSv4]
errx(GLIBC_2.2)[LSB]	open(GLIBC_2.2) [SUSv4]	vdprintf(GLIBC_2.4) [SUSv4]
execl(GLIBC_2.2) [SUSv4]	open64(GLIBC_2.2) [LFS]	verrx(GLIBC_2.2)[LSB]
execlp(GLIBC_2.2) [SUSv4]	open_memstream(GLIBC_2.2)[SUSv4]	vfork(GLIBC_2.2) [SUSv3]
execv(GLIBC_2.2) [SUSv4]	opendir(GLIBC_2.2) [SUSv4]	vfprintf(GLIBC_2.2) [SUSv4]
	openlog(GLIBC_2.2) [SUSv4]	vfprintf(GLIBC_2.4) [SUSv4]

execve(GLIBC_2.2) [SUSv4]	pathconf(GLIBC_2.2) [SUSv4]	vfscanf(GLIBC_2.2) [LSB]
execvp(GLIBC_2.2) [SUSv4]	pause(GLIBC_2.2) [SUSv4]	vfscanf(GLIBC_2.4) [LSB]
exit(GLIBC_2.2)[SUSv4]	pclose(GLIBC_2.2) [SUSv4]	vfwprintf(GLIBC_2.2) [SUSv4]
fchdir(GLIBC_2.2) [SUSv4]	perror(GLIBC_2.2) [SUSv4]	vfwprintf(GLIBC_2.4) [SUSv4]
fchmod(GLIBC_2.2) [SUSv4]	pipe(GLIBC_2.2) [SUSv4]	vfwscanf(GLIBC_2.2) [LSB]
fchown(GLIBC_2.2) [SUSv4]	pmap_getport(GLIBC_2. 2)[LSB]	vfwscanf(GLIBC_2.4) [LSB]
fclose(GLIBC_2.2) [SUSv4]	pmap_set(GLIBC_2.2) [LSB]	vprintf(GLIBC_2.2) [SUSv4]
fcntl(GLIBC_2.2)[LSB]	pmap_unset(GLIBC_2.2) [LSB]	vprintf(GLIBC_2.4) [SUSv4]
fcvt(GLIBC_2.2)[SUSv3]	poll(GLIBC_2.2)[SUSv4]	vscanf(GLIBC_2.2)[LSB]
fdasynchrn(GLIBC_2.2) [SUSv4]	popen(GLIBC_2.2) [SUSv4]	vscanf(GLIBC_2.4)[LSB]
fdopen(GLIBC_2.2) [SUSv4]	posix_fadvise(GLIBC_2. 2)[SUSv4]	vsnprintf(GLIBC_2.2) [SUSv4]
feof(GLIBC_2.2)[SUSv4]	posix_fadvise64(GLIBC_ 2.2)[LSB]	vsnprintf(GLIBC_2.4) [SUSv4]
feof_unlocked(GLIBC_2. 2)[LSB]	posix_fallocate(GLIBC_2 .2)[SUSv4]	vsprintf(GLIBC_2.2) [SUSv4]
ferror(GLIBC_2.2) [SUSv4]	posix_fallocate64(GLIBC_ 2.2)[LSB]	vsprintf(GLIBC_2.4) [SUSv4]
ferror_unlocked(GLIBC_ 2.2)[LSB]	posix_madvise(GLIBC_2. 2)[SUSv4]	vsscanf(GLIBC_2.2) [LSB]
fexecve(GLIBC_2.2) [SUSv4]	posix_memalign(GLIBC_2. 2)[SUSv4]	vsscanf(GLIBC_2.4) [LSB]
fflush(GLIBC_2.2) [SUSv4]	posix_openpt(GLIBC_2.2 .1)[SUSv4]	vswprintf(GLIBC_2.2) [SUSv4]
fflush_unlocked(GLIBC_ 2.2)[LSB]	posix_spawn(GLIBC_2.1 5)[SUSv4]	vswprintf(GLIBC_2.4) [SUSv4]
ffs(GLIBC_2.2)[SUSv4]	posix_spawn_file_actions _addclose(GLIBC_2.2) [SUSv4]	vswscanf(GLIBC_2.2) [LSB]
fgetc(GLIBC_2.2) [SUSv4]	posix_spawn_file_actions _adddup2(GLIBC_2.2) [SUSv4]	vswscanf(GLIBC_2.4) [LSB]
fgetc_unlocked(GLIBC_2. 2)[LSB]	posix_spawn_file_actions _addopen(GLIBC_2.2) [SUSv4]	vsyslog(GLIBC_2.2) [LSB]
fgetpos(GLIBC_2.2) [SUSv4]	posix_spawn_file_actions _destroy(GLIBC_2.2) [SUSv4]	vsyslog(GLIBC_2.4) [LSB]
fgetpos64(GLIBC_2.2) [LFS]	posix_spawn_file_actions _init(GLIBC_2.2) [SUSv4]	vwprintf(GLIBC_2.2) [SUSv4]

## Interfaces by Library

fgets(GLIBC_2.2) [SUSv4]	posix_spawnattr_destroy(GLIBC_2.2) [SUSv4]	vwprintf(GLIBC_2.4) [SUSv4]
fgets_unlocked(GLIBC_2.2) [LSB]	posix_spawnattr_getflags(GLIBC_2.2) [SUSv4]	vwscanf(GLIBC_2.2) [LSB]
fgetwc(GLIBC_2.2) [SUSv4]	posix_spawnattr_getpgroup(GLIBC_2.2) [SUSv4]	vwscanf(GLIBC_2.4) [LSB]
fgetwc_unlocked(GLIBC_2.2) [LSB]	posix_spawnattr_getschedparam(GLIBC_2.2) [SUSv4]	wait(GLIBC_2.2) [SUSv4]
fgetws(GLIBC_2.2) [SUSv4]	posix_spawnattr_getschedpolicy(GLIBC_2.2) [SUSv4]	wait4(GLIBC_2.2) [LSB]
fgetws_unlocked(GLIBC_2.2) [LSB]	posix_spawnattr_getsigdefault(GLIBC_2.2) [SUSv4]	waitid(GLIBC_2.2) [SUSv4]
fileno(GLIBC_2.2) [SUSv4]	posix_spawnattr_getsigmask(GLIBC_2.2) [SUSv4]	waitpid(GLIBC_2.2) [SUSv4]
fileno_unlocked(GLIBC_2.2) [LSB]	posix_spawnattr_init(GLIBC_2.2) [SUSv4]	warn(GLIBC_2.2) [LSB]
flock(GLIBC_2.2) [LSB]	posix_spawnattr_setflags(GLIBC_2.2) [SUSv4]	warnx(GLIBC_2.2) [LSB]
flockfile(GLIBC_2.2) [SUSv4]	posix_spawnattr_setpgroup(GLIBC_2.2) [SUSv4]	wcpncpy(GLIBC_2.2) [SUSv4]
fmemopen(GLIBC_2.2) [SUSv4]	posix_spawnattr_setschedparam(GLIBC_2.2) [SUSv4]	wcpncpy(GLIBC_2.2) [SUSv4]
fmtmsg(GLIBC_2.2) [SUSv4]	posix_spawnattr_setschedpolicy(GLIBC_2.2) [SUSv4]	wcrtomb(GLIBC_2.2) [SUSv4]
fnmatch(GLIBC_2.2.3) [LSB]	posix_spawnattr_setsigdefault(GLIBC_2.2) [SUSv4]	wescasecmp(GLIBC_2.2) [SUSv4]
fopen(GLIBC_2.2) [SUSv4]	posix_spawnattr_setsigmaask(GLIBC_2.2) [SUSv4]	wcscat(GLIBC_2.2) [SUSv4]
fopen64(GLIBC_2.2) [LFS]	posix_spawnp(GLIBC_2.15) [SUSv4]	wcschr(GLIBC_2.2) [SUSv4]
fork(GLIBC_2.2) [SUSv4]	pread(GLIBC_2.2) [SUSv4]	wcscmp(GLIBC_2.2) [SUSv4]
fpathconf(GLIBC_2.2) [SUSv4]	pread64(GLIBC_2.2) [LSB]	wescoll(GLIBC_2.2) [SUSv4]
fprintf(GLIBC_2.2) [SUSv4]	printf(GLIBC_2.2) [SUSv4]	wescpy(GLIBC_2.2) [SUSv4]
fprintf(GLIBC_2.4) [SUSv4]	printf(GLIBC_2.4) [SUSv4]	wcscspn(GLIBC_2.2) [SUSv4]
fputc(GLIBC_2.2) [SUSv4]	pselect(GLIBC_2.2) [SUSv4]	wcsdup(GLIBC_2.2) [SUSv4]
fputc_unlocked(GLIBC_2.2) [LSB]	psignal(GLIBC_2.2) [SUSv4]	wcsftime(GLIBC_2.2) [SUSv4]
fputs(GLIBC_2.2) [SUSv4]	ptrace(GLIBC_2.2) [LSB]	wcslen(GLIBC_2.2) [SUSv4]

## LSB Core - S390X 5.0

fputs_unlocked(GLIBC_2.2)[ <a href="#">LSB</a> ]	ptsname(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	wcsncasecmp(GLIBC_2.2) [ <a href="#">SUSv4</a> ]
fputwc(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	putc(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	wcsncat(GLIBC_2.2) [ <a href="#">SUSv4</a> ]
fputwc_unlocked(GLIBC_2.2)[ <a href="#">LSB</a> ]	putc_unlocked(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	wcsncmp(GLIBC_2.2) [ <a href="#">SUSv4</a> ]
fputws(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	putchar(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	wcsncpy(GLIBC_2.2) [ <a href="#">SUSv4</a> ]
fputws_unlocked(GLIBC_2.2)[ <a href="#">LSB</a> ]	putchar_unlocked(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	wcsnlen(GLIBC_2.2) [ <a href="#">SUSv4</a> ]
fread(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	putenv(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	wcsnrtombs(GLIBC_2.2) [ <a href="#">SUSv4</a> ]
fread_unlocked(GLIBC_2.2)[ <a href="#">LSB</a> ]	puts(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	wcsnbrk(GLIBC_2.2) [ <a href="#">SUSv4</a> ]
free(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	pututxline(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	wcsrchr(GLIBC_2.2) [ <a href="#">SUSv4</a> ]
freeaddrinfo(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	putw(GLIBC_2.2) [ <a href="#">SUSv2</a> ]	wcsrtomb(GLIBC_2.2) [ <a href="#">SUSv4</a> ]
freopen(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	putwc(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	wcsspn(GLIBC_2.2) [ <a href="#">SUSv4</a> ]
freopen64(GLIBC_2.2) [ <a href="#">LFS</a> ]	putwc_unlocked(GLIBC_2.2)[ <a href="#">LSB</a> ]	wcsstr(GLIBC_2.2) [ <a href="#">SUSv4</a> ]
fscanf(GLIBC_2.2)[ <a href="#">LSB</a> ]	putwchar(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	wcstod(GLIBC_2.2) [ <a href="#">SUSv4</a> ]
fscanf(GLIBC_2.4)[ <a href="#">LSB</a> ]	putwchar_unlocked(GLIBC_2.2)[ <a href="#">LSB</a> ]	wcstof(GLIBC_2.2) [ <a href="#">SUSv4</a> ]
fseek(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	pwrite(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	wcstoimax(GLIBC_2.2) [ <a href="#">SUSv4</a> ]
fseeko(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	pwrite64(GLIBC_2.2) [ <a href="#">LSB</a> ]	wcstok(GLIBC_2.2) [ <a href="#">SUSv4</a> ]
fseeko64(GLIBC_2.2) [ <a href="#">LFS</a> ]	qsort(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	wcstol(GLIBC_2.2) [ <a href="#">SUSv4</a> ]
fsetpos(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	raise(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	wcstold(GLIBC_2.2) [ <a href="#">SUSv4</a> ]
fsetpos64(GLIBC_2.2) [ <a href="#">LFS</a> ]	rand(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	wcstold(GLIBC_2.4) [ <a href="#">SUSv4</a> ]
fstatfs(GLIBC_2.2)[ <a href="#">LSB</a> ]	rand_r(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	wcstoll(GLIBC_2.2) [ <a href="#">SUSv4</a> ]
fstatfs64(GLIBC_2.2) [ <a href="#">LSB</a> ]	random(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	wcsrtomb(GLIBC_2.2) [ <a href="#">SUSv4</a> ]
fstatvfs(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	random_r(GLIBC_2.2) [ <a href="#">LSB</a> ]	wcstoq(GLIBC_2.2) [ <a href="#">LSB</a> ]
fstatvfs64(GLIBC_2.2) [ <a href="#">LFS</a> ]	read(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	wcstoul(GLIBC_2.2) [ <a href="#">SUSv4</a> ]
fsync(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	readdir(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	wcstoull(GLIBC_2.2) [ <a href="#">SUSv4</a> ]
ftell(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	readdir64(GLIBC_2.2) [ <a href="#">LFS</a> ]	wcstoumax(GLIBC_2.2) [ <a href="#">SUSv4</a> ]
ftello(GLIBC_2.2) [ <a href="#">SUSv4</a> ]	readdir64_r(GLIBC_2.2) [ <a href="#">LSB</a> ]	wcstouq(GLIBC_2.2) [ <a href="#">LSB</a> ]

ftello64(GLIBC_2.2) [LFS]	readdir_r(GLIBC_2.2) [SUSv4]	wcswcs(GLIBC_2.2) [SUSv3]
ftime(GLIBC_2.2) [SUSv3]	readlink(GLIBC_2.2) [SUSv4]	wcswidth(GLIBC_2.2) [SUSv4]
ftok(GLIBC_2.2)[SUSv4]	readv(GLIBC_2.2) [SUSv4]	wcsxfrm(GLIBC_2.2) [SUSv4]
ftruncate(GLIBC_2.2) [SUSv4]	realloc(GLIBC_2.2) [SUSv4]	wctob(GLIBC_2.2) [SUSv4]
ftruncate64(GLIBC_2.2) [LFS]	realpath(GLIBC_2.3) [SUSv4]	wctomb(GLIBC_2.2) [SUSv4]
ftrylockfile(GLIBC_2.2) [SUSv4]	recv(GLIBC_2.2) [SUSv4]	wctrans(GLIBC_2.2) [SUSv4]
ftw(GLIBC_2.2)[SUSv4]	recvfrom(GLIBC_2.2) [SUSv4]	wctype(GLIBC_2.2) [SUSv4]
ftw64(GLIBC_2.2)[LFS]	recvmsg(GLIBC_2.2) [SUSv4]	wcwidth(GLIBC_2.2) [SUSv4]
funlockfile(GLIBC_2.2) [SUSv4]	regcomp(GLIBC_2.2) [SUSv4]	wmemchr(GLIBC_2.2) [SUSv4]
fwide(GLIBC_2.2) [SUSv4]	regetror(GLIBC_2.2) [SUSv4]	wmemcmp(GLIBC_2.2) [SUSv4]
fwprintf(GLIBC_2.2) [SUSv4]	regexec(GLIBC_2.3.4) [LSB]	wmemcpy(GLIBC_2.2) [SUSv4]
fwprintf(GLIBC_2.4) [SUSv4]	regfree(GLIBC_2.2) [SUSv4]	wmemmove(GLIBC_2.2) [SUSv4]
fwrite(GLIBC_2.2) [SUSv4]	remove(GLIBC_2.2) [SUSv4]	wmemset(GLIBC_2.2) [SUSv4]
fwrite_unlocked(GLIBC_2.2)[LSB]	remque(GLIBC_2.2) [SUSv4]	wordexp(GLIBC_2.2) [SUSv4]
fwscanf(GLIBC_2.2) [LSB]	rename(GLIBC_2.2) [SUSv4]	wordfree(GLIBC_2.2) [SUSv4]
fwscanf(GLIBC_2.4) [LSB]	rewind(GLIBC_2.2) [SUSv4]	wprintf(GLIBC_2.2) [SUSv4]
gai_strerror(GLIBC_2.2) [SUSv4]	rewinddir(GLIBC_2.2) [SUSv4]	wprintf(GLIBC_2.4) [SUSv4]
gcvt(GLIBC_2.2) [SUSv3]	rindex(GLIBC_2.2) [SUSv3]	write(GLIBC_2.2) [SUSv4]
getaddrinfo(GLIBC_2.2) [SUSv4]	rmdir(GLIBC_2.2) [SUSv4]	writev(GLIBC_2.2) [SUSv4]
getc(GLIBC_2.2) [SUSv4]	sbrk(GLIBC_2.2) [SUSv2]	wscanf(GLIBC_2.2) [LSB]
getc_unlocked(GLIBC_2.2)[SUSv4]	scandir(GLIBC_2.2) [SUSv4]	wscanf(GLIBC_2.4) [LSB]
getchar(GLIBC_2.2) [SUSv4]	scandir64(GLIBC_2.2) [LSB]	xdr_accepted_reply(GLIB C_2.2)[SVID.4]
getchar_unlocked(GLIBC_2.2)[SUSv4]	scanf(GLIBC_2.2)[LSB]	xdr_array(GLIBC_2.2) [SVID.4]
getcontext(GLIBC_2.2) [SUSv3]	scanf(GLIBC_2.4)[LSB]	xdr_bool(GLIBC_2.2) [SVID.4]
getcwd(GLIBC_2.2) [LSB]	sched_get_priority_max(GLIBC_2.2)[SUSv4]	xdr_bytes(GLIBC_2.2) [SVID.4]

getdate(GLIBC_2.2) [SUSv4]	sched_get_priority_min(GLIBC_2.2)[SUSv4]	xdr_callhdr(GLIBC_2.2) [SVID.4]
getdelim(GLIBC_2.2) [SUSv4]	sched_getparam(GLIBC_2.2)[SUSv4]	xdr_callmsg(GLIBC_2.2) [SVID.4]
getdomainname(GLIBC_2.2)[LSB]	sched_getscheduler(GLIBC_2.2)[SUSv4]	xdr_char(GLIBC_2.2) [SVID.4]
getdtblsize(GLIBC_2.2) [LSB]	sched_rr_get_interval(GLIBC_2.2)[SUSv4]	xdr_double(GLIBC_2.2) [SVID.4]
getegid(GLIBC_2.2) [SUSv4]	sched_setparam(GLIBC_2.2)[SUSv4]	xdr_enum(GLIBC_2.2) [SVID.4]
getenv(GLIBC_2.2) [SUSv4]	sched_setscheduler(GLIBC_2.2)[LSB]	xdr_float(GLIBC_2.2) [SVID.4]
geteuid(GLIBC_2.2) [SUSv4]	sched_yield(GLIBC_2.2) [SUSv4]	xdr_free(GLIBC_2.2) [SVID.4]
getgid(GLIBC_2.2) [SUSv4]	seed48(GLIBC_2.2) [SUSv4]	xdr_int(GLIBC_2.2) [SVID.4]
getrent(GLIBC_2.2) [SUSv4]	seed48_r(GLIBC_2.2) [LSB]	xdr_long(GLIBC_2.2) [SVID.4]
getrent_r(GLIBC_2.2) [LSB]	seekdir(GLIBC_2.2) [SUSv4]	xdr_opaque(GLIBC_2.2) [SVID.4]
getrgid(GLIBC_2.2) [SUSv4]	select(GLIBC_2.2) [SUSv4]	xdr_opaque_auth(GLIBC_2.2)[SVID.4]
getrgid_r(GLIBC_2.2) [SUSv4]	semctl(GLIBC_2.2) [SUSv4]	xdr_pointer(GLIBC_2.2) [SVID.4]
getgrnam(GLIBC_2.2) [SUSv4]	semget(GLIBC_2.2) [SUSv4]	xdr_reference(GLIBC_2.2)[SVID.4]
getgrnam_r(GLIBC_2.2) [SUSv4]	semop(GLIBC_2.2) [SUSv4]	xdr_rejected_reply(GLIBC_2.2)[SVID.4]
getgrouplist(GLIBC_2.2. 4)[LSB]	send(GLIBC_2.2) [SUSv4]	xdr_replymsg(GLIBC_2.2)[SVID.4]
getgroups(GLIBC_2.2) [SUSv4]	sendfile(GLIBC_2.2) [LSB]	xdr_short(GLIBC_2.2) [SVID.4]
gethostbyaddr(GLIBC_2. 2)[SUSv3]	sendmsg(GLIBC_2.2) [SUSv4]	xdr_string(GLIBC_2.2) [SVID.4]
gethostbyaddr_r(GLIBC_2. 2)[LSB]	sendto(GLIBC_2.2) [SUSv4]	xdr_u_char(GLIBC_2.2) [SVID.4]
gethostbyname(GLIBC_2. 2)[SUSv3]	setbuf(GLIBC_2.2) [SUSv4]	xdr_u_int(GLIBC_2.2) [LSB]
gethostbyname2(GLIBC_2. 2)[LSB]	setbuffer(GLIBC_2.2) [LSB]	xdr_u_long(GLIBC_2.2) [SVID.4]
gethostbyname2_r(GLIB C_2.2)[LSB]	setcontext(GLIBC_2.2) [SUSv3]	xdr_u_short(GLIBC_2.2) [SVID.4]
gethostbyname_r(GLIBC_2. 2)[LSB]	setegid(GLIBC_2.2) [SUSv4]	xdr_union(GLIBC_2.2) [SVID.4]
gethostid(GLIBC_2.2) [SUSv4]	setenv(GLIBC_2.2) [SUSv4]	xdr_vector(GLIBC_2.2) [SVID.4]
gethostname(GLIBC_2.2) [SUSv4]	seteuid(GLIBC_2.2) [SUSv4]	xdr_void(GLIBC_2.2) [SVID.4]
getitimer(GLIBC_2.2) [SUSv4]	setgid(GLIBC_2.2) [SUSv4]	xdr_wrapstring(GLIBC_2. 2)[SVID.4]

getline(GLIBC_2.2) [SUSv4]	setgrent(GLIBC_2.2) [SUSv4]	xdrmem_create(GLIBC_2.2)[SVID.4]
getloadavg(GLIBC_2.2) [LSB]	setgroups(GLIBC_2.2) [LSB]	xdrrec_create(GLIBC_2.2)[SVID.4]
getlogin(GLIBC_2.2) [SUSv4]	sethostname(GLIBC_2.2) [LSB]	xdrrec_endofrecord(GLIBC_2.2)[RPC + XDR]
getlogin_r(GLIBC_2.2) [SUSv4]	settimer(GLIBC_2.2) [SUSv4]	xdrrec_eof(GLIBC_2.2)[SVID.4]
getnameinfo(GLIBC_2.2) [SUSv4]	setlocale(GLIBC_2.2) [SUSv4]	xdrrec_skiprecord(GLIBC_2.2)[RPC + XDR]
getopt(GLIBC_2.2)[LSB]	setlogmask(GLIBC_2.2) [SUSv4]	xdrstdio_create(GLIBC_2.2)[LSB]
getopt_long(GLIBC_2.2) [LSB]	setpgid(GLIBC_2.2) [SUSv4]	
getopt_long_only(GLIBC_2.2)[LSB]	setpgrp(GLIBC_2.2) [SUSv4]	

**Table A-2 libc Data Interfaces**

__daylight[LSB]	__tzname[LSB]	in6addr_loopback[SUSv3]
__environ[LSB]	__sys_errlist[LSB]	
__timezone[LSB]	in6addr_any[SUSv3]	

## A.2 libcrypt

The behavior of the interfaces in this library is specified by the following Standards.

[LSB Core - Generic](#) [LSB]

[POSIX 1003.1-2008 \(ISO/IEC 9945-2009\)](#) [SUSv4]

**Table A-3 libcrypt Function Interfaces**

crypt(GLIBC_2.2) [SUSv4]	encrypt(GLIBC_2.2) [SUSv4]	setkey(GLIBC_2.2) [SUSv4]
crypt_r(GLIBC_2.2) [LSB]	encrypt_r(GLIBC_2.2) [LSB]	setkey_r(GLIBC_2.2) [LSB]

## A.3 libdl

The behavior of the interfaces in this library is specified by the following Standards.

[LSB Core - Generic](#) [LSB]

[POSIX 1003.1-2008 \(ISO/IEC 9945-2009\)](#) [SUSv4]

**Table A-4 libdl Function Interfaces**

dladdr(GLIBC_2.2)[LSB]	dlerror(GLIBC_2.2) [SUSv4]	dlsym(GLIBC_2.2)[LSB]
dlclose(GLIBC_2.2) [SUSv4]	dlopen(GLIBC_2.2) [LSB]	dlvsym(GLIBC_2.2) [LSB]

## A.4 libgcc\_s

The behavior of the interfaces in this library is specified by the following Standards.

[LSB Core - Generic](#) [LSB]

**Table A-5 libgcc\_s Function Interfaces**

_Unwind_Backtrace(GC)	_Unwind_GetDataRelBas	_Unwind_RaiseException
-----------------------	-----------------------	------------------------

<a href="#">C_3.3)[LSB]</a>	<a href="#">e(GCC_3.0)[LSB]</a>	<a href="#">(GCC_3.0)[LSB]</a>
<a href="#">_Unwind_DeleteException(GCC_3.0)[LSB]</a>	<a href="#">_Unwind_GetGR(GCC_3.0)[LSB]</a>	<a href="#">_Unwind_Resume(GCC_3.0)[LSB]</a>
<a href="#">_Unwind_FindEnclosingFunction(GCC_3.3)[LSB]</a>	<a href="#">_Unwind_GetIP(GCC_3.0)[LSB]</a>	<a href="#">_Unwind_Resume_or_Rethrow(GCC_3.3)[LSB]</a>
<a href="#">_Unwind_Find_FDE(GCC_3.0)[LSB]</a>	<a href="#">_Unwind_GetLanguageSpecificData(GCC_3.0)[LSB]</a>	<a href="#">_Unwind_SetGR(GCC_3.0)[LSB]</a>
<a href="#">_Unwind_ForcedUnwind(GCC_3.0)[LSB]</a>	<a href="#">_Unwind_GetRegionStart(GCC_3.0)[LSB]</a>	<a href="#">_Unwind_SetIP(GCC_3.0)[LSB]</a>
<a href="#">_Unwind_GetCFA(GCC_3.3)[LSB]</a>	<a href="#">_Unwind_GetTextRelBase(GCC_3.0)[LSB]</a>	

## A.5 libm

The behavior of the interfaces in this library is specified by the following Standards.

[LSB Core - Generic](#) [LSB]

[POSIX 1003.1-2001 \(ISO/IEC 9945-2003\)](#) [SUSv3]

[POSIX 1003.1-2008 \(ISO/IEC 9945-2009\)](#) [SUSv4]

**Table A-6 libm Function Interfaces**

<a href="#">__finite(GLIBC_2.2)[LSB]</a>	<a href="#">csinl(GLIBC_2.2)[SUSv4]</a>	<a href="#">log10(GLIBC_2.2)[SUSv4]</a>
<a href="#">__finitef(GLIBC_2.2)[LSB]</a>	<a href="#">csinl(GLIBC_2.4)[SUSv4]</a>	<a href="#">log10f(GLIBC_2.2)[SUSv4]</a>
<a href="#">__finitel(GLIBC_2.2)[LSB]</a>	<a href="#">csqrtl(GLIBC_2.2)[SUSv4]</a>	<a href="#">log10l(GLIBC_2.2)[SUSv4]</a>
<a href="#">__finitel(GLIBC_2.4)[LSB]</a>	<a href="#">csqrfl(GLIBC_2.2)[SUSv4]</a>	<a href="#">log10l(GLIBC_2.4)[SUSv4]</a>
<a href="#">__fpclassify(GLIBC_2.2)[LSB]</a>	<a href="#">csqrfl(GLIBC_2.2)[SUSv4]</a>	<a href="#">log1p(GLIBC_2.2)[SUSv4]</a>
<a href="#">__fpclassifyf(GLIBC_2.2)[LSB]</a>	<a href="#">csqrfl(GLIBC_2.4)[SUSv4]</a>	<a href="#">log1pf(GLIBC_2.2)[SUSv4]</a>
<a href="#">__fpclassifyl(GLIBC_2.4)[LSB]</a>	<a href="#">ctanl(GLIBC_2.2)[SUSv4]</a>	<a href="#">log1pl(GLIBC_2.2)[SUSv4]</a>
<a href="#">__signbit(GLIBC_2.2)[LSB]</a>	<a href="#">ctanf(GLIBC_2.2)[SUSv4]</a>	<a href="#">log1pl(GLIBC_2.4)[SUSv4]</a>
<a href="#">__signbitf(GLIBC_2.2)[LSB]</a>	<a href="#">ctanhf(GLIBC_2.2)[SUSv4]</a>	<a href="#">log2(GLIBC_2.2)[SUSv4]</a>
<a href="#">__signbitl(GLIBC_2.4)[LSB]</a>	<a href="#">ctanhf(GLIBC_2.2)[SUSv4]</a>	<a href="#">log2f(GLIBC_2.2)[SUSv4]</a>
<a href="#">acos(GLIBC_2.2)[SUSv4]</a>	<a href="#">ctanhf(GLIBC_2.2)[SUSv4]</a>	<a href="#">log2l(GLIBC_2.2)[SUSv4]</a>
<a href="#">acosf(GLIBC_2.2)[SUSv4]</a>	<a href="#">ctanhf(GLIBC_2.4)[SUSv4]</a>	<a href="#">log2l(GLIBC_2.4)[SUSv4]</a>
<a href="#">acosh(GLIBC_2.2)[SUSv4]</a>	<a href="#">ctanl(GLIBC_2.2)[SUSv4]</a>	<a href="#">logb(GLIBC_2.2)[SUSv4]</a>
<a href="#">acoshf(GLIBC_2.2)[SUSv4]</a>	<a href="#">ctanl(GLIBC_2.4)[SUSv4]</a>	<a href="#">logbf(GLIBC_2.2)[SUSv4]</a>
<a href="#">acoshl(GLIBC_2.2)[SUSv4]</a>	<a href="#">drem(GLIBC_2.2)[LSB]</a>	<a href="#">logbl(GLIBC_2.2)[SUSv4]</a>

<code>acosh(GLIBC_2.4) [SUSv4]</code>	<code>dremf(GLIBC_2.2) [LSB]</code>	<code>logl(GLIBC_2.4) [SUSv4]</code>
<code>acos(GLIBC_2.2) [SUSv4]</code>	<code>dreml(GLIBC_2.2) [LSB]</code>	<code>logf(GLIBC_2.2) [SUSv4]</code>
<code>acosl(GLIBC_2.4) [SUSv4]</code>	<code>dreml(GLIBC_2.4) [LSB]</code>	<code>logl(GLIBC_2.2) [SUSv4]</code>
<code>asin(GLIBC_2.2) [SUSv4]</code>	<code>erf(GLIBC_2.2) [SUSv4]</code>	<code>logl(GLIBC_2.4) [SUSv4]</code>
<code>asinf(GLIBC_2.2) [SUSv4]</code>	<code>erfc(GLIBC_2.2) [SUSv4]</code>	<code>lrint(GLIBC_2.2) [SUSv4]</code>
<code>asinh(GLIBC_2.2) [SUSv4]</code>	<code>erfcf(GLIBC_2.2) [SUSv4]</code>	<code>lrintf(GLIBC_2.2) [SUSv4]</code>
<code>asinhf(GLIBC_2.2) [SUSv4]</code>	<code>erfc1(GLIBC_2.2) [SUSv4]</code>	<code>lrintl(GLIBC_2.2) [SUSv4]</code>
<code>asinhl(GLIBC_2.2) [SUSv4]</code>	<code>erfc1(GLIBC_2.4) [SUSv4]</code>	<code>lrintl(GLIBC_2.4) [SUSv4]</code>
<code>asinhl(GLIBC_2.4) [SUSv4]</code>	<code>erff(GLIBC_2.2) [SUSv4]</code>	<code>lround(GLIBC_2.2) [SUSv4]</code>
<code>asinl(GLIBC_2.2) [SUSv4]</code>	<code>erfl(GLIBC_2.2) [SUSv4]</code>	<code>lroundf(GLIBC_2.2) [SUSv4]</code>
<code>asinl(GLIBC_2.4) [SUSv4]</code>	<code>erfl(GLIBC_2.4) [SUSv4]</code>	<code>lroundl(GLIBC_2.2) [SUSv4]</code>
<code>atan(GLIBC_2.2) [SUSv4]</code>	<code>exp(GLIBC_2.2) [SUSv4]</code>	<code>lroundl(GLIBC_2.4) [SUSv4]</code>
<code>atan2(GLIBC_2.2) [SUSv4]</code>	<code>exp10(GLIBC_2.2) [LSB]</code>	<code>matherr(GLIBC_2.2) [LSB]</code>
<code>atan2f(GLIBC_2.2) [SUSv4]</code>	<code>exp10f(GLIBC_2.2) [LSB]</code>	<code>modf(GLIBC_2.2) [SUSv4]</code>
<code>atan2l(GLIBC_2.2) [SUSv4]</code>	<code>exp10l(GLIBC_2.2) [LSB]</code>	<code>modff(GLIBC_2.2) [SUSv4]</code>
<code>atan2l(GLIBC_2.4) [SUSv4]</code>	<code>exp10l(GLIBC_2.4) [LSB]</code>	<code>modfl(GLIBC_2.2) [SUSv4]</code>
<code>atanf(GLIBC_2.2) [SUSv4]</code>	<code>exp2(GLIBC_2.2) [SUSv4]</code>	<code>modfl(GLIBC_2.4) [SUSv4]</code>
<code>atanh(GLIBC_2.2) [SUSv4]</code>	<code>exp2f(GLIBC_2.2) [SUSv4]</code>	<code>nan(GLIBC_2.2) [SUSv4]</code>
<code>atanhf(GLIBC_2.2) [SUSv4]</code>	<code>exp2l(GLIBC_2.4) [SUSv4]</code>	<code>nanf(GLIBC_2.2) [SUSv4]</code>
<code>atanhl(GLIBC_2.2) [SUSv4]</code>	<code>expf(GLIBC_2.2) [SUSv4]</code>	<code>nanl(GLIBC_2.2) [SUSv4]</code>
<code>atanhl(GLIBC_2.4) [SUSv4]</code>	<code>expl(GLIBC_2.2) [SUSv4]</code>	<code>nanl(GLIBC_2.4) [SUSv4]</code>
<code>atanl(GLIBC_2.2) [SUSv4]</code>	<code>expl(GLIBC_2.4) [SUSv4]</code>	<code>nearbyint(GLIBC_2.2) [SUSv4]</code>
<code>atanl(GLIBC_2.4) [SUSv4]</code>	<code>expml(GLIBC_2.2) [SUSv4]</code>	<code>nearbyintf(GLIBC_2.2) [SUSv4]</code>
<code>cabs(GLIBC_2.2) [SUSv4]</code>	<code>expmlf(GLIBC_2.2) [SUSv4]</code>	<code>nearbyintl(GLIBC_2.2) [SUSv4]</code>
<code>cabsf(GLIBC_2.2) [SUSv4]</code>	<code>expml1(GLIBC_2.2) [SUSv4]</code>	<code>nearbyintl(GLIBC_2.4) [SUSv4]</code>

cabsl(GLIBC_2.2) <a href="#">[SUSv4]</a>	expm1l(GLIBC_2.4) <a href="#">[SUSv4]</a>	nextafter(GLIBC_2.2) <a href="#">[SUSv4]</a>
cabsl(GLIBC_2.4) <a href="#">[SUSv4]</a>	fabs(GLIBC_2.2) <a href="#">[SUSv4]</a>	nextafterf(GLIBC_2.2) <a href="#">[SUSv4]</a>
cacos(GLIBC_2.2) <a href="#">[SUSv4]</a>	fabsf(GLIBC_2.2) <a href="#">[SUSv4]</a>	nextafterl(GLIBC_2.2) <a href="#">[SUSv4]</a>
cacosf(GLIBC_2.2) <a href="#">[SUSv4]</a>	fabsl(GLIBC_2.2) <a href="#">[SUSv4]</a>	nextafterl(GLIBC_2.4) <a href="#">[SUSv4]</a>
cacosh(GLIBC_2.2) <a href="#">[SUSv4]</a>	fabsl(GLIBC_2.4) <a href="#">[SUSv4]</a>	nexttoward(GLIBC_2.2) <a href="#">[SUSv4]</a>
cacoshf(GLIBC_2.2) <a href="#">[SUSv4]</a>	fdim(GLIBC_2.2) <a href="#">[SUSv4]</a>	nexttoward(GLIBC_2.4) <a href="#">[SUSv4]</a>
cacoshl(GLIBC_2.2) <a href="#">[SUSv4]</a>	fdimf(GLIBC_2.2) <a href="#">[SUSv4]</a>	nexttowardf(GLIBC_2.2) <a href="#">[SUSv4]</a>
cacoshl(GLIBC_2.4) <a href="#">[SUSv4]</a>	fdiml(GLIBC_2.2) <a href="#">[SUSv4]</a>	nexttowardf(GLIBC_2.4) <a href="#">[SUSv4]</a>
cacosl(GLIBC_2.2) <a href="#">[SUSv4]</a>	fdiml(GLIBC_2.4) <a href="#">[SUSv4]</a>	nexttowardl(GLIBC_2.2) <a href="#">[SUSv4]</a>
cacosl(GLIBC_2.4) <a href="#">[SUSv4]</a>	feclearexcept(GLIBC_2.2) )( <a href="#">[SUSv4]</a>	nexttowardl(GLIBC_2.4) <a href="#">[SUSv4]</a>
carg(GLIBC_2.2) <a href="#">[SUSv4]</a>	fedisableexcept(GLIBC_2.2) <a href="#">[LSB]</a>	pow(GLIBC_2.2) <a href="#">[SUSv4]</a>
cargf(GLIBC_2.2) <a href="#">[SUSv4]</a>	feenableexcept(GLIBC_2.2) <a href="#">[LSB]</a>	pow10(GLIBC_2.2) <a href="#">[LSB]</a>
cargl(GLIBC_2.2) <a href="#">[SUSv4]</a>	fegetenv(GLIBC_2.2) <a href="#">[SUSv4]</a>	pow10f(GLIBC_2.2) <a href="#">[LSB]</a>
cargl(GLIBC_2.4) <a href="#">[SUSv4]</a>	fegetexcept(GLIBC_2.2) <a href="#">[LSB]</a>	pow10l(GLIBC_2.2) <a href="#">[LSB]</a>
casin(GLIBC_2.2) <a href="#">[SUSv4]</a>	fegetexceptflag(GLIBC_2.2) )( <a href="#">[SUSv4]</a>	pow10l(GLIBC_2.4) <a href="#">[LSB]</a>
casinf(GLIBC_2.2) <a href="#">[SUSv4]</a>	fegetround(GLIBC_2.2) <a href="#">[SUSv4]</a>	powf(GLIBC_2.2) <a href="#">[SUSv4]</a>
casinh(GLIBC_2.2) <a href="#">[SUSv4]</a>	feholdexcept(GLIBC_2.2) )( <a href="#">[SUSv4]</a>	powl(GLIBC_2.2) <a href="#">[SUSv4]</a>
casinhf(GLIBC_2.2) <a href="#">[SUSv4]</a>	feraiseexcept(GLIBC_2.2) )( <a href="#">[SUSv4]</a>	powl(GLIBC_2.4) <a href="#">[SUSv4]</a>
casinhl(GLIBC_2.2) <a href="#">[SUSv4]</a>	fesetenv(GLIBC_2.2) <a href="#">[SUSv4]</a>	remainder(GLIBC_2.2) <a href="#">[SUSv4]</a>
casinhl(GLIBC_2.4) <a href="#">[SUSv4]</a>	fesetexceptflag(GLIBC_2.2) )( <a href="#">[SUSv4]</a>	remainderf(GLIBC_2.2) <a href="#">[SUSv4]</a>
casinl(GLIBC_2.2) <a href="#">[SUSv4]</a>	fesetround(GLIBC_2.2) <a href="#">[SUSv4]</a>	remainderl(GLIBC_2.2) <a href="#">[SUSv4]</a>
casinl(GLIBC_2.4) <a href="#">[SUSv4]</a>	fetestexcept(GLIBC_2.2) )( <a href="#">[SUSv4]</a>	remainderl(GLIBC_2.4) <a href="#">[SUSv4]</a>
catan(GLIBC_2.2) <a href="#">[SUSv4]</a>	feupdateenv(GLIBC_2.2) <a href="#">[SUSv4]</a>	remquo(GLIBC_2.2) <a href="#">[SUSv4]</a>
catanf(GLIBC_2.2) <a href="#">[SUSv4]</a>	finite(GLIBC_2.2) <a href="#">[LSB]</a>	remquof(GLIBC_2.2) <a href="#">[SUSv4]</a>
catanh(GLIBC_2.2) <a href="#">[SUSv4]</a>	finitef(GLIBC_2.2) <a href="#">[LSB]</a>	remquol(GLIBC_2.2) <a href="#">[SUSv4]</a>

<code>catanhf(GLIBC_2.2) [SUSv4]</code>	<code>finitel(GLIBC_2.2) [LSB]</code>	<code>remquo(GLIBC_2.4) [SUSv4]</code>
<code>catanhl(GLIBC_2.2) [SUSv4]</code>	<code>finitel(GLIBC_2.4) [LSB]</code>	<code>rint(GLIBC_2.2) [SUSv4]</code>
<code>catanhl(GLIBC_2.4) [SUSv4]</code>	<code>floor(GLIBC_2.2) [SUSv4]</code>	<code>rintf(GLIBC_2.2) [SUSv4]</code>
<code>catanl(GLIBC_2.2) [SUSv4]</code>	<code>floorf(GLIBC_2.2) [SUSv4]</code>	<code>rintl(GLIBC_2.2) [SUSv4]</code>
<code>catanl(GLIBC_2.4) [SUSv4]</code>	<code>floorl(GLIBC_2.2) [SUSv4]</code>	<code>rintl(GLIBC_2.4) [SUSv4]</code>
<code>cbrt(GLIBC_2.2) [SUSv4]</code>	<code>floorl(GLIBC_2.4) [SUSv4]</code>	<code>round(GLIBC_2.2) [SUSv4]</code>
<code>cbrtf(GLIBC_2.2) [SUSv4]</code>	<code>fma(GLIBC_2.2) [SUSv4]</code>	<code>roundf(GLIBC_2.2) [SUSv4]</code>
<code>cbrtl(GLIBC_2.2) [SUSv4]</code>	<code>fmaf(GLIBC_2.2) [SUSv4]</code>	<code>roundl(GLIBC_2.2) [SUSv4]</code>
<code>cbrtl(GLIBC_2.4) [SUSv4]</code>	<code>fmal(GLIBC_2.2) [SUSv4]</code>	<code>roundl(GLIBC_2.4) [SUSv4]</code>
<code>ccos(GLIBC_2.2) [SUSv4]</code>	<code>fmal(GLIBC_2.4) [SUSv4]</code>	<code>scalb(GLIBC_2.2) [SUSv3]</code>
<code>ccosf(GLIBC_2.2) [SUSv4]</code>	<code>fmax(GLIBC_2.2) [SUSv4]</code>	<code>scalbf(GLIBC_2.2) [LSB]</code>
<code>ccosh(GLIBC_2.2) [SUSv4]</code>	<code>fmaxf(GLIBC_2.2) [SUSv4]</code>	<code>scalbl(GLIBC_2.2) [LSB]</code>
<code>ccoshf(GLIBC_2.2) [SUSv4]</code>	<code>fmaxl(GLIBC_2.2) [SUSv4]</code>	<code>scalbl(GLIBC_2.4) [LSB]</code>
<code>ccoshl(GLIBC_2.2) [SUSv4]</code>	<code>fmaxl(GLIBC_2.4) [SUSv4]</code>	<code>scalbln(GLIBC_2.2) [SUSv4]</code>
<code>ccoshl(GLIBC_2.4) [SUSv4]</code>	<code>fmin(GLIBC_2.2) [SUSv4]</code>	<code>scalblnf(GLIBC_2.2) [SUSv4]</code>
<code>ccosl(GLIBC_2.2) [SUSv4]</code>	<code>fminf(GLIBC_2.2) [SUSv4]</code>	<code>scalblnl(GLIBC_2.2) [SUSv4]</code>
<code>ccosl(GLIBC_2.4) [SUSv4]</code>	<code>fminl(GLIBC_2.2) [SUSv4]</code>	<code>scalblnl(GLIBC_2.4) [SUSv4]</code>
<code>ceil(GLIBC_2.2) [SUSv4]</code>	<code>fminl(GLIBC_2.4) [SUSv4]</code>	<code>scalbn(GLIBC_2.2) [SUSv4]</code>
<code>celf(GLIBC_2.2) [SUSv4]</code>	<code>fmod(GLIBC_2.2) [SUSv4]</code>	<code>scalbnf(GLIBC_2.2) [SUSv4]</code>
<code>ceil(GLIBC_2.2) [SUSv4]</code>	<code>fmodf(GLIBC_2.2) [SUSv4]</code>	<code>scalbnl(GLIBC_2.2) [SUSv4]</code>
<code>ceil(GLIBC_2.4) [SUSv4]</code>	<code>fmodl(GLIBC_2.2) [SUSv4]</code>	<code>scalbnl(GLIBC_2.4) [SUSv4]</code>
<code>cexp(GLIBC_2.2) [SUSv4]</code>	<code>fmodl(GLIBC_2.4) [SUSv4]</code>	<code>significand(GLIBC_2.2) [LSB]</code>
<code>cexpf(GLIBC_2.2) [SUSv4]</code>	<code>frexp(GLIBC_2.2) [SUSv4]</code>	<code>significandf(GLIBC_2.2) [LSB]</code>
<code>cexpl(GLIBC_2.2) [SUSv4]</code>	<code>frexpf(GLIBC_2.2) [SUSv4]</code>	<code>significndl(GLIBC_2.2) [LSB]</code>
<code>cexpl(GLIBC_2.4) [SUSv4]</code>	<code>frexpl(GLIBC_2.2) [SUSv4]</code>	<code>significndl(GLIBC_2.4) [LSB]</code>

cimag(GLIBC_2.2) [SUSv4]	frexp1(GLIBC_2.4) [SUSv4]	sin(GLIBC_2.2)[SUSv4]
cimaf(GLIBC_2.2) [SUSv4]	gamma(GLIBC_2.2) [LSB]	sincos(GLIBC_2.2)[LSB]
cimagl(GLIBC_2.2) [SUSv4]	gammal(GLIBC_2.2) [LSB]	sincosf(GLIBC_2.2) [LSB]
cimagl(GLIBC_2.4) [SUSv4]	gammal(GLIBC_2.2) [LSB]	sincosl(GLIBC_2.2) [LSB]
clog(GLIBC_2.2) [SUSv4]	gammal(GLIBC_2.4) [LSB]	sincosl(GLIBC_2.4) [LSB]
clog10(GLIBC_2.2) [LSB]	hypot(GLIBC_2.2) [SUSv4]	sinf(GLIBC_2.2)[SUSv4]
clog10f(GLIBC_2.2) [LSB]	hypotf(GLIBC_2.2) [SUSv4]	sinh(GLIBC_2.2) [SUSv4]
clog10l(GLIBC_2.2) [LSB]	hypotl(GLIBC_2.2) [SUSv4]	sinhf(GLIBC_2.2) [SUSv4]
clog10l(GLIBC_2.4) [LSB]	hypotl(GLIBC_2.4) [SUSv4]	sinhl(GLIBC_2.2) [SUSv4]
clogf(GLIBC_2.2) [SUSv4]	ilogb(GLIBC_2.2) [SUSv4]	sinhl(GLIBC_2.4) [SUSv4]
clogl(GLIBC_2.2) [SUSv4]	ilogbf(GLIBC_2.2) [SUSv4]	sinl(GLIBC_2.2)[SUSv4]
clogl(GLIBC_2.4) [SUSv4]	ilogbl(GLIBC_2.2) [SUSv4]	sinl(GLIBC_2.4)[SUSv4]
conj(GLIBC_2.2) [SUSv4]	ilogbl(GLIBC_2.4) [SUSv4]	sqrt(GLIBC_2.2)[SUSv4]
conjf(GLIBC_2.2) [SUSv4]	j0(GLIBC_2.2)[SUSv4]	sqrtf(GLIBC_2.2) [SUSv4]
conjl(GLIBC_2.2) [SUSv4]	j0f(GLIBC_2.2)[LSB]	sqrtl(GLIBC_2.2) [SUSv4]
conjl(GLIBC_2.4) [SUSv4]	j0l(GLIBC_2.2)[LSB]	sqrtl(GLIBC_2.4) [SUSv4]
copysign(GLIBC_2.2) [SUSv4]	j0l(GLIBC_2.4)[LSB]	tan(GLIBC_2.2)[SUSv4]
copysignf(GLIBC_2.2) [SUSv4]	j1(GLIBC_2.2)[SUSv4]	tanf(GLIBC_2.2)[SUSv4]
copysignl(GLIBC_2.2) [SUSv4]	j1f(GLIBC_2.2)[LSB]	tanh(GLIBC_2.2) [SUSv4]
copysignl(GLIBC_2.4) [SUSv4]	j1l(GLIBC_2.2)[LSB]	tanhf(GLIBC_2.2) [SUSv4]
cos(GLIBC_2.2)[SUSv4]	j1l(GLIBC_2.4)[LSB]	tanhl(GLIBC_2.2) [SUSv4]
cosf(GLIBC_2.2) [SUSv4]	jn(GLIBC_2.2)[SUSv4]	tanhl(GLIBC_2.4) [SUSv4]
cosh(GLIBC_2.2) [SUSv4]	jnf(GLIBC_2.2)[LSB]	tanl(GLIBC_2.2)[SUSv4]
coshf(GLIBC_2.2) [SUSv4]	jnl(GLIBC_2.2)[LSB]	tanl(GLIBC_2.4)[SUSv4]
coshl(GLIBC_2.2) [SUSv4]	jnl(GLIBC_2.4)[LSB]	tgamma(GLIBC_2.2) [SUSv4]

coshl(GLIBC_2.4) [SUSv4]	ldexp(GLIBC_2.2) [SUSv4]	tgammaf(GLIBC_2.2) [SUSv4]
cosl(GLIBC_2.2) [SUSv4]	ldexpf(GLIBC_2.2) [SUSv4]	tgammal(GLIBC_2.2) [SUSv4]
cosl(GLIBC_2.4) [SUSv4]	ldexpl(GLIBC_2.2) [SUSv4]	tgammal(GLIBC_2.4) [SUSv4]
cpow(GLIBC_2.2) [SUSv4]	ldexpl(GLIBC_2.4) [SUSv4]	trunc(GLIBC_2.2) [SUSv4]
cpowf(GLIBC_2.2) [SUSv4]	lgamma(GLIBC_2.2) [SUSv4]	truncf(GLIBC_2.2) [SUSv4]
cpowl(GLIBC_2.2) [SUSv4]	lgamma_r(GLIBC_2.2) [LSB]	truncl(GLIBC_2.2) [SUSv4]
cpowl(GLIBC_2.4) [SUSv4]	lgammaf(GLIBC_2.2) [SUSv4]	truncl(GLIBC_2.4) [SUSv4]
cproj(GLIBC_2.2) [SUSv4]	lgammaf_r(GLIBC_2.2) [LSB]	y0(GLIBC_2.2) [SUSv4]
cprojf(GLIBC_2.2) [SUSv4]	lgammal(GLIBC_2.2) [SUSv4]	y0f(GLIBC_2.2) [LSB]
cprojl(GLIBC_2.2) [SUSv4]	lgammal(GLIBC_2.4) [SUSv4]	y0l(GLIBC_2.2) [LSB]
cprojl(GLIBC_2.4) [SUSv4]	lgammal_r(GLIBC_2.2) [LSB]	y0l(GLIBC_2.4) [LSB]
creal(GLIBC_2.2) [SUSv4]	lgammal_r(GLIBC_2.4) [LSB]	y1(GLIBC_2.2) [SUSv4]
crealf(GLIBC_2.2) [SUSv4]	llrint(GLIBC_2.2) [SUSv4]	y1f(GLIBC_2.2) [LSB]
creall(GLIBC_2.2) [SUSv4]	llrintf(GLIBC_2.2) [SUSv4]	y1l(GLIBC_2.2) [LSB]
creall(GLIBC_2.4) [SUSv4]	llrintl(GLIBC_2.2) [SUSv4]	y1l(GLIBC_2.4) [LSB]
csin(GLIBC_2.2) [SUSv4]	llrintl(GLIBC_2.4) [SUSv4]	yn(GLIBC_2.2) [SUSv4]
csinf(GLIBC_2.2) [SUSv4]	llround(GLIBC_2.2) [SUSv4]	ynf(GLIBC_2.2) [LSB]
csinh(GLIBC_2.2) [SUSv4]	llroundf(GLIBC_2.2) [SUSv4]	ynl(GLIBC_2.2) [LSB]
csinhf(GLIBC_2.2) [SUSv4]	llroundl(GLIBC_2.2) [SUSv4]	ynl(GLIBC_2.4) [LSB]
csinhl(GLIBC_2.2) [SUSv4]	llroundl(GLIBC_2.4) [SUSv4]	
csinhl(GLIBC_2.4) [SUSv4]	log(GLIBC_2.2) [SUSv4]	

**Table A-7 libm Data Interfaces**

signgam [SUSv4]		
--------------------	--	--

## A.6 libpthread

The behavior of the interfaces in this library is specified by the following Standards.

[Large File Support](#) [LFS]

[LSB Core - Generic](#) [LSB]

[POSIX 1003.1-2001 \(ISO/IEC 9945-2003\) \[SUSv3\]](#)  
[POSIX 1003.1-2008 \(ISO/IEC 9945-2009\) \[SUSv4\]](#)

**Table A-8 libpthread Function Interfaces**

<code>__errno_location(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>pthread_barrierattr_setpushed(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_rwlockattr_destroy(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>_h_errno_location(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>pthread_cancel(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_rwlockattr_getkind_np(GLIBC_2.2)</code> <a href="#">[LSB]</a>
<code>_libc_current_sigrtmax(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>pthread_cond_broadcast(GLIBC_2.3.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_rwlockattr_getpshared(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>_libc_current_sigrtmin(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>pthread_cond_destroy(GLIBC_2.3.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_rwlockattr_init(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>_pthread_cleanup_pop(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>pthread_cond_init(GLIBC_2.3.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_rwlockattr_setkind_np(GLIBC_2.2)</code> <a href="#">[LSB]</a>
<code>_pthread_cleanup_push(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>pthread_cond_signal(GLIBC_2.3.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_rwlockattr_setshare(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>accept(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_cond_timedwait(GLIBC_2.3.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_self(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>close(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_cond_wait(GLIBC_2.3.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_setcancelstate(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>connect(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_condattr_destroy(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_setcanceltype(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>fcntl(GLIBC_2.2)</code> <a href="#">[LSB]</a>	<code>pthread_condattr_getpushed(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_setconcurrency(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>flockfile(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_condattr_init(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_setschedparam(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>fork(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_condattr_setpushed(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_setspecific(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>fsync(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_create(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_sigmask(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>ftrylockfile(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_detach(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_spin_destroy(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>funlockfile(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_equal(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_spin_init(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>longjmp(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_exit(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_spin_lock(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>lseek(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_getattr_np(GLIBC_2.2.3)</code> <a href="#">[LSB]</a>	<code>pthread_spin_trylock(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>lseek64(GLIBC_2.2)</code> <a href="#">[LFS]</a>	<code>pthread_getconcurrency(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_spin_unlock(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>msync(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_getcpuclockid(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_testcancel(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>nanosleep(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_getschedparam(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pwrite(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>
<code>open(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pthread_getspecific(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>pwrite64(GLIBC_2.2)</code> <a href="#">[LSB]</a>
<code>open64(GLIBC_2.2)</code> <a href="#">[LFS]</a>	<code>pthread_join(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>	<code>raise(GLIBC_2.2)</code> <a href="#">[SUSv4]</a>

pause(GLIBC_2.2) [SUSv4]	pthread_key_create(GLIBC_2.2)[SUSv4]	read(GLIBC_2.2) [SUSv4]
pread(GLIBC_2.2) [SUSv4]	pthread_key_delete(GLIBC_2.2)[SUSv4]	recv(GLIBC_2.2) [SUSv4]
pread64(GLIBC_2.2) [LSB]	pthread_kill(GLIBC_2.2)[SUSv4]	recvfrom(GLIBC_2.2) [SUSv4]
pthread_attr_destroy(GLIBC_2.2)[SUSv4]	pthread_mutex_consistent_np(GLIBC_2.4)[LSB]	recvmsg(GLIBC_2.2) [SUSv4]
pthread_attr_getdetachstate(GLIBC_2.2)[SUSv4]	pthread_mutex_destroy(GLIBC_2.2)[SUSv4]	sem_close(GLIBC_2.2) [SUSv4]
pthread_attr_getguardsize(GLIBC_2.2)[SUSv4]	pthread_mutex_init(GLIBC_2.2)[SUSv4]	sem_destroy(GLIBC_2.2) [SUSv4]
pthread_attr_getinheritsched(GLIBC_2.2)[SUSv4]	pthread_mutex_lock(GLIBC_2.2)[SUSv4]	sem_getvalue(GLIBC_2.2)[SUSv4]
pthread_attr_getschedparam(GLIBC_2.2)[SUSv4]	pthread_mutex_timedlock(GLIBC_2.2)[SUSv4]	sem_init(GLIBC_2.2) [SUSv4]
pthread_attr_getschedpolicy(GLIBC_2.2)[SUSv4]	pthread_mutex_trylock(GLIBC_2.2)[SUSv4]	sem_open(GLIBC_2.2) [SUSv4]
pthread_attr_getscope(GLIBC_2.2)[SUSv4]	pthread_mutex_unlock(GLIBC_2.2)[SUSv4]	sem_post(GLIBC_2.2) [SUSv4]
pthread_attr_getstack(GLIBC_2.2)[SUSv4]	pthread_mutexattr_destroy(GLIBC_2.2)[SUSv4]	sem_timedwait(GLIBC_2.2)[SUSv4]
pthread_attr_getstackaddr(GLIBC_2.2)[SUSv3]	pthread_mutexattr_getpushred(GLIBC_2.2)[SUSv4]	sem_trywait(GLIBC_2.2) [SUSv4]
pthread_attr_getstacksize(GLIBC_2.2)[SUSv4]	pthread_mutexattr_getrobust_np(GLIBC_2.4)[LSB]	sem_unlink(GLIBC_2.2) [SUSv4]
pthread_attr_init(GLIBC_2.2)[SUSv4]	pthread_mutexattr_gettype(GLIBC_2.2)[SUSv4]	sem_wait(GLIBC_2.2) [SUSv4]
pthread_attr_setdetachstate(GLIBC_2.2)[SUSv4]	pthread_mutexattr_init(GLIBC_2.2)[SUSv4]	send(GLIBC_2.2) [SUSv4]
pthread_attr_setguardsize(GLIBC_2.2)[SUSv4]	pthread_mutexattr_setpushred(GLIBC_2.2)[SUSv4]	sendmsg(GLIBC_2.2) [SUSv4]
pthread_attr_setinheritsched(GLIBC_2.2)[SUSv4]	pthread_mutexattr_setrobust_np(GLIBC_2.4)[LSB]	sendto(GLIBC_2.2) [SUSv4]
pthread_attr_setschedparam(GLIBC_2.2)[SUSv4]	pthread_mutexattr_settype(GLIBC_2.2)[SUSv4]	sigaction(GLIBC_2.2) [SUSv4]
pthread_attr_setschedpolicy(GLIBC_2.2)[SUSv4]	pthread_once(GLIBC_2.2)[SUSv4]	siglongjmp(GLIBC_2.2) [SUSv4]
pthread_attr_setscope(GLIBC_2.2)[SUSv4]	pthread_rwlock_destroy(GLIBC_2.2)[SUSv4]	sigwait(GLIBC_2.2) [SUSv4]
pthread_attr_setstack(GLIBC_2.2)[SUSv4]	pthread_rwlock_init(GLIBC_2.2)[SUSv4]	system(GLIBC_2.2) [LSB]
pthread_attr_setstackaddr(GLIBC_2.2)[SUSv3]	pthread_rwlock_rdlock(GLIBC_2.2)[SUSv4]	tcdrain(GLIBC_2.2) [SUSv4]
pthread_attr_setstacksize(GLIBC_2.2)[SUSv4]	pthread_rwlock_timedunlock(GLIBC_2.2)[SUSv4]	vfork(GLIBC_2.2) [SUSv3]

pthread_barrier_destroy(GLIBC_2.2) <a href="#">[SUSv4]</a>	pthread_rwlock_timedwrlock(GLIBC_2.2) <a href="#">[SUSv4]</a>	wait(GLIBC_2.2) <a href="#">[SUSv4]</a>
pthread_barrier_init(GLIBC_2.2) <a href="#">[SUSv4]</a>	pthread_rwlock_tryrdlock(GLIBC_2.2) <a href="#">[SUSv4]</a>	waitpid(GLIBC_2.2) <a href="#">[LSB]</a>
pthread_barrier_wait(GLIBC_2.2) <a href="#">[SUSv4]</a>	pthread_rwlock_trywrlock(GLIBC_2.2) <a href="#">[SUSv4]</a>	write(GLIBC_2.2) <a href="#">[SUSv4]</a>
pthread_barrierattr_destroy(GLIBC_2.2) <a href="#">[SUSv4]</a>	pthread_rwlock_unlock(GLIBC_2.2) <a href="#">[SUSv4]</a>	
pthread_barrierattr_init(GLIBC_2.2) <a href="#">[SUSv4]</a>	pthread_rwlock_wrlock(GLIBC_2.2) <a href="#">[SUSv4]</a>	

## A.7 librt

The behavior of the interfaces in this library is specified by the following Standards.  
[Large File Support](#) [LFS]  
[POSIX 1003.1-2008 \(ISO/IEC 9945-2009\)](#) [SUSv4]

**Table A-9 librt Function Interfaces**

aio_cancel(GLIBC_2.2) <a href="#">[SUSv4]</a>	aio_return64(GLIBC_2.2) <a href="#">[LFS]</a>	clock_settime(GLIBC_2.2) <a href="#">[SUSv4]</a>
aio_cancel64(GLIBC_2.2) <a href="#">[LFS]</a>	aio_suspend(GLIBC_2.2) <a href="#">[SUSv4]</a>	shm_open(GLIBC_2.2) <a href="#">[SUSv4]</a>
aio_error(GLIBC_2.2) <a href="#">[SUSv4]</a>	aio_suspend64(GLIBC_2.2) <a href="#">[LFS]</a>	shm_unlink(GLIBC_2.2) <a href="#">[SUSv4]</a>
aio_error64(GLIBC_2.2) <a href="#">[LFS]</a>	aio_write(GLIBC_2.2) <a href="#">[SUSv4]</a>	timer_create(GLIBC_2.3.3) <a href="#">[SUSv4]</a>
aio_fsync(GLIBC_2.2) <a href="#">[SUSv4]</a>	aio_write64(GLIBC_2.2) <a href="#">[LFS]</a>	timer_delete(GLIBC_2.3.3) <a href="#">[SUSv4]</a>
aio_fsync64(GLIBC_2.2) <a href="#">[LFS]</a>	clock_getcpuclockid(GLIBC_2.2) <a href="#">[SUSv4]</a>	timer_getoverrun(GLIBC_2.3.3) <a href="#">[SUSv4]</a>
aio_read(GLIBC_2.2) <a href="#">[SUSv4]</a>	clock_getres(GLIBC_2.2) <a href="#">[SUSv4]</a>	timer_gettime(GLIBC_2.3.3) <a href="#">[SUSv4]</a>
aio_read64(GLIBC_2.2) <a href="#">[LFS]</a>	clock_gettime(GLIBC_2.2) <a href="#">[SUSv4]</a>	timer_settime(GLIBC_2.3.3) <a href="#">[SUSv4]</a>
aio_return(GLIBC_2.2) <a href="#">[SUSv4]</a>	clock_nanosleep(GLIBC_2.2) <a href="#">[SUSv4]</a>	

## A.8 libutil

The behavior of the interfaces in this library is specified by the following Standards.  
[LSB Core - Generic](#) [LSB]

**Table A-10 libutil Function Interfaces**

forkpty(GLIBC_2.2) <a href="#">[LSB]</a>	login_tty(GLIBC_2.2) <a href="#">[LSB]</a>	logwtmp(GLIBC_2.2) <a href="#">[LSB]</a>
login(GLIBC_2.2) <a href="#">[LSB]</a>	logout(GLIBC_2.2) <a href="#">[LSB]</a>	openpty(GLIBC_2.2) <a href="#">[LSB]</a>

## Annex B GNU Free Documentation License (Informative)

This specification is published under the terms of the GNU Free Documentation License, Version 1.1, March 2000

Copyright (C) 2000 Free Software Foundation, Inc. 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

### B.1 PREAMBLE

The purpose of this License is to make a manual, textbook, or other written document "free" in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondarily, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of "copyleft", which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

### B.2 APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. The "Document", below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as "you".

A "Modified Version" of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (For example, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License.

The "Cover Texts" are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License.

A "Transparent" copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, whose contents can be viewed and edited directly and straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup has been designed to thwart or discourage subsequent modification by readers is not Transparent. A copy that is not "Transparent"

is called "Opaque".

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML designed for human modification. Opaque formats include PostScript, PDF, proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML produced by some word processors for output purposes only.

The "Title Page" means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, "Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

## B.3 VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or non-commercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

## B.4 COPYING IN QUANTITY

If you publish printed copies of the Document numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a publicly-accessible computer-network location containing a complete Transparent copy of the Document, free of added material, which the general network-using public has access to download anonymously at no charge using public-standard network protocols. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

## B.5 MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.
- B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has less than five).
- C. State on the Title page the name of the publisher of the Modified Version, as the publisher.
- D. Preserve all the copyright notices of the Document.
- E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
- F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
- G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.
- H. Include an unaltered copy of this License.
- I. Preserve the section entitled "History", and its title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.
- J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.
- K. In any section entitled "Acknowledgements" or "Dedications", preserve the section's title, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
- L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
- M. Delete any section entitled "Endorsements". Such a section may not be included in the Modified Version.
- N. Do not retitle any existing section as "Endorsements" or to conflict in title with any Invariant Section.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version's license notice. These

titles must be distinct from any other section titles.

You may add a section entitled "Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties--for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

## B.6 COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections entitled "History" in the various original documents, forming one section entitled "History"; likewise combine any sections entitled "Acknowledgements", and any sections entitled "Dedications". You must delete all sections entitled "Endorsements."

## B.7 COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

## B.8 AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, does not as a whole count as a Modified Version of the Document, provided no compilation copyright is claimed for the compilation. Such a compilation is called an "aggregate", and this License does not apply to the other self-contained works thus compiled with the Document, on account of their being thus compiled, if they are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one quarter of the entire aggregate, the Document's Cover Texts may be placed on covers that surround only the Document within the aggregate. Otherwise they must appear on covers around the whole aggregate.

## **B.9 TRANSLATION**

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License provided that you also include the original English version of this License. In case of a disagreement between the translation and the original English version of this License, the original English version will prevail.

## **B.10 TERMINATION**

You may not copy, modify, sublicense, or distribute the Document except as expressly provided for under this License. Any other attempt to copy, modify, sublicense or distribute the Document is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

## **B.11 FUTURE REVISIONS OF THIS LICENSE**

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See <http://www.gnu.org/copyleft/>.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License "or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation.

## **B.12 How to use this License for your documents**

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

Copyright (c) YEAR YOUR NAME. Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.1 or any later version published by the Free Software Foundation; with the Invariant Sections being LIST THEIR TITLES, with the Front-Cover Texts being LIST, and with the Back-Cover Texts being LIST. A copy of the license is included in the section entitled "GNU Free Documentation License".

If you have no Invariant Sections, write "with no Invariant Sections" instead of saying which ones are invariant. If you have no Front-Cover Texts, write "no Front-Cover Texts" instead of "Front-Cover Texts being LIST"; likewise for Back-Cover Texts.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.